

Advance Security  
Lab 9  
Student Name: Jonathan Riordan  
Student ID: C13432152

Self Signed Certificate

**Question 1**

Part 1.

```
jonathan:Lab Jonathan$ openssl genrsa -des3 -out server.key 2048
Generating RSA private key, 2048 bit long modulus
.....+++
.....+++
e is 65537 (0x10001)
Enter pass phrase for server.key:
Verifying - Enter pass phrase for server.key:
```

Part 2.


```
jonathan:Lab Jonathan$ openssl req -new -key server.key -out server.csr
Enter pass phrase for server.key:
You are about to be asked to enter information that will be incorporated
into your certificate request.
What you are about to enter is what is called a Distinguished Name or a DN.
There are quite a few fields but you can leave some blank
For some fields there will be a default value,
If you enter '.', the field will be left blank.
-----
Country Name (2 letter code) [AU]:Ireland
string is too long, it needs to be less than 2 bytes long
Country Name (2 letter code) [AU]:Dublin
string is too long, it needs to be less than 2 bytes long
Country Name (2 letter code) [AU]:DB
State or Province Name (full name) [Some-State]:LE
Locality Name (eg, city) []:Blackrock
Organization Name (eg, company) [Internet Widgits Pty Ltd]:Lols
Organizational Unit Name (eg, section) []:.
Common Name (e.g. server FQDN or YOUR name) []:JR
Email Address []:C13432152@mydit.ie

Please enter the following 'extra' attributes
to be sent with your certificate request
A challenge password []:password
An optional company name []:.
```

Part 3.

```
jonathan:Lab Jonathan$ openssl x509 -req -days 365 -in server.csr -signkey server.key -o
ut server.crt
Signature ok
subject=/C=DB/ST=LE/L=Blackrock/O=Lols/CN=JR/emailAddress=C13432152@mydit.ie
Getting Private key
Enter pass phrase for server.key:
```

Below is the screen shot of the self certificate I created. The public key 256bytes and the algorithm is RSA algorithm.



## Question 2.

Part 1.

The command to create a 1024 bit key is `ssh-keygen -t rsa -b 1024`

```
The key fingerprint is:
SHA256:QtVAosoCJJJe0m8xvLVLtk0qqplvo7R5FgmswTb/8ys Jonathan@jonathan.ict.ad.dit.ie
The key's randomart image is:
+----[RSA 1024]-----+
|...0+ ..+0|
|00.+ 0 0 .|
|*+= + .|
|*@.= 0|
|=.0 0 . S|
|.0 + .|
|..+ 0|
|o=0= E|
|++*.. +0.|
+----[SHA256]-----+
```

Part 2.

```

jonathan:Lab 9 Jonathan$ openssl req -new -key rsa -out rsaserver.csr
You are about to be asked to enter information that will be incorporated
into your certificate request.
What you are about to enter is what is called a Distinguished Name or a DN.
There are quite a few fields but you can leave some blank
For some fields there will be a default value,
If you enter '.', the field will be left blank.
-----
Country Name (2 letter code) [AU]:IE
State or Province Name (full name) [Some-State]:LE
Locality Name (eg, city) []:Blackrock
Organization Name (eg, company) [Internet Widgits Pty Ltd]:Lols
Organizational Unit Name (eg, section) []:lol
Common Name (e.g. server FQDN or YOUR name) []:Jonathan Riordan
Email Address []:C13432152@mydit.ie

Please enter the following 'extra' attributes
to be sent with your certificate request
A challenge password []:password

```

```

jonathan:Lab 9 Jonathan$ openssl x509 -req -days 365 -in rsaserver.csr -signkey rsa -out
rsaserver.crt
Signature ok
subject=C=IE/ST=LE/L=Blackrock/O=Lols/OU=lol/CN=Jonathan Riordan/emailAddress=C13432152@
mydit.ie
Getting Private key

```



## Jonathan Riordan

### Issuer Name

Country IE  
 State/Province LE  
 Locality Blackrock  
 Organization Lols  
 Organizational Unit lol  
 Common Name Jonathan Riordan  
 Email Address C13432152@mydit.ie

Serial Number 00 BA A6 B3 83 30 4B 58 9E

Version 1

Signature Algorithm SHA-1 with RSA Encryption ( 1.2.840.113549.1.1.5 )

### Subject Name

Country IE  
 State/Province LE  
 Locality Blackrock  
 Organization Lols  
 Organizational Unit lol  
 Common Name Jonathan Riordan  
 Email Address C13432152@mydit.ie

Not Valid Before Wednesday 7 December 2016 at 16:11:18 Greenwich Mean Time

Not Valid After Thursday 7 December 2017 at 16:11:18 Greenwich Mean Time

### Public Key Info

Algorithm RSA Encryption ( 1.2.840.113549.1.1.1 )  
 Public Key 128 bytes : C6 B7 1C 40 82 E3 5C B3 ...  
 Exponent 65537  
 Key Size 1024 bits  
 Key Usage Any

### Question 3.

Validate certificates.

The first certificate. We check to verify the server.csr. The verification comes back as "Ok". The key is 2048 bit and the algorithm is RSA.

```
jonathan:Lab 9 Jonathan$ openssl req -text -noout -verify -in server.csr
verify OK
Certificate Request:
  Data:
    Version: 0 (0x0)
    Subject: C=DB, ST=LE, L=Blackrock, O=Lols, CN=JR/emailAddress=C13432152@mydit.ie
    Subject Public Key Info:
      Public Key Algorithm: rsaEncryption
      RSA Public Key: (2048 bit)
        Modulus (2048 bit):
          00:ab:ef:94:b7:6c:a6:2f:66:ee:48:d1:ea:82:d2:
          6e:1b:07:6b:a4:02:5a:66:84:26:47:7f:7c:d2:68:
          70:ab:0a:d5:dd:02:f4:c2:d9:4a:62:28:8f:b7:4b:
          86:b7:7f:4b:64:ec:1b:aa:22:04:70:82:d9:11:f6:
          89:f3:23:8e:e9:6d:a4:13:6c:ed:48:d5:90:4f:9e:
          14:4f:fd:6b:8b:1e:ff:89:ea:09:6a:e2:06:41:9e:
          48:09:e9:27:0f:b3:42:1d:fb:dd:d4:c0:cf:23:b4:
          30:8b:25:82:ed:c5:71:7a:b6:d2:2b:0e:95:44:9d:
          b4:9c:33:90:49:51:66:35:78:ff:de:58:1e:28:b6:
          28:d6:fa:a2:fa:77:3e:9e:62:08:f5:89:e6:4a:0c:
          86:0b:cd:db:76:ea:c1:29:f5:f0:51:e0:88:d2:c2:
          02:b3:1e:53:c0:ed:2c:f4:46:8b:da:7f:37:85:9f:
          58:07:0a:be:c7:2e:4d:39:2a:95:1d:75:6f:46:8e:
          a5:c9:85:54:8b:60:5c:61:87:d3:f9:20:9d:ee:00:
          5c:a3:28:34:65:46:dc:f0:2e:ce:1d:e6:3e:c0:80:
          36:c1:d7:2e:41:3b:9e:44:3a:28:ce:d6:f3:ad:78:
          9d:a6:b2:d9:f7:70:6f:3a:41:e1:db:97:c0:6f:96:
          05:d1
        Exponent: 65537 (0x10001)
    Attributes:
      challengePassword      :password
  Signature Algorithm: sha1WithRSAEncryption
    11:36:1d:65:e8:d7:b3:db:56:ad:24:62:09:84:9d:bb:0b:99:
    2f:8b:73:01:37:48:04:a2:3d:50:45:50:c0:83:47:02:cb:85:
    0a:51:cc:77:3a:d8:78:2f:a5:e3:ff:2c:eb:05:93:37:75:b6:
    29:8f:86:0b:71:1d:43:4a:ac:e9:9b:8e:34:d1:79:c3:23:28:
    db:e9:e7:0b:5e:41:db:55:49:23:08:52:2f:32:85:8a:ef:66:
    90:9a:4e:a5:55:0c:bd:e1:74:9a:dc:f5:5e:f0:b5:36:c5:23:
    70:2b:51:b5:0a:5c:df:77:c3:0e:7a:bb:f0:0c:7e:9b:96:09:
    5f:e5:2e:8d:ec:e1:fb:08:a3:e7:f1:06:39:76:c7:41:dd:72:
    3b:64:1f:70:97:c0:72:3b:77:78:3d:78:ee:0e:05:20:85:de:
    3a:f6:75:de:f3:14:53:ba:1a:85:b9:5d:0c:ea:16:46:c2:7e:
    d2:20:5f:df:11:0b:0e:c1:1b:ab:46:99:f4:c0:a7:7f:ba:96:
    31:e4:78:99:a9:3b:3c:80:bb:b8:45:9e:9b:c9:82:b6:ab:99:
    e5:0a:26:47:35:08:0c:29:a0:48:26:89:8a:f0:83:39:bd:f2:
    ff:e1:31:5c:2d:70:58:49:38:43:98:a3:44:9d:c5:55:fa:50:
    ff:28:0d:2d
jonathan:Lab 9 Jonathan$
```

The second certificate.

Validating for the rsaserver.csr. The validation comes back as "Ok". The key is 1024 bit and the algorithm used is RSA.

### Question 4.

```





jonathan:Lab 9 Jonathan$ openssl req -text -noout -verify -in rsaserver.csr
verify OK
Certificate Request:
Data:
  Version: 0 (0x0)
  Subject: C=IE, ST=LE, L=Blackrock, O=Lols, OU=lol, CN=Jonathan Riordan/emailAddress=C13432152@mydit.ie
  Subject Public Key Info:
    Public Key Algorithm: rsaEncryption
    RSA Public Key: (1024 bit)
      Modulus (1024 bit):
        00:c6:b7:1c:40:82:e3:5c:b3:4c:22:58:1c:2f:a0:
        58:81:ab:24:11:0c:3f:73:0e:05:e5:37:e2:0c:8d:
        77:2c:19:45:2f:5c:a1:e6:45:12:2c:04:9b:bf:2f:
        bd:bf:d0:87:40:53:f0:bf:7c:04:db:89:6a:ab:e6:
        12:ec:6a:f8:46:53:8e:b1:25:ca:cb:4a:89:e1:60:
        95:66:79:e9:d8:bb:5e:f7:e7:48:e1:49:eb:cf:52:
        df:8a:5a:cb:6f:c0:51:9c:16:c8:12:ca:54:cb:f7:
        7a:da:1d:92:f2:d6:85:cb:77:7e:20:52:f5:67:3c:
        35:c6:6c:22:ea:3b:e6:47:c3
      Exponent: 65537 (0x10001)
  Attributes:
    challengePassword :password
  Signature Algorithm: sha1WithRSAEncryption
    a9:49:4b:45:e7:7d:c7:a7:df:67:de:e3:52:8e:67:0f:85:b1:
    1c:8b:17:21:d5:6a:16:53:68:fd:0f:f5:c0:c0:d7:a1:59:83:
    c3:2a:ea:66:c7:6d:d6:a8:ba:bc:62:98:c2:b1:c3:05:6b:62:
    94:19:dc:99:20:90:d4:6b:c0:9e:b9:d8:68:54:10:41:1f:56:
    3a:05:7b:60:ca:51:d6:13:f0:e6:2e:89:73:c5:ee:b7:a7:b7:
    2a:07:73:96:d7:f7:62:d8:59:5b:38:8b:f8:6e:a4:9f:95:bd:
    94:3a:9a:2f:29:42:a0:c4:26:84:8c:66:08:f5:c2:7e:89:ac:
    96:5d

```





Question 4.

I used the website <https://certlogik.com/decoder/> to check the strength and to get the configuration of my certificates.

Testing the strength of my rsaserver certificate, the results are as follows. The key size provides a warning as the key is not big enough. The signature is valid. other information I can receive from this service is the configuration of the certificate, the md5 checksum and the SHA-1.

| CSR Checks  |                           |  |
|---|---------------------------|--|
| Status  | Check                     | Information  |
|  | <a href="#">Signature</a> | Valid  |
|  | <a href="#">Weak-Key</a>  | Does not use a key on our blacklist – this is good |
|  | <a href="#">Key-Size</a>  | 1024 bits  |
|  | <a href="#">Subject</a>   | Subject does not contain empty values              |

I also used this website to check the strength and configuration of the other certificate I created. As above, I can retrieve information about the key size, the md5 checksum and SHA-1. The results are as follows for my server.csr certificate.

| CSR Checks  |                           |  |
|---|---------------------------|--|
| Status  | Check                     | Information  |
|  | <a href="#">Signature</a> | Valid  |
|  | <a href="#">Weak-Key</a>  | Does not use a key on our blacklist – this is good |
|  | <a href="#">Key-Size</a>  | 2048 bits  |
|  | <a href="#">Subject</a>   | Subject does not contain empty values              |