

Using policy_name to Define a Role for Nodes


Using policy_name instead of role objects

Objectives

After completing this brief module, you should be able to

- Explain how `policy_name` replaces the legacy Role object
- Use knife search to display nodes

CONCEPT



policy_name


Chef users sometimes used **role** objects to describe a run list of recipes that are executed on the node and to use for node searches.

Nowadays we use the policy_name for those purposes.

For example, all nodes that possess the **company_web** policy name would be configured in a similar or identical manner.

<https://docs.chef.io/roles.html>

CONCEPT




policy_name

When you assign a common policy_name to a group of nodes, each node will receive the same cookbooks (assuming they also utilize the same policy_group).

When these nodes perform a chef-client run, they utilize recipes specified in the Policyfile run list.

<https://docs.chef.io/roles.html>

EXERCISE



GL: Verify that All Web Nodes Use the Same `policy_name`

Give your nodes a `policy_name` to better describe them and so we can configure them in a similar manner.

Objective:

- ☐ Confirm our `iis_web` node has the same `policy_name` (`company_web`) as the `apache_web` node
- ☐ use ``knife search`` to list all or specific nodes

DISCUSSION



company_web Policy Name

In a previous module we set the `iis_web` node to use the `company_web` policy name with this command:

```
knife node policy set iis_web prod company_web
```

Now, when we update the cookbooks that are associated to the `company_web` policy name, the nodes that use the `company_web` policy name will be updated as well

We will also be able to easily search for all nodes that have the `company_web` policy name.

Note: In the next module you will learn more about using search.

GL: List Your Nodes



```
$ knife node list
```

```
apache_web  
iis_web  
lb
```

GL: Searching for All Nodes with knife



```
$ knife search node *:*
```

```
Node Name:  apache_web
Policy Name: company_web
Policy Group: prod
FQDN:       ip-172-31-57-169.ec2.internal
IP:         34.196.104.17
Run List:    recipe[company_web::default]
Recipes:     company_web::default, apache::default, apache::server
Platform:    centos 7.6.1810
Tags:

Node Name:  iis_web
Policy Name: company_web
Policy Group: prod
FQDN:       WIN-DQFQCUFHDCP.ec2.internal
IP:         34.195.38.226
Run List:    recipe[company_web::default]
Recipes:     company_web::default, myiis::default, myiis::server
Platform:    windows 6.3.9600
Tags:

Node Name:  lb
Policy Name: myhaproxy
Policy Group: prod
FQDN:       ip-172-31-22-163.ec2.internal
IP:         34.196.50.77
Run List:    recipe[myhaproxy::default] ...
```


GL: Searching for Nodes With a Specific policy_name



```
$ knife search node policy_name:company_web
```

```
Node Name:    apache_web
Policy Name:   company_web
Policy Group:  prod
FQDN:         ip-172-31-57-169.ec2.internal
IP:           34.196.104.17
Run List:      recipe[company_web::default]
Recipes:       company_web::default, apache::default, apache::server
Platform:      centos 7.6.1810
Tags:
```

```
Node Name:    iis_web
Policy Name:   company_web
Policy Group:  prod
FQDN:         WIN-DQFQCUFHDCP.ec2.internal
IP:           34.195.38.226
Run List:      recipe[company_web::default]
Recipes:       company_web::default, myiis::default, myiis::server
Platform:      windows 6.3.9600
```



GL: Verify that All Web Nodes Use the Same policy_name

We will give our nodes a role to better describe them and so we can configure them in a similar manner.

Objective:

- ✓ Confirm our iis_web node has the same policy_name (company_web) as the apache_web node
- ✓ Use `knife search` to list all or specific nodes

DISCUSSION

company_web Policy Name



In the next module you will learn more about using search and you will put the company_web policy name to work for you.

DISCUSSION



Q&A

What questions can we help you answer?



CHEF™