

## U-value calculations for the alterations to the extension

### Floor

Material	Thickness (mm)	Fraction of area (%)	Conductivity (W/mK)	Resistance (m2K/W)
Cement	50	100	0.6	0.08
Concrete	100	100	0.6	0.17
Kingspan TF70	120	100	0.019	6.32
Total Resistance				6.57
U-value (W/m2K)				0.15

### Front Wall

Material	Thickness (mm)	Fraction of area (%)	Conductivity (W/mK)	Resistance (m2K/W)
Brick	102.5	100	0.6	0.17
Clear cavity	50	100	-	0.18
Kingspan K106	100	100	0.019	5.26
Brick	102.5	100	0.6	0.17
Plasterboard	12.5	100	0.19	0.07
Total Resistance				5.85
U-value (W/m2K)				0.17

### Extension-garage wall

Material	Thickness (mm)	Fraction of area (%)	Conductivity (W/mK)	Resistance (m2K/W)
Brick	102.5	100	0.6	0.17
Knauff DriTherm	85	100	0.032	2.66
Brick	102.5	100	0.6	0.17
Plasterboard	12.5	100	0.19	0.07
Total Resistance				3.06
U-value (W/m2K)				0.33

### Roof

Material	Thickness (mm)	Fraction of area (%)	Conductivity (W/mK)	Resistance (m2K/W)
OSB	18	100	0.13	0.14
Kingspan T27	150	100	0.024	6.25
OSB	18	100	0.13	0.14
Plasterboard	12.5	100	0.19	0.07
Total Resistance				6.59
U-value (W/m2K)				0.15