

Arc Cheat Sheet

Personal Knowledge Engine

TUI — Launch & Panes

arc	# launch TUI (no subcommand)
# Pane focus	
Tab	Nav <-> Content toggle
Shift+Tab	always jump to Nav pane
Esc	jump to Command input
Alt+1	Nav pane
Alt+2	Content pane
Alt+3	Tab bar (Library / Agent / Stats)
# Split sub-panes	
Ctrl+X	toggle global AskX pane
Ctrl+O	toggle Preview pane
Ctrl+L	toggle Scratch pane

TUI — Keys

# Universal	
j/k or Up/Down	move up/down
PgDn/Ctrl+D	page down
PgUp/Ctrl+U	page up
g/Home	go to top
G/End	go to bottom
Enter	select / expand / collapse
Space	expand / collapse
q / Ctrl+C	quit
?	show key bindings help
/	open command input
# Nav pane (articles/collections/workspaces)	
r	mark article read
u	mark article unread
f	toggle favorite
o	open source URL in browser
v	view article in terminal
D	delete current item
U	unlink from workspace
a	move to attic
b	restore from attic
Ctrl+R	refresh
# Content pane (article view)	
h/Left or l/Right	prev/next tab (Flash/Summary/Body/Cards)
s	speak current tab (TTS)
[]	TTS slower / faster
# Content pane (workspace chat)	
j/k	prev/next message box
s	speak selected box
v	expand/collapse box
#	comment/uncomment box
x	delete box

# Command input	
Up/Down	recall command history
Ctrl+G	correct spelling/grammar

TUI — Global Commands

/search <query>	full-text search
/article ingest <url>	add a new article
/stats	library stats + cost
/models	list LLM profiles
/config	show resolved config
/config-edit	open config in \$EDITOR
/scratch [msg]	workspace-local scratch
/Scratch [msg]	global scratch
/AskX <prompt>	global LLM query
/tags	list all tags
/log	open/close debug log tail
/help [group]	key/command help

TUI — Chat Commands

# Active in workspace chat context:	
/mode	show grounding mode
/mode corpus-only	corpus only (no web)
/mode corpus-first	prefer corpus (default)
/mode open	unrestricted
/clear	clear conversation history
/reload	rebuild corpus
/stats	session token + cost
/system	show system prompt
/meta	workspace details
/save [file]	save session to outcomes/
/new <name>	create workspace
/delete [name]	delete workspace
/rename <name>	rename workspace
/describe <text>	set workspace description
/populate [--hint ""]	[--edit] [--dry-run]
/remove [--article slug]	[--all-articles] ...
/resource-list	
/resource-add <path url>	[--into <dir>] \
	[--as <name>] [--comment "..."]
/resource-view <name>	
/resource-edit <name>	
/resource-new <name>	
/resource-remove <name>	
/resource-save [filename]	
/scratch [msg]	workspace scratch
/askX <prompt>	workspace LLM query
/AskX <prompt>	global LLM query
/models	list profiles
/help	list chat commands

Ingest

Ingest from URL

```
arc ingest https://example.com/article

# Ingest from local file
arc ingest ~/papers/paper.pdf

# Ingest with collection tag
arc ingest <url> --collection ml

# Ingest without summary (flash only)
arc ingest <url> --no-summary

# Force re-ingest (already exists)
arc ingest <url> --force

# Dry run -> extract only, no write
arc ingest <url> --dry-run
```

Extract / Summarize / Flash

# Extract text only	
arc extract <url>	
# Summarize piped text	
arc extract <url> arc summarize	
# Summarize with style	
arc summarize --style bullets <slug>	
# Generate flash summary	
arc flash <slug>	
# Generate flashcards	
arc flashcards <slug>	
# Write results back to article dir	
arc summarize --write <slug>	
arc flash --write <slug>	

Read

# Read flash summary	
arc read <slug>	
arc read --flash <slug>	
# Read full summary	
arc read --summary <slug>	
# Read flashcards	
arc read --flashcards <slug>	
# Read raw extracted text	
arc read --body <slug>	

List & Search

# List all articles	
arc list	

```
# List agent-ingested only
arc list --agent

# List from specific run
arc list --agent-run <run-id>

# List slugs only (for scripting)
arc list --slugs

# Full-text search
arc search "attention mechanism"

# Search with limit
arc search "golang concurrency" -n 20
```

Reprocess & Reindex

```
# Reprocess flash only
arc reprocess <slug> \
  --no-summary --no-flashcards --no-embed

# Reprocess missing only (skip existing)
arc reprocess <slug> --missing

# Rebuild search index
arc reindex
```

Collections

```
# List / create / delete
arc collections list
arc collections create ml
arc collections delete ml

# Add / remove article
arc collections add <slug> ml
arc collections remove <slug> ml

# Show articles in collection
arc collections show ml

# Set description / rename
arc collections describe ml "ML papers"
arc collections rename ml machine-learning

# Read flashes / summaries across collection
arc collections read ml
arc collections read ml --summary

# AI-suggest collections
arc collections suggest
arc collections suggest --apply
```

Workspaces

```
# Create / list / show / delete
arc workspace new <name> "description"
arc workspace list
arc workspace show <name>
arc workspace delete <name>

# Add content
arc workspace add <name> --article <slug>
arc workspace add <name> --collection <slug>

# Resources
arc workspace resource add <name> <file>
arc workspace resource add <name> <url>

# System prompt
arc workspace system set <name> "You are..."
```

Workspace Chat (CLI)

```
# Start interactive chat REPL
arc workspace chat <name>

# Chat with specific profile
arc workspace chat <name> --profile opus

# Clear history before starting
arc workspace chat <name> --clear
```

Chat Config

```
# Show config
arc workspace chat-config <name>

# Set fields
arc workspace chat-config <name> \
  --profile sonnet
arc workspace chat-config <name> \
  --max-output-tokens 2048
arc workspace chat-config <name> \
  --max-user-messages 20

# Global template: ~/.arc/config.json "chat"
# Per-workspace:
#   ~/.arc/workspaces/<name>/chat/chat.json
```

Agent

```
# Run feed agent (one cycle)
arc agent run

# Dry run -> filter only, no ingest
arc agent run --dry-run

# Run with temporary focus
arc agent run \
  --focus "Kubernetes performance"
```

```
# Process decisions file
arc agent run \
  --decisions ~/.arc/agent/decisions-<id>.json

# View run history
arc agent log
arc agent log -n 5

# Per-feed signal/noise stats
arc agent stats

# Print digest for last run
arc agent digest
arc agent digest --run <run-id>
arc agent digest --tts
```

Decisions File Workflow

```
# 1. Edit decisions file:
#   change action:"- to action:+"
vi ~/.arc/agent/decisions-<run-id>.json

# 2. Process overrides
arc-digest-rerun <run-id>

# Or interactive fzf review
arc-digest-review [run-id]
```

Email Scripts

```
# Run agent (no email)
arc-digest

# Send digest email for run(s)
arc-digest-email
arc-digest-email <run-id>

# Run decisions + ingest overrides
arc-digest-rerun [run-id]

# Full morning chain (launchd)
arc-digest && arc-digest-email
```

Other Commands

arc open <slug>	# open URL in browser
arc delete <slug>	# delete article
arc stats	# show library stats
arc profiles	# list LLM profiles + pricing
arc config	# print resolved config
arc mcp	# start MCP server
arc init	# initialise arc

Key Paths

~/.arc/articles/<slug>/	# article data
~/.arc/collections/	# collection symlinks
~/.arc/workspaces/<name>/	# workspace root

chat/chat.json	#	chat config
chat/history.json	#	conversation history
system.txt	#	system prompt
resources/	#	uploaded files
outcomes/	#	saved transcripts
~/.arc/agent/runs.jsonl	#	run history
~/.arc/agent/decisions-*	#	decisions files
~/.arc/config.json	#	main config

~/.arc/events.jsonl	#	LLM cost events
---------------------	---	-----------------

Global Flags

--config <file>	config file path
--data-root <dir>	arc data root
--log-level debug	verbose logging
--json	JSON output

Environment Variables

ARC_ANTHROPIC_API_KEY	Anthropic API key
ARC_RECIPIENT	digest email recipient
ARC_FROM	digest email sender
ARC	arc binary path