

Arc Cheat Sheet

Personal Knowledge Engine

Ingest

```
# Ingest from URL
arc ingest https://example.com/article

# Ingest from local file
arc ingest ~/papers/paper.pdf

# Ingest with collection tag
arc ingest <url> --collection ml

# Ingest without summary (flash only)
arc ingest <url> --no-summary

# Force re-ingest (already exists)
arc ingest <url> --force

# Dry run -> extract only, no write
arc ingest <url> --dry-run
```

Extract / Summarize / Flash

```
# Extract text only
arc extract <url>

# Summarize piped text
arc extract <url> | arc summarize

# Summarize with style
arc summarize --style bullets <slug>

# Generate flash summary
arc flash <slug>

# Generate flashcards
arc flashcards <slug>

# Write results back to article dir
arc summarize --write <slug>
arc flash --write <slug>
```

Read

```
# Read flash summary
arc read <slug>
arc read --flash <slug>

# Read full summary
arc read --summary <slug>

# Read flashcards
arc read --flashcards <slug>

# Read raw extracted text
arc read --body <slug>
```

List & Search

```
# List all articles
arc list

# List agent-ingested only
arc list --agent

# List from specific run
arc list --agent-run <run-id>

# List slugs only (for scripting)
arc list --slugs

# Full-text search
arc search "attention mechanism"

# Search with limit
arc search "golang concurrency" -n 20
```

Reprocess & Reindex

```
# Reprocess flash only
arc reprocess <slug> \
  --no-summary --no-flashcards --no-embed

# Reprocess missing flash across run
arc list --agent-run <run-id> --slugs | \
  xargs -I{} arc reprocess {} \
  --no-summary --no-flashcards --no-embed

# Reprocess missing only (skip existing)
arc reprocess <slug> --missing

# Rebuild search index
arc reindex
```

Collections

```
# List all collections
arc collections list

# Create collection
arc collections create ml

# Add article to collection
arc collections add <slug> ml

# Remove from collection
arc collections remove <slug> ml

# Show articles in collection
arc collections show ml

# Show collections for an article
arc collections show <slug>

# Set description
```

```
arc collections describe ml "ML papers"

# Rename
arc collections rename ml machine-learning

# Delete (--purge removes articles too)
arc collections delete ml

# Read flashes across collection
arc collections read ml

# Read summaries
arc collections read ml --summary

# AI-suggest collections
arc collections suggest
arc collections suggest --apply

# Search within collections
arc collections read ml --search "transformers"
```

Workspaces

```
# Create workspace
arc workspace new <name> "description"

# List workspaces
arc workspace list

# Show workspace detail
arc workspace show <name>

# Add articles / collections
arc workspace add <name> --article <slug>
arc workspace add <name> --collection <slug>

# Add resource file or URL
arc workspace resource add <name> <file>
arc workspace resource add <name> <url>

# Set system prompt
arc workspace system set <name> "You are..."

# Archive / delete
arc workspace archive <name>
arc workspace delete <name>
```

Workspace Chat

```
# Start interactive chat REPL
arc workspace chat <name>

# Chat with specific profile
arc workspace chat <name> --profile opus

# Chat with strategy override
arc workspace chat <name> \
  --strategy token-budget \
```

```
--context-limit 8000

# Clear history before starting
arc workspace chat <name> --clear

# In-session slash commands:
# /clear      clear conversation history
# /history    show turn count + token usage
# /stats      session token + cost summary
# /system     show system prompt
# /save [file] save transcript to outcomes/
# /help       list commands
# /exit       quit
```

Chat Config

```
# Show config with descriptions
arc workspace chat-config <name>

# Set fields
arc workspace chat-config <name> \
  --profile sonnet
arc workspace chat-config <name> \
  --strategy token-budget \
  --context-limit 8000
arc workspace chat-config <name> \
  --max-output-tokens 2048
arc workspace chat-config <name> \
  --max-user-messages 20
arc workspace chat-config <name> \
  --summarizer-profile haiku \
  --verbatim-ratio 0.3

# Global template (copied on workspace new):
# ~/.arc/config.json "chat" section

# Per-workspace live config:
# ~/.arc/workspaces/<name>/chat/chat.json
```

Agent

```
# Run feed agent (one cycle)
arc agent run

# Dry run -> filter only, no ingest
arc agent run --dry-run

# Run with temporary focus
arc agent run \
  --focus "Kubernetes performance"

# Process decisions file
arc agent run \
  --decisions ~/.arc/agent/decisions-<id>.json

# View run history
arc agent log
arc agent log -n 5

# Per-feed signal/noise stats
arc agent stats

# Print digest for last run
arc agent digest

# Digest for specific run
arc agent digest --run <run-id>

# TTS-friendly digest (no URLs/unicode)
arc agent digest --tts

# Include full summaries
arc agent digest --summary
```

Decisions File Workflow

```
# 1. Edit decisions file:
#   change action:"- " to action: "+"
#   on items to promote (status:"pending")
vi ~/.arc/agent/decisions-<run-id>.json

# 2. Process overrides
arc-digest-rerun <run-id>

# Or interactive fzf review
arc-digest-review [run-id]
```

Email Scripts

```
# Run agent (no email)
arc-digest

# Send digest email for run(s)
arc-digest-email
arc-digest-email <run-id>
arc-digest-email <daily-id> <rerun-id>
```

```
# Run decisions + ingest overrides
arc-digest-rerun [run-id]

# Full morning chain (launchd)
arc-digest && arc-digest-email
```

Other Commands

```
# Open source URL in browser
arc open <slug>

# Delete article
arc delete <slug>

# Delete by run
arc delete --agent-run <run-id>

# Dry run delete
arc delete <slug> --dry-run

# Show stats
arc stats

# List LLM profiles + pricing
arc profiles

# Print resolved config
arc config

# Start MCP server
arc mcp

# Initialize arc
arc init
```

Key Paths

~/.arc/articles/<slug>/	# article data
~/.arc/collections/	# collection symlinks
~/.arc/workspaces/<name>/	# workspace root
chat/chat.json	# chat config
chat/history.json	# conversation history
system.txt	# system prompt
articles/	# article symlinks
resources/	# uploaded files
outcomes/	# saved transcripts
~/.arc/agent/runs.jsonl	# run history
~/.arc/agent/decisions-*	# decisions files
~/.arc/config.json	# main config
~/.arc/agent/config.json	# agent config

Global Flags

--config <file>	config file path
--data-root <dir>	arc data root
--articles-root <dir>	articles directory
--json	JSON output

Environment Variables

ARC_ANTHROPIC_API_KEY Anthropic API key

ARC_RECIPIENT digest email recipient
ARC_FROM digest email sender

ARC arc binary path
ARC_AGENT_DIR agent directory