


Temperture Range:-40°C to+105°C



Technical drawing of a 2x10 grid of holes. The drawing shows two rows of ten holes each. The horizontal distance between the center of the first hole and the center of the fourth hole in the top row is dimensioned as 2.0 ± 0.05 . The vertical distance between the center of a hole in the top row and the center of a hole in the bottom row is dimensioned as 2.0 . The diameter of each hole is dimensioned as $\varnothing 0.8 \pm 0.05$. A green wavy line is drawn on the left side of the grid, and a green arrow points to the top-left corner of the grid.

ITEM	D		H			C	
Standard	0		4.0	4.3	4.5	2.8	3.3
Alternate							

					operatlop		SCALE		Fit		 深圳市镁旺电子科技有限公司 Shenzhen Meiwang Electronic Technology Co.,ltd.	
					X.X	±0.25	UNIT		MM			
					X.XX	±0.20	SIZE	A4	DFSIGH	江泽富	PART NO.	F2XX-12XXXXXSUX0
					X.XXX	±0.10						
					Angle	±3°	SHEET	1/1	CHECK		TITLE:	2.0MM双排母 180度 U型镀金/PA6T料黑色
REV	DATE	MODIFICATION DESCRIPTION	CHANGE	APPROVE	DIM	TOL	PROJ.		APPROLE		Customer No.	