

[ABOUT](#) [INDEX](#) [CONTACT](#)[HOME](#)[SAS](#)[R](#)[PYTHON](#)[DATA SCIENCE](#)[CREDIT RISK](#)[SQL](#)[EXCEL](#)[SPSS](#)[INFOGRAPHICS](#)

SEARCH...

GO

[Home](#) » [SAS](#) » Check number of observations in SAS dataset

## CHECK NUMBER OF OBSERVATIONS IN SAS DATASET

 Deepanshu Bhalla  7 Comments  SAS

This post explains how to determine the number of observations in a SAS dataset. Most of the times we need to check whether a SAS dataset is empty or not. In macro, we generally tell SAS to go to the next iteration only when SAS dataset is non-empty. In this post, we will see various methods to count number of rows (records) in SAS table.

### Get Free Email Updates

Join us with 5000+ Subscribers

 Follow us on **Facebook**

♥ Love this Post? Spread the Word!

 Share Share Tweet Subscribe

## Efficient)

In the example below, we will use **CARS** dataset from **SASHELP** library. This dataset contains 428 observations and 15 columns.

The easiest method is to use **count(\*)** in Proc SQL. It returns all rows (missing plus non-missing rows) in a dataset.

```
proc sql;  
  select count(*) as N from  
  sashelp.cars;  
quit;
```

**Result : 428**

In case you want to store it in a macro variable, you can use **INTO :** keyword.

```
proc sql noprint;  
  select count(*) into :N from  
  sashelp.cars;
```

♥ Love this Post? Spread the Word!

f Share

in Share

🐦 Tweet

✉ Subscribe



```
%put &N;
```

This will print the number of records in SAS log.  
Check log after running the above program.

## Is it an efficient method?

*No, it is not efficient at all. It does not use metadata information of SAS dataset. Instead it reads through each record (row) of your SAS dataset. It takes a long time to do it in big SAS tables. However, it is a simple and handy trick to calculate the number of rows in a SAS dataset.*

## Method 2 : Descriptor Portion (Efficient)

Before getting into detail, we need to understand

♥ Love this Post? Spread the Word!

f Share

in Share

🐦 Tweet

✉ Subscribe



**SAS dataset consists of the following two portion -**

1. **Descriptor portion.** It constitutes information about name of dataset, number of observations and variables, creation date, engine type.
2. **Data portion.** It stores values of data.

This method is one of the **most efficient way to count observations** in a SAS table as it uses metadata information and does not search in dataset.

```
data _NULL_;  
  if 0 then set sashelp.cars  
nobs=n;  
  put "no. of observations =" n;  
  stop;  
run;
```

### Explanation

1. The '**if 0**' statement does not process at execution time because IF statement

♥ Love this Post? Spread the Word!

f Share

in Share

🐦 Tweet

✉ Subscribe



information of the data set and later hand over to the compiler to adjust it to the PDV.

2. **NOBS** is a SAS automatic variable which contains the number of rows in a dataset i.e. SASHELP.CARS dataset.
3. **NOBS = N** puts the returns count of records in the variable n.
4. The **STOP statement** is used to stop an endless loop.

Like the first method, we can keep it in a macro variable. See the implementation below -

```
data _NULL_;  
  if 0 then set sashelp.cars  
  nobs=n;  
  call symputx('totobs',n);  
  stop;  
run;  
%put no. of observations =  
&totobs;
```

♥ Love this Post? Spread the Word!

f Share

in Share

🐦 Tweet

✉ Subscribe



## SAS Output

**CALL SYMPUT** is one of the method to create a SAS macro variable in data step. In this case, we have used a newer function i.e. **CALL SYMPUTX** which left justifies and trims trailing blanks from a numeric value. If you want to stick to the old style **CALL SYMPUT**, you can write like below -

```
call symput('totobs',left(n));
```

### 3. Proc SQL Dictionary Method (Efficient)

Like second method, we can use metadata information of a dataset with PROC SQL **Dictionary.Tables**.

```
proc sql noprint;  
  select nobs into :totobs  
  separated by ' ' from
```

♥ Love this Post? Spread the Word!

f Share

in Share

🐦 Tweet

✉ Subscribe



```
memname='CARS';  
quit;  
%put total records = &totobs.;
```

```
67          %put total records = &totobs.;  
total records = 428
```

Proc SQL Dictionary.Tables

It is an efficient method as it does not look into each values of a dataset to determine the count. The **LIBNAME=** refers to the name of the library in which data is stored. The **MEMNAME=** refers to SAS table (dataset). The separated by ' ' is used in this case to left align the numeric value.

#### 4. Macro Language Method (Efficient)

This method also uses metadata information but it is via the macro language using DATA step functions. The **OPEN function** is used to open a data. The **ATTRN function** returns the value of a numeric attribute for a SAS data set. When it is

♥ Love this Post? Spread the Word!

f Share

in Share

🐦 Tweet

✉ Subscribe



number of observations. Later we are closing the opened dataset using **CLOSE function**.

```
%macro totobs(mydata);  
  %let mydataID=%sysfunc(OPEN  
(&mydata.,IN));  
  %let NOBS=%sysfunc(ATTRN  
(&mydataID,NOBS));  
  %let RC=%sysfunc(CLOSE  
(&mydataID));  
  &NOBS  
%mend;  
%put %totobs(sashelp.cars);
```

## SAS : Check if it is empty table

Suppose you only need to check whether a table is empty or not. You can use the same logic as explained above. And if the returned value is 0, write 'Empty Data' in log. Otherwise, count the number of records.

♥ Love this Post? Spread the Word!

f Share

in Share

🐦 Tweet

✉ Subscribe





```
if n = 0 then put 'empty dataset';  
else put 'Not empty. Total  
records=' n;  
stop;  
run;
```

**Result :** Not Empty. Total records = 428

***Let's create a blank dataset to check the above code. The following program returns empty dataset as 1=2 condition does not meet.***

```
proc sql noprint;  
create table temp as  
select * from sashelp.cars  
where 1 = 2;  
quit;
```

**Try it yourself!**

***Let's wrap the above code in a SAS macro***

```
%macro emntvdataset
```

♥ Love this Post? Spread the Word!

f Share

in Share

🐦 Tweet

✉ Subscribe



```
data _NULL_;  
  if 0 then set &inputdata. nobs=n;  
  call symputx('totobs',n);  
  stop;  
run;  
%if &totobs. = 0 %then %put Empty  
dataset;  
%else %do;  
  %put TotalObs=&totobs;  
%end;  
%mend;
```

```
%emptydataset(inputdata=sashelp.cars);
```

**Result :** TotalObs=428

```
%emptydataset(inputdata=work.temp);
```

**Result :** Empty dataset

**If you think it's difficult to memorize sas code of descriptor portion method, you can use the code below.**

```
data _NULL_;  
  set sashelp.cars nobs=N;
```

♥ Love this Post? Spread the Word!

f Share

in Share

🐦 Tweet

✉ Subscribe



```
put N;  
run;
```

```
data _NULL_;  
set sashelp.cars nobs=N;  
if _N_ = 2 then stop;  
put N;  
run;
```

There were 2 observations read from the data set SASHELP.CARS.

SAS log

It reads only first two observations from the dataset. See log above.

**SAS Tutorials :** [100 Free SAS Tutorials](#)

 **SUBSCRIBE TO GET EMAIL UPDATES!**

## Related Posts

- [Extract last 4 characters / digits of value in SAS](#)
- [SAS : Calculate AUC of Validation Data](#)
- [Detecting Interaction in Regression Model](#)

♥ Love this Post? Spread the Word!

 Share

 Share

 Tweet

 Subscribe



- Predictive Modeling Interview Questions and Answers

### About Author:



Deepanshu founded ListenData with a simple objective - Make anal easy to understand and follow. He has over 8 years of experience in science. During his tenure, he has worked with global clients in various domains like Banking, Insurance, Telecom and Human Resource.

While I love having friends who agree, I only learn from those who don't  
Let's Get Connected: [Email](#) | [LinkedIn](#)

## 7 Responses to "Check number of observations in SAS dataset"



**Hanish Arora** 1 May 2017 at 00:56

Hi,  
Can you please help me in deleting all the empty data sets of any library without opening it or how to check if particular data set is empty or not.

Thanks

[Reply](#)

▼ [Replies](#)



**Arun** 9 May 2017 at 14:28

Create macro var from proc SQL and use dictionary.tables where nobs=0 then use proc datasets and after delete values use ref to that macro var

♥ Love this Post? Spread the Word!

[f](#) Share

[in](#) Share

[t](#) Tweet

[✉](#) Subscribe



[Reply](#)**Juan V.** 14 May 2017 at 05:24

Hi Deepanshu, very useful post

I have a question about "model scoring" task. I have created and registered a model in Enterprise Miner, now I am scoring this model from Enterprise Guide using "model scoring" task. In the output variables of the model I have three types of var: P\_targetvar Q\_targetvar U\_targetvar V\_targetvar

I think that P\_targetvar is the predicted value for target variable of the model, but I would like to know the meaning of Q\_, U\_ and V\_ vars.

Another question I would like to know if I can define and use a Enterprise Miner model with parameters. I mean not only the vars of the dataset, this parameters would be about the type of model (selection criteria, type of decision tree...)

Thanks in advance

Juan

[Reply](#)**Unknown** 15 October 2017 at 20:37

Thnaks good presentation

[Reply](#)**Pavan Kumar** 23 August 2018 at 06:05

Excellent site for knowing SAS knowledge. :)

[Reply](#)**Unknown** 30 April 2019 at 09:06

Very Informative

**Love this Post? Spread the Word!**

Share

 Share

Tweet



Subscribe





← PREV    NEXT →

---

Copyright 2019 [ListenData](#)

♥ Love this Post? Spread the Word!

[f Share](#)[in Share](#)[t Tweet](#)[✉ Subscribe](#)