

## CMISS Function

---

Counts the number of missing arguments.

Categories: CAS

Descriptive Statistics

### Table of Contents

Syntax

Arguments

Details

Example

See Also

---

## Syntax

**CMISS**(*argument* [, ...*argument*,])

## Arguments

***argument***

specifies a constant, variable, or expression. *argument* can be either a character value or a numeric value.

---

## Details

A character expression is counted as missing if it evaluates to a string that contains all blanks or has a length of zero, except when you use the CMISS function in macro processing. A numeric expression is counted as missing if it evaluates to a numeric missing value: ., .\_, .A, ... , .Z.

When you use the CMISS function in macro processing, use a period (.) to represent both a character and a numeric missing value. If you use a blank or null value for a character argument, SAS returns an error. Here are three examples that result in an error:

```
%let macvar=%sysfunc(cmiss(A,%str( )));  
%let macvar=%sysfunc(cmiss(A, ));  
%let macvar=%sysfunc(cmiss(A,));
```


Here is the example to use to avoid the error condition:

```
%let macvar=%sysfunc(cmiss(A,.));
```

---

## Example

The following program illustrates the CMISS function:

```
 data test (overwrite=yes);  
    dcl char a b;  
    method run();  
        a=cmiss(1,0, ' ' , 2,5,' ');  
        b=cmiss(1, ' ');  
        put 'a=' a;  
        put 'b=' b;  
    end;  
enddata;  
run;
```

SAS writes the following output to the log.

```
a= 2  
b= 1
```

---

## See Also

### Functions:

MISSING Function

NMISS Function

---

Copyright © SAS Institute Inc. All Rights Reserved.  
Last updated: September 25, 2020