



#### 3 HOME > PYTHON > HOW TO CREATE FUNCTION IN PYTHON

Last updated on February 4th, 2017 by Yogesh Singh

## How to create function in Python

A function is a block of code which performs some specific task and returns back to the caller. It has a unique name.



They are helpful when need to perform the same task with differentdifferent values or require to use the same block of code in other places within the program.

If any changes require in the future then only need to update the function code and it will automatically make change where the function it been called.

The main aim of a function is -





# Contents

- 1. Defining a function
- 2. Calling a function
- 3. Function with parameter
- 4. Function with return
- 5. Default value
- 6. Multiple parameter

3

# 1. Defining a function

To create function def keyword is use in Python. Define a unique name for the function and in parenthesis, you can specify your parameters.

Function block starts with colon(:) symbol.

#### Syntax -

```
def function-name(paramenter):
    # statement
```

#### **Example**

```
def callMe():
   print("Function is called")
```

In above example, I have created a callMe() function which not take any arguments. It print text on the screen when it called.

# 2. Calling a function

Specify the function name and specify the parameters in parentensis () if its takes. After completing the task it return back to the program.

#### Syntax -

3

```
def function-name(parameter): # defining function
    # statement
function-name(parameter) # calling function
```

#### **Example**

```
def callMe():
    print("Function is called")

callMe()
callMe()
```

#### **Output**

```
Function is called Function is called
```

# 3. Function with parameter

3 Specify the parameter in the function if you want to perform the task with different-different parameters.

#### Syntax -

```
def function-name(parameter):
    # statement
function-name(parameter)
```

#### **Example**

```
def checkevenOrodd(num):
    if num%2 == 0:
    print("Even number")
    else:
    print("Odd number")

checkevenOrodd(2)
checkevenOrodd(5)
checkevenOrodd(8)
```

#### **Output**

```
Even number
Odd number
Even number
```

## 4. Function with return

Use return statement to return value from the function to the caller.

3

#### Syntax -

```
def function-name(paramenter):
    # statement
    return value
```

#### **Example**

```
def maxlist(list1):
    max = list1[0]
    for l in list1:
    if l > max:
    max = l
    return max

list1 = [1,55,23,2]
list2 = [4,24,78,6,21]

print("max value in list1 is ",maxlist(list1))
print("max value in list2 is ",maxlist(list2))
```

Above I create function maxlist() which returns max value from the list.

#### Output

```
max value in list1 is 55
max value in list2 is 78
```

3

# 5. Default value

Default parameter automatically supplies value even if you don't supply value while calling the function. Default argument declaration starts from right to left.

#### Syntax -

```
def function-name(variable=value,variable=value,...):
    # statement
```

#### **Example**

```
def displayInfo(fname,lname="Singh",age=22):
    print("first name : ",fname,", last name : ",lname,"

displayInfo("Yogesh")
displayInfo("Vishal",age=24) # Changing age default value displayInfo("Mohit","Sharma")
```

Above I specify the default value in 1name and age variable. If this variables values not defined while calling then it will use the default set value.

#### **Output**

3

```
first name : Yogesh , last name = Singh , age : 22
first name : Vishal , last name = Singh , age : 24
first name : Mohit , last name = Sharma , age : 22
```

6. Multiple parameter

For handling an unknown amount of items to function we use a asterisk (\*) symbol in function. It holds as many values in a single argument.

#### Syntax -

```
def function-name(*argument):
    # statement
```

#### **Example**

```
def display(name,*friends):
    print("name : ",name)
    print("friends : ",friends)

display("Yogesh singh","Sonarika","Vishal","Vijay")
display("Jiten singh","Mohit","Ajay","Abhilash","Gane:
```

I defined asterisk (\*) on the second argument. When the function is called then the first paremeter goes to name variable and all other parameters goes to friends variable.

It converts the friends argument into a tuple.

3

#### **Output**

```
name : Yogesh singh
friends : ('Sonarika','Vishal','Vijay')
name : Jiten singh
friends : ('Mohit','Ajay','Abhilash','Ganesh','Aditya
```

## Related posts:

Looping statement in Python Dictionary in Python

Loop control statements in Python

#### **Spread the love**

#### **Previous Post**

Loop control statements in Python

#### **Next Post**

3

How to install Node.js on Windows

### Yogesh Singh

Yogesh Singh is a web developer and founder of makitweb . He mainly blogs about PHP, AJAX, JavaScript, jQuery, AngularJS, Database, Python, and something that interest him.

**PYTHON** 

FUNCTION

## Be First to Comment

## Leave a Reply

Your email address will not be published. Required fields are marked \*

|        | our Comment                    |            |            |      |  |
|--------|--------------------------------|------------|------------|------|--|
|        |                                |            |            |      |  |
|        |                                |            |            |      |  |
|        |                                |            |            |      |  |
| Your N | ame*                           |            |            |      |  |
| V      |                                |            |            |      |  |
| Your E | mail*                          |            |            |      |  |
|        |                                |            |            |      |  |
| Your U | RL (optional)                  |            |            |      |  |
|        | RL (optional) ify me of follow | v-up comme | ents by em | ail. |  |
| □ Not  |                                |            |            | ail. |  |
| □ Not  | ify me of follov               |            |            | ail. |  |
| □ Not  | ify me of follov               |            |            | ail. |  |
| □ Not  | ify me of follov               |            |            | ail. |  |
| □ Not  | ify me of follov               |            |            | ail. |  |
| □ Not  | ify me of follov               |            |            | ail. |  |

#### **RECENT POSTS**

|   | Dynamically load data in Select2 with AJAX PDO and PHP |  |  |  |  |
|---|--|--|--|--|--|
| 3 | How to Auto populate dropdown with AJAX PDO and PHP    |  |  |  |  |
|   | Top 5 jQuery Techniques to Enhance User Experience     |  |  |  |  |
|   | Ember vs. Vue: Which Framework Suits You?              |  |  |  |  |
|   | Filter records by Date range with Vue and PHP          |  |  |  |  |

#### **CATEGORIES**

PHP

| AJAX        |  |  |
|-------------|--|--|
| AngularJS   |  |  |
| Codelgniter |  |  |
| DataBase    |  |  |
| How To      |  |  |
| Javascript  |  |  |
| JQuery      |  |  |
| Laravel     |  |  |
| Phonegap    |  |  |
|             |  |  |

| Python |  |  |  |
|--------|--|--|--|
| Vue.js |  |  |  |

WordPress



3



# Subscribe to Blog via Email

Join 5,000+ other subscribers.

Email address

f 💆 🖸 in 🖗

Home About Privacy Policy Contact Sitemap

3

Select Language ▼