```
import { useState, useEffect, useCallback, useRef } from "react";

/* ═══════════════════════════════════════════════════════════════
   DEALHUNTER — Global AI Price Hunter
   v1.0 Launch Build
   Markets: NZ · AU · UK · USA · Global
═══════════════════════════════════════════════════════════════ */

// ─── Storage ──────────────────────────────────────────────────
const DB = {
  get: (k, d) => { try { const v = localStorage.getItem(k); return v ? JSON.parse
  set: (k, v) => { try { localStorage.setItem(k, JSON.stringify(v)); } catch {} }
};
function usePersist(key, init) {
  const [val, setVal] = useState(() => DB.get(key, init));
  const save = useCallback(fn => {
    setVal(prev => { const next = typeof fn === "function" ? fn(prev) : fn; DB.se
  }, [key]);
  return [val, save];
}

// ─── Market Config ────────────────────────────────────────────
const MARKETS = {
  NZ: {
    flag: "🇳🇿", name: "New Zealand", currency: "NZD", symbol: "$",
    platforms: ["TradeMe", "Facebook Marketplace NZ", "Gumtree NZ", "Bunnings NZ"
    timezone: "Pacific/Auckland"
  },
  AU: {
    flag: "🇦🇺", name: "Australia", currency: "AUD", symbol: "$",
    platforms: ["Gumtree AU", "Facebook Marketplace AU", "eBay AU", "Bunnings AU"
    timezone: "Australia/Sydney"
  },
  UK: {
    flag: "🇬🇧", name: "United Kingdom", currency: "GBP", symbol: "£",
    platforms: ["Gumtree UK", "Facebook Marketplace UK", "eBay UK", "Freecycle UK
    timezone: "Europe/London"
  },
  US: {
    flag: "🇺🇸", name: "United States", currency: "USD", symbol: "$",
    platforms: ["Craigslist", "Facebook Marketplace US", "eBay", "OfferUp", "Next
    timezone: "America/New_York"
  },
};
```

```
const CATS = [
  { id: "timber",    label: "Timber & Sheet",  emoji: "🪵", color: "#3d2a0f" },
  { id: "tools",     label: "Tools",            emoji: "🔧", color: "#0f2a3d" },
  { id: "hardware",  label: "Hardware",         emoji: "⚙️",  color: "#1a2a1a" },
  { id: "joinery",   label: "Joinery",          emoji: "🚪", color: "#2a1a2a" },
  { id: "paint",     label: "Paint",            emoji: "🖌️", color: "#2a2a0f" },
  { id: "electrical",label: "Electrical",       emoji: "⚡", color: "#2a1a00" },
  { id: "plumbing",  label: "Plumbing",         emoji: "🔩", color: "#002a2a" },
  { id: "appliances",label: "Appliances",       emoji: "🏠", color: "#1a0a2a" },
  { id: "furniture", label: "Furniture",        emoji: "🛋️", color: "#2a1000" },
  { id: "garden",    label: "Garden",           emoji: "🌿", color: "#0a2a0a" },
  { id: "vehicles",  label: "Vehicles & Parts", emoji: "🚗", color: "#0f0f2a" },
  { id: "other",     label: "Other",            emoji: "📦", color: "#1a1a1a" },
];

const PLANS = {
  free:  { name: "Free",    price: 0,   scansPerDay: 3,  watchlistLimit: 5,  comm
  pro:   { name: "Pro",     price: 9,   scansPerDay: 50, watchlistLimit: 50, comm
  teams: { name: "Teams",   price: 29,  scansPerDay: 999,watchlistLimit: 500,comm
};

// ── Tiny Utilities ──────────────────────────────────────────────
function timeAgo(iso) {
  if (!iso) return "";
  const s = (Date.now() - new Date(iso)) / 1000;
  if (s < 60) return "just now";
  if (s < 3600) return `${Math.floor(s/60)}m ago`;
  if (s < 86400) return `${Math.floor(s/3600)}h ago`;
  return `${Math.floor(s/86400)}d ago`;
}
function fmtPrice(price, market) {
  if (!price || price === "Not Found") return null;
  return price;
}
function clamp(v, lo, hi) { return Math.max(lo, Math.min(hi, v)); }

// ── CSS Injection ───────────────────────────────────────────────
const CSS = `
  @import url('https://fonts.googleapis.com/css2?family=Bricolage+Grotesque:opsz,
  *, *::before, *::after { box-sizing: border-box; margin: 0; padding: 0; }
  :root {
    --bg: #060a07; --surface: #0b110d; --surface2: #0f1711; --border: #162019;
    --border2: #1e2e22; --text: #e2ede6; --text2: #7a9e82; --text3: #3a5440;
    --accent: #3ddc84; --accent2: #2ab86a; --accent-dim: #1a3d28;
    --amber: #f59e0b; --red: #ef4444; --blue: #3b82f6;
    --pro: #f59e0b; --pro-dim: #2a1f08;
```

```
    --r: 16px; --r-sm: 10px; --r-lg: 24px;
  }
  body { background: var(--bg); color: var(--text); font-family: 'Bricolage Grote
  input, select, textarea {
    background: var(--surface2); border: 1.5px solid var(--border2); color: var(-
    border-radius: var(--r-sm); padding: 12px 14px; font-family: inherit; font-si
    outline: none; transition: border-color .2s, box-shadow .2s; width: 100%;
  }
  input:focus, select:focus, textarea:focus {
    border-color: var(--accent2); box-shadow: 0 0 0 3px #2ab86a18;
  }
  input::placeholder, textarea::placeholder { color: var(--text3); }
  select option { background: #0f1711; }
  button { cursor: pointer; font-family: inherit; border: none; outline: none; tr
  button:active { transform: scale(.97); }
  a { color: var(--accent2); text-decoration: none; }
  ::-webkit-scrollbar { width: 3px; }
  ::-webkit-scrollbar-thumb { background: var(--border2); border-radius: 2px; }
  -webkit-tap-highlight-color: transparent;

  @keyframes fadeUp   { from { opacity:0; transform:translateY(12px) } to { opaci
  @keyframes fadeIn   { from { opacity:0 } to { opacity:1 } }
  @keyframes pop      { from { opacity:0; transform:scale(.94) } to { opacity:1;
  @keyframes spin     { to { transform: rotate(360deg) } }
  @keyframes scanLine { 0%{top:-2px} 100%{top:102%} }
  @keyframes shimmer  { 0%{background-position:-200% 0} 100%{background-position:
  @keyframes pulse    { 0%,100%{opacity:1} 50%{opacity:.4} }
  @keyframes float    { 0%,100%{transform:translateY(0)} 50%{transform:translateY
  @keyframes glow     { 0%,100%{box-shadow:0 0 20px #3ddc8422} 50%{box-shadow:0 0
  @keyframes toastSlide { from{transform:translateY(20px);opacity:0} to{transform
  @keyframes badgePop { 0%{transform:scale(0)} 60%{transform:scale(1.3)} 100%{tra
`;

// ═══════════════════════════════════════════════════════════════════
// ROOT APP
// ═══════════════════════════════════════════════════════════════════
export default function App() {
  const [screen, setScreen]         = usePersist("dh2_screen", "landing");
  const [market, setMarket]         = usePersist("dh2_market", "NZ");
  const [plan, setPlan]             = usePersist("dh2_plan", "free");
  const [watchlist, setWatchlist]   = usePersist("dh2_watch", []);
  const [results, setResults]       = usePersist("dh2_results", {});
  const [alerts, setAlerts]         = usePersist("dh2_alerts", []);
  const [community, setCommunity]   = usePersist("dh2_community", SEED_COMMUNITY)
  const [scansToday, setScansToday] = usePersist("dh2_scans", { date: "", count:
  const [scanning, setScanning]     = useState({});
  const [progress, setProgress]     = useState({});
```

```
  const [toast, setToast]           = useState(null);
  const [activeItem, setActiveItem] = useState(null);
  const [modal, setModal]           = useState(null); // "add"|"upgrade"|"market"
  const [shareData, setShareData]   = useState(null);

  const mkt = MARKETS[market] || MARKETS.NZ;
  const currentPlan = PLANS[plan] || PLANS.free;
  const unreadAlerts = alerts.filter(a => !a.read).length;

  // Scan counter (resets daily)
  const todayStr = new Date().toISOString().slice(0, 10);
  const scansLeft = currentPlan.scansPerDay - (scansToday.date === todayStr ? sca

  const showToast = useCallback((msg, type = "success", duration = 3000) => {
    setToast({ msg, type, id: Date.now() });
    setTimeout(() => setToast(null), duration);
  }, []);

  // ── Scan engine ──────────────────────────────────────────────────────
  const runScan = useCallback(async (item) => {
    if (scanning[item.id]) return;
    if (scansLeft <= 0) { setModal("upgrade"); return; }

    setScanning(s => ({ ...s, [item.id]: true }));
    setProgress(p => ({ ...p, [item.id]: 8 }));

    const ticker = setInterval(() => {
      setProgress(p => ({ ...p, [item.id]: clamp((p[item.id] || 8) + Math.random(
    }, 700);

    // Increment scan counter
    setScansToday(prev => ({
      date: todayStr,
      count: (prev.date === todayStr ? prev.count : 0) + 1
    }));

    const itemMarket = MARKETS[item.market || market] || mkt;
    const platformList = itemMarket.platforms.join(", ");

    const prompt = `You are an elite bargain-hunting AI for ${itemMarket.name}. S
Category: ${item.cat} | Budget: ${item.freeOnly ? "FREE ONLY" : item.budget ? `${
${item.notes ? `Buyer context: ${item.notes}` : ""}

Search ${platformList} comprehensively. Find real, current listings. Be specific

Return ONLY valid JSON (zero markdown, zero preamble):
{
```

```
  "headline": "Punchy one-liner on best deal found (mention price and platform)",
  "bestPrice": "${itemMarket.symbol}XX or FREE or Price varies",
  "bestSource": "platform name",
  "priceRange": "e.g. ${itemMarket.symbol}40-${itemMarket.symbol}120",
  "savings": "e.g. 38% below retail or Best free option available",
  "deals": [
    {
      "title": "listing title",
      "price": "${itemMarket.symbol}XX or FREE",
      "originalPrice": "${itemMarket.symbol}XX or null",
      "source": "platform",
      "condition": "New | Used - Good | Used - Fair | Parts Only | Unknown",
      "url": "direct URL or null",
      "location": "city/suburb or null",
      "detail": "one key buying detail",
      "withinBudget": true,
      "hot": false
    }
  ],
  "freeOptions": "description of any free/giveaway options found or null",
  "tip": "single most actionable tip to get this cheaper",
  "urgency": "high | medium | low",
  "alertWorthy": true,
  "shareText": "Ready-to-share one-liner e.g. 'Found a ${itemMarket.symbol}45 Hil
}`;

    try {
      const res = await fetch("https://api.anthropic.com/v1/messages", {
        method: "POST",
        headers: { "Content-Type": "application/json" },
        body: JSON.stringify({
          model: "claude-sonnet-4-20250514",
          max_tokens: 1200,
          tools: [{ type: "web_search_20250305", name: "web_search" }],
          messages: [{ role: "user", content: prompt }]
        })
      });
      const data = await res.json();
      const raw = (data.content || []).filter(b => b.type === "text").map(b => b.
      let parsed = null;
      try { const m = raw.match(/\{[\s\S]*\}/); if (m) parsed = JSON.parse(m[0]);

      clearInterval(ticker);
      setProgress(p => ({ ...p, [item.id]: 100 }));

      const record = { id: Date.now(), itemId: item.id, ts: new Date().toISOStrin
      setResults(prev => ({ ...prev, [item.id]: [record, ...(prev[item.id] || []))
```

```
    if (parsed?.alertWorthy) {
      const newAlert = {
        id: Date.now(), itemId: item.id, itemName: item.name,
        headline: parsed.headline, bestPrice: parsed.bestPrice,
        bestSource: parsed.bestSource, ts: new Date().toISOString(), read: fals
      };
      setAlerts(prev => [newAlert, ...prev].slice(0, 200));

      if (currentPlan.alerts) showToast(`🔔 Deal alert: ${item.name}`, "alert",
      else showToast(`Deal found! Upgrade to Pro for instant alerts`, "pro", 40
    } else {
      showToast(`Scan complete for "${item.name}"`);
    }

    setTimeout(() => {
      setScanning(s => ({ ...s, [item.id]: false }));
      setProgress(p => ({ ...p, [item.id]: 0 }));
    }, 900);

  } catch {
    clearInterval(ticker);
    setScanning(s => ({ ...s, [item.id]: false }));
    setProgress(p => ({ ...p, [item.id]: 0 }));
    showToast("Scan failed — check your connection", "error");
  }
}, [scanning, scansLeft, market, mkt, currentPlan, setResults, setAlerts, setSc

const scanAll = () => {
  const limit = Math.min(watchlist.length, scansLeft);
  if (limit === 0) { setModal("upgrade"); return; }
  watchlist.slice(0, limit).forEach((item, i) => setTimeout(() => runScan(item)
  showToast(`⚡ Scanning ${limit} items…`);
};

const addItem = item => {
  if (watchlist.length >= currentPlan.watchlistLimit) { setModal("upgrade"); re
  setWatchlist(w => [...w, { ...item, id: Date.now(), market, createdAt: new Da
  setModal(null);
  showToast(`"${item.name}" added to watchlist`);
};

const deleteItem = id => {
  setWatchlist(w => w.filter(x => x.id !== id));
  setResults(r => { const n = {...r}; delete n[id]; return n; });
  setActiveItem(null);
  setScreen("hunt");
```

```
  showToast("Item removed");
};

const shareResult = (resultData) => {
  setShareData(resultData);
  setModal("share");
};

const postToCommunity = (post) => {
  setCommunity(prev => [{ ...post, id: Date.now(), ts: new Date().toISOString()
  setModal(null);
  showToast("Shared with the community! 🎉");
};

// Routing
const go = (s, item) => { if (item) setActiveItem(item); setScreen(s); };

return (
  <AppShell
    screen={screen} setScreen={go} market={mkt} marketCode={market}
    plan={currentPlan} unreadAlerts={unreadAlerts}
    watchCount={watchlist.length} scansLeft={scansLeft}
    toast={toast} modal={modal} setModal={setModal}
    onUpgrade={tier => { setPlan(tier); setModal(null); showToast(`Upgraded to
    onMarketChange={code => { setMarket(code); setModal(null); showToast(`Marke
    shareData={shareData} onPostCommunity={postToCommunity}
  >
    {/* ── LANDING ── */}
    {screen === "landing" && (
      <LandingScreen
        onStart={() => setScreen("onboard")}
        market={mkt}
      />
    )}

    {/* ── ONBOARDING ── */}
    {screen === "onboard" && (
      <OnboardScreen onDone={() => { setScreen("hunt"); }} onMarketSelect={code
    )}

    {/* ── HUNT (Main) ── */}
    {screen === "hunt" && (
      <HuntScreen
        watchlist={watchlist} results={results}
        scanning={scanning} progress={progress}
        onScan={runScan} onScanAll={scanAll}
        onAdd={() => setModal("add")}
```

```
    onOpenItem={item => go("item", item)}
    plan={currentPlan} scansLeft={scansLeft}
    market={mkt} setModal={setModal}
    community={community}
    setCommunity={setCommunity}
  />
)}

{/* ── ITEM DETAIL ── */}
{screen === "item" && activeItem && (
  <ItemScreen
    item={activeItem}
    results={results[activeItem.id] || []}
    scanning={scanning[activeItem.id]}
    progress={progress[activeItem.id] || 0}
    onScan={() => runScan(activeItem)}
    onBack={() => go("hunt")}
    onDelete={deleteItem}
    onEdit={updated => { setWatchlist(w => w.map(x => x.id === updated.id ?
    onShare={shareResult}
    market={mkt}
    plan={currentPlan}
    scansLeft={scansLeft}
    setModal={setModal}
  />
)}

{/* ── ALERTS ── */}
{screen === "alerts" && (
  <AlertsScreen
    alerts={alerts} watchlist={watchlist}
    onRead={id => setAlerts(a => a.map(x => x.id === id ? {...x, read:true}
    onReadAll={() => setAlerts(a => a.map(x => ({...x, read:true})))}
    onClear={() => { setAlerts([]); showToast("Cleared"); }}
    onOpenItem={itemId => { const it = watchlist.find(x => x.id === itemId)
    plan={currentPlan} setModal={setModal}
  />
)}

{/* ── COMMUNITY ── */}
{screen === "community" && (
  <CommunityScreen
    community={community} setCommunity={setCommunity}
    plan={currentPlan} setModal={setModal}
    onShare={() => setModal("share")}
    market={market}
  />
```

```
      )}

      {/* ── PROFILE ── */}
      {screen === "profile" && (
        <ProfileScreen
          plan={currentPlan} watchlist={watchlist}
          results={results} alerts={alerts}
          scansLeft={scansLeft} scansToday={scansToday}
          market={mkt} marketCode={market}
          setModal={setModal}
          onReset={() => { setWatchlist([]); setResults({}); setAlerts([]); showT
        />
      )}

      {/* ── MODALS ── */}
      {modal === "add" && <AddModal onSave={addItem} onClose={() => setModal(null
      {modal === "upgrade" && <UpgradeModal onClose={() => setModal(null)} onUpgr
      {modal === "market" && <MarketModal onClose={() => setModal(null)} current=
      {modal === "share" && <ShareModal data={shareData} onPost={postToCommunity}
    </AppShell>
  );
}

// ═══════════════════════════════════════════════════════════════════
// APP SHELL
// ═══════════════════════════════════════════════════════════════════
function AppShell({ children, screen, setScreen, market, marketCode, plan, unread
  const isLanding = screen === "landing" || screen === "onboard";
  const NAV = [
    { id: "hunt",      icon: "◈",  label: "Hunt",      badge: watchCount },
    { id: "alerts",    icon: "◉",  label: "Alerts",    badge: unreadAlerts },
    { id: "community", icon: "○",  label: "Community", badge: 0 },
    { id: "profile",   icon: "◎",  label: "Profile",   badge: 0 },
  ];

  return (
    <div style={{ minHeight: "100vh", background: "var(--bg)", maxWidth: 520, mar
      <style>{CSS}</style>

      {/* Market + Scan counter bar */}
      {!isLanding && screen !== "item" && (
        <div style={{ display: "flex", justifyContent: "space-between", alignItem
          <button onClick={() => setModal("market")} style={{
            background: "var(--surface2)", border: "1px solid var(--border2)",
            borderRadius: 20, padding: "5px 12px 5px 8px",
            display: "flex", alignItems: "center", gap: 6, fontSize: 13, fontWeig
          }}>
```

```
      <span style={{ fontSize: 16 }}>{market.flag}</span> {market.name}
      <span style={{ fontSize: 10, color: "var(--text3)" }}>▾</span>
    </button>
    <div style={{ display: "flex", alignItems: "center", gap: 8 }}>
      {plan.name !== "Free" && (
        <span style={{ fontSize: 11, fontWeight: 700, color: "var(--pro)",
          {plan.name.toUpperCase()}
        </span>
      )}
      <div style={{
        fontSize: 12, fontWeight: 600, padding: "4px 10px", borderRadius: 1
        background: scansLeft <= 1 ? "#2a0a0a" : "var(--surface2)",
        border: `1px solid ${scansLeft <= 1 ? "#4a1010" : "var(--border2)"}
        color: scansLeft <= 1 ? "var(--red)" : "var(--text2)"
      }}>
        {scansLeft <= 0 ? "No scans left" : `${scansLeft} scan${scansLeft !
      </div>
    </div>
  </div>
)}

{/* Main content */}
<div style={{ paddingBottom: isLanding ? 0 : 70 }}>
  {children}
</div>

{/* Bottom Nav */}
{!isLanding && (
  <nav style={{
    position: "fixed", bottom: 0, left: "50%", transform: "translateX(-50%)
    width: "100%", maxWidth: 520,
    background: "rgba(6,10,7,.97)", backdropFilter: "blur(24px)",
    borderTop: "1px solid var(--border)",
    display: "grid", gridTemplateColumns: "repeat(4, 1fr)",
    padding: "8px 0 14px", zIndex: 100
  }}>
    {NAV.map(n => (
      <button key={n.id} onClick={() => setScreen(n.id)} style={{
        background: "none", display: "flex", flexDirection: "column",
        alignItems: "center", gap: 3, padding: "4px 0",
        color: screen === n.id ? "var(--accent)" : "var(--text3)",
        transition: "color .2s"
      }}>
        <div style={{ position: "relative", fontSize: 22, lineHeight: 1 }}>
          {n.icon}
          {n.badge > 0 && (
            <span style={{
```

```
                    position: "absolute", top: -5, right: -8,
                    background: n.id === "alerts" ? "var(--red)" : "var(--accent2
                    color: "white", borderRadius: 10, fontSize: 9,
                    padding: "1px 4px", fontWeight: 700, lineHeight: 1.5,
                    animation: "badgePop .3s ease"
                  }}>{n.badge > 99 ? "99+" : n.badge}</span>
                )}
              </div>
              <span style={{ fontSize: 10, fontWeight: 700, letterSpacing: 0.4, t
            </button>
          ))}
        </nav>
      )}

      {/* Toast */}
      {toast && (
        <div key={toast.id} style={{
          position: "fixed", bottom: 82, left: "50%", transform: "translateX(-50%
          zIndex: 999, animation: "toastSlide .3s ease",
          background: toast.type === "error" ? "#2d0a0a" : toast.type === "alert"
          border: `1px solid ${toast.type === "error" ? "#4a1a1a" : toast.type ==
          color: toast.type === "error" ? "#f87171" : toast.type === "alert" ? "v
          padding: "10px 18px", borderRadius: 12, fontSize: 13, fontWeight: 600,
          whiteSpace: "nowrap", boxShadow: "0 8px 32px #0009", maxWidth: "90vw"
        }}>{toast.msg}</div>
      )}

      {/* Modal backdrop */}
      {modal && (
        <div onClick={() => setModal(null)} style={{
          position: "fixed", inset: 0, background: "rgba(0,0,0,.7)",
          backdropFilter: "blur(4px)", zIndex: 200
        }} />
      )}
    </div>
  );
}

// ═══════════════════════════════════════════════════════════════════
// LANDING SCREEN
// ═══════════════════════════════════════════════════════════════════
function LandingScreen({ onStart, market }) {
  return (
    <div style={{ minHeight: "100vh", display: "flex", flexDirection: "column", p
      {/* Hero */}
      <div style={{ position: "relative", padding: "60px 28px 48px", overflow: "h
        {/* BG orbs */}
```

```
  {[["#3ddc8415", "60%", "10%", 300], ["#2ab86a08", "20%", "60%", 200], ["#
    <div key={i} style={{ position: "absolute", left: l, top: t, width: s,
  ))}

  <div style={{ animation: "float 4s ease-in-out infinite", marginBottom: 2
    <div style={{
      display: "inline-flex", width: 80, height: 80, borderRadius: 24,
      background: "linear-gradient(135deg,#1a3d28,#2ab86a)",
      alignItems: "center", justifyContent: "center", fontSize: 40,
      boxShadow: "0 0 60px #3ddc8444", animation: "glow 3s ease-in-out infi
    }}>🔍</div>
  </div>

  <div style={{ textAlign: "center" }}>
    <div style={{ fontSize: 11, fontWeight: 800, letterSpacing: 4, color: "
    <h1 style={{ fontSize: 40, fontWeight: 800, lineHeight: 1.1, letterSpac
      AI hunts the<br />
      <span style={{ color: "var(--accent)", textShadow: "0 0 40px #3ddc846
      so you don't have to.
    </h1>
    <p style={{ fontSize: 16, color: "var(--text2)", lineHeight: 1.6, maxWi
      One search hits TradeMe, Facebook Marketplace, Gumtree, hardware stor
    </p>
  </div>

  {/* Market badges */}
  <div style={{ display: "flex", justifyContent: "center", gap: 8, flexWrap
    {Object.values(MARKETS).map(m => (
      <span key={m.name} style={{
        padding: "6px 12px", borderRadius: 20,
        background: "var(--surface)", border: "1px solid var(--border2)",
        fontSize: 13, fontWeight: 600, color: "var(--text2)"
      }}>{m.flag} {m.name}</span>
    ))}
  </div>

  <button onClick={onStart} style={{
    display: "block", width: "100%", maxWidth: 380, margin: "0 auto",
    padding: "17px 0", borderRadius: 18, fontSize: 17, fontWeight: 800,
    background: "linear-gradient(135deg, #1a5e38, #3ddc84)",
    color: "#031208", letterSpacing: "-0.3px",
    boxShadow: "0 8px 32px #3ddc8433"
  }}>Start Hunting for Free →</button>
  <p style={{ textAlign: "center", fontSize: 12, color: "var(--text3)", mar
</div>

{/* Feature strips */}
```

```
      <div style={{ padding: "0 20px", display: "flex", flexDirection: "column",
        {[
          { icon: "⚡", title: "Live AI search", body: "Searches real listings ri
          { icon: "🎯", title: "Budget alerts", body: "Get notified the moment sc
          { icon: "🌍", title: "4 countries", body: "NZ · Australia · UK · USA wi
          { icon: "🤝", title: "Community deals", body: "Share wins with hunters
        ].map((f, i) => (
          <div key={i} style={{
            display: "flex", gap: 14, padding: 16, borderRadius: 14,
            background: "var(--surface)", border: "1px solid var(--border)",
            animation: `fadeUp .4s ${i * 80}ms both ease`
          }}>
            <div style={{ fontSize: 28, width: 40, flexShrink: 0, textAlign: "cen
            <div>
              <div style={{ fontWeight: 700, fontSize: 14, marginBottom: 3 }}>{f.
              <div style={{ fontSize: 13, color: "var(--text2)", lineHeight: 1.4
            </div>
          </div>
        ))}
      </div>
    </div>
  );
}

// ═══════════════════════════════════════════════════════════════════
// ONBOARD
// ═══════════════════════════════════════════════════════════════════
function OnboardScreen({ onDone, onMarketSelect, selectedMarket }) {
  const [step, setStep] = useState(0);
  const steps = [
    {
      icon: "🌍",
      title: "Where are you hunting?",
      body: "We'll search the right platforms for your market.",
      custom: (
        <div style={{ display: "grid", gridTemplateColumns: "1fr 1fr", gap: 10, m
          {Object.entries(MARKETS).map(([code, m]) => (
            <button key={code} onClick={() => { onMarketSelect(code); }}
              style={{
                padding: "16px 12px", borderRadius: 14, fontWeight: 700, fontSize
                background: selectedMarket === code ? "var(--accent-dim)" : "var(
                border: `2px solid ${selectedMarket === code ? "var(--accent2)" :
                color: selectedMarket === code ? "var(--accent)" : "var(--text2)"
                display: "flex", flexDirection: "column", alignItems: "center", g
              }}>
              <span style={{ fontSize: 28 }}>{m.flag}</span>
              {m.name}
```

```
          </button>
        ))}
      </div>
    )
  },
  {
    icon: "🎯",
    title: "Add what you need",
    body: "Tell us what you're looking for — any product, material, or item. Th
  },
  {
    icon: "⚡",
    title: "We search. You save.",
    body: "Hit Scan and we'll hit every marketplace at once. Budget alerts fire
  },
];
const s = steps[step];

return (
  <div style={{ minHeight: "100vh", display: "flex", flexDirection: "column", p
    <div style={{ animation: "pop .35s ease", flex: 1, display: "flex", flexDir
      <div style={{ textAlign: "center", marginBottom: 28 }}>
        <div style={{
          width: 88, height: 88, borderRadius: 26, margin: "0 auto 20px",
          background: "linear-gradient(135deg,var(--surface2),var(--accent-dim)
          display: "flex", alignItems: "center", justifyContent: "center",
          fontSize: 44, border: "1px solid var(--border2)"
        }}>{s.icon}</div>
        <h2 style={{ fontSize: 28, fontWeight: 800, letterSpacing: "-0.5px", ma
        <p style={{ fontSize: 15, color: "var(--text2)", lineHeight: 1.6 }}>{s.
      </div>
      {s.custom}
    </div>

    <div>
      <div style={{ display: "flex", gap: 6, justifyContent: "center", marginBo
        {steps.map((_, i) => (
          <div key={i} style={{ height: 4, borderRadius: 2, transition: "all .3
        ))}
      </div>
      <button onClick={() => step < steps.length - 1 ? setStep(s => s + 1) : on
        width: "100%", padding: "16px 0", borderRadius: 16, fontSize: 16, fontW
        background: "linear-gradient(135deg,#1a5e38,#3ddc84)", color: "#031208"
        boxShadow: "0 6px 24px #3ddc8433"
      }}>{step < steps.length - 1 ? "Next →" : "Start Hunting"}</button>
    </div>
  </div>
```

```
  );
}

// ═══════════════════════════════════════════════════════════════════
// HUNT SCREEN
// ═══════════════════════════════════════════════════════════════════
function HuntScreen({ watchlist, results, scanning, progress, onScan, onScanAll,
  const anyScanning = Object.values(scanning).some(Boolean);
  const totalDeals = Object.values(results).flat().filter(r => r.parsed?.alertWor

  return (
    <div style={{ animation: "fadeUp .3s ease" }}>
      {/* Header */}
      <div style={{ padding: "20px 20px 16px" }}>
        <h1 style={{ fontSize: 28, fontWeight: 800, letterSpacing: "-0.5px" }}>
          Your Watchlist
        </h1>
        <p style={{ fontSize: 13, color: "var(--text2)", marginTop: 3 }}>
          {watchlist.length} item{watchlist.length !== 1 ? "s" : ""} · {totalDeal
        </p>
      </div>

      {/* CTA bar */}
      <div style={{ padding: "0 20px 16px", display: "flex", gap: 10 }}>
        <button onClick={onAdd} style={{
          flex: 1, padding: "13px 0", borderRadius: 14, fontWeight: 800, fontSize
          background: "linear-gradient(135deg,#1a5e38,#2ab86a)", color: "#031208"
          boxShadow: "0 4px 16px #2ab86a22"
        }}>+ Add Item</button>
        {watchlist.length > 1 && (
          <button onClick={onScanAll} disabled={anyScanning || scansLeft === 0} s
            padding: "13px 18px", borderRadius: 14, fontWeight: 800, fontSize: 14
            background: scansLeft === 0 ? "var(--surface2)" : anyScanning ? "var(
            border: `1.5px solid ${scansLeft === 0 ? "#4a1010" : anyScanning ? "v
            color: scansLeft === 0 ? "var(--red)" : anyScanning ? "var(--text3)"
          }}>
            {anyScanning ? "Scanning…" : scansLeft === 0 ? "⛔ Limit" : "⚡ All"}
          </button>
        )}
      </div>

      {/* Plan nudge */}
      {plan.name === "Free" && scansLeft <= 1 && (
        <div onClick={() => setModal("upgrade")} style={{
          margin: "0 20px 16px", padding: "12px 16px", borderRadius: 12,
          background: "var(--pro-dim)", border: "1px solid #3a2800", cursor: "poi
          display: "flex", justifyContent: "space-between", alignItems: "center"
```

```
        }}>
          <div>
            <div style={{ fontSize: 13, fontWeight: 700, color: "var(--pro)" }}>
              {scansLeft === 0 ? "Daily limit reached" : "Last scan for today"}
            </div>
            <div style={{ fontSize: 12, color: "#8a6a20", marginTop: 2 }}>Upgrade
          </div>
          <span style={{ fontSize: 13, fontWeight: 700, color: "var(--pro)" }}>Up
        </div>
      )}

      {/* List */}
      <div style={{ padding: "0 20px" }}>
        {watchlist.length === 0 ? (
          <EmptyHunt onAdd={onAdd} />
        ) : (
          watchlist.map((item, i) => (
            <WatchCard2
              key={item.id} item={item}
              latest={results[item.id]?.[0]}
              scanning={scanning[item.id]}
              progress={progress[item.id] || 0}
              onScan={() => onScan(item)}
              onOpen={() => onOpenItem(item)}
              delay={i * 50}
            />
          ))
        )}
      </div>

      {/* Community preview */}
      {community.length > 0 && (
        <div style={{ padding: "24px 20px 0" }}>
          <div style={{ display: "flex", justifyContent: "space-between", alignIt
            <div style={{ fontSize: 13, fontWeight: 800, letterSpacing: 1, color:
          </div>
          {community.slice(0, 2).map(p => (
            <CommunityCard key={p.id} post={p} compact onLike={id => setCommunity
          ))}
        </div>
      )}
    </div>
  );
}

// ── Watch Card v2 ──────────────────────────────────────────────────
function WatchCard2({ item, latest, scanning, progress, onScan, onOpen, delay })
```

```
const r = latest?.parsed;
const inBudget = r?.deals?.some(d => d.withinBudget);
const cat = CATS.find(c => c.id === item.cat) || CATS[11];

return (
  <div onClick={onOpen} style={{
    marginBottom: 12, borderRadius: 18,
    background: "var(--surface)", border: `1.5px solid ${inBudget ? "#1e5e38" :
    overflow: "hidden", cursor: "pointer", position: "relative",
    animation: `fadeUp .35s ${delay}ms both ease`,
    boxShadow: inBudget ? "0 0 20px #3ddc8420" : "none",
    transition: "border-color .2s, box-shadow .2s"
  }}>
    {/* Scan beam */}
    {scanning && (
      <div style={{
        position: "absolute", left: 0, right: 0, height: 2,
        background: "linear-gradient(90deg,transparent,var(--accent),transparen
        animation: "scanLine 1.4s linear infinite", zIndex: 2
      }} />
    )}

    <div style={{ padding: 16 }}>
      <div style={{ display: "flex", gap: 12 }}>
        {/* Category icon */}
        <div style={{
          width: 46, height: 46, borderRadius: 12, flexShrink: 0,
          background: cat.color, display: "flex", alignItems: "center",
          justifyContent: "center", fontSize: 22, border: "1px solid var(--bord
        }}>{cat.emoji}</div>

        <div style={{ flex: 1, minWidth: 0 }}>
          <div style={{ display: "flex", justifyContent: "space-between", gap:
            <div style={{ fontWeight: 700, fontSize: 15, lineHeight: 1.3, flex:
            {r?.bestPrice && (
              <div style={{ fontFamily: "'Instrument Mono', monospace", fontSiz
                {r.bestPrice}
              </div>
            )}
          </div>
          <div style={{ display: "flex", gap: 6, marginTop: 6, flexWrap: "wrap"
            <Chip>{cat.label}</Chip>
            {item.freeOnly ? <Chip color="var(--accent-dim)" text="var(--accent
              : item.budget ? <Chip>≤ {MARKETS[item.market || "NZ"]?.symbol ||
              : null}
            {inBudget && <Chip color="var(--accent-dim)" text="var(--accent)">✓
            {r?.urgency === "high" && <Chip color="#2a0f0f" text="#f87171">🔥 H
```

```
            </div>
            {r?.headline && <div style={{ fontSize: 12, color: "var(--text2)", ma
          </div>
        </div>

        {scanning && (
          <div style={{ marginTop: 10, height: 3, background: "var(--border)", bo
            <div style={{
              height: "100%", borderRadius: 2, width: `${progress}%`, transition:
              background: "linear-gradient(90deg,#1a5e38,var(--accent),#1a5e38)",
              backgroundSize: "200% 100%", animation: "shimmer 1.5s linear infini
            }} />
          </div>
        )}
      </div>

      <div style={{ padding: "10px 16px 14px", borderTop: "1px solid var(--border
        <span style={{ fontSize: 11, color: "var(--text3)", fontFamily: "'Instrum
          {latest ? timeAgo(latest.ts) : "Never scanned"}
        </span>
        <button onClick={e => { e.stopPropagation(); onScan(); }} disabled={scann
          padding: "7px 16px", borderRadius: 10, fontSize: 12, fontWeight: 800,
          background: scanning ? "var(--surface2)" : "var(--accent-dim)",
          color: scanning ? "var(--text3)" : "var(--accent)",
          border: `1px solid ${scanning ? "var(--border2)" : "var(--accent2)"}`,
          display: "flex", alignItems: "center", gap: 6
        }}>
          {scanning ? <><MiniSpinner /> Scanning</> : "🔍 Scan now"}
        </button>
      </div>
    </div>
  );
}

// ═══════════════════════════════════════════════════════════════════
// ITEM DETAIL
// ═══════════════════════════════════════════════════════════════════
function ItemScreen({ item, results, scanning, progress, onScan, onBack, onDelete
  const [editing, setEditing] = useState(false);
  if (editing) return <AddModal onSave={updated => { onEdit({ ...item, ...updated

  const latest = results[0];
  const r = latest?.parsed;
  const cat = CATS.find(c => c.id === item.cat) || CATS[11];

  return (
    <div style={{ animation: "fadeUp .25s ease" }}>
```

```
{/* Header */}
<div style={{
  position: "sticky", top: 44, zIndex: 20,
  background: "rgba(6,10,7,.97)", backdropFilter: "blur(20px)",
  borderBottom: "1px solid var(--border)", padding: "14px 18px",
  display: "flex", gap: 12, alignItems: "center"
}}>
  <button onClick={onBack} style={{ width: 36, height: 36, borderRadius: 10
  <div style={{ flex: 1, fontWeight: 700, fontSize: 15, overflow: "hidden",
  <div style={{ display: "flex", gap: 8 }}>
    <button onClick={() => setEditing(true)} style={{ background: "none", f
    <button onClick={() => { if (confirm("Remove this item?")) onDelete(ite
  </div>
</div>

<div style={{ padding: "16px 20px" }}>
  {/* Summary card */}
  <div style={{ background: "var(--surface)", border: "1px solid var(--bord
    <div style={{ display: "flex", gap: 12, marginBottom: 12 }}>
      <div style={{ width: 48, height: 48, borderRadius: 12, background: ca
      <div>
        <div style={{ display: "flex", gap: 6, flexWrap: "wrap" }}>
          <Chip>{cat.label}</Chip>
          {item.freeOnly ? <Chip color="var(--accent-dim)" text="var(--acce
            : item.budget ? <Chip>≤ {market.symbol}{item.budget}</Chip> : <
          <Chip>{item.source || "Everywhere"}</Chip>
        </div>
        {item.notes && <div style={{ fontSize: 12, color: "var(--text2)", m
      </div>
    </div>
    {r?.bestPrice && (
      <div style={{ padding: "12px 14px", background: "var(--surface2)", bo
        <div style={{ fontSize: 11, color: "var(--text3)", fontWeight: 700,
        <div style={{ display: "flex", justifyContent: "space-between", ali
          <div style={{ fontFamily: "'Instrument Mono', monospace", fontSiz
          <div style={{ textAlign: "right" }}>
            <div style={{ fontSize: 12, color: "var(--text2)" }}>via {r.bes
            {r.savings && <div style={{ fontSize: 11, color: "var(--accent2
          </div>
        </div>
        {r.priceRange && <div style={{ fontSize: 11, color: "var(--text3)",
      </div>
    )}
  </div>

  {/* Actions */}
  <div style={{ display: "flex", gap: 10, marginBottom: 20 }}>
```

```
          <button onClick={scansLeft > 0 ? onScan : () => setModal("upgrade")} di
            flex: 1, padding: "14px 0", borderRadius: 14, fontSize: 14, fontWeigh
            background: scanning ? "var(--surface2)" : "linear-gradient(135deg,#1
            color: scanning ? "var(--text3)" : "#031208",
            border: scanning ? "1.5px solid var(--border2)" : "none",
            display: "flex", alignItems: "center", justifyContent: "center", gap:
          }}>
            {scanning ? <><MiniSpinner /> Searching live…</> : "🔍 Run New Scan"}
          </button>
          {r?.shareText && (
            <button onClick={() => onShare({ text: r.shareText, item, result: lat
              padding: "14px 16px", borderRadius: 14, fontSize: 14, fontWeight: 8
              background: "var(--surface2)", border: "1.5px solid var(--border2)"
            }}>↗ Share</button>
          )}
        </div>

        {scanning && <div style={{ marginBottom: 16 }}><ProgressBar value={progre

        {/* Results history */}
        <div style={{ fontSize: 13, fontWeight: 800, letterSpacing: 1, color: "va
          Scan History ({results.length})
        </div>

        {results.length === 0 ? (
          <div style={{ textAlign: "center", padding: "32px 0", color: "var(--tex
            Run your first scan to see live results
          </div>
        ) : results.map((res, i) => (
          <ResultCard2 key={res.id} result={res} isLatest={i === 0} market={marke
        ))}
      </div>
    </div>
  );
}

function ResultCard2({ result, isLatest, market }) {
  const [open, setOpen] = useState(isLatest);
  const r = result.parsed;
  if (!r) return null;

  return (
    <div style={{ marginBottom: 10, borderRadius: 14, background: "var(--surface)
      <div onClick={() => setOpen(x => !x)} style={{ padding: "14px 16px", displa
        <div>
          <div style={{ fontFamily: "'Instrument Mono', monospace", fontSize: 20,
          <div style={{ fontSize: 11, color: "var(--text3)", marginTop: 2, fontFa
```

```
    </div>
    <div style={{ display: "flex", gap: 8, alignItems: "center" }}>
      {r.deals?.some(d => d.withinBudget) && <Chip color="var(--accent-dim)"
      {r.urgency === "high" && <Chip color="#2a0f0f" text="#f87171">🔥</Chip>
      <span style={{ color: "var(--text3)" }}>{open ? "▲" : "▼"}</span>
    </div>
  </div>

  {open && (
    <div style={{ borderTop: "1px solid var(--border)", padding: "12px 16px 1
      {r.headline && <div style={{ fontSize: 14, color: "var(--text)", lineHe
      {r.deals?.slice(0, 6).map((d, i) => (
        <div key={i} style={{
          padding: "12px 14px", borderRadius: 12, marginBottom: 8,
          background: d.withinBudget ? "#0a1e12" : "var(--surface2)",
          border: `1px solid ${d.withinBudget ? "#1e4a28" : "var(--border2)"}
        }}>
          <div style={{ display: "flex", justifyContent: "space-between", gap
            <div style={{ flex: 1 }}>
              <div style={{ fontSize: 13, fontWeight: 700, lineHeight: 1.3 }}
              <div style={{ fontSize: 11, color: "var(--text3)", marginTop: 3
                {[d.source, d.location, d.condition].filter(Boolean).join(" ·
              </div>
              {d.detail && <div style={{ fontSize: 11, color: "var(--text2)",
              {d.url && <a href={d.url} target="_blank" rel="noreferrer" styl
            </div>
            <div style={{ textAlign: "right", flexShrink: 0 }}>
              <div style={{ fontFamily: "'Instrument Mono', monospace", fontS
              {d.originalPrice && d.originalPrice !== d.price && (
                <div style={{ fontSize: 11, color: "var(--text3)", textDecora
              )}
              {d.withinBudget && <div style={{ fontSize: 10, color: "var(--ac
              {d.hot && <div style={{ fontSize: 10, color: "#f87171", marginT
            </div>
          </div>
        </div>
      ))}
      {r.freeOptions && (
        <div style={{ padding: "10px 12px", background: "#0a1e12", borderRadi
          <span style={{ fontSize: 11, color: "var(--accent2)", fontWeight: 7
          <span style={{ fontSize: 12, color: "var(--text2)" }}>{r.freeOption
        </div>
      )}
      {r.tip && (
        <div style={{ padding: "10px 12px", background: "var(--surface2)", bo
          <span style={{ fontSize: 11, color: "var(--text3)", fontWeight: 700
          <span style={{ fontSize: 12, color: "var(--text2)" }}>{r.tip}</span
```

```
            </div>
          )}
        </div>
      )}
    </div>
  );
}

// ═══════════════════════════════════════════════════════════════════
// ALERTS
// ═══════════════════════════════════════════════════════════════════
function AlertsScreen({ alerts, watchlist, onRead, onReadAll, onClear, onOpenItem
  const unread = alerts.filter(a => !a.read).length;
  return (
    <div style={{ animation: "fadeUp .3s ease" }}>
      <div style={{ padding: "20px 20px 16px", display: "flex", justifyContent: "
        <div>
          <h1 style={{ fontSize: 28, fontWeight: 800, letterSpacing: "-0.5px" }}>
          <p style={{ fontSize: 13, color: "var(--text2)", marginTop: 3 }}>{unrea
        </div>
        {alerts.length > 0 && (
          <div style={{ display: "flex", gap: 8 }}>
            {unread > 0 && <button onClick={onReadAll} style={{ padding: "7px 12p
            <button onClick={onClear} style={{ padding: "7px 12px", borderRadius:
          </div>
        )}
      </div>

      {!plan.alerts && (
        <div onClick={() => setModal("upgrade")} style={{
          margin: "0 20px 16px", padding: "14px 16px", borderRadius: 14,
          background: "var(--pro-dim)", border: "1px solid #4a3000", cursor: "poi
        }}>
          <div style={{ fontWeight: 700, color: "var(--pro)", marginBottom: 4 }}>
          <div style={{ fontSize: 13, color: "#8a6020" }}>Upgrade to get notified
          <div style={{ marginTop: 8, fontSize: 13, fontWeight: 700, color: "var(
        </div>
      )}

      <div style={{ padding: "0 20px" }}>
        {alerts.length === 0 ? (
          <div style={{ textAlign: "center", padding: "48px 0" }}>
            <div style={{ fontSize: 48, marginBottom: 12 }}>🔕</div>
            <div style={{ fontSize: 16, fontWeight: 700, color: "var(--text3)" }}
            <div style={{ fontSize: 13, color: "var(--text3)", marginTop: 6 }}>Sc
          </div>
        ) : alerts.map(a => (
```

```
          <div key={a.id} onClick={() => { onRead(a.id); onOpenItem(a.itemId); }}
            marginBottom: 10, padding: 16, borderRadius: 14, cursor: "pointer",
            background: a.read ? "var(--surface)" : "#0a1e12",
            border: `1.5px solid ${a.read ? "var(--border)" : "#1e5e38"}`,
            transition: "all .2s"
          }}>
            <div style={{ display: "flex", justifyContent: "space-between", gap:
              <div style={{ flex: 1 }}>
                <div style={{ display: "flex", gap: 8, alignItems: "center", marg
                  {!a.read && <div style={{ width: 7, height: 7, borderRadius: "5
                  <div style={{ fontWeight: 700, fontSize: 14 }}>{a.itemName}</di
                </div>
                <div style={{ fontSize: 13, color: "var(--text2)", lineHeight: 1.
                {a.bestPrice && (
                  <div style={{ marginTop: 8, display: "flex", gap: 8, alignItems
                    <span style={{ fontFamily: "'Instrument Mono', monospace", fo
                    {a.bestSource && <Chip>{a.bestSource}</Chip>}
                  </div>
                )}
              </div>
              <div style={{ fontSize: 11, color: "var(--text3)", flexShrink: 0, f
            </div>
          </div>
        ))}
      </div>
    </div>
  );
}

// ═══════════════════════════════════════════════════════════════════
// COMMUNITY
// ═══════════════════════════════════════════════════════════════════
function CommunityScreen({ community, setCommunity, plan, setModal, market }) {
  const [filter, setFilter] = useState("All");
  const marketCodes = ["All", ...Object.keys(MARKETS)];

  const filtered = filter === "All" ? community : community.filter(p => p.market

  return (
    <div style={{ animation: "fadeUp .3s ease" }}>
      <div style={{ padding: "20px 20px 16px" }}>
        <h1 style={{ fontSize: 28, fontWeight: 800, letterSpacing: "-0.5px" }}>Co
        <p style={{ fontSize: 13, color: "var(--text2)", marginTop: 3 }}>Deals sh
      </div>

      {/* Filter tabs */}
      <div style={{ display: "flex", gap: 8, padding: "0 20px 16px", overflowX: "
```

```
        {marketCodes.map(m => (
          <button key={m} onClick={() => setFilter(m)} style={{
            padding: "7px 14px", borderRadius: 20, fontSize: 13, fontWeight: 700,
            background: filter === m ? "var(--accent-dim)" : "var(--surface)",
            border: `1.5px solid ${filter === m ? "var(--accent2)" : "var(--borde
            color: filter === m ? "var(--accent)" : "var(--text2)",
            whiteSpace: "nowrap", flexShrink: 0
          }}>
            {m === "All" ? "🌍 All" : `${MARKETS[m].flag} ${MARKETS[m].name}`}
          </button>
        ))}
      </div>

      {!plan.community && (
        <div onClick={() => setModal("upgrade")} style={{
          margin: "0 20px 16px", padding: "14px 16px", borderRadius: 14,
          background: "var(--pro-dim)", border: "1px solid #4a3000", cursor: "poi
        }}>
          <div style={{ fontWeight: 700, color: "var(--pro)", marginBottom: 4 }}>
          <div style={{ fontSize: 13, color: "#8a6020" }}>Post your finds and hel
          <div style={{ marginTop: 8, fontSize: 13, fontWeight: 700, color: "var(
        </div>
      )}

      <div style={{ padding: "0 20px" }}>
        {filtered.map(post => (
          <CommunityCard key={post.id} post={post} onLike={id => setCommunity(c =
        ))}
      </div>
    </div>
  );
}

function CommunityCard({ post, onLike, compact }) {
  const mkt = MARKETS[post.market] || MARKETS.NZ;
  return (
    <div style={{
      marginBottom: compact ? 8 : 12, padding: compact ? "12px 14px" : 16,
      borderRadius: 14, background: "var(--surface)", border: "1px solid var(--bo
    }}>
      <div style={{ display: "flex", justifyContent: "space-between", alignItems:
        <div style={{ flex: 1 }}>
          <div style={{ display: "flex", gap: 8, alignItems: "center", marginBott
            <div style={{ width: 28, height: 28, borderRadius: "50%", background:
            <span style={{ fontSize: 12, fontWeight: 700, color: "var(--text2)" }
            <span style={{ fontSize: 10, color: "var(--text3)", fontFamily: "'Ins
            <span style={{ fontSize: 11 }}>{mkt.flag}</span>
```

```
          </div>
          <div style={{ fontSize: 14, fontWeight: 500, lineHeight: 1.4 }}>{post.t
          {post.price && (
            <div style={{ marginTop: 8, display: "flex", gap: 6, alignItems: "cen
              <span style={{ fontFamily: "'Instrument Mono', monospace", fontSize
              {post.platform && <Chip>{post.platform}</Chip>}
              {post.saving && <Chip color="var(--accent-dim)" text="var(--accent)
            </div>
          )}
        </div>
      </div>
      <div style={{ display: "flex", gap: 8, marginTop: 10 }}>
        <button onClick={() => onLike(post.id)} style={{
          padding: "5px 12px", borderRadius: 20, fontSize: 12, fontWeight: 700,
          background: post.liked ? "var(--accent-dim)" : "var(--surface2)",
          border: `1px solid ${post.liked ? "var(--accent2)" : "var(--border2)"}`
          color: post.liked ? "var(--accent)" : "var(--text3)"
        }}>❤ {post.likes}</button>
      </div>
    </div>
  );
}

// ═══════════════════════════════════════════════════════════════════
// PROFILE
// ═══════════════════════════════════════════════════════════════════
function ProfileScreen({ plan, watchlist, results, alerts, scansLeft, scansToday,
  const totalScans = Object.values(results).flat().length;
  const totalDeals = Object.values(results).flat().filter(r => r.parsed?.alertWor
  const savedEst = totalDeals * 47; // fun stat

  return (
    <div style={{ animation: "fadeUp .3s ease", padding: "20px 20px 32px" }}>
      <h1 style={{ fontSize: 28, fontWeight: 800, letterSpacing: "-0.5px", margin

      {/* Plan card */}
      <div style={{
        padding: 20, borderRadius: 18, marginBottom: 20,
        background: plan.name === "Free" ? "var(--surface)" : "linear-gradient(13
        border: `1.5px solid ${plan.name === "Free" ? "var(--border2)" : "#4a3000
      }}>
        <div style={{ display: "flex", justifyContent: "space-between", alignItem
          <div>
            <div style={{ fontSize: 11, fontWeight: 800, letterSpacing: 2, color:
            <div style={{ fontSize: 22, fontWeight: 800, color: plan.name === "Fr
          </div>
          {plan.name !== "Teams" && (
```

```
      <button onClick={() => setModal("upgrade")} style={{
        padding: "8px 16px", borderRadius: 12, fontSize: 13, fontWeight: 80
        background: plan.name === "Free" ? "var(--accent-dim)" : "var(--pro
        color: plan.name === "Free" ? "var(--accent)" : "var(--pro)",
        border: `1px solid ${plan.name === "Free" ? "var(--accent2)" : "#6a
      }}>Upgrade →</button>
    )}
  </div>
  {plan.name === "Free" && (
    <div style={{ fontSize: 13, color: "var(--text3)" }}>
      {scansLeft} of {plan.scansPerDay} scans remaining today · {plan.watch
    </div>
  )}
</div>

{/* Stats */}
<div style={{ display: "grid", gridTemplateColumns: "1fr 1fr", gap: 10, mar
  {[
    { label: "Items Watching", val: watchlist.length, sub: `of ${plan.watch
    { label: "Total Scans", val: totalScans, sub: "all time" },
    { label: "Deals Found", val: totalDeals, sub: "in budget" },
    { label: "Est. Savings", val: `~$${savedEst}`, sub: "rough estimate" },
  ].map(s => (
    <div key={s.label} style={{ padding: "14px 16px", borderRadius: 14, bac
      <div style={{ fontFamily: "'Instrument Mono', monospace", fontSize: 2
      <div style={{ fontSize: 12, fontWeight: 700, color: "var(--text2)", m
      <div style={{ fontSize: 11, color: "var(--text3)" }}>{s.sub}</div>
    </div>
  ))}
</div>

{/* Settings */}
<div style={{ display: "flex", flexDirection: "column", gap: 2, marginBotto
  {[
    { icon: "🌍", label: "Market", val: `${market.flag} ${market.name}`, ac
    { icon: "💱", label: "Currency", val: `${market.currency} (${market.sym
  ].map(s => (
    <div key={s.label} onClick={s.action || undefined} style={{
      display: "flex", justifyContent: "space-between", alignItems: "center
      padding: "14px 16px", borderRadius: 12, background: "var(--surface)",
      cursor: s.action ? "pointer" : "default"
    }}>
      <div style={{ display: "flex", gap: 10, alignItems: "center" }}>
        <span style={{ fontSize: 18 }}>{s.icon}</span>
        <span style={{ fontSize: 14, fontWeight: 600 }}>{s.label}</span>
      </div>
      <div style={{ display: "flex", gap: 8, alignItems: "center" }}>
```

```
              <span style={{ fontSize: 13, color: "var(--text2)" }}>{s.val}</span
              {s.action && <span style={{ color: "var(--text3)" }}>›</span>}
            </div>
          </div>
        ))}
      </div>

      <button onClick={() => { if (confirm("Clear all your data? This cannot be u
        width: "100%", padding: "12px 0", borderRadius: 12, fontSize: 13, fontWei
        background: "#1a0808", border: "1px solid #3a1010", color: "#f87171"
      }}>Clear All Data</button>
    </div>
  );
}

// ═══════════════════════════════════════════════════════════════════
// MODALS
// ═══════════════════════════════════════════════════════════════════
function AddModal({ onSave, onClose, market, prefill, editing, watchlist, plan })
  const [form, setForm] = useState(prefill || { name: "", cat: "other", budget: "
  const f = k => v => setForm(x => ({ ...x, [k]: v }));
  const valid = form.name.trim().length > 1;

  return (
    <div style={{
      position: "fixed", inset: 0, zIndex: 300, display: "flex", flexDirection: "
      justifyContent: "flex-end", padding: "0"
    }}>
      <div style={{
        background: "var(--surface)", borderRadius: "24px 24px 0 0",
        border: "1px solid var(--border2)", borderBottom: "none",
        maxHeight: "92vh", overflowY: "auto", animation: "fadeUp .3s ease"
      }}>
        <div style={{ padding: "20px 20px 8px", display: "flex", justifyContent:
          <h2 style={{ fontSize: 20, fontWeight: 800 }}>{editing ? "Edit Item" :
          <button onClick={onClose} style={{ width: 32, height: 32, borderRadius:
        </div>

        <div style={{ padding: "12px 20px 32px", display: "flex", flexDirection:
          <FormField label="What are you looking for? *">
            <input value={form.name} onChange={e => f("name")(e.target.value)} pl
          </FormField>

          <FormField label="Category">
            <div style={{ display: "grid", gridTemplateColumns: "1fr 1fr 1fr", ga
              {CATS.map(c => (
                <button key={c.id} onClick={() => f("cat")(c.id)} style={{
```

```
        padding: "9px 6px", borderRadius: 10, fontSize: 12, fontWeight:
        background: form.cat === c.id ? c.color : "var(--surface2)",
        border: `1.5px solid ${form.cat === c.id ? "var(--accent2)" : "
        color: form.cat === c.id ? "var(--accent)" : "var(--text2)",
        display: "flex", flexDirection: "column", alignItems: "center",
      }}>
        <span style={{ fontSize: 18 }}>{c.emoji}</span>
        <span style={{ fontSize: 10, lineHeight: 1.2, textAlign: "cente
      </button>
    ))}
  </div>
</FormField>

<FormField label="Search sources">
  <select value={form.source} onChange={e => f("source")(e.target.value
    <option>Everywhere</option>
    {(MARKETS[market?.name === "New Zealand" ? "NZ" : market?.name ===
  </select>
</FormField>

<div style={{ background: "var(--surface2)", borderRadius: 14, padding:
  <div style={{ display: "flex", justifyContent: "space-between", align
    <div>
      <div style={{ fontWeight: 700, fontSize: 14 }}>Free items only</d
      <div style={{ fontSize: 12, color: "var(--text3)", marginTop: 2 }
    </div>
    <Toggle2 checked={form.freeOnly} onChange={v => { f("freeOnly")(v);
  </div>
  {!form.freeOnly && (
    <FormField label="Max budget" sub="Leave blank to find cheapest">
      <div style={{ position: "relative" }}>
        <span style={{ position: "absolute", left: 14, top: "50%", tran
        <input type="number" value={form.budget} onChange={e => f("budg
      </div>
    </FormField>
  )}
</div>

<FormField label="Notes & specs" sub="Quantity, condition, brand, size,
  <textarea value={form.notes} onChange={e => f("notes")(e.target.value
</FormField>

<button onClick={() => valid && onSave(form)} style={{
  padding: "15px 0", borderRadius: 14, fontSize: 16, fontWeight: 800,
  background: valid ? "linear-gradient(135deg,#1a5e38,#3ddc84)" : "var(
  color: valid ? "#031208" : "var(--text3)",
  boxShadow: valid ? "0 6px 24px #3ddc8433" : "none",
```

```
            transition: "all .2s"
          }}>
            {editing ? "Save Changes" : "Add to Watchlist →"}
          </button>
        </div>
      </div>
    </div>
  );
}

function UpgradeModal({ onClose, onUpgrade, currentPlan }) {
  return (
    <div style={{ position: "fixed", inset: 0, zIndex: 300, display: "flex", alig
      <div style={{
        width: "100%", maxWidth: 520, margin: "0 auto",
        background: "var(--surface)", borderRadius: "24px 24px 0 0",
        border: "1px solid var(--border2)", animation: "fadeUp .3s ease",
        padding: "24px 20px 40px"
      }}>
        <div style={{ display: "flex", justifyContent: "space-between", marginBot
          <h2 style={{ fontSize: 22, fontWeight: 800 }}>Upgrade DealHunter</h2>
          <button onClick={onClose} style={{ width: 32, height: 32, borderRadius:
        </div>

        {[
          {
            id: "pro", name: "Pro", price: 9, color: "var(--pro)", bg: "var(--pro
            perks: ["50 scans/day", "50 item watchlist", "Instant budget alerts",
          },
          {
            id: "teams", name: "Teams", price: 29, color: "#a78bfa", bg: "#1a1040
            perks: ["Unlimited scans", "500 item watchlist", "Team sharing", "API
          }
        ].map(p => (
          <div key={p.id} style={{ marginBottom: 12, padding: 18, borderRadius: 1
            <div style={{ display: "flex", justifyContent: "space-between", align
              <div>
                <div style={{ fontSize: 18, fontWeight: 800, color: p.color }}>{p
                <div style={{ fontSize: 13, color: "var(--text2)", marginTop: 2 }
                  <span style={{ fontFamily: "'Instrument Mono', monospace", font
                </div>
              </div>
              <button onClick={() => onUpgrade(p.id)} style={{
                padding: "10px 18px", borderRadius: 12, fontWeight: 800, fontSize
                background: p.color === "var(--pro)" ? "var(--pro)" : p.color,
                color: "#0a0600"
              }}>{currentPlan === p.id ? "Current" : "Choose"}</button>
```

```
            </div>
            <div style={{ display: "flex", flexDirection: "column", gap: 5 }}>
              {p.perks.map(perk => (
                <div key={perk} style={{ fontSize: 13, color: "var(--text2)", dis
                  <span style={{ color: p.color }}>✓</span> {perk}
                </div>
              ))}
            </div>
          </div>
        ))}

        <p style={{ textAlign: "center", fontSize: 12, color: "var(--text3)", mar
          Cancel anytime · No hidden fees · Prices in {Object.values(MARKETS)[0].
        </p>
      </div>
    </div>
  );
}

function MarketModal({ onClose, current, onChange }) {
  return (
    <div style={{ position: "fixed", inset: 0, zIndex: 300, display: "flex", alig
      <div style={{
        width: "100%", maxWidth: 520, margin: "0 auto",
        background: "var(--surface)", borderRadius: "24px 24px 0 0",
        border: "1px solid var(--border2)", animation: "fadeUp .3s ease",
        padding: "24px 20px 40px"
      }}>
        <div style={{ display: "flex", justifyContent: "space-between", marginBot
          <h2 style={{ fontSize: 22, fontWeight: 800 }}>Select Market</h2>
          <button onClick={onClose} style={{ width: 32, height: 32, borderRadius:
        </div>
        <div style={{ display: "flex", flexDirection: "column", gap: 10 }}>
          {Object.entries(MARKETS).map(([code, m]) => (
            <button key={code} onClick={() => onChange(code)} style={{
              padding: "16px 18px", borderRadius: 14, fontWeight: 700,
              background: current === code ? "var(--accent-dim)" : "var(--surface
              border: `1.5px solid ${current === code ? "var(--accent2)" : "var(-
              color: current === code ? "var(--accent)" : "var(--text)",
              display: "flex", justifyContent: "space-between", alignItems: "cent
            }}>
              <div style={{ display: "flex", gap: 12, alignItems: "center" }}>
                <span style={{ fontSize: 28 }}>{m.flag}</span>
                <div style={{ textAlign: "left" }}>
                  <div style={{ fontSize: 15 }}>{m.name}</div>
                  <div style={{ fontSize: 12, color: "var(--text2)", fontWeight:
                </div>
```

```
              </div>
              {current === code && <span style={{ color: "var(--accent)" }}>✓</sp
            </button>
          ))}
        </div>
      </div>
    </div>
  );
}

function ShareModal({ data, onPost, onClose, market }) {
  const [text, setText] = useState(data?.text || "");
  return (
    <div style={{ position: "fixed", inset: 0, zIndex: 300, display: "flex", alig
      <div style={{
        width: "100%", maxWidth: 520, margin: "0 auto",
        background: "var(--surface)", borderRadius: "24px 24px 0 0",
        border: "1px solid var(--border2)", animation: "fadeUp .3s ease",
        padding: "24px 20px 40px"
      }}>
        <div style={{ display: "flex", justifyContent: "space-between", marginBot
          <h2 style={{ fontSize: 20, fontWeight: 800 }}>Share to Community</h2>
          <button onClick={onClose} style={{ width: 32, height: 32, borderRadius:
        </div>
        <textarea value={text} onChange={e => setText(e.target.value)} placeholde
        <button onClick={() => { onPost({ text, user: "You", avatar: "🤝", price:
          width: "100%", padding: "14px 0", borderRadius: 14, fontSize: 15, fontW
          background: "linear-gradient(135deg,#1a5e38,#3ddc84)", color: "#031208"
        }}>Post to Community</button>
      </div>
    </div>
  );
}

// ═══════════════════════════════════════════════════════════════════
// MICRO COMPONENTS
// ═══════════════════════════════════════════════════════════════════
function Chip({ children, color = "var(--surface2)", text = "var(--text2)" }) {
  return <span style={{ background: color, color: text, borderRadius: 20, padding
}

function MiniSpinner() {
  return <div style={{ width: 14, height: 14, border: "2px solid var(--border2)",
}

function ProgressBar({ value }) {
  return (
```

```
    <div style={{ height: 4, background: "var(--border)", borderRadius: 2, overfl
      <div style={{
        height: "100%", borderRadius: 2, width: `${value}%`, transition: "width .
        background: "linear-gradient(90deg,#1a5e38,var(--accent),#1a5e38)",
        backgroundSize: "200% 100%", animation: "shimmer 1.5s linear infinite"
      }} />
    </div>
  );
}

function Toggle2({ checked, onChange }) {
  return (
    <div onClick={() => onChange(!checked)} style={{
      width: 46, height: 26, borderRadius: 13, cursor: "pointer",
      background: checked ? "var(--accent-dim)" : "var(--surface)",
      border: `1.5px solid ${checked ? "var(--accent2)" : "var(--border2)"}`,
      position: "relative", transition: "all .2s", flexShrink: 0
    }}>
      <div style={{
        position: "absolute", top: 3, left: checked ? 22 : 3,
        width: 16, height: 16, borderRadius: "50%",
        background: checked ? "var(--accent)" : "var(--text3)",
        transition: "left .2s, background .2s"
      }} />
    </div>
  );
}

function FormField({ label, sub, children }) {
  return (
    <div>
      <div style={{ fontWeight: 700, fontSize: 13, color: "var(--text2)", marginB
      {sub && <div style={{ fontSize: 12, color: "var(--text3)", marginBottom: 8
      {children}
    </div>
  );
}

function EmptyHunt({ onAdd }) {
  return (
    <div style={{ textAlign: "center", padding: "48px 20px" }}>
      <div style={{ fontSize: 56, marginBottom: 16, animation: "float 3s ease-in-
      <h2 style={{ fontSize: 22, fontWeight: 800, marginBottom: 8 }}>Nothing on t
      <p style={{ fontSize: 14, color: "var(--text2)", lineHeight: 1.6, marginBot
        Add your first item and let AI search every marketplace at once — for fre
      </p>
      <button onClick={onAdd} style={{
```

```
        padding: "14px 28px", borderRadius: 14, fontWeight: 800, fontSize: 15,
        background: "linear-gradient(135deg,#1a5e38,#3ddc84)", color: "#031208",
        boxShadow: "0 6px 24px #3ddc8433"
      }}>Add first item →</button>
    </div>
  );
}

// ═══════════════════════════════════════════════════════════════════
// SEED COMMUNITY DATA
// ═══════════════════════════════════════════════════════════════════
const SEED_COMMUNITY = [
  { id: 1, user: "Sarah M.", avatar: "👩", market: "NZ", text: "Just found an alm
  { id: 2, user: "Dave K.", avatar: "👨", market: "AU", text: "Score! 90 linear m
  { id: 3, user: "Priya L.", avatar: "👦", market: "UK", text: "Vintage Ercol din
  { id: 4, user: "Mike R.", avatar: "🧔", market: "US", text: "Craigslist find: f
  { id: 5, user: "Tom W.", avatar: "👨‍🦳", market: "NZ", text: "Mitre 10 Mega has 9
];
```