

NOTES: (UNLESS OTHERWISE SPECIFIED)

- 1) J5 / IO CONNECTORS MAY NOT FUNCTION WITH DCS-BIOS WHILE MASTER FUNCTIONALITY IS IN USE.
- 2) ABSIS RS485 BUS SPECIFICATION
- 2.1) BUS IS HALF DUPLEX: EITHER TRANSMITTING OR RECIEVING AT ANY GIVEN TIME.
- 2.2) PIN FUNCTION: R: DATA OUTPUT / D: DATA INPUT / DE HAS INTERNAL PULL-DOWN
(DRIVER DISABLED BY DEFAULT) / RE HAS INTERNAL PULL-UP (RECIEVER DISABLED BY DEFAULT)
- 2.3) CIRCUIT CONTAINS OPEN, SHORT, AND IDLE BUS FAILSAFE WHICH PREVENTS THE SYSTEM FROM INTERPRETING ELECTRICAL NOISE AS VALID DATA.
- 2.4) THVD1410DR TRANSCEIVER OPERATES WITH TTL LEVEL INPUTS. (LOGIC HIGH: 2V - VCC / LOGIC LOW: 0V - .8VCC)
- 2.5) CAUTION: AS CABLE LENGTH INCREASES, DATA RATE DECREASES PROPORTIONALLY.

