



NOTES: (UNLESS OTHERWISE SPECIFIED)


1. SPECIFICATIONS AND DOCUMENTS:
- 1.1. PANEL CONSTRUCTION SHALL BE IAW OH-SPEC-001, PANEL TYPE A, METHOD 1.
- 1.2. ELECTRICAL CONNECTIONS SHALL BE IAW OH-INTERCONNECT.
2. ALL ITEMS NOT EXPLICITLY DEFINED IN THIS DRAWING ARE DEFINED BY THE MASTER CAD MODELS. ALL DIMENSIONS NOT DEFINED ON THIS DRAWING ARE CONTAINED WITHIN THE FOLLOWING INTERMEDIATE FILES:
- 2.1. FLAT PARTS: <MATERIAL> <MATERIAL COLOR, IF APPLICABLE>_ <THICKNESS, IN DECIMAL INCHES> <PN> <REV>.v<VERSION NUMBER OF MODEL>.DXF
- 2.2. FDM 3D PRINTED PARTS: FDM_<PN> <REV>.v<VERSION # OF MODEL>.STL
- 2.3. RESIN 3D PRINTED PARTS: RESIN_<PN>_<REV>.v<VERSION # OF MODEL>.STL



-1 ASSY
SCALE 1.2:1




-1 ISO
SCALE 1.2:1



-1 ASSY
SCALE 1.2:1

REVISION HISTORY			
REV	DESCRIPTION	DATE	APPROVED
-	INITIAL RELEASE	3/30/2023	
A	FN 22: REPLACED WITH ALE+	9/26/2026	



-1 TOP
SCALE 1:1

22	1	ABSIS001	ASSY, ABSIS ALE+	N/A
21	8	94070A076	PHS, #2-56 X .1875, BRASS	BRS
20	3	90272A106	PHS, #4-40 X .250, STEEL	STL
19	1	OH4A7A2-15	OBOGS KNOB	ACRL
18	4	91780A105	STANDOFF, #2-56 X .375, .1875 HEX, FEMALE, ALUMINUM	ALU
17	1	91841A005	NUT, #4-40, 18-8	STL
16	3	91780A045	STANDOFF, #4-40 X 2.50, HEX, FEMALE, ALU	ALU
15	1	OHC0003-A-4OXYGW4	KNOB, OBOGS	----
14	4	91251A115	SHCS, 4-40 X 1.000, STEEL, BLACK OXIDE	STL
13	1	C7 NUT	HEX NUT FOR C7 SWITCH, 3/8-32 UNF	BRS
12	1	A11405RNZQ	SWITCH, ROTARY, 90 DEG, 2 POS	N/A
11	2	90760A007	NUT, JAM, #6-32, STEEL	STL
10	2	91249A151	PHS, #6-32 X .625, 18-8, BLK	SS
9	1	AT503M	HEX NUT FOR SWITCH, M12-1	SS
8	1	AT537	O-RING FOR SWITCH, 12 MM ID	RBR
7	1	AT508	LOCK WASHER FOR SWITCH, M12	SS
6	1	OHC0001-1	FAUX DZUS STUD	----
5	1	OH4A7A2-14	OBOGS REGULATOR	PETG
4	1	OH4A7A2-13	OBOGS LEGEND PLATE	RMRK
3	1	OH4A7A2-12	OBOGS LIGHTPLATE	ACRL
2	1	OH4A7A2-11	OBOGS BACKPLATE	ACRL
1	1	OH4A7A2-10	OBOGS PANEL PCB V2	N/A
ITEM	QTY	PART NUMBER	DESCRIPTION	MATERIAL

UNLESS OTHERWISE SPECIFIED:			PARTS LIST	
DIMENSIONS ARE IN INCHES.			DECIMALS:	
DUAL DIMENSIONS ARE IN MILLIMETERS AND ENCLOSED IN SQUARE BRACKETS.			.X ± .1	
INTERPRET DRAWING IAW ASME Y14.100-2017.			.XX ± .03	
INTERPRET DIM AND TOL IAW ASME Y14.5-2009.			.XXX ± .010	
REMOVE ALL BURRS AND SHARP EDGES TO .05 MAX.			ANGLES:	
DIMENSIONS APPLY BEFORE FINISH.			MACHINED ± 5°	
			LOCATING ± 5°	
			FORMED ± 2°	
			CHAMFERS ± 5°	
			DRILLED HOLE DIAMETERS:	
			.0135 - .125: +.004/- .001	
			.126 - .250: +.005/- .001	
			.251 - .500: +.006/- .001	
			.501 - .750: +.008/- .001	
			.751 - 1.000: +.010/- .001	
			1.001 - 2.000: +.012/- .001	
DESIGNED	J. STEENSEN	3/30/2023		
CHECKED	J. STEENSEN	3/30/2023		
DRAWN	B. LAZARUS	3/30/2023		
SIZE	D	DWG NO	OH4A7A2-1	
SCALE	1:1	DO NOT SCALE DWG	SHEET 1/1	
			REV	
			A	



ASSY, OBOGS PANEL

LEFT CONSOLE