Chapter 30 | Written solutions

Scientific Sequences and Biological Structure

All eleven exercises distinguish sequence order, learned representations, geometric contacts and structural confidence. Exercises 1-4 use hand calculations, 5-8 use the canonical NumPy helpers, and 9-11 design scientific evaluations. The written PDF contains every explanation and three plots; the notebook and its PDF add code and recorded checks. Supplied vectors and confidence values are teaching fixtures, not outputs from a protein model.

1. Read aligned columns

Read positions 2 and 4 from each row of the alignment, using one-based indices. They are target-alignment positions, not arbitrary adjacent letters.

Row	Sequence	Letters at columns 2 and 4
1	ACDG	C, G
2	ACEG	C, G
3	ASDA	S, A
4	ASEA	S, A

The counts are CG: 2 and SA: 2; CA and SG occur zero times. One explanation is shared ancestry: rows 1 and 2 inherited CG from one branch, while rows 3 and 4 inherited SA from another. This association need not imply a physical contact. Four related rows are not four independent experiments.

In the chapter's toy example, four rows and four positions happen to give two axes of length four. The pair grid still indexes two target positions, not two sequences. A learned pair vector can be directed and need not be a symmetric distance or a contact probability.

2. Preserve some order

Both CAAC and CCAA contain two A and two C residues. Divide counts by length four to get A = C = 1/2; all other composition entries are zero. Slide a two-residue window by one position, giving three overlapping pairs.

Sequence	Adjacent pairs in order	Nonzero normalized counts
CAAC	CA, AA, AC	CA = AA = AC = 1/3
CCAA	CC, CA, AA	CC = CA = AA = 1/3

CA and AC occupy different matrix entries: the first letter sets the row and the second sets the column. The pair frequencies distinguish these sequences, although Exercise 5 will show that they do not retain every aspect of order.

3. Pool only residues

The mask $(0, 1, 1, 0)$ keeps the vectors $(2, 0)$ and $(0, 4)$. Their coordinate-wise mean is

$$\frac{(2, 0) + (0, 4)}{2} = (1, 2).$$

If all four positions are included, the two marker vectors cancel in the sum, but they still count in the denominator:

$$\frac{(10, 10) + (2, 0) + (0, 4) + (-10, -10)}{4} = (0.5, 1).$$

Masking therefore matters even when the unwanted vectors happen to sum to zero. At least one residue must be selected. The helper selects rows before averaging; the numerator and denominator both depend only on actual residues.

4. Read a geometric threshold

The three residues are numbered in the given chain order. A pair must pass both the distance cutoff and the sequence-separation rule.

Unordered pair	Index separation	Distance	Accepted?
$(1, 2)$	1	2	No: adjacent in sequence.
$(1, 3)$	2	3	Yes: both tests include equality.
$(2, 3)$	1	$\sqrt{13} > 3$	No: fails both tests.

Only $(1, 3)$ is accepted. It activates matrix entries $(1, 3)$ and $(3, 1)$, which are array entries `[0,2]` and `[2,0]` in zero-based Python indexing. Every other Boolean entry is false. In the book's diagram convention, pairs excluded by sequence separation would be displayed as dashes. A Boolean false alone does not say which cutoff failed.

5. Verify the pair representation


A composition vector gives the fraction of residues that are each letter. In both `CAAC` and `CCAA`, two of the four residues are A and two are C. The A and C entries are each $2/4 = 1/2$. Every other entry is zero.

A dipeptide is a pair of neighboring residues read in sequence order. Move a two-residue window one position at a time. In `CAAC` it gives `CA`, `AA`, and `AC`. In `CCAA` it gives `CC`, `CA`, and `AA`. The pair matrix stores each frequency at the row for the first letter and the column for the second. Each listed pair occurs once among the three windows, so it has frequency $1/3$. All other pair entries are zero.

The expected arrays below come from those counts. The checks compare every entry, including the zeros, and verify that both totals are one for each four-residue sequence.

The sequence `A` contains one residue, so its composition assigns all the frequency to A. Its composition total is still one. It contains zero adjacent pairs, so there is no positive pair count to divide by. The function returns a matrix of zeros in this case, with total zero.

For AACAC, the windows are AA, AC, CA, AC. For ACAAC they are AC, CA, AA, AC. Both therefore have AA = 1/4, AC = 1/2 and CA = 1/4, with all other pair frequencies zero. Both have A = 3/5 and C = 2/5. The order differs but both summaries agree. Dipeptides retain more order than composition, yet they cannot always reconstruct the original sequence. The heatmap shows only the A/C and AA/AC/CA/CC entries; all others are zero.



6. Change only padding

The chapter's pooling figure shows five vectors in token order. The beginning marker (BOS) has $(9, 9)$, residue A has $(1, 0)$, residue C has $(1, 2)$, the ending marker (EOS) has $(-9, -9)$, and padding (PAD) has $(0, 0)$. The mask has one Boolean value per row. Only the two residue rows have a value of `True`.
Mean pooling averages each coordinate over the selected rows.

$$\frac{(1, 0) + (1, 2)}{2} = (1, 1).$$

Copy the array, replace the last row with $(7, 9)$, and pass the same mask both times. The two selected rows and their count stay the same. Both runs should therefore return $(1, 1)$.

Both calls return the same two coordinates. The function selects rows using the mask before taking the mean. The padding vector contributes neither to the coordinate sums nor to the number of rows averaged.

This check holds the supplied residue vectors fixed. When using a real encoder, padding must also be handled by its attention mask. Excluding padding from the final mean cannot repair residue vectors that already read padding incorrectly. Freeze the encoder's weights and use evaluation mode for reproducible features; those two settings have different purposes.

7. Translate the coordinates

Use the four points from the chapter's contact-map figure. In chain order they are $(0, 0, 0)$, $(3, 0, 0)$, $(0, 4, 0)$, and $(8, 0, 0)$. A pair is a contact when its Euclidean distance is at most 5 and its residue numbers differ by at least 2.

Using one-based residue numbers, only three unordered pairs pass the sequence-separation rule.

Pair	Index separation	Distance	Contact
$(1, 3)$	2	4	Yes
$(1, 4)$	3	8	No
$(2, 4)$	2	5	Yes

For each of these pairs, just one coordinate differs, so the distance is the size of that difference. Pair $(2, 4)$ qualifies at both cutoffs. Pair $(1, 2)$ is only 3 units apart, but its index separation is 1, so its entry is false. The diagonal has separation 0. Each accepted pair contributes two true entries, one in each half of the symmetric matrix.

A translation adds the same vector to every point. If $\mathbf{p}_i$ is the coordinate of residue i and $\mathbf{t} = (10, -3, 2)$, then


$$(\mathbf{p}_i + \mathbf{t}) - (\mathbf{p}_j + \mathbf{t}) = \mathbf{p}_i - \mathbf{p}_j.$$

Taking the length of that difference gives the same distance as before. The chain order stays fixed, so the index separation also stays fixed. Since each entry depends only on these two quantities, a shared translation preserves the whole map.

The rotation $(x, y, z) \mapsto (-y, x, z)$ also preserves distances and sequence indices. It changes coordinates while leaving the contact map invariant. The array multiplication below applies that rotation to row vectors.

Moving the threshold to the next representable floating-point number below 5 removes pair $(2, 4)$, whose distance is exactly 5. Pair $(1, 3)$ at distance 4 remains. The code's inclusive comparison is intentional. Large translations or values extremely close to a cutoff can introduce rounding effects; mathematical invariance does not imply exact floating-point equality under every transformation.

The three displayed maps use the same coordinate-index convention. Their row numbers are consecutive positions of one chain. Missing residues or concatenated chains would require explicit sequence indices and chain-aware rules.



8. Measure two classes

The first two proteins are correctly predicted as A. The third is an A predicted as B, and the fourth is the only true B. We score each class separately. For the class being scored, a true positive (TP) has that true label and is predicted to have it. A false positive (FP) receives that prediction in error. A false negative (FN) has that true label but is predicted to belong to the other class.

For each class, compute $F_1 = 2TP/(2TP + FP + FN)$. Both classes have a positive denominator in both runs. The support is the number of proteins with that true label, which equals $TP + FN$. Macro-F1 is the mean of the two class scores, giving A and B equal weight even though A has three examples and B has one.

Before the change, protein 3 contributes a false negative for A and a false positive for B. This gives A an F1 of $4/5$ and B an F1 of $2/3$, for a macro-F1 of $11/15$.

After the change, protein 4 also becomes an error. It contributes a false positive for A and a false negative for B. A keeps its two true positives and now scores $4/6 = 2/3$. B loses its only true positive and scores 0. The new macro-F1 is $1/3$.

9. Split by relatedness

Suppose 40 proteins labeled nuclear all belong to one family. A random protein split can put near relatives on both sides and reward recognition of that family's patterns. To test transfer across families, assign entire families to training, validation or test. A target allocation such as 70/15/15 percent is subordinate to having enough distinct families for the classes being evaluated. Families can contain several labels, so inspect actual sequence and family counts per class after assignment.

Fit preprocessing and classifiers on training families, select settings on validation families and score the test once. Record the source and version of family annotations. Screen duplicates and close relatives that have different family labels. If nominal groups are linked by near matches under the declared identity and alignment-coverage rule, keep them together or omit problematic records under a rule fixed before scoring. Check the closest cross-split pairs; distinct group names alone do not certify a sequence-identity bound.

A label represented by only one family cannot have supervised training examples and a family-disjoint transfer test at the same time. One defensible choice keeps that family entirely in training and marks its test recall/F1 unavailable for this transfer question. Predefine a macro average over the classes with held-out reference support, list them, and report every class's support. Predictions of the unsupported label on other test classes still count as mistakes for those examples. This restricted macro is not an estimate of transfer for all labels. More independent families are needed for the single-family label.

The illustrative assignment below uses N and C families for supported labels, and a single M family retained in training. It verifies bookkeeping only; real sequence comparisons are still needed to audit relatedness.

10. Test what an embedding adds

Use the same family-disjoint labeled splits and the same eligible test proteins for composition, dipeptides and frozen embeddings. Decide how to handle duplicate sequences, ambiguous symbols, incomplete chains and long sequences in advance. If the encoder's limit excludes some proteins, define a common eligible population and report exclusions. Quietly dropping difficult examples only for one method changes the comparison.

Composition has 20 entries; dipeptides have 400 after flattening, with the chapter's all-zero convention for a single residue. For embeddings, record the checkpoint, layer, feature width, residue mask, attention mask, evaluation mode and pooling rule. Mean contextual vectors can preserve order information that a mean of static letter vectors loses. Keep encoder weights frozen.

Fit the same classifier family, such as regularized multinomial logistic regression, for each representation. Learn any scaling on training proteins, tune regularization on the same validation set with equal search budgets, and report per-class scores, support and macro-F1 on identical test proteins. Different feature widths and prior training remain part of what is being compared.

Record the encoder's pretraining corpus/version and cutoff when documented. If searchable, audit identifiers, exact sequence hashes and close matches with an explicit alignment method and identity/coverage rule. Report exact matches, nonexact close matches, no match detected in the searched corpus, and unchecked cases separately. An unavailable corpus means overlap is unknown, not absent. A family split in the labeled task cannot establish pretraining independence.

Fit a length-only classifier using log length on the same splits. Define bins from training lengths, then compare representations on the same test proteins within each bin, reporting sample and class counts and a common supported-class set. Also give every representation the same length feature and repeat. An embedding advantage that persists within length strata and after this control supports a claim beyond length alone; it does not prove that all confounding factors have been removed.

The fixture checks a common length-eligibility rule and training-defined bins. It does not run a pretrained encoder or invent benchmark scores.

11. Assess a structural claim


One domain may supply a pocket wall and the other a putative ligand contact. Changing the angle between them can destroy the proposed pocket while preserving each domain's local geometry. Inspect pLDDT at the candidate residues and the linker, then inspect PAE within each domain and in both directions across domains.

In the constructed six-position plot, domain A is 1-3 and domain B is 4-6. The supplied pLDDT values are all 94-97. Off-diagonal PAE values within each domain are 2 angstroms; the two cross-domain blocks are 18 and 12 angstroms. Here the row is the residue whose positional error is estimated and the column is the alignment anchor. Thus PAE[1,4] is 18 and PAE[4,1] is 12 with one-based indices. The direction changes the question; PAE need not be symmetric.

These values support greater confidence in each local domain than in their relative placement. They do not say that the domains are 18 or 12 angstroms apart: PAE is predicted aligned error, not distance. Nor are they measured errors against a known structure. pLDDT is not a probability of binding or function. The entire plot is a supplied teaching construction.

Separate two experimental questions. A direct binding measurement, such as isothermal titration calorimetry, can test whether the ligand interacts with the full-length protein under the assay conditions. Include background controls and replication. Locating the interaction requires complementary evidence, such as a ligand-bound experimental structure with adequate support for the ligand and nearby residues in both domains.

Candidate-contact changes on each side, compared with the unmodified protein and a control change away from the site, can test the proposed explanation. Check folding and assembly: reduced binding can arise from a disrupted protein or altered domain orientation rather than loss of a direct contact. Binding measurements, structural evidence and these controls address different parts of the claim. A confident predicted pocket alone does not establish it.


Local confidence
pLDDT
Residue
Domain A
Domain B
Predicted aligned error
Residue i whose error is estimated
Alignment anchor j
PAE (angstroms)