Chapter 30 | Written solutions

Decisions and Embodied Action

These solutions connect a reward log to action choices and then to the consequences of executing those choices. The same return-conditioned table reaches the goal on the original grid and hits the moved trap on the shifted grid. A requested score does not determine an outcome.

Exercises 1-4 develop the representations by hand; 5-8 run the canonical Python routines; 9-11 give sample evaluation designs. The counts and grid are teaching examples, not trained Transformer or robot benchmark results. The last timing calculation is an idealized schedule, not a measured robot speed.

1. Compute returns-to-go

Work backward from the last reward. With $G_4 = 0$, the four sums are

$$G_3 = 4, \quad G_2 = -1 + 4 = 3, \quad G_1 = 2 + 3 = 5, \quad G_0 = 0 + 5 = 5.$$

The chronological answer is $(5, 5, 3, 4)$. At step 2 the current return includes a penalty of -1. Once paid, the remaining return increases: $G_3 = G_2 - r_2 = 3 - (-1) = 4$. Reward r_t belongs to the action at step t, not the action before it. These are realized returns computed from a complete recorded episode.

2. Identify the available tokens


The full record begins $G_0, s_0, a_0, G_1, s_1, a_1, G_2, s_2, a_2$. For the prediction at s_2, a two-step input window keeps steps 1 and 2. It can read G_1, s_1, a_1, G_2, s_2. Step 0 has been removed, and a_2 is causally blocked.

Step	**Tokens**	**Available at s_2**
0	G_0, s_0, a_0	None: outside the input window
1	G_1, s_1, a_1	All three
2	G_2, s_2, a_2	G_2, s_2 only

The recorded a_1 describes an earlier decision. The recorded a_2 is the target being predicted; allowing it into its own context would leak the answer. In deployment, the history contains previously executed actions.

During training, G_0 is computed from recorded future rewards (5 in Exercise 1). During deployment, the initial return token is a supplied request $\widehat{G}_0$. Its later values subtract observed rewards. It cannot be filled with the realized future return of the test episode.

The figure shows three separately cropped input windows, each containing at most two steps. A full sequence with only a local per-layer mask can transmit older information across multiple layers; that is not the same construction.



3. Count the two policies

At the start, three failed episodes vote for right and one successful episode votes for down. The state-only fit pools all four votes and selects right. The fit conditioned on return +1 sees only the successful episode and selects down. Conditioning on -1 selects the three failed episodes and right.

Fit at the start	Up	Right	Down	Left	Choice
State only	0	3	1	0	Right
Return +1	0	0	1	0	Down
Return -1	0	3	0	0	Right

Both tables use the same log. The change is which records contribute to each lookup, not a new interaction with the environment.

4. Read an action bin

Zero-based bin 1 means -1 cm; bin 4 means +2 cm. If the controller reverses the ordered table, it decodes bin 1 as +1 cm instead. A syntactically valid token can therefore move in the wrong direction.

The interface must also specify the reference frame, units, and execution interval. A displacement is not a velocity: interpreting +1 cm as +1 cm/s would change the motion. The five values here are a teaching table, not RT-2's actual discretization.

5. Check the return routine

Start at the end of the trajectory with rewards $(0, 2, -1, 4)$. The last action earns 4, so its return-to-go is 4. One step earlier, the action costs 1 and the later action earns 4, leaving 3. Moving back two more steps adds 2 and then 0. In chronological order, the four returns are $(5, 5, 3, 4)$.

In general, the return-to-go G_t includes the reward r_t from the current action and all rewards after it. With $G_T = 0$ after the final action, the backward calculation uses $G_t = r_t + G_{t+1}$. When we read the trajectory forward, the same rule gives $G_{t+1} = G_t - r_t$. After the penalty at step 2, subtracting -1 gives $G_3 = 3 - (-1) = 4$.

At step 0 the return includes the whole trajectory, so it equals the sum $0+2-1+4=5$. A trajectory with just one reward of -3 has only one return, which also equals its total of -3. The code checks both full vectors, compares their first entries with Python's `sum`, and verifies the forward rule through the terminal zero.

An empty trajectory has no current step, so its return vector is empty; indexing its first entry is invalid. The function correctly returns an array of length zero.

For the optional discounted extension, use $\gamma = 1/2$. Working backward gives 4, then $-1 + (1/2)4 = 1$, then $2 + (1/2)1 = 2.5$, then $(1/2)2.5 = 1.25$. Thus the vector is $(1.25, 2.5, 1, 4)$. Its first entry is not the undiscounted total 5. The forward rule is $G_{t+1} = (G_t - r_t)/\gamma$, including the final zero.

6. Test an unsupported target

The log starts every demonstration at $(0, 0)$. The three failed episodes each have a return of -1 there, and the successful episode has a return of $+1$. Fitting the second table stores an action for each observed pair of position and return-to-go. At the initial position a request for $+2$ has no entry. With -1, the same table has the action `R` for right.

Keep the original grid and run the conditioned policy with both targets. The trace records the initial state even when the first table lookup fails. Each action that executes adds one resulting state and one reward.

With $+2$, the policy stops with `unsupported` at the first lookup. The visited state list contains just $(0, 0)$. The action and reward lists are empty, so the total reward is 0. With -1, the policy chooses `R`. The simulator moves to $(0, 1)$, records reward -1, and ends the episode with `trap`. The first stop comes from a missing entry in the learned table. The second comes from an executed action reaching a terminal cell.

Request 0 is unsupported too: the fitted table has no start entry with that return. Nevertheless, total reward 0 is possible under the episode time limit: an explicit policy that always moves up from the top-left cell stays against the wall. It reaches the step limit with zero reward. Request +2 is different: the environment can supply at most one terminal reward +1, so +2 is impossible. A missing lookup alone cannot distinguish these cases.

7. Inspect the shifted rollout

Keep the fitted policy and the starting target $+1$ fixed. The original grid has its trap at $(0, 1)$ and the shifted grid moves it to $(1, 1)$, a cell on the route to the goal. Run the chapter's example module to see what the move changes.


The subprocess uses the notebook's Python interpreter and runs from the repository root so Python can find the module. The JSON file lives in a temporary directory and the parsed result stays available as a Python dictionary.

Each trace records the starting position as its first state. With zero-based indices, `actions[i]` leaves `states[i]` and arrives at `states[i + 1]` with reward `rewards[i]`. Print both transitions using one-based step numbers, then compare the resulting state and reward at each step the runs have in common.

The first difference is the reward from the second action. Both agents move right into $(1, 1)$. That cell gives 0 on the original grid and -1 on the shifted grid, where entering it ends the episode. Subtracting the reward leaves a target of $1 - 0 = 1$ on the original grid and $1 - (-1) = 2$ on the shifted grid. The latter is recorded in the trace at termination.

The policy looks up an action using the current position and the remaining target. In both runs it starts at $((0, 0), +1)$ and chooses `D`. That move goes to $(1, 0)$ and gives reward 0 on both grids. The next lookup is therefore $((1, 0), +1)$ in both runs, so the policy chooses `R` before receiving the reward for that move.

The reward plot ends each line when its episode ends; it does not invent later zero rewards for the stopped run. The changed layout is not an input to this policy. Both first decisions therefore receive identical keys, even though the second action now has a different consequence. More frequent observations of position alone would not reveal the relocated trap.



8. Vary the demonstrations

On the original grid, each trap demonstration starts with `R` and each goal demonstration starts with `D`. The chapter's original log has three trap demonstrations and one goal demonstration. Keep the same two routes and reverse how often they appear. Count the logged actions at the start and use the chapter's function to fit both policy tables on each log.

Now run both fitted policies on the original grid. The simulator uses the original trap by default. For the conditioned policy, pass `target_return=1` so that it follows the decisions recorded with a remaining target of $+1$.

The state-only table pools all visits to the start. In the original log its majority action is `R` by three votes to one, so it enters the trap immediately. In the new log its majority action is `D` by the same margin. At the later cells on the goal route, the log contains only the demonstrated goal actions, so it completes `D, R, R, U` and earns $+1$.

The conditioned table counts the two kinds of start visits under separate keys. The `D` votes have return-to-go $+1$ and the `R` votes have return-to-go -1. Repeating the goal demonstration adds votes for the same action at each key on the goal route, so the $+1$ rollout reaches the goal with either log.

With two copies of each route, the start has two right votes and two down votes. The fixed priority is up, right, down, left; right wins this tie and the state-only rollout hits the trap. The conditioned +1 fit still has only down votes at the start and reaches the goal. Reordering the log does not change this tie rule.

9. Split entire episodes

Give each trajectory an episode ID, a layout ID, and a starting condition before extracting training windows. Assign whole episodes to splits. If an episode was copied or replayed verbatim, keep its copies together. Neighboring windows may share states, actions, and return tokens computed from overlapping future rewards.

For familiar-layout generalization, reserve complete episodes beginning at selected positions within layouts represented in training. To claim a new starting position, remove other episodes starting there from training too. A position may still occur later along a training route; distinguish an unseen start from an unseen state. Separate validation starts are needed to choose settings without using the test set.

For layout generalization, withhold layout E from fitting and tuning. Train on A-D, with a separate validation group within those layouts. The observation interface must tell the learner enough about a layout if it is expected to adapt to it: equal position coordinates do not distinguish different obstacles. If feasible, rotate the held-out layout and report each result, retaining a genuine test boundary in every run.

The fact that there are 100 episodes over five layouts does not establish how many starts each layout contains. The audit below constructs 20 episode IDs per layout only to illustrate grouping. It is not a measured dataset or a guarantee that there are enough examples of each starting position.

10. Compare imitation with closed-loop success

Choose held-out starts and goals before inspecting the policies' outcomes. Use identical resets, rewards, observation and action interfaces, time budgets, and termination rules. Include ordinary starts and starts near a junction with a recoverable side route. In a stochastic simulator, pair suitable seeds and repeat independent episodes.

First run both policies without intervention and let their actions determine subsequent observations. Record goal success, total reward, executed steps, elapsed time, and stop reason. Report unsupported actions or states separately from traps and timeouts. Equal held-out action accuracy does not imply equal severity or locations of mistakes.

Run a separate recovery test with the same controlled disturbance applied to both policies: for example, force one wrong turn into a recoverable alcove, then return control to the policy. Feed it the actual resulting observation and the actually executed action history. Measure whether it returns to a valid route, actions and time to recovery, and eventual goal completion. Check that the off-route states are absent from training if the test claims recovery from unfamiliar states.

A policy can recover more often and reach more goals despite matching the same fraction of demonstration actions. Report ordinary and perturbed trials separately, with sample counts and episode-level uncertainty. Never combine them into an unspecified success denominator.

The small record below only demonstrates outcome accounting; it is supplied teaching data, not a simulator comparison. Three goals in five independent trials would be 60% observed success, with substantial uncertainty. An unsupported zero-reward trial is not a success.

11. Evaluate the control interface

Keep the trained checkpoint, observation and instruction inputs, action decoding, controller, and prediction horizon $H = 8$ fixed. Compare execution horizons $K = 8$ and $K = 2$. The latter executes the first two actions, discards the unused six, obtains a fresh image, and predicts another eight. Update any action history with executed commands only.

If each action lasts 0.1 s and inference takes no time, refresh intervals are $8(0.1) = 0.8$ s and $2(0.1) = 0.2$ s: idealized refresh rates of 1.25 and 5 Hz. Both execute actions at 10 Hz. Refresh rate and action execution rate are different quantities.

Use paired resets with the same object, pose, lighting, camera placement, instruction, and target. Include nominal trials and separate trials in which the object is displaced just after the first executed action. Align the perturbation to physical progress and use matched displacements. Define success, time and action budgets, and recovery before collecting results.

Timestamp image acquisition, inference start and end, command dispatch, and execution on one clock. Attach the source frame ID to each command. Measure observation age at execution, image-to-first-command latency, model-call count, idle waiting, completion time, goal placement, drops, and constraint violations. A command produced quickly can still use a stale queued image.

For disturbed trials, record when the shift occurred, when an observation first reflected it, when corrective movement began, whether a secure grasp or route was regained, and eventual success. Include non-recoveries, distinguishing traps or other failures from timeouts.

The figure assumes zero inference latency. With an additional 0.15 s of blocking inference at every refresh, an idealized cycle would take $0.8 + 0.15 = 0.95$ s for $K = 8$ and $0.2 + 0.15 = 0.35$ s for $K = 2$. Real systems may overlap computation with movement, so these are serial scheduling calculations, not universal latency formulas. More frequent high-level replanning can improve reaction opportunities while increasing waiting time or disrupting coordinated motion. Low-level sensor control may continue between image refreshes.

