

```
USE ROLE ACCOUNTADMIN;  
USE WAREHOUSE COMPUTE_WH;  
USE DATABASE SNOWFLAKE_FUNDAMENTALS;  
USE SCHEMA DAY2;
```

```
/*=====Create ROLES=====*/
```

```
CREATE ROLE HR_ROLE;  
CREATE ROLE FINANCE_ROLE;
```

```
-- Create users
```

```
CREATE USER hr_user PASSWORD='password';  
CREATE USER finance_user PASSWORD='password';
```

```
-- Assign roles to users
```

```
GRANT ROLE HR_ROLE TO USER hr_user;  
GRANT ROLE FINANCE_ROLE TO USER finance_user;
```

```
GRANT USAGE ON DATABASE SNOWFLAKE_FUNDAMENTALS TO ROLE  
HR_ROLE;  
GRANT USAGE ON SCHEMA SNOWFLAKE_FUNDAMENTALS.DAY2 TO ROLE  
HR_ROLE;  
GRANT SELECT ON TABLE SNOWFLAKE_FUNDAMENTALS.DAY2.employees TO  
ROLE HR_ROLE;  
GRANT USAGE ON WAREHOUSE COMPUTE_WH TO ROLE HR_ROLE;
```

```
GRANT USAGE ON DATABASE SNOWFLAKE_FUNDAMENTALS TO ROLE  
FINANCE_ROLE;  
GRANT USAGE ON SCHEMA SNOWFLAKE_FUNDAMENTALS.DAY2 TO ROLE  
FINANCE_ROLE;  
GRANT SELECT ON TABLE SNOWFLAKE_FUNDAMENTALS.DAY2.employees TO  
ROLE FINANCE_ROLE;  
GRANT USAGE ON WAREHOUSE COMPUTE_WH TO ROLE FINANCE_ROLE;
```

```
CREATE OR REPLACE TABLE employees (  
    id INT,  
    name STRING,  
    department STRING,  
    salary DECIMAL  
);
```

```
INSERT INTO employees (id, name, department, salary) VALUES  
(1, 'John Doe', 'HR', 55000),  
(2, 'Jane Smith', 'Finance', 75000),  
(3, 'Sam Brown', 'IT', 62000),  
(4, 'Emily White', 'Finance', 80000),  
(5, 'Mike Black', 'HR', 52000);
```

/*

*/

```
CREATE OR REPLACE ROW ACCESS POLICY dept_filter_policy
AS (department STRING)
RETURNS BOOLEAN ->
CASE
  WHEN CURRENT_ROLE() = 'HR_ROLE' THEN TRUE  -- HR users can see all
rows
```