

```
USE ROLE ACCOUNTADMIN;
USE WAREHOUSE COMPUTE_WH;
USE DATABASE SNOWFLAKE_FUNDAMENTALS;
USE SCHEMA DAY4;
```

```
ALTER WAREHOUSE COMPUTE_WH SET WAREHOUSE_SIZE='X-SMALL';
```

```
ALTER WAREHOUSE COMPUTE_WH SUSPEND;
--Make sure query results cache is not used
ALTER SESSION SET USE_CACHED_RESULT = FALSE;
```

```
/*
```

```
Create a copy of the table with 15B records with random order and no cluster
```

```
*/
```

```
create or replace TABLE
SNOWFLAKE_FUNDAMENTALS.DAY4.ORDERS_CLUSTERING_DEMO_NO_NAT
URAL_ORDER (
    O_ORDERKEY NUMBER(38,0),
    O_CUSTKEY NUMBER(38,0),
    O_ORDERSTATUS VARCHAR(1),
    O_TOTALPRICE NUMBER(12,2),
    O_ORDERDATE DATE,
    O_ORDERPRIORITY VARCHAR(15),
    O_CLERK VARCHAR(15),
    O_SHIPPRIORITY NUMBER(38,0),
    O_COMMENT VARCHAR(79)
);
```

```
INSERT INTO
SNOWFLAKE_FUNDAMENTALS.DAY4.ORDERS_CLUSTERING_DEMO_NO_NAT
URAL_ORDER
SELECT * FROM SNOWFLAKE_SAMPLE_DATA.TPCH_SF1000.ORDERS
ORDER BY RANDOM();
```

```
SELECT * FROM ORDERS_CLUSTERING_DEMO WHERE
O_ORDERDATE='1997-09-19';
```

```
/*
```

```
Create a copy of the table with 15B records a cluster
```

```
*/
```

```
create or replace TABLE
SNOWFLAKE_FUNDAMENTALS.DAY4.ORDERS_CLUSTERING_DEMO_WITH_C
LUSTER (
```

```
O_ORDERKEY NUMBER(38,0),
O_CUSTKEY NUMBER(38,0),
O_ORDERSTATUS VARCHAR(1),
O_TOTALPRICE NUMBER(12,2),
O_ORDERDATE DATE,
O_ORDERPRIORITY VARCHAR(15),
O_CLERK VARCHAR(15),
O_SHIPPRIORITY NUMBER(38,0),
O_COMMENT VARCHAR(79)
) CLUSTER BY (O_ORDERDATE);
```

```
INSERT INTO
SNOWFLAKE_FUNDAMENTALS.DAY4.ORDERS_CLUSTERING_DEMO_WITH_C
LUSTER
```