

```

USE ROLE ACCOUNTADMIN;
USE WAREHOUSE COMPUTE_WH;
USE DATABASE SNOWFLAKE_FUNDAMENTALS;
USE SCHEMA DAY3;

--Variant data type can hold any data type value
CREATE OR REPLACE TABLE raw_source (
  SRC VARIANT);

--Create a stage with JSON from S3
CREATE OR REPLACE STAGE my_json_stage
  URL = 's3://snowflake-docs/tutorials/json';

--Load the json file from external stage
COPY INTO raw_source
  FROM @my_json_stage/server/2.6/2016/07/15/15
  FILE_FORMAT = (TYPE = JSON);

--Verify the data
SELECT * FROM raw_source;

--Parse the device type which is the root element
SELECT
  src:device_type
FROM raw_source;

--Parse and remove the Quotes from the root element
SELECT
  src:device_type::string AS device_type
FROM raw_source;

--to parse the array of values we need to use the flatten function.
SELECT
  value:f::number
FROM
  raw_source
,LATERAL FLATTEN( INPUT => SRC:events );

---

select
  src:device_type::string          as device_type
, src:version::string             as version
, value:f::number                 as f
, value:rv::variant               as rv
, value:t::number                 as t

```

```
, value:v.ACHZ::number      as achz
, value:v.ACVC::number      as acv
, value:v.DCA::number       as dca
, value:v.DCV::number       as dcv
, value:v.ENJR::number      as enjr
, value:v.ERRS::number      as errs
, value:v.MXEC::number      as mxec
, value:v.TMPI::number      as tmpi
, value:vd::number          as vd
, value:z::number           as z
from
  raw_source
, lateral flatten ( input => SRC:events );
```