

```
USE ROLE ACCOUNTADMIN;
```

---Enabling the mutlicluster warehouse

```
CREATE OR REPLACE WAREHOUSE NEW_COMPUTE_WH
WITH
  WAREHOUSE_SIZE = 'XSMALL' -- You can choose from 'XSMALL', 'SMALL',
'MEDIUM', 'LARGE', 'XLARGE', etc.
  MAX_CLUSTER_COUNT = 10    -- The maximum number of clusters Snowflake
can scale up to
  MIN_CLUSTER_COUNT = 2     -- The minimum number of clusters to maintain
  SCALING_POLICY = 'STANDARD' -- This controls the scaling behavior (options:
'ECONOMY', 'STANDARD')
  AUTO_SUSPEND = 300        -- The number of seconds to wait before
suspending the warehouse when idle
  AUTO_RESUME = TRUE;       -- Whether the warehouse should automatically
resume when a query is run
```

```
USE ROLE ACCOUNTADMIN;
USE WAREHOUSE NEW_COMPUTE_WH;
```

```
--Alter session the session not to use the query cache
ALTER SESSION SET USE_CACHED_RESULT = FALSE;
```

```
--XS
SELECT
  C_CUSTKEY,
  SUM(O_TOTALPRICE) TOTAL_SALES,
FROM SNOWFLAKE_SAMPLE_DATA.TPCH_SF1000.ORDERS O
INNER JOIN SNOWFLAKE_SAMPLE_DATA.TPCH_SF1000.CUSTOMER C -- ON
O.O_CUSTKEY=C.C_CUSTKEY
GROUP BY C_CUSTKEY ;
```