


iFrame protection

iFrames are widely used. We can embed different websites, ads, videos in our own website.



a.com is our website. We have embedded b.com , google.com and ads using iFrame in our website.


If not handled properly, b and ads can access different parts of our web application which we don't want. It poses a security threat to us.

Take another example, we have embedded google and we are allowing users to do google search in our application. So basically we are using google's all resources for free which shouldn't be the case.

Security

Namaste Frontend System Design

IFrame Protection



Vulnerability

- Clickhijacking
- Data theft via javascript
- Session & Cookie theft

Mitigation

- X-Frame-Options: DENY
- CSP: frame-ancestors 'self'
- sandbox iframe
- httpOnly: true, secure: true, sameSite: 'strict' } cookie

VULNERABILITIES

1. Click Hijacking

We place an transparent iFrame on top of our website. User clicks on submit button. User thinks he has click on submit button but he/she clicks on transparent iFrame's button and ends up sending critical info

2. Data theft via javascript


I am parent window(a) and I am able to access something in child window(b) or vice versa

3. Session and cookie theft

Parent to child or vice versa

Project folder code

<https://github.com/namastedev/namaste-frontend-system-design/tree/master/Security/IframeProtection>




example1.html

```
<!DOCTYPE html>
<html>
  <head>
    <title>Clickjacking Example</title>
  </head>
  <body>
    <h1>Clickjacking Example</h1>
    <p>Click the button below to see a simple clickjacking demonstration.</p>
    <button id="overlay-button">Click Me!</button>
    <script>
      // Simulate a clickjacking attack by overlaying the button on top of the iframe
      document
        .getElementById("overlay-button")
```

```

        .addEventListener("click", () => {
            alert("Button clicked!");
        });
    </script>
</body>
</html>

```



iframe-webiste1.html


```

<!DOCTYPE html>
<html>
  <head>
    <title>Clickjacking IFrame</title>
  </head>
  <body>
    <h1>Child Iframe</h1>
    <p>Iframe: Click the button below to see a simple clickja

```

clicking demonstration.</p>

```
<button style="background-color: red;" onclick="alert('clicked iframe button')">Pay Now</button>
</body>
</html>
```



Child IFrame

Iframe: Click the button below to see a simple clickjacking demonstration.

Pay Now



1. CLICK HIJACKING example

Adding iframe of iframe-website in example1

example1

```
<!DOCTYPE html>
<html>
```

```

<head>
  <title>Clickjacking Example</title>
</head>
<body>
  <h1>Clickjacking Example</h1>
  <p>Click the button below to see a simple clickjacking demonstration.</p>


  <iframe src="http://localhost:5011/iframe-webiste1" id="legit-iframe"></iframe>

  <button id="overlay-button">Click Me!</button>
  <!-- <style>
    #legit-iframe {
      background-color: #ccc;
      opacity: 0;
      position: absolute;
      top: 0px;
      left: 0;
      width: 100%;
      height: 100%;
      z-index: 1;
    }
  </style> -->

  <script>
    // Simulate a clickjacking attack by overlaying the button on top of the iframe
    document
      .getElementById("overlay-button")
      .addEventListener("click", () => {
        alert("Button clicked!");
      });
  </script>


```

```
</body>
</html>
```



Uncommenting style in above code

Styling child iFrame such that Pay now button overlaps Click me button but opacity is 0(transparent)



When user clicks on Click Me, he has actually clicked on Pay now button of iFrame. This is known as click hijacking.

2. Data theft | session theft | cookie theft

example2.html

```
<!DOCTYPE html>
<html>
  <head>
    <title>Data Theft via JavaScript</title>
    <script>
      function setCookie(name, value, days) {
        var expires = "";

        if (days) {
          var date = new Date();

```



```

        date.setTime(date.getTime() + days * 24 * 60 * 60 *
1000);
        expires = "; expires=" + date.toUTCString();
    }

    document.cookie = name + "=" + value + expires + "; path=/";
}

    setCookie("parentCookie", "secret", 1);
</script>
</head>
<body>
    <h1>Data Theft via JavaScript</h1>

    <iframe
        src="http://localhost:5011/iframe-webiste2"
        sandbox="allow-same-origin allow-scripts allow-modals"
    ></iframe>
</body>
</html>

```

iframe-webiste2.html

```

<!DOCTYPE html>
<html>
<head>
    <title>Malicious iframe</title>
</head>
<body>
    <h1>Malicious iframe</h1>
    <p>This iframe attempts to steal data from the parent window.</p>


```

```

<script>
  window.alert('Hi');
  // Malicious JavaScript code in the iframe
  window.onload = function () {
    try {
      const parentWindow = window.parent;
      const parentDocument = parentWindow.document;

      // Attempt to read html
      const stolenData = parentDocument.innerHTML;
      alert("Stolen Data: " + stolenData);
    } catch (error) {
      console.error("Data theft failed:", error);
    }
  };
</script>
</body>
</html>

```



As you can see, modern browsers doesn't allow embedded iFrame to access parent dom but issue still exists in older browsers

We can similarly access cookie data as well in older browsers.

MITIGATIONS

1. X-Frame-Options: DENY(older way)


CSP- frame ancestors 'self' (we can use none as well)

If we don't want our website to be iframed we can use both the ways above

If we add below code in index file of server2

```
app.use((req, res, next) => {  
  res.setHeader('Content-Security-Policy', "frame-ancestors  
'self'")  
  next();  
})
```

Try to access example2 as above




Another example, let's try to access google as iFrame in our website

example3.html

```
<!DOCTYPE html>
<html>
  <head>
    <title>Clickjacking Example</title>
  </head>
  <body>
    <h1>Render google in iframe</h1>
    <p>Click the button below to see a simple clickjacking demonstration.</p>

    <iframe src="http://google.co.in"></iframe>
```

```
</body>
</html>
```



2. sandbox

The `sandbox` attribute enables an extra set of restrictions for the content in the iframe.

When the `sandbox` attribute is present, and it will:

- treat the content as being from a unique origin
- block form submission
- block script execution
- disable APIs
- prevent links from targeting other browsing contexts

- prevent content from using plugins (through `<embed>`, `<object>`, `<applet>`, or other)
- prevent the content to navigate its top-level browsing context
- block automatically triggered features (such as automatically playing a video or automatically focusing a form control)

Value	Description
<i>(no value)</i>	Applies all restrictions
allow-forms	Allows form submission
allow-modals	Allows to open modal windows
allow-orientation-lock	Allows to lock the screen orientation
allow-pointer-lock	Allows to use the Pointer Lock API
allow-popups	Allows popups
allow-popups-to-escape-sandbox	Allows popups to open new windows without inheriting the sandboxing
allow-presentation	Allows to start a presentation session
allow-same-origin	Allows the iframe content to be treated as being from the same origin
allow-scripts	Allows to run scripts
allow-top-navigation	Allows the iframe content to navigate its top-level browsing context
allow-top-navigation-by-user-activation	Allows the iframe content to navigate its top-level browsing context, but only if initiated by user

example2.html

```
<!DOCTYPE html>
<html>
  <head>
    <title>Data Theft via JavaScript</title>
    <script>
      function setCookie(name, value, days) {
        var expires = "";
```

```

        if (days) {
            var date = new Date();
            date.setTime(date.getTime() + days * 24 * 60 * 60 *
1000);
            expires = "; expires=" + date.toUTCString();
        }


        document.cookie = name + "=" + value + expires + "; p
ath=/";
    }

    setCookie("parentCookie", "secret", 1);
</script>
</head>
<body>
    <h1>Data Theft via JavaScript</h1>


    <iframe
        src="http://localhost:5011/iframe-webiste2"
        sandbox
    ></iframe>
</body>
</html>

```

Remove CSP header from index.js of server 2



```
<iframe
  src="http://localhost:5011/iframe-webiste2"
  sandbox="allow-same-origin allow-scripts allow-modals"
></iframe>
```



3. If parent tries to steal something from child. You can mention below code in child script

```
<script>
  if (top !== self) {
    top.location = self.location;
```



```
    }  
</script>
```

We have added this in iframe-webiste1.html as we are adding its iFrame in example 1.html. This is to prevent example 1 from accessing anything from iframe-webiste1.

4. Setting extra headers in cookie

`httpOnly: true` - it means you can only access cookies only on the server. You cannot access cookie using JavaScript (cannot use `document.cookie` etc)

`secure: true` - cookie will be sent to the client if it is https

`sameSite: 'strict'` - if APIs are being called to some other domain, your cookies will not travel along with them

```
app.use((req, res, next) => {  
  res.setHeader('Content-Security-Policy', "frame-ancestors  
    'self'")  
  
  res.cookie('sessionID', '12345', {  
    httpOnly: true,  
    secure: true,  
    sameSite: 'strict',  
  });  
  next();  
})
```

This code is present in server 2 - index.js

Example - linkedn inspect

The screenshot shows a web browser with the LinkedIn profile of Sharvil Ajmani. The developer tools are open, and the 'Application' tab is selected, showing a list of cookies. The cookies are organized by domain and path, with columns for Name, Value, Domain, Path, Expires / Max-Age, Size, HttpOnly, Secure, SameSite, Partition Key, and Priority.

N	Value	Domain	Path	Expires / Max-Age	Size	HttpOnly	Secure	SameSite	Partition Key	Priority
N 51...		.google.co.in	/	2024-05-19T13:20:21...	319	✓	✓	None		Medium
N 32...		.google.co.in	/	2025-01-07T09:29:23...	51		✓	None		High
A A...		.google.co.in	/	2024-01-27T05:37:24...	62	✓	✓	Lax		Medium
S 32...		.google.co.in	/	2025-01-07T09:29:23...	41		✓			High
L A...		.doubleclick.net	/	2024-10-16T07:31:18...	70	✓	✓	None		Medium
S Ai...		.google.co.in	/	2025-01-07T09:29:23...	21	✓	✓			High
J si...		.google.com	/	2025-01-09T15:11:21...	94	✓	✓	None		High
J A...		.google.com	/	2025-01-09T15:11:21...	92	✓	✓			High
J si...		.google.com	/	2025-01-09T15:11:21...	94	✓	✓			High
http		.google.com	/	2025-01-20T17:58:42...	51		✓			High
b *v...		.linkedin.com	/	2025-01-09T15:11:21...	49		✓	None		Medium
http		.google.com	/	2025-01-20T17:58:42...	41		✓			High
L v...		.linkedin.com	/	Session	18		✓	None		Medium
Interes		.google.com	/	2024-07-11T14:51:16...	529	✓	✓	None		Medium
I A...		.linkedin.com	/	2024-02-09T15:11:17...	103		✓	None		Medium

The console shows 82 issues, with 173 errors and 2 warnings. The system clock indicates 17°C Cloudy, 20:42, 10-01-2024.