MIN/MAX ALARM

Digital Thermometer



- High/low temperature alarm setting
- Internal/External sensor switchable
- Display backlight
- °C/°F selectable
- Min/Max memory for internal or external sensor lowest & highest reading stored for instant recall.
- Attachable magnet and suction cup sensor holder included

| Temperature Range | Internal Sensor: 14°F to 122°F (-10°C to 50°C) |
|------------------------------|---|
| | External Sensor: -58°F to 158°F (-50°C to 70°C) |
| Accuracy | ±1.8°F (±1.0°C) |
| Resolution | 0.1°F (0.1°C) |
| Display Reading Update | 10 seconds |
| Sensor | Thermistor |
| External Sensor Cable Length | 10 ft. (3m) |
| Display Window Size | 1.9 in. (W) x .8 in. (H) (48 mm x 21 mm) |
| Product Size | 2.9 in. (W) x 2 in. (H) x 6 in. (D) (73 mm x 52 mm x 15 mm) |
| Weight | 2.5 oz. (70 g) |
| Body Casing | Polycarbonate and ABS plastic |
| Probe | Stainless steel probe, .875 in. (L) (17.8 mm) |
| Battery (included) | 1.5 volt AAA/ UM4 or equivalent |
| Certification/Calibration | CE mark, N.I.S.T. traceable by lot |

1-800-962-6776 • www.deltatrak.com



P.O. Box 398

Pleasanton CA 94566

(925) 249-2250

Fax (925) 249-2251