

Racecar 101

James Wright

September 8, 2022

Outline

1 What makes a car fast?

2 Vehicle Basics

Note

This first part is a very simplified breakdown

- It's not the most accurate
- It's not to insult anyone's intelligence

It's simply to not distract from the things that can be easily forgotten or muddled.

What makes a car go fast?

$$\text{Time} = \frac{\text{Distance}}{\text{Velocity}}$$

¹Assuming distance is constant

What makes a car go fast?

$$\text{Time} = \frac{\text{Distance}}{\text{Velocity}}$$

- To lower time, we need to increase velocity¹

¹Assuming distance is constant

What makes a car go fast?

$$\text{Time} = \frac{\text{Distance}}{\text{Velocity}}$$

- To lower time, we need to increase velocity¹
- All motorsports have velocity changes during a race
 - Excluding top-speed records of course

¹Assuming distance is constant

What makes a car go fast?

$$\text{Time} = \frac{\text{Distance}}{\text{Velocity}}$$

- To lower time, we need to increase velocity¹
- All motorsports have velocity changes during a race
 - Excluding top-speed records of course
- Change in velocity is...

¹Assuming distance is constant

What makes a car go fast?

$$\text{Time} = \frac{\text{Distance}}{\text{Velocity}}$$

- To lower time, we need to increase velocity¹
- All motorsports have velocity changes during a race
 - Excluding top-speed records of course
- Change in velocity is... **Acceleration**

¹Assuming distance is constant

What makes a car go fast?

$$\text{Time} = \frac{\text{Distance}}{\text{Velocity}}$$

- To lower time, we need to increase velocity¹
- All motorsports have velocity changes during a race
 - Excluding top-speed records of course
- Change in velocity is... **Acceleration**
- To maximize velocity, you must maximize acceleration
 - ie. Whatever changes in velocity you make, do them as quickly as possible

¹Assuming distance is constant

What makes a car go fast?

$$\text{Time} = \frac{\text{Distance}}{\text{Velocity}}$$

- To lower time, we need to increase velocity¹
- All motorsports have velocity changes during a race
 - Excluding top-speed records of course
- Change in velocity is... **Acceleration**
- To maximize velocity, you must maximize acceleration
 - ie. Whatever changes in velocity you make, do them as quickly as possible

To make a car **faster**, you must make the car **accelerate more**

¹Assuming distance is constant

What famous equation involves acceleration?

What famous equation involves acceleration?

Newton's 2nd law!

$$F = ma$$

What famous equation involves acceleration?

Newton's 2nd law!

$$F = ma$$

We care about acceleration, so rearrange:

$$a = \frac{F}{m}$$

How do we maximize acceleration?

$$a = \frac{F}{m}$$

Decrease Mass

- Make things lighter

How do we maximize acceleration?

$$a = \frac{F}{m}$$

Decrease Mass

- Make things lighter

Increase Force

How do we maximize acceleration?

$$a = \frac{F}{m}$$

Decrease Mass

- Make things lighter

Increase Force

- Increase the force the tires can apply to the ground

How do we maximize acceleration?

$$a = \frac{F}{m}$$

Decrease Mass

- Make things lighter

Increase Force

- Increase the force the tires can apply to the ground
- Increase power output

How do we maximize acceleration?

$$a = \frac{F}{m}$$

Decrease Mass

- Make things lighter

Increase Force

- Increase the force the tires can apply to the ground
- Increase power output
- Increase braking torque

How do we maximize acceleration?

$$a = \frac{F}{m}$$

Decrease Mass

- Make things lighter

Increase Force

- Increase the force the tires can apply to the ground
- Increase power output
- Increase braking torque

The latter two hold **only if the tires can transfer the torque**

Balancing \uparrow Force vs \downarrow Mass

Sometimes \uparrow mass + \uparrow force = \uparrow acceleration

Balancing \uparrow Force vs \downarrow Mass

Sometimes \uparrow mass + \uparrow force = \uparrow acceleration

Bigger Engine

Increases the total vehicle mass, but increases power output
Depending on the ratio, can lead to better acceleration.

Balancing \uparrow Force vs \downarrow Mass

Sometimes \uparrow mass + \uparrow force = \uparrow acceleration

Bigger Engine

Increases the total vehicle mass, but increases power output
Depending on the ratio, can lead to better acceleration.

Sometimes \downarrow mass + \downarrow force = \uparrow acceleration

Balancing \uparrow Force vs \downarrow Mass

Sometimes \uparrow mass + \uparrow force = \uparrow acceleration

Bigger Engine

Increases the total vehicle mass, but increases power output
Depending on the ratio, can lead to better acceleration.

Sometimes \downarrow mass + \downarrow force = \uparrow acceleration

Smaller/Narrower Tires

Decreases total vehicle mass, but decreases total acceleration potential
Also reduces unsprung mass (improves vehicle handling and response)

Longitudinal Acceleration

Simplest acceleration to model:

$$a = \frac{F}{m}$$

Tire traction capacity sets upper limit of the acceleration.

Longitudinal Acceleration

Simplest acceleration to model:

$$a = \frac{F}{m}$$

Tire traction capacity sets upper limit of the acceleration.

Divided into 2 components:

Longitudinal Acceleration

Simplest acceleration to model:

$$a = \frac{F}{m}$$

Tire traction capacity sets upper limit of the acceleration.

Divided into 2 components:

- 1 Braking (negative)

Longitudinal Acceleration

Simplest acceleration to model:

$$a = \frac{F}{m}$$

Tire traction capacity sets upper limit of the acceleration.

Divided into 2 components:

- 1 Braking (negative)

Braking should **ALWAYS** be limited by tire traction

Longitudinal Acceleration

Simplest acceleration to model:

$$a = \frac{F}{m}$$

Tire traction capacity sets upper limit of the acceleration.

Divided into 2 components:

① Braking (negative)

Braking should **ALWAYS** be limited by tire traction

- This is as much for safety as it is performance
- Ensure that care is capable of absolute maximum braking acceleration

Longitudinal Acceleration

Simplest acceleration to model:

$$a = \frac{F}{m}$$

Tire traction capacity sets upper limit of the acceleration.

Divided into 2 components:

① Braking (negative)

Braking should **ALWAYS** be limited by tire traction

- This is as much for safety as it is performance
- Ensure that care is capable of absolute maximum braking acceleration

② Power (positive)

Longitudinal Acceleration

Simplest acceleration to model:

$$a = \frac{F}{m}$$

Tire traction capacity sets upper limit of the acceleration.

Divided into 2 components:

① Braking (negative)

Braking should **ALWAYS** be limited by tire traction

- This is as much for safety as it is performance
- Ensure that care is capable of absolute maximum braking acceleration

② Power (positive)

- Almost always limited by the power unit (ICE, electric motor, rubber band windup, etc.)

Lateral Acceleration

Turning causes *Lateral Acceleration*, which is not a change in speed, but of direction:

$$a_{\text{lat}} = \frac{V^2}{r}$$

where V is velocity, and r is the turning radius.

Lateral Acceleration

Turning causes *Lateral Acceleration*, which is not a change in speed, but of direction:

$$a_{\text{lat}} = \frac{V^2}{r}$$

where V is velocity, and r is the turning radius.

Plugging back into momentum balance yields:

$$F = m \frac{V^2}{r} \Rightarrow V = \sqrt{\frac{Fr}{m}}$$

Lateral Acceleration

Turning causes *Lateral Acceleration*, which is not a change in speed, but of direction:

$$a_{\text{lat}} = \frac{V^2}{r}$$

where V is velocity, and r is the turning radius.

Plugging back into momentum balance yields:

$$F = m \frac{V^2}{r} \Rightarrow V = \sqrt{\frac{Fr}{m}}$$

Therefore given:

- a force, F (tire traction)
- a mass, m (the car)
- and a radius, r (the track/racing line)

there is a **limit to the maximum velocity**

Lateral Acceleration cont.

How do we maximize the velocity? $V = \sqrt{\frac{Fr}{m}}$

Lateral Acceleration cont.

How do we maximize the velocity? $V = \sqrt{\frac{Fr}{m}}$

- 1 Decrease mass m

Lateral Acceleration cont.

How do we maximize the velocity? $V = \sqrt{\frac{Fr}{m}}$

- ① Decrease mass m
 - Add lightness
 - Has compounding affect due to load transfer (discussed later)

Lateral Acceleration cont.

How do we maximize the velocity? $V = \sqrt{\frac{Fr}{m}}$

- ① Decrease mass m
 - Add lightness
 - Has compounding affect due to load transfer (discussed later)
- ② Increase force F

Lateral Acceleration cont.

How do we maximize the velocity? $V = \sqrt{\frac{Fr}{m}}$

- ① Decrease mass m
 - Add lightness
 - Has compounding affect due to load transfer (discussed later)
- ② Increase force F
 - Increase the maximum force the tires can exert

Lateral Acceleration cont.

How do we maximize the velocity? $V = \sqrt{\frac{Fr}{m}}$

- ① Decrease mass m
 - Add lightness
 - Has compounding affect due to load transfer (discussed later)
- ② Increase force F
 - Increase the maximum force the tires can exert
 - How?

Lateral Acceleration cont.

How do we maximize the velocity? $V = \sqrt{\frac{Fr}{m}}$

① Decrease mass m

- Add lightness
- Has compounding affect due to load transfer (discussed later)

② Increase force F

- Increase the maximum force the tires can exert
- How?
 - Aero downforce
 - Different tires
 - Suspension design, etc....

Quick Review

Higher Acceleration = Faster Car

	Limited by	How to make better?
Longitudinal Acceleration	Force (Braking and Power)	Bigger Engine/Brakes
	Mass	Reduce it
Lateral Acceleration	Force (Tire Traction)	Increase Grip
	Mass	Reduce it

G-G Curve

What about lateral and longitudinal acceleration at the same time?

G-G Curve

What about lateral and longitudinal acceleration at the same time? Answer: look at a G-G curve for the car




Figure 2

G-G Curve

What about lateral and longitudinal acceleration at the same time? Answer: look at a G-G curve for the car

G-G Curve (or Traction Circle)

- Plots **maximum steady-state acceleration** that a vehicle can have in **any direction**




Figure 2

G-G Curve

What about lateral and longitudinal acceleration at the same time? Answer: look at a G-G curve for the car

G-G Curve (or Traction Circle)

- Plots **maximum steady-state acceleration** that a vehicle can have in **any direction**
- Outside circle = lost traction, locked wheels, etc




Figure 2

G-G Curve

What about lateral and longitudinal acceleration at the same time? Answer: look at a G-G curve for the car

G-G Curve (or Traction Circle)

- Plots **maximum steady-state acceleration** that a vehicle can have in **any direction**
- Outside circle = lost traction, locked wheels, etc
- Inside circle = within limits of the vehicle




Figure 2

G-G Curve

What about lateral and longitudinal acceleration at the same time? Answer: look at a G-G curve for the car

G-G Curve (or Traction Circle)

- Plots **maximum steady-state acceleration** that a vehicle can have in **any direction**
- Outside circle = lost traction, locked wheels, etc
- Inside circle = within limits of the vehicle
- On the circle = driving at the edge




Figure 2

G-G Curve: Misc Remarks

- Circles




Figure 2

G-G Curve: Misc Remarks

- Circles
 - Shape of the curve is circular, due to tires




Figure 2

G-G Curve: Misc Remarks

- Circles
 - Shape of the curve is circular, due to tires
 - Tires can be assumed to have a maximum **force vector** which can be applied in **any direction**




Figure 2

G-G Curve: Misc Remarks

- Circles
 - Shape of the curve is circular, due to tires
 - Tires can be assumed to have a maximum **force vector** which can be applied in **any direction**
- Positive Acceleration shape




Figure 2

G-G Curve: Misc Remarks

- Circles
 - Shape of the curve is circular, due to tires
 - Tires can be assumed to have a maximum **force vector** which can be applied in **any direction**
- Positive Acceleration shape
 - Top part of curve isn't *quite* circular




Figure 2

G-G Curve: Misc Remarks

- Circles
 - Shape of the curve is circular, due to tires
 - Tires can be assumed to have a maximum **force vector** which can be applied in **any direction**
- Positive Acceleration shape
 - Top part of curve isn't *quite* circular
 - **Positive acceleration is nearly always limited by the power unit, not the tires**
 - For (nearly) all cars, the power unit is the most severe acceleration limitation.




Figure 2

How do tires generate force?

How do tires generate force?

Via friction with the ground

Tires and Friction

Newton's Law of Friction

$$F = N\mu$$

where F is the max static friction force, N is the normal force, and μ is the static friction coefficient

Tires and Friction

Newton's Law of Friction

$$F = N\mu$$

where F is the max static friction force, N is the normal force, and μ is the static friction coefficient

- Tires create force via **static friction**
 - A tire is in *kinetic* friction if it's locked up or doing a burnout

Tires and Friction

Newton's Law of Friction

$$F = N\mu$$


where F is the max static friction force, N is the normal force, and μ is the static friction coefficient

- Tires create force via **static friction**
 - A tire is in *kinetic* friction if it's locked up or doing a burnout
- μ is generally assumed to be constant
 - So F is linearly dependent on N

Tires and Load Sensitivity

- Tires **do not** have a constant μ :

$$F = N\mu(N)$$




Tires and Load Sensitivity

- Tires **do not** have a constant μ :

$$F = N\mu(N)$$

- This phenomena is known as **Load Sensitivity**




Tires and Load Sensitivity

- Tires **do not** have a constant μ :

$$F = N\mu(N)$$

- This phenomena is known as **Load Sensitivity**
- Generally, μ and N are inversely proportional
 - As $\uparrow N$, $\downarrow \mu$




Tires and Load Sensitivity

- Tires **do not** have a constant μ :

$$F = N\mu(N)$$

- This phenomena is known as **Load Sensitivity**
- Generally, μ and N are inversely proportional
 - As $\uparrow N$, $\downarrow \mu$



Load Sensitivity is the singular most impactful thing in racecar design

It alters practically every single decision

Load Transfer

Load Transfer

Load Transfer

Load Transfer

- Weight of vehicle shifting due to acceleration

Load Transfer

Load Transfer

- Weight of vehicle shifting due to acceleration
- Caused by torque of tires against CG, *not by body roll*

Load Transfer


Load Transfer

- Weight of vehicle shifting due to acceleration
- Caused by torque of tires against CG, *not by body roll*
- **Reduces global vehicle grip due to load sensitivity**

Load Transfer Example

No load transfer vs 50% load transfer

Assume 4.5kN of static vertical load on each tire.




Load Transfer Example

No load transfer vs 50% load transfer

Assume 4.5kN of static vertical load on each tire.
Static traction:

$$F(4.5\text{kN}) = 5.55\text{kN} \Rightarrow F_{\text{tot}}^{\text{static}} = 5.55 \cdot 4 = 22.2\text{kN}$$



Load Transfer Example

No load transfer vs 50% load transfer


Assume 4.5kN of static vertical load on each tire.
Static traction:

$$F(4.5\text{kN}) = 5.55\text{kN} \Rightarrow F_{\text{tot}}^{\text{static}} = 5.55 \cdot 4 = 22.2\text{kN}$$

With load transfer:

$$F(0.5 \cdot 4.5\text{kN} = 2.25\text{kN}) = 2.7\text{kN}$$

$$F(1.5 \cdot 4.5\text{kN} = 6.75\text{kN}) = 7.5\text{kN}$$



Load Transfer Example

No load transfer vs 50% load transfer

Assume 4.5kN of static vertical load on each tire.
Static traction:


$$F(4.5\text{kN}) = 5.55\text{kN} \Rightarrow F_{\text{tot}}^{\text{static}} = 5.55 \cdot 4 = 22.2\text{kN}$$

With load transfer:

$$F(0.5 \cdot 4.5\text{kN} = 2.25\text{kN}) = 2.7\text{kN}$$

$$F(1.5 \cdot 4.5\text{kN} = 6.75\text{kN}) = 7.5\text{kN}$$

$$\therefore F_{\text{tot}}^{\text{transfer}} = 2(2.7\text{kN} + 7.5\text{kN}) = 20.4\text{kN}$$



Load Transfer Example

No load transfer vs 50% load transfer

Assume 4.5kN of static vertical load on each tire.
Static traction:

$$F(4.5\text{kN}) = 5.55\text{kN} \Rightarrow F_{\text{tot}}^{\text{static}} = 5.55 \cdot 4 = 22.2\text{kN}$$


With load transfer:

$$F(0.5 \cdot 4.5\text{kN} = 2.25\text{kN}) = 2.7\text{kN}$$

$$F(1.5 \cdot 4.5\text{kN} = 6.75\text{kN}) = 7.5\text{kN}$$

$$\therefore F_{\text{tot}}^{\text{transfer}} = 2(2.7\text{kN} + 7.5\text{kN}) = 20.4\text{kN}$$

8% Drop in total traction!



Three Tenants of Racecar Building

In order of importance:

- ① Make it Lighter
 - Improves acceleration, load transfer, responsiveness, etc.

Three Tenants of Racecar Building

In order of importance:

- ① Make it Lighter
 - Improves acceleration, load transfer, responsiveness, etc.
- ② Make it Lower
 - Lowering a component lowers DG \Rightarrow reduces load transfer

Three Tenants of Racecar Building

In order of importance:

- ① Make it Lighter
 - Improves acceleration, load transfer, responsiveness, etc.
- ② Make it Lower
 - Lowering a component lowers DG \Rightarrow reduces load transfer
- ③ Make it more Central
 - When turning, car has to physically rotate:

$$T = I\alpha$$

where T is torque, I is rotational inertia, and α is angular acceleration

- Reducing inertia is similar to reducing mass

Three Tenants of Racecar Building

In order of importance:

- ① Make it Lighter
 - Improves acceleration, load transfer, responsiveness, etc.
- ② Make it Lower
 - Lowering a component lowers DG \Rightarrow reduces load transfer
- ③ Make it more Central
 - When turning, car has to physically rotate:

$$T = I\alpha$$

where T is torque, I is rotational inertia, and α is angular acceleration

- Reducing inertia is similar to reducing mass

The car that is lighter, has a lower CG, or has a lower inertia will be faster

Questions