Racecar 101

James Wright

September 8, 2022

Outline

1. What makes a car fast?
2. Vehicle Basics
3. Anatomy of a Corner
4. Three Tenants of Racecar Design

Table of Contents

1. What makes a car fast?
2. Vehicle Basics
3. Anatomy of a Corner
4. Three Tenants of Racecar Design

Note

This first part is a very simplified breakdown

- It's not the most accurate
- It's not to insult anyone's intelligence

It's simply to not distract from the things that can be easily forgotten or muddied.

What makes a car go fast?

$$\text{Time} = \frac{\text{Distance}}{\text{Velocity}}$$

[1] Assuming distance is constant

What makes a car go fast?

$$\text{Time} = \frac{\text{Distance}}{\text{Velocity}}$$

- To lower time, we need to increase velocity[1]

[1] Assuming distance is constant

What makes a car go fast?

$$\text{Time} = \frac{\text{Distance}}{\text{Velocity}}$$

- To lower time, we need to increase velocity[1]
- All motorsports have velocity changes during a race
  - Excluding top-speed records of course

[1] Assuming distance is constant

What makes a car go fast?

$$\text{Time} = \frac{\text{Distance}}{\text{Velocity}}$$

- To lower time, we need to increase velocity[1]
- All motorsports have velocity changes during a race
  - Excluding top-speed records of course
- Change in velocity is...

[1] Assuming distance is constant

What makes a car go fast?

$$\text{Time} = \frac{\text{Distance}}{\text{Velocity}}$$

- To lower time, we need to increase velocity[1]
- All motorsports have velocity changes during a race
  - Excluding top-speed records of course
- Change in velocity is... **Acceleration**

[1] Assuming distance is constant

What makes a car go fast?

$$\text{Time} = \frac{\text{Distance}}{\text{Velocity}}$$

- To lower time, we need to increase velocity[1]
- All motorsports have velocity changes during a race
  - Excluding top-speed records of course
- Change in velocity is... **Acceleration**
- To maximize velocity, you must maximize acceleration
  - ie. Whatever changes in velocity you make, do them as quickly as possible

[1] Assuming distance is constant

What makes a car go fast?

$$\text{Time} = \frac{\text{Distance}}{\text{Velocity}}$$

- To lower time, we need to increase velocity[1]
- All motorsports have velocity changes during a race
  - Excluding top-speed records of course
- Change in velocity is... **Acceleration**
- To maximize velocity, you must maximize acceleration
  - ie. Whatever changes in velocity you make, do them as quickly as possible

To make a car **faster**, you must make the car **accelerate more**

[1] Assuming distance is constant

What famous equation involves acceleration?

What famous equation involves acceleration?

Newton's 2nd law!

$$F = ma$$

What famous equation involves acceleration?

Newton's 2nd law!

$$F = ma$$

We care about acceleration, so rearange:

$$a = \frac{F}{m}$$

How do we maximize acceleration?

$$a = \frac{F}{m}$$

Decrease Mass

- Make things lighter

How do we maximize acceleration?

$$a = \frac{F}{m}$$

Decrease Mass

- Make things lighter

Increase Force

How do we maximize acceleration?

$$a = \frac{F}{m}$$

Decrease Mass

- Make things lighter

Increase Force

- Increase the force the tires can apply to the ground

How do we maximize acceleration?

$$a = \frac{F}{m}$$

Decrease Mass

- Make things lighter

Increase Force

- Increase the force the tires can apply to the ground
- Increase power output

How do we maximize acceleration?

$$a = \frac{F}{m}$$

Decrease Mass

- Make things lighter

Increase Force

- Increase the force the tires can apply to the ground
- Increase power output
- Increase braking torque

How do we maximize acceleration?

$$a = \frac{F}{m}$$

Decrease Mass

- Make things lighter

Increase Force

- Increase the force the tires can apply to the ground
- Increase power output
- Increase braking torque

The latter two hold **only if the tires can transfer the torque**

Balancing ↑Force vs ↓Mass

Balancing ↑Force vs ↓Mass

Sometimes ↑ mass + ↑ force = ↑ acceleration

Balancing ↑Force vs ↓Mass

Sometimes ↑ mass + ↑ force = ↑ acceleration

Bigger Engine

Increases the total vehicle mass, but increases power output
Depending on the ratio, can lead to better acceleration.

Balancing ↑Force vs ↓Mass

Sometimes ↑ mass + ↑ force = ↑ acceleration

Bigger Engine

Increases the total vehicle mass, but increases power output
Depending on the ratio, can lead to better acceleration.

Sometimes ↓ mass + ↓ force = ↑ acceleration

Balancing ↑Force vs ↓Mass

Sometimes ↑ mass + ↑ force = ↑ acceleration

Bigger Engine

Increases the total vehicle mass, but increases power output
Depending on the ratio, can lead to better acceleration.

Sometimes ↓ mass + ↓ force = ↑ acceleration

Smaller/Narrower Tires

Decreases total vehicle mass, but decreases total acceleration potential
Also reduces unsprung mass (improves vehicle handling and response)

Longitudinal Acceleration

Simplest acceleration to model:

$$a = \frac{F}{m}$$

Tire traction capacity sets upper limit of the acceleration.

Longitudinal Acceleration

Simplest acceleration to model:

$$a = \frac{F}{m}$$

Tire traction capacity sets upper limit of the acceleration.
Divided into 2 components:

Longitudinal Acceleration

Simplest acceleration to model:

$$a = \frac{F}{m}$$

Tire traction capacity sets upper limit of the acceleration.
Divided into 2 components:

1. Braking (negative)

Longitudinal Acceleration

Simplest acceleration to model:

$$a = \frac{F}{m}$$

Tire traction capacity sets upper limit of the acceleration.
Divided into 2 components:

1. Braking (negative)

Braking should ALWAYS be limited by tire traction

Longitudinal Acceleration

Simplest acceleration to model:

$$a = \frac{F}{m}$$

Tire traction capacity sets upper limit of the acceleration.
Divided into 2 components:

1. Braking (negative)

Braking should ALWAYS be limited by tire traction

- This is as much for safety as it is performance
- Ensure that car is capable of absolute maximum braking acceleration

Longitudinal Acceleration

Simplest acceleration to model:

$$a = \frac{F}{m}$$

Tire traction capacity sets upper limit of the acceleration.
Divided into 2 components:

1. Braking (negative)

Braking should ALWAYS be limited by tire traction

- This is as much for safety as it is performance
- Ensure that car is capable of absolute maximum braking acceleration

2. Power (positive)

Longitudinal Acceleration

Simplest acceleration to model:

$$a = \frac{F}{m}$$

Tire traction capacity sets upper limit of the acceleration.
Divided into 2 components:

1. Braking (negative)

Braking should ALWAYS be limited by tire traction

- This is as much for safety as it is performance
- Ensure that car is capable of absolute maximum braking acceleration

2. Power (positive)
   - Almost always limited by the power unit (ICE, electric motor, rubber band windup, etc.)

Lateral Acceleration

Turning causes *Lateral Acceleration*, which is not a change in speed, but of direction:

$$a_{\text{lat}} = \frac{V^2}{r}$$

where V is velocity, and r is the turning radius.

Lateral Acceleration

Turning causes *Lateral Acceleration*, which is not a change in speed, but of direction:

$$a_{\text{lat}} = \frac{V^2}{r}$$

where V is velocity, and r is the turning radius.

Plugging back into momentum balance yields:

$$F = m\frac{V^2}{r} \;\Rightarrow\; V = \sqrt{\frac{Fr}{m}}$$

Lateral Acceleration

Turning causes *Lateral Acceleration*, which is not a change in speed, but of direction:

$$a_{\text{lat}} = \frac{V^2}{r}$$

where V is velocity, and r is the turning radius.

Plugging back into momentum balance yields:

$$F = m\frac{V^2}{r} \;\Rightarrow\; V = \sqrt{\frac{Fr}{m}}$$

Therefore given:

- a force, F (tire traction)
- a mass, m (the car)
- and a radius, r (the track/racing line)

there is a **limit to the maximum velocity**

Lateral Acceleration cont.

How do we maximize the velocity? $V = \sqrt{\frac{Fr}{m}}$

Lateral Acceleration cont.

How do we maximize the velocity? $V = \sqrt{\frac{Fr}{m}}$

1. Decrease mass m

Lateral Acceleration cont.

How do we maximize the velocity? $V = \sqrt{\frac{Fr}{m}}$

1. Decrease mass m
   - Add lightness
   - Has compounding affect due to load transfer (discussed later)

Lateral Acceleration cont.

How do we maximize the velocity? $V = \sqrt{\frac{Fr}{m}}$

1. Decrease mass m
   - Add lightness
   - Has compounding affect due to load transfer (discussed later)
2. Increase force F

Lateral Acceleration cont.

How do we maximize the velocity? $V = \sqrt{\frac{Fr}{m}}$

1. Decrease mass m
   - Add lightness
   - Has compounding affect due to load transfer (discussed later)
2. Increase force F
   - Increase the maximum force the tires can exert

Lateral Acceleration cont.

How do we maximize the velocity? $V = \sqrt{\frac{Fr}{m}}$

1. Decrease mass m
   - Add lightness
   - Has compounding affect due to load transfer (discussed later)
2. Increase force F
   - Increase the maximum force the tires can exert
   - How?

Lateral Acceleration cont.

How do we maximize the velocity? $V = \sqrt{\frac{Fr}{m}}$

1. Decrease mass m
   - Add lightness
   - Has compounding affect due to load transfer (discussed later)
2. Increase force F
   - Increase the maximum force the tires can exert
   - How?
     - Aero downforce
     - Different tires
     - Suspension design, etc....

Quick Review

Higher Acceleration = Faster Car

	Limited by	How to make better?
Longitudinal Acceleration	Force (Braking and Power)	Bigger Engine/Brakes
	Mass	Reduce it
Lateral Acceleration	Force (Tire Traction)	Increase Grip
	Mass	Reduce it

Table of Contents

1 What makes a car fast?

2 Vehicle Basics

3 Anatomy of a Corner

4 Three Tenants of Racecar Design

G-G Curve

What about lateral and longitudinal acceleration at the same time?

G-G Curve

What about lateral and longitudinal acceleration at the same time? Answer: look at a G-G curve for the car



Figure 2

G-G Curve

What about lateral and longitudinal acceleration at the same time? Answer: look at a G-G curve for the car

G-G Curve (or Traction Circle)

- Plots **maximum steady-state acceleration** that a vehicle can have in **any direction**



Figure 2

G-G Curve

What about lateral and longitudinal acceleration at the same time? Answer: look at a G-G curve for the car

G-G Curve (or Traction Circle)

- Plots **maximum steady-state acceleration** that a vehicle can have in **any direction**
- Outside circle = lost traction, locked wheels, etc



Figure 2

G-G Curve

What about lateral and longitudinal acceleration at the same time? Answer: look at a G-G curve for the car

G-G Curve (or Traction Circle)

- Plots **maximum steady-state acceleration** that a vehicle can have in **any direction**
- Outside circle = lost traction, locked wheels, etc
- Inside circle = within limits of the vehicle



Figure 2

G-G Curve

What about lateral and longitudinal acceleration at the same time? Answer: look at a G-G curve for the car

G-G Curve (or Traction Circle)

- Plots **maximum steady-state acceleration** that a vehicle can have in **any direction**
- Outside circle = lost traction, locked wheels, etc
- Inside circle = within limits of the vehicle
- On the circle = driving at the edge



Figure 2

G-G Curve: Misc Remarks

- Circles



Figure 2

G-G Curve: Misc Remarks

- Circles
  - Shape of the curve is circular, due to tires



Figure 2

G-G Curve: Misc Remarks

- Circles
  - Shape of the curve is circular, due to tires
  - Tires can be assumed to have a maximum **force vector** which can be applied in **any direction**



Figure 2

G-G Curve: Misc Remarks

- Circles
  - Shape of the curve is circular, due to tires
  - Tires can be assumed to have a maximum **force vector** which can be applied in **any direction**
- Positive Acceleration shape



Figure 2

G-G Curve: Misc Remarks

- Circles
  - Shape of the curve is circular, due to tires
  - Tires can be assumed to have a maximum **force vector** which can be applied in **any direction**
- Positive Acceleration shape
  - Top part of curve isn't *quite* circular



Figure 2

G-G Curve: Misc Remarks

- Circles
  - Shape of the curve is circular, due to tires
  - Tires can be assumed to have a maximum **force vector** which can be applied in **any direction**
- Positive Acceleration shape
  - Top part of curve isn't *quite* circular
  - **Positive acceleration is nearly always limited by the power unit, not the tires**
  - For (nearly) all cars, the power unit is the most severe acceleration limitation.



Figure 2

How do tires generate force?

How do tires generate force?

Via friction with the ground

Tires and Friction

Newton's Law of Friction

$$F = N\mu$$

where F is the max static friction force, N is the normal force, and μ is the static friction coefficient

Tires and Friction

Newton's Law of Friction

$$F = N\mu$$

where F is the max static friction force, N is the normal force, and μ is the static friction coefficient

- Tires create force via **static friction**
  - A tire is in *kinetic* friction if it's locked up or doing a burnout

Tires and Friction

Newton's Law of Friction

$$F = N\mu$$

where F is the max static friction force, N is the normal force, and μ is the static friction coefficient

- Tires create force via **static friction**
  - A tire is in *kinetic* friction if it's locked up or doing a burnout
- μ is generally assumed to be constant
  - So F is linearly dependent on N

Tires and Load Sensitivity

- Tires **do not** have a constant μ:

$$F = N\mu(N)$$



Tires and Load Sensitivity

- Tires **do not** have a constant μ:

$$F = N\mu(N)$$

- This phenomena is known as **Load Sensitivity**



Tires and Load Sensitivity

- Tires **do not** have a constant μ:

$$F = N\mu(N)$$

- This phenomena is known as **Load Sensitivity**
- Generally, μ and N are inversely proportional
  - As $\uparrow N$, $\downarrow \mu$



Tires and Load Sensitivity

- Tires **do not** have a constant μ:

$$F = N\mu(N)$$

- This phenomena is known as **Load Sensitivity**
- Generally, μ and N are inversely proportional
  - As $\uparrow N$, $\downarrow \mu$



Load Sensitivity is the singular most impactful thing in racecar design

It alters practically every single decision

Load Transfer

Load Transfer

Load Transfer

Load Transfer

- Weight of vehicle shifting due to acceleration

Load Transfer

Load Transfer

- Weight of vehicle shifting due to acceleration
- Caused by torque of tires against CG, *not by body roll*



Load Transfer

Load Transfer

- Weight of vehicle shifting due to acceleration
- Caused by torque of tires against CG, *not by body roll*

- **Reduces global vehicle grip due to load sensitivity**



Load Transfer Example

No load transfer vs 50% load transfer

Assume 4.5kN of static vertical load on each tire.



Load Transfer Example

No load transfer vs 50% load transfer

Assume 4.5kN of static vertical load on each tire.
Static traction:

$$F(4.5\text{kN}) = 5.55\text{kN} \;\Rightarrow\; F_{\text{tot}}^{\text{static}} = 5.55 \cdot 4 = 22.2\text{kN}$$



Load Transfer Example

No load transfer vs 50% load transfer

Assume 4.5kN of static vertical load on each tire.
Static traction:

$$F(4.5\text{kN}) = 5.55\text{kN} \;\Rightarrow\; F_{\text{tot}}^{\text{static}} = 5.55 \cdot 4 = 22.2\text{kN}$$

With load transfer:

$$F(0.5 \cdot 4.5\text{kN} = 2.25\text{kN}) = 2.7\text{kN}$$
$$F(1.5 \cdot 4.5\text{kN} = 6.75\text{kN}) = 7.5\text{kN}$$



Load Transfer Example

No load transfer vs 50% load transfer

Assume 4.5kN of static vertical load on each tire.
Static traction:

$$F(4.5\text{kN}) = 5.55\text{kN} \;\Rightarrow\; F_{\text{tot}}^{\text{static}} = 5.55 \cdot 4 = 22.2\text{kN}$$

With load transfer:

$$F(0.5 \cdot 4.5\text{kN} = 2.25\text{kN}) = 2.7\text{kN}$$
$$F(1.5 \cdot 4.5\text{kN} = 6.75\text{kN}) = 7.5\text{kN}$$
$$\therefore F_{\text{tot}}^{\text{transfer}} = 2(2.7\text{kN} + 7.5\text{kN}) = 20.4\text{kN}$$



Load Transfer Example

No load transfer vs 50% load transfer

Assume 4.5kN of static vertical load on each tire.
Static traction:

$$F(4.5\text{kN}) = 5.55\text{kN} \;\Rightarrow\; F_{\text{tot}}^{\text{static}} = 5.55 \cdot 4 = 22.2\text{kN}$$

With load transfer:

$$F(0.5 \cdot 4.5\text{kN} = 2.25\text{kN}) = 2.7\text{kN}$$
$$F(1.5 \cdot 4.5\text{kN} = 6.75\text{kN}) = 7.5\text{kN}$$
$$\therefore F_{\text{tot}}^{\text{transfer}} = 2(2.7\text{kN} + 7.5\text{kN}) = 20.4\text{kN}$$

8% Drop in total traction!



Table of Contents

1 What makes a car fast?

2 Vehicle Basics

3 Anatomy of a Corner

4 Three Tenants of Racecar Design

How does a car turn?

How does a car turn?

The car uses the tires to generate a **lateral force to redirect the car** and a **torque to rotate the car**

How does a car turn?

The car uses the tires to generate a **lateral force to redirect the car** and a **torque to rotate the car**

Corners represent a change in two different things:

How does a car turn?

The car uses the tires to generate a **lateral force to redirect the car** and a **torque to rotate the car**

Corners represent a change in two different things:

1. Change in **translation**

How does a car turn?

The car uses the tires to generate a **lateral force to redirect the car** and a **torque to rotate the car**

Corners represent a change in two different things:

1. Change in **translation**
2. Change in **orientation**

Vehicle Balance

Why do Formula 1 and Indy cars have larger tires at the rear than the front?

Vehicle Balance - Formula 1 Car

Balance the moments of the car $M = F \times r$



Vehicle Balance - Delta Wing

Balance the moments of the car $M = F \times r$



Oversteer vs Understeer

Neutral Steer

Moments balance out

Oversteer vs Understeer

Neutral Steer

Moments balance out

Under Steer

Unbalance moments cause under-rotation

Oversteer vs Understeer

Neutral Steer

Moments balance out

Under Steer

Unbalance moments cause under-rotation

Over Steer

Unbalance moments cause over-rotation

Oversteer vs Understeer

Neutral Steer

Moments balance out

Under Steer

Unbalance moments cause under-rotation

Over Steer

Unbalance moments cause over-rotation

- A car can dynamically change between all three states

Oversteer vs Understeer

Neutral Steer

Moments balance out

Under Steer

Unbalance moments cause under-rotation

Over Steer

Unbalance moments cause over-rotation

- A car can dynamically change between all three states
- Changes occur due to differences in load transfer, suspension magic, and through dynamic movement

Table of Contents

1 What makes a car fast?

2 Vehicle Basics

3 Anatomy of a Corner

4 Three Tenants of Racecar Design

Three Tenants of Racecar Design

In order of importance:

1. Make it Lighter
   - Improves acceleration, load transfer, responsiveness, etc.

Three Tenants of Racecar Design

In order of importance:

1. Make it Lighter
   - Improves acceleration, load transfer, responsiveness, etc.
2. Make it Lower
   - Lowering a component lowers CG $\Rightarrow$ reduces load transfer

Three Tenants of Racecar Design

In order of importance:

1. Make it Lighter
   - Improves acceleration, load transfer, responsiveness, etc.
2. Make it Lower
   - Lowering a component lowers CG $\Rightarrow$ reduces load transfer
3. Make it more Central
   - When turning, car has to physically rotate:

$$T = I\alpha$$

     where T is torque, I is rotational inertia, and α is angular acceleration
   - Reducing inertia is similar to reducing mass

Three Tenants of Racecar Design

In order of importance:

1. Make it Lighter
   - Improves acceleration, load transfer, responsiveness, etc.
2. Make it Lower
   - Lowering a component lowers CG $\Rightarrow$ reduces load transfer
3. Make it more Central
   - When turning, car has to physically rotate:

$$T = I\alpha$$

   where T is torque, I is rotational inertia, and α is angular acceleration
   - Reducing inertia is similar to reducing mass

The car that is lighter, has a lower CG, or has a lower inertia will be faster

Questions