

Racecar 101

James Wright

September 7, 2022

Outline

1 What makes a car fast?

2 Blocks in Beamer

Note

This first part is a very simplified breakdown

- It's not the most accurate
- It's not to insult anyone's intelligence

It's simply to not distract from the things that can be easily forgotten or muddled.

What makes a car go fast?

$$\text{Time} = \frac{\text{Distance}}{\text{Velocity}}$$

¹Assuming distance is constant

What makes a car go fast?

$$\text{Time} = \frac{\text{Distance}}{\text{Velocity}}$$

- To lower time, we need to increase velocity¹

¹Assuming distance is constant

What makes a car go fast?

$$\text{Time} = \frac{\text{Distance}}{\text{Velocity}}$$

- To lower time, we need to increase velocity¹
- All motorsports have velocity changes during a race
 - Excluding top-speed records of course

¹Assuming distance is constant

What makes a car go fast?

$$\text{Time} = \frac{\text{Distance}}{\text{Velocity}}$$

- To lower time, we need to increase velocity¹
- All motorsports have velocity changes during a race
 - Excluding top-speed records of course
- Change in velocity is...

¹Assuming distance is constant

What makes a car go fast?

$$\text{Time} = \frac{\text{Distance}}{\text{Velocity}}$$

- To lower time, we need to increase velocity¹
- All motorsports have velocity changes during a race
 - Excluding top-speed records of course
- Change in velocity is... **Acceleration**

¹Assuming distance is constant

What makes a car go fast?

$$\text{Time} = \frac{\text{Distance}}{\text{Velocity}}$$

- To lower time, we need to increase velocity¹
- All motorsports have velocity changes during a race
 - Excluding top-speed records of course
- Change in velocity is... **Acceleration**
- To maximize velocity, you must maximize acceleration
 - ie. Whatever changes in velocity you make, do them as quickly as possible

¹Assuming distance is constant

What makes a car go fast?

$$\text{Time} = \frac{\text{Distance}}{\text{Velocity}}$$

- To lower time, we need to increase velocity¹
- All motorsports have velocity changes during a race
 - Excluding top-speed records of course
- Change in velocity is... **Acceleration**
- To maximize velocity, you must maximize acceleration
 - ie. Whatever changes in velocity you make, do them as quickly as possible

To make a car **faster**, you must make the car **accelerate more**

¹Assuming distance is constant

What famous equation involves acceleration?

What famous equation involves acceleration?

Newton's 2nd law!

$$F = ma$$

What famous equation involves acceleration?

Newton's 2nd law!

$$F = ma$$

We care about acceleration, so rearrange:

$$a = \frac{F}{m}$$

How do we maximize acceleration?

$$a = \frac{F}{m}$$

Decrease Mass

- Make things lighter

How do we maximize acceleration?

$$a = \frac{F}{m}$$

Decrease Mass

- Make things lighter

Increase Force

How do we maximize acceleration?

$$a = \frac{F}{m}$$

Decrease Mass

- Make things lighter

Increase Force

- Increase the force the tires can apply to the ground

How do we maximize acceleration?

$$a = \frac{F}{m}$$

Decrease Mass

- Make things lighter

Increase Force

- Increase the force the tires can apply to the ground
- Increase power output

How do we maximize acceleration?

$$a = \frac{F}{m}$$

Decrease Mass

- Make things lighter

Increase Force

- Increase the force the tires can apply to the ground
- Increase power output
- Increase braking torque

How do we maximize acceleration?

$$a = \frac{F}{m}$$

Decrease Mass

- Make things lighter

Increase Force

- Increase the force the tires can apply to the ground
- Increase power output
- Increase braking torque

The latter two hold **only if the tires can transfer the torque**

Balancing \uparrow Force vs \downarrow Mass

Sometimes \uparrow mass + \uparrow force = \uparrow acceleration

Balancing \uparrow Force vs \downarrow Mass

Sometimes \uparrow mass + \uparrow force = \uparrow acceleration

Bigger Engine

Increases the total vehicle mass, but increases power output
Depending on the ratio, can lead to better acceleration.

Sometimes \downarrow mass + \downarrow force = \uparrow acceleration

Balancing \uparrow Force vs \downarrow Mass

Sometimes \uparrow mass + \uparrow force = \uparrow acceleration

Bigger Engine

Increases the total vehicle mass, but increases power output
Depending on the ratio, can lead to better acceleration.

Sometimes \downarrow mass + \downarrow force = \uparrow acceleration

Smaller/Narrower Tires

Decreases total vehicle mass, but decreases total acceleration potential
Also reduces unsprung mass (improves vehicle handling and response)

Longitudinal Acceleration

Simplest acceleration to model:

$$a = \frac{F}{m}$$

Tire traction capacity sets upper limit of the acceleration.

Longitudinal Acceleration

Simplest acceleration to model:

$$a = \frac{F}{m}$$

Tire traction capacity sets upper limit of the acceleration.

Divided into 2 components:

Longitudinal Acceleration

Simplest acceleration to model:

$$a = \frac{F}{m}$$

Tire traction capacity sets upper limit of the acceleration.

Divided into 2 components:

- 1 Braking (negative)

Longitudinal Acceleration

Simplest acceleration to model:

$$a = \frac{F}{m}$$

Tire traction capacity sets upper limit of the acceleration.

Divided into 2 components:

- 1 Braking (negative)

Braking should **ALWAYS** be limited by tire traction

Longitudinal Acceleration

Simplest acceleration to model:

$$a = \frac{F}{m}$$

Tire traction capacity sets upper limit of the acceleration.

Divided into 2 components:

① Braking (negative)

Braking should **ALWAYS** be limited by tire traction

- This is as much for safety as it is performance
- Ensure that care is capable of absolute maximum braking acceleration

Longitudinal Acceleration

Simplest acceleration to model:

$$a = \frac{F}{m}$$

Tire traction capacity sets upper limit of the acceleration.

Divided into 2 components:

① Braking (negative)

Braking should **ALWAYS** be limited by tire traction

- This is as much for safety as it is performance
- Ensure that care is capable of absolute maximum braking acceleration

② Power (positive)

Longitudinal Acceleration

Simplest acceleration to model:

$$a = \frac{F}{m}$$

Tire traction capacity sets upper limit of the acceleration.

Divided into 2 components:

① Braking (negative)

Braking should **ALWAYS** be limited by tire traction

- This is as much for safety as it is performance
- Ensure that care is capable of absolute maximum braking acceleration

② Power (positive)

- Almost always limited by the power unit (ICE, electric motor, rubber band windup, etc.)

Lateral Acceleration

Turning causes *Lateral Acceleration*, which is not a change in speed, but of direction:

$$a_{\text{lat}} = \frac{V^2}{r}$$

Lateral Acceleration

Turning causes *Lateral Acceleration*, which is not a change in speed, but of direction:

$$a_{\text{lat}} = \frac{V^2}{r}$$

$$F = m \frac{V^2}{r} \Rightarrow V = \sqrt{\frac{Fr}{m}}$$

Blocks in Beamer

Standard Block

This is a standard block.

Alert Message

This block presents alert message.

An example of typesetting tool

Example: MS Word, \LaTeX