# Performance-Portable Implicit Scale-Resolving Compressible Flow Using libCEED

SIAM CSE 2023

James Wright, Jed Brown, Kenneth Jansen, Leila Ghaffari February 27, 2023

Ann and H.J. Smead Department of Aerospace Engineering Sciences



#### Outline

- 1. libCEED Overview
- 2. Compressible Fluid Equations in libCEED
- 3. Viscous Outflow Boundary Conditions
- 4. Efficient Implicit Timestepping



## libCEED Overview



- · C library for element-based discretizations
  - · Bindings available for Fortran, Rust, Python, and Julia



- · C library for element-based discretizations
  - · Bindings available for Fortran, Rust, Python, and Julia
- Designed for matrix-free operator evaluation



- · C library for element-based discretizations
  - · Bindings available for Fortran, Rust, Python, and Julia
- Designed for matrix-free operator evaluation
- · Portable to different hardware via computational backends
  - · Code that runs on CPU also runs on GPU without changes
  - · Computational backend selectable at runtime, using runtime compilation



- · C library for element-based discretizations
  - · Bindings available for Fortran, Rust, Python, and Julia
- Designed for matrix-free operator evaluation
- · Portable to different hardware via computational backends
  - · Code that runs on CPU also runs on GPU without changes
  - · Computational backend selectable at runtime, using runtime compilation
- Geared toward high-order finite element discretizations




$$A = \mathcal{P}^T \mathcal{E}^T B^T D B \mathcal{E} \mathcal{P}$$


global domain all (shared) dofs



T-vector

$$A = \mathcal{P}^T \mathcal{E}^T B^T D B \mathcal{E} \mathcal{P}$$






L-vector


E-vector

T-vector

$$A = \mathcal{P}^T \mathcal{E}^T B^T D B \mathcal{E} \mathcal{P}$$



$$A = \mathcal{P}^T \mathcal{E}^T B^T DB \mathcal{E} \mathcal{P}$$



# Compressible Fluid Equations in libCEED

## Compressible Navier-Stokes

$$\mathbf{A_0}\mathbf{Y}_{.t} + \mathbf{F}_{i.i}(\mathbf{Y}) - S(\mathbf{Y}) = 0$$

for

$$\mathbf{A_0} \underbrace{\begin{bmatrix} p \\ u_i \\ T \end{bmatrix}}_{\mathbf{Y}} = \begin{bmatrix} \rho \\ \rho u_i \\ \rho e \end{bmatrix}, \quad \mathbf{F}_i(\mathbf{Y}) = \underbrace{\begin{pmatrix} \rho u_i \\ \rho u_i u_j + p \delta_{ij} \\ (\rho e + p) u_i \end{pmatrix}}_{\mathbf{F}_i^{\text{adv}}} + \underbrace{\begin{pmatrix} 0 \\ -\sigma_{ij} \\ -\rho u_j \sigma_{ij} - kT_{,i} \end{pmatrix}}_{\mathbf{F}_i^{\text{diff}}}, \quad S(\mathbf{Y}) = -\begin{pmatrix} 0 \\ \rho \mathbf{g} \\ 0 \end{pmatrix}$$

SIAM CSF 2023

Find  $\boldsymbol{Y} \in \mathcal{S}^h$  ,  $\forall \boldsymbol{v} \in \mathcal{V}^h$ 

$$\int_{\Omega} \boldsymbol{v} \cdot \left( \boldsymbol{A_0} \boldsymbol{Y}_{,t} - \boldsymbol{S}(\boldsymbol{Y}) \right) \, \mathrm{d}\Omega + \int_{\Omega} \boldsymbol{v} \cdot \boldsymbol{F}_{i,i}(\boldsymbol{Y}) \, \, \mathrm{d}\Omega$$

Find  $oldsymbol{Y} \in \mathcal{S}^h$  ,  $orall oldsymbol{v} \in \mathcal{V}^h$ 

$$\int_{\Omega} \boldsymbol{v} \cdot \left( \boldsymbol{A_0} \boldsymbol{Y}_{,t} - \boldsymbol{S}(\boldsymbol{Y}) \right) d\Omega - \int_{\Omega} \boldsymbol{v}_{,i} \cdot \boldsymbol{F}_i(\boldsymbol{Y}) d\Omega + \int_{\partial \Omega} \boldsymbol{v} \cdot \boldsymbol{F}_i(\boldsymbol{Y}) \cdot \widehat{\boldsymbol{n}}_i d\partial \Omega$$

Find  $oldsymbol{Y} \in \mathcal{S}^h$  ,  $orall oldsymbol{v} \in \mathcal{V}^h$ 

$$\int_{\Omega} \boldsymbol{v} \cdot (\boldsymbol{A_0} \boldsymbol{Y}_{,t} - \boldsymbol{S}(\boldsymbol{Y})) \, d\Omega - \int_{\Omega} \boldsymbol{v}_{,i} \cdot \boldsymbol{F}_{i}(\boldsymbol{Y}) \, d\Omega + \int_{\partial\Omega} \boldsymbol{v} \cdot \boldsymbol{F}_{i}(\boldsymbol{Y}) \cdot \hat{\boldsymbol{n}}_{i} \, d\partial\Omega$$

$$+ \int_{\Omega} \mathcal{L}(\boldsymbol{v}) \, (\boldsymbol{A_0} \boldsymbol{Y}_{,t} + \boldsymbol{F}_{i,i}(\boldsymbol{Y}) - \boldsymbol{S}(\boldsymbol{Y})) \, d\Omega = 0$$
SUPG

Find  $oldsymbol{Y} \in \mathcal{S}^h$  ,  $orall oldsymbol{v} \in \mathcal{V}^h$ 

$$\int_{\Omega} \boldsymbol{v} \cdot (\boldsymbol{A_0} \boldsymbol{Y}_{,t} - \boldsymbol{S}(\boldsymbol{Y})) \, d\Omega - \int_{\Omega} \boldsymbol{v}_{,i} \cdot \boldsymbol{F}_{i}(\boldsymbol{Y}) \, d\Omega + \int_{\partial\Omega} \boldsymbol{v} \cdot \boldsymbol{F}_{i}(\boldsymbol{Y}) \cdot \hat{\boldsymbol{n}}_{i} \, d\partial\Omega$$

$$+ \int_{\Omega} \mathcal{L}(\boldsymbol{v}) \, (\boldsymbol{A_0} \boldsymbol{Y}_{,t} + \boldsymbol{F}_{i,i}(\boldsymbol{Y}) - \boldsymbol{S}(\boldsymbol{Y})) \, d\Omega = 0$$
SUPG

Simplify into residual form:

$$\mathcal{G}(\mathbf{Y}_{,t},\mathbf{Y})=0$$

Find  $\boldsymbol{Y} \in \mathcal{S}^h$  .  $\forall \boldsymbol{v} \in \mathcal{V}^h$ 

$$\int_{\Omega} \boldsymbol{v} \cdot (\boldsymbol{A_0} \boldsymbol{Y}_{,t} - \boldsymbol{S}(\boldsymbol{Y})) \, d\Omega - \int_{\Omega} \boldsymbol{v}_{,i} \cdot \boldsymbol{F}_i(\boldsymbol{Y}) \, d\Omega + \int_{\partial\Omega} \boldsymbol{v} \cdot \boldsymbol{F}_i(\boldsymbol{Y}) \cdot \hat{\boldsymbol{n}}_i \, d\partial\Omega$$

$$+ \int_{\Omega} \mathcal{L}(\boldsymbol{v}) \, \left(\boldsymbol{A_0} \boldsymbol{Y}_{,t} + \boldsymbol{F}_{i,i}(\boldsymbol{Y}) - \boldsymbol{S}(\boldsymbol{Y})\right) \, d\Omega = 0$$
SUPG


Simplify into residual form:

$$\mathcal{G}(\mathbf{Y}_{,t}, \mathbf{Y}) = 0$$


$$\Rightarrow \quad \mathcal{P}^{T} \mathcal{E}^{T} B^{T} G B \mathcal{E} \mathcal{P} \begin{bmatrix} \mathbf{Y}_{,t} \\ \mathbf{Y} \end{bmatrix} = 0$$



· Riemann Flux BCs everywhere is ideal



- · Riemann Flux BCs everywhere is ideal
- · Velocity not known a priori traditional Riemann BCs not applicable



- · Riemann Flux BCs everywhere is ideal
- · Velocity not known a priori traditional Riemann BCs not applicable

#### Solution


· Calculate  $F_i^{\text{adv}}$  via Riemann solver, setting  $u_i^{\text{ext}} = u_i^{\text{int}}$ 




- · Riemann Flux BCs everywhere is ideal
- · Velocity not known a priori traditional Riemann BCs not applicable

#### Solution

· Calculate  $F_i^{\text{adv}}$  via Riemann solver, setting  $u_i^{\text{ext}} = u_i^{\text{int}}$ 







Riemann Outflow Boundary Condition Flux

- · Riemann Flux BCs everywhere is ideal
- · Velocity not known a priori traditional Riemann BCs not applicable

#### Solution


- · Calculate  $F_i^{\text{adv}}$  via Riemann solver, setting  $u_i^{\text{ext}} = u_i^{\text{int}}$
- · Calculate  $m{F}_i^{ ext{diff}}$  from solution, then  $m{F}_i = m{F}_i^{ ext{adv}} + m{F}_i^{ ext{diff}}$





Riemann Outflow Boundary Condition Flux

## Viscous Outflow Boundary Conditions Demonstration



- · Cylinder in cross flow torture test
- · Stable despite recirculation
- Only p and T set at boundary

## **Efficient Implicit Timestepping**

Implicit timestepping requires solving:

$$\frac{\mathrm{d}\mathcal{G}(\boldsymbol{Y}_{,t},\boldsymbol{Y})}{\mathrm{d}\boldsymbol{Y}}\Delta\boldsymbol{Y} = -\mathcal{G}(\boldsymbol{Y}_{,t},\boldsymbol{Y})$$

Implicit timestepping requires solving:

$$\frac{\mathrm{d}\mathcal{G}(\boldsymbol{Y}_{,t},\boldsymbol{Y})}{\mathrm{d}\boldsymbol{Y}}\Delta\boldsymbol{Y} = -\mathcal{G}(\boldsymbol{Y}_{,t},\boldsymbol{Y})$$

• System too large for direct solve  $\longrightarrow$  iterative solve

Implicit timestepping requires solving:

$$\frac{\mathrm{d}\mathcal{G}(\boldsymbol{Y}_{,t},\boldsymbol{Y})}{\mathrm{d}\boldsymbol{Y}}\Delta\boldsymbol{Y} = -\mathcal{G}(\boldsymbol{Y}_{,t},\boldsymbol{Y})$$

- System too large for direct solve  $\longrightarrow$  iterative solve
- Krylov iterative solvers used most commonly

Implicit timestepping requires solving:

$$\frac{\mathrm{d}\mathcal{G}(\boldsymbol{Y}_{,t},\boldsymbol{Y})}{\mathrm{d}\boldsymbol{Y}}\Delta\boldsymbol{Y} = -\mathcal{G}(\boldsymbol{Y}_{,t},\boldsymbol{Y})$$

- $\cdot$  System too large for direct solve  $\longrightarrow$  iterative solve
- Krylov iterative solvers used most commonly
- · Krylov solvers form solution basis from  $\operatorname{span}\left\{\left[\frac{\mathrm{d}\mathcal{G}(\boldsymbol{Y}_{\!,t},\boldsymbol{Y})}{\mathrm{d}\boldsymbol{Y}}\right]^n\Delta\boldsymbol{Y}\right\}_{n=0}$

Implicit timestepping requires solving:

$$\frac{\mathrm{d}\mathcal{G}(\boldsymbol{Y}_{,t},\boldsymbol{Y})}{\mathrm{d}\boldsymbol{Y}}\Delta\boldsymbol{Y} = -\mathcal{G}(\boldsymbol{Y}_{,t},\boldsymbol{Y})$$

- $\cdot$  System too large for direct solve  $\longrightarrow$  iterative solve
- Krylov iterative solvers used most commonly
- Krylov solvers form solution basis from  $\operatorname{span}\left\{\left[\frac{\mathrm{d}\mathcal{G}(\boldsymbol{Y}_{\!t},\boldsymbol{Y})}{\mathrm{d}\boldsymbol{Y}}\right]^n\Delta\boldsymbol{Y}\right\}_{n=0}$

#### **Bottom Line**

Cost of  $\frac{\mathrm{d}\mathcal{G}(Y_{,t},Y)}{\mathrm{d}Y}\Delta Y$  dominates implicit timestepping cost



## Jacobian Matrix-Vector Multiply Options

How to compute  $\frac{\mathrm{d}\mathcal{G}(\pmb{Y}_{\!,t},\pmb{Y})}{\mathrm{d}\pmb{Y}}\Delta\pmb{Y}$ ?

## Jacobian Matrix-Vector Multiply Options

How to compute 
$$\frac{\mathrm{d}\mathcal{G}(\pmb{Y}_{\!,t},\pmb{Y})}{\mathrm{d}\pmb{Y}}\Delta\pmb{Y}$$
?

- Store  $\frac{\mathrm{d}\mathcal{G}}{\mathrm{d}\mathbf{Y}}$  directly (sparse matrix representation)
  - · Pros: Opens up preconditioning options
  - · Cons: Is large, expensive to store

## Jacobian Matrix-Vector Multiply Options

How to compute 
$$\frac{\mathrm{d}\mathcal{G}(\boldsymbol{Y}_{\!,t},\boldsymbol{Y})}{\mathrm{d}\boldsymbol{Y}}\Delta\boldsymbol{Y}$$
?


- Store  $\frac{d\mathcal{G}}{d\mathbf{v}}$  directly (sparse matrix representation)
  - · Pros: Opens up preconditioning options
  - · Cons: Is large, expensive to store
- Finite difference matrix-free approximation:


$$\frac{\mathrm{d}\mathcal{G}(\boldsymbol{Y}_{,t},\boldsymbol{Y})}{\mathrm{d}\boldsymbol{Y}}\Delta\boldsymbol{Y}\approx\frac{\mathcal{G}(\boldsymbol{Y}_{,t},\boldsymbol{Y}+\epsilon\Delta\boldsymbol{Y})-\mathcal{G}(\boldsymbol{Y}_{,t},\boldsymbol{Y})}{\epsilon}$$

- · Pros: Just need a residual evaluation, cheap (in programming and computation)
- Cons: Accuracy limited to  $\sqrt{\epsilon_{\text{machine}}}$ , preconditiong require partial assembly


$$\frac{\mathrm{d}\mathcal{G}}{\mathrm{d}\boldsymbol{Y}}\Delta\boldsymbol{Y} = \frac{\mathrm{d}}{\mathrm{d}\boldsymbol{Y}} \left[ \mathcal{P}^T \mathcal{E}^T B^T G B \mathcal{E} \mathcal{P} \right] \Delta \boldsymbol{Y}$$
$$= \left[ \mathcal{P}^T \mathcal{E}^T B^T \frac{\mathrm{d}G}{\mathrm{d}\boldsymbol{Y}} B \mathcal{E} \mathcal{P} \right] \Delta \boldsymbol{Y}$$

$$\frac{\mathrm{d}\mathcal{G}}{\mathrm{d}\boldsymbol{Y}}\Delta\boldsymbol{Y} = \frac{\mathrm{d}}{\mathrm{d}\boldsymbol{Y}} \left[ \mathcal{P}^T \mathcal{E}^T B^T G B \mathcal{E} \mathcal{P} \right] \Delta \boldsymbol{Y}$$
$$= \left[ \mathcal{P}^T \mathcal{E}^T B^T \frac{\mathrm{d}G}{\mathrm{d}\boldsymbol{Y}} B \mathcal{E} \mathcal{P} \right] \Delta \boldsymbol{Y}$$





$$\frac{\mathrm{d}\mathcal{G}}{\mathrm{d}\boldsymbol{Y}}\Delta\boldsymbol{Y} = \frac{\mathrm{d}}{\mathrm{d}\boldsymbol{Y}} \left[ \mathcal{P}^T \mathcal{E}^T B^T G B \mathcal{E} \mathcal{P} \right] \Delta \boldsymbol{Y}$$
$$= \left[ \mathcal{P}^T \mathcal{E}^T B^T \frac{\mathrm{d}G}{\mathrm{d}\boldsymbol{Y}} B \mathcal{E} \mathcal{P} \right] \Delta \boldsymbol{Y}$$



$$\frac{\mathrm{d}\mathcal{G}}{\mathrm{d}\boldsymbol{Y}}\Delta\boldsymbol{Y} = \frac{\mathrm{d}}{\mathrm{d}\boldsymbol{Y}} \left[ \mathcal{P}^{T} \mathcal{E}^{T} B^{T} G B \mathcal{E} \mathcal{P} \right] \Delta \boldsymbol{Y} \\
= \left[ \mathcal{P}^{T} \mathcal{E}^{T} B^{T} \frac{\mathrm{d}G}{\mathrm{d}\boldsymbol{Y}} B \mathcal{E} \mathcal{P} \right] \Delta \boldsymbol{Y}$$


$$= \left[ \mathcal{P}^{T} \mathcal{E}^{T} B^{T} \frac{\mathrm{d}G}{\mathrm{d}\boldsymbol{Y}} B \mathcal{E} \mathcal{P} \right] \Delta \boldsymbol{Y}$$

$$= \underbrace{\left[ \mathcal{P}^{T} \mathcal{E}^{T} B^{T} \frac{\mathrm{d}G}{\mathrm{d}\boldsymbol{Y}} B \mathcal{E} \mathcal{P} \right] \Delta \boldsymbol{Y}}_{store\ at\ quad\ points}$$

$$\underbrace{\left[ \mathcal{P}^{T} \mathcal{E}^{T} B^{T} \frac{\mathrm{d}G}{\mathrm{d}\boldsymbol{Y}} B \mathcal{E} \mathcal{P} \right] \Delta \boldsymbol{Y}}_{store\ at\ quad\ points}$$


- Pros: Exact Jacobian matrix-vector product (potentially faster convergence)
- · Cons: Preconditioning requires partial assembly

## Performance Exact Matrix-Free Jacobian via CeedOperator




Matrix-Free Application Comparison (Reproduced from Brown et al. 2022). Not from fluids code, but representative of libCEED matrix-free

## Performance Exact Matrix-Free Jacobian via CeedOperator




Matrix-Free Application Comparison (Reproduced from Brown et al. 2022). Not from fluids code, but representative of libCEED matrix-free




Fluids performance, DoFs fixed. Run on ALCE's Polaris on two nodes (8 x NVIDIA A100)

## Performance Exact Matrix-Free Jacobian via CeedOperator



Matrix-Free Application Comparison (Reproduced from Brown et al. 2022). Not from fluids code, but representative of libCEED matrix-free



Fluids performance, DoFs fixed. Run on ALCE's Polaris on two nodes (8 x NVIDIA A100)

## **Support and References**

This work was supported by.... Add in sponsor support (ALCF, FastMATH DOE, ECP, etc)

