Spectral Rigid Body Dynamics

Mikola Lysenko

May 5, 2010

Overview

Rigid Body Dynamics

Lagrangian Mechanics

Standard Collisions

Constraint Based Collisions

Fourier Methods

Rigid Body Dynamics

An approximate model of low energy physics for stiff objects

Rigid Body Dynamics

An approximate model of low energy physics for stiff objects

Pros:

- + Pretty accurate at human energy scales
- + Good for stiff materials (ie metals, plastics etc.)
- + Easy kinematic constraints (useful for mechanisms)
- + Standard animation tool (videogames!)

Rigid Body Dynamics

An approximate model of low energy physics for stiff objects

Pros:

- + Pretty accurate at human energy scales
- + Good for stiff materials (ie metals, plastics etc.)
- + Easy kinematic constraints (useful for mechanisms)
- + Standard animation tool (videogames!)


Cons:

- Inaccurate at extremely large energies
- Bad for materials with low elastic modulus
- Not always solvable! (See: Painleve's paradox)




An idealized solid object with elastic modulus $=\infty$

An idealized solid object with elastic modulus $=\infty$ We identify a body B with a scalar field, $\varphi:\mathbb{R}^d\to\mathbb{R}^+$




An idealized solid object with elastic modulus $=\infty$ We identify a body B with a scalar field, $\varphi:\mathbb{R}^d\to\mathbb{R}^+$



 φ represents the mass distribution of ${\it B}$

An idealized solid object with elastic modulus $=\infty$ We identify a body B with a scalar field, $\varphi:\mathbb{R}^d\to\mathbb{R}^+$



 φ represents the mass distribution of B $\varphi(x)=0$ indicates B does not occupy the space at x

Transformations of rigid mass fields must preserve distance and handedness


Transformations of rigid mass fields must preserve distance and handedness

In other words, must be a direct Euclidean isometry

Isomorphic to finite dimensional Lie group, $SE(d) \cong SO(d) \ltimes \mathbb{R}^d$

Transformations of rigid mass fields must preserve distance and handedness

In other words, must be a direct Euclidean isometry Isomorphic to finite dimensional Lie group, $SE(d) \cong SO(d) \ltimes \mathbb{R}^d$



Can be parameterized by a translation t and a rotation R

Matrix:
$$\begin{pmatrix} R & t \\ 0 & 1 \end{pmatrix}$$

 $\binom{d+1}{2}$ degrees of freedom


Tangent space: $\mathfrak{so}(d+1)$



Transformations of rigid mass fields must preserve distance and handedness

In other words, must be a direct Euclidean isometry

Isomorphic to finite dimensional Lie group, $SE(d)\cong SO(d)\ltimes \mathbb{R}^d$



Can be parameterized by a translation t and a rotation R

Matrix:
$$\begin{pmatrix} R & t \\ 0 & 1 \end{pmatrix}$$

 $\binom{d+1}{2}$ degrees of freedom

Tangent space: $\mathfrak{so}(d+1)$

Motions of rigid objects \cong curves $q(t) \subset SE(d)$



Turns physics into an optimization problem.

Turns physics into an optimization problem.

Given a configuration curve q at time t, define the Lagrangian

$$\mathcal{L}(q,\dot{q},t) = T(\dot{q}) - U(q,t)$$

Where $T(\dot{q}) = \frac{1}{2}\dot{q}^T M \dot{q}$ is the kinetic energy and U is a potential

Turns physics into an optimization problem.

Given a configuration curve q at time t, define the Lagrangian

$$\mathcal{L}(q,\dot{q},t) = T(\dot{q}) - U(q,t)$$

Where $T(\dot{q}) = \frac{1}{2}\dot{q}^T M \dot{q}$ is the kinetic energy and U is a potential

Hamilton's Principle of Least Action:

Physically plausible motions do minimal work



Turns physics into an optimization problem.

Given a configuration curve q at time t, define the Lagrangian

$$\mathcal{L}(q,\dot{q},t) = T(\dot{q}) - U(q,t)$$

Where $T(\dot{q}) = \frac{1}{2}\dot{q}^T M \dot{q}$ is the kinetic energy and U is a potential

Hamilton's Principle of Least Action:

Physically plausible motions do minimal work

In other words:

$$\underset{q:[t_0,t_1)\to SE(d)}{\operatorname{argmin}} \int\limits_{t_0}^{t_1} L(q,\dot{q},t)dt$$

Solve:

$$\underset{q:[t_0,t_1)\to SE(d)}{\operatorname{argmin}} \int\limits_{t_0}^{t_1} L(q,\dot{q},t)dt$$

Solve:

$$\underset{q:[t_0,t_1)\to SE(d)}{\operatorname{argmin}} \int_{t_0}^{t_1} L(q,\dot{q},t)dt$$

This is a 1st order variational problem, so use Euler-Lagrange:

$$\frac{d}{dt}\left(\frac{\partial L(q,\dot{q},t)}{\partial \dot{q}}\right) = \frac{\partial L(q,\dot{q},t)}{\partial q}$$

Solve:

$$\underset{q:[t_0,t_1)\to SE(d)}{\operatorname{argmin}} \int_{t_0}^{t_1} L(q,\dot{q},t)dt$$

This is a 1st order variational problem, so use Euler-Lagrange:

$$\frac{d}{dt}\left(\frac{\partial L(q,\dot{q},t)}{\partial \dot{q}}\right) = \frac{\partial L(q,\dot{q},t)}{\partial q}$$

Unpack definitions and simplify:

$$\frac{d}{dt} \left(\frac{\partial \frac{1}{2} \dot{q}^T M \dot{q}}{\partial \dot{q}} \right) = \frac{\partial U(q, t)}{\partial q}$$

Solve:

$$\underset{q:[t_0,t_1)\to SE(d)}{\operatorname{argmin}} \int_{t_0}^{t_1} L(q,\dot{q},t)dt$$

This is a 1st order variational problem, so use Euler-Lagrange:

$$\frac{d}{dt}\left(\frac{\partial L(q,\dot{q},t)}{\partial \dot{q}}\right) = \frac{\partial L(q,\dot{q},t)}{\partial q}$$

Unpack definitions and simplify:

$$\frac{d}{dt} \left(\frac{\partial \frac{1}{2} \dot{q}^T M \dot{q}}{\partial \dot{q}} \right) = \frac{\partial U(q, t)}{\partial q}$$

$$M \ddot{q} = \nabla U$$

Newton's equations!



Multiple Bodies

Q: How to deal with multiple independent bodies?

Multiple Bodies

Q: How to deal with multiple independent bodies?

A: Tensor sum

Let B_i, B_j be independent rigid bodies with motions q_i, q_j

Configuration space
$$SE(d)^2 \cong SE(d) \oplus SE(d)$$

Motion $q(t) \cong q_i(t) \oplus q_j(t)$
Lagrangian $L(q,\dot{q},t) = L(q_i,\dot{q}_i,t) + L(q_j,\dot{q}_j,t)$

Multiple Bodies

Q: How to deal with multiple independent bodies?

A: Tensor sum


Let B_i, B_j be independent rigid bodies with motions q_i, q_j

Configuration space
$$SE(d)^2 \cong SE(d) \oplus SE(d)$$

Motion $q(t) \cong q_i(t) \oplus q_j(t)$
Lagrangian $L(q, \dot{q}, t) = L(q_i, \dot{q}_i, t) + L(q_j, \dot{q}_j, t)$


Scales to n bodies, get Lagrangian in $SE(d)^n$

Solids can't physically occupy the same space.



Need to keep them separated

Solids can't physically occupy the same space.




Standard method:

► Time step to point of impact

Need to keep them separated


Solids can't physically occupy the same space.



Need to keep them separated

- ► Time step to point of impact
- ▶ Determine contact manifold


Solids can't physically occupy the same space.



Need to keep them separated

- ► Time step to point of impact
- Determine contact manifold
- Apply penalty force/impulse to separate objects


Solids can't physically occupy the same space.



Need to keep them separated

- ► Time step to point of impact
- Determine contact manifold
- Apply penalty force/impulse to separate objects
- Iterate until all collisions are resolved

Solids can't physically occupy the same space.



Need to keep them separated

- ► Time step to point of impact
- Determine contact manifold
- Apply penalty force/impulse to separate objects
- Iterate until all collisions are resolved
- + Just like high school physics

Problems with typical collision methods

Handling collisions this way is hard

Problems with typical collision methods

Handling collisions this way is hard

- Finding exact point/time of impact is expensive
- Contact manifolds can be difficult to classify
- Normal forces are ambiguous for curvy shapes
- Impulses are discontinuous; results in stiff system
- Penalty methods don't gaurantee separation
- Convergence properties not well understood
- Unclear how to handle sharp corners
- Discontinuity in simulation
- Complicated, ad-hoc

Problems with typical collision methods

Handling collisions this way is hard

- Finding exact point/time of impact is expensive
- Contact manifolds can be difficult to classify
- Normal forces are ambiguous for curvy shapes
- Impulses are discontinuous; results in stiff system
- Penalty methods don't gaurantee separation
- Convergence properties not well understood
- Unclear how to handle sharp corners
- Discontinuity in simulation
- Complicated, ad-hoc

But can be made to work with enough hacking...

There has got to be an easier way...

There has got to be an easier way...

Minimal requirement for physical plausibility

At all times no two solids intersect

There has got to be an easier way...

Minimal requirement for physical plausibility

At all times no two solids intersect

Is this really all there is to it?

For any body B_i with mass field φ_i , define the set:

$$A_i = \kappa \iota \operatorname{supp} \varphi$$

For any body B_i with mass field φ_i , define the set:

$$A_i = \kappa \iota \operatorname{supp} \varphi$$

So two solids, A_i , A_j , collide at a configuration q_i , q_j iff:

$$\mathsf{collide}(q_iA_i,q_jA_j) \Leftrightarrow \iota(q_iA_i \cap q_jA_j) \neq \emptyset$$

For any body B_i with mass field φ_i , define the set:

$$A_i = \kappa \iota \operatorname{supp} \varphi$$

So two solids, A_i , A_j , collide at a configuration q_i , q_j iff:

$$\mathsf{collide}(q_iA_i,q_jA_j) \Leftrightarrow \iota(q_iA_i \cap q_jA_j) \neq \emptyset$$

But,

$$\iota(q_iA_i\cap q_jA_j)\neq\emptyset\Leftrightarrow \mathrm{vol}\ q_iA_i\cap q_jA_j>0$$

For any body B_i with mass field φ_i , define the set:

$$A_i = \kappa \iota \operatorname{supp} \varphi$$

So two solids, A_i , A_j , collide at a configuration q_i , q_j iff:

$$\mathsf{collide}(q_iA_i,q_jA_j) \Leftrightarrow \iota(q_iA_i \cap q_jA_j) \neq \emptyset$$

But,

$$\iota(q_iA_i\cap q_jA_j)\neq\emptyset\Leftrightarrow \operatorname{vol}\ q_iA_i\cap q_jA_j>0$$

Define

$$C_{i,j}(q_i,q_j)\stackrel{def}{\equiv} \operatorname{vol} \ q_iA_i\cap q_jA_j$$

And so we replace the impact forces with a system of differentiable holonomic inequality constraints:

$$C_{i,j} \leq 0$$

Equations of motion revisited

New problem:

minimize
$$\int\limits_{t_0}^{t_1}L(q,\dot{q},t)dt$$
 subject to $C_{i,j}(q_i,q_j)\leq 0 \ \ orall t\in [t_0,t_1), i
eq j$

Equations of motion revisited

New problem:

minimize
$$\int\limits_{t_0}^{t_1}L(q,\dot{q},t)dt$$
 subject to $C_{i,j}(q_i,q_j)\leq 0 \ \ orall t\in [t_0,t_1), i
eq j$

Apply KKT conditions + Euler-Lagrange to get complementarity problem:

$$\frac{d}{dt} \left(\frac{\partial T(\dot{q}_i)}{\partial \dot{q}_i} \right) - \frac{\partial U(q,t)}{\partial q_i} + \sum_{j \neq i} \mu_{i,j} \frac{\partial C_{i,j}(q_i, q_j)}{\partial q_i} = 0$$

$$0 \le \mu_{i,j} \perp - C_{i,j} \ge 0$$

Equations of motion revisited

New problem:

minimize
$$\int\limits_{t_0}^{t_1}L(q,\dot{q},t)dt$$
 subject to $C_{i,j}(q_i,q_j)\leq 0 \ \ orall t\in [t_0,t_1), i
eq j$

Apply KKT conditions + Euler-Lagrange to get complementarity problem:

$$\frac{d}{dt}\left(\frac{\partial T(\dot{q}_i)}{\partial \dot{q}_i}\right) - \frac{\partial U(q,t)}{\partial q_i} + \sum_{j\neq i} \mu_{i,j} \frac{\partial C_{i,j}(q_i,q_j)}{\partial q_i} = 0$$

$$0 \leq \mu_{i,j} \perp -C_{i,j} \geq 0$$

Exactly elastic collision response!

Slack variables are impulse forces



Need to compute:

$$C_{i,j}(q_i,q_j) = \text{vol } q_i A_i \cap q_j A_j$$

Need to compute:

$$C_{i,j}(q_i,q_j) = \text{vol } q_i A_i \cap q_j A_j$$

Construct the indicator on A

$$\mathbf{1}_{A}(x) = \left\{ \begin{array}{ll} 1 & \text{if } x \in A \\ 0 & \text{otherwise} \end{array} \right.$$

Need to compute:

$$C_{i,j}(q_i,q_j) = \text{vol } q_i A_i \cap q_j A_j$$

Construct the indicator on A

$$\mathbf{1}_{\mathcal{A}}(x) = \left\{ egin{array}{ll} 1 & ext{if } x \in \mathcal{A} \\ 0 & ext{otherwise} \end{array}
ight.$$

Observe:

$$\mathbf{1}_{A_i\cap A_j}(x)=\mathbf{1}_{A_i}(x)\mathbf{1}_{A_j}(x)$$
 vol $A_i=\int\limits_{\mathbb{R}^d}\mathbf{1}_{A_i}(x)dx$

Need to compute:

$$C_{i,j}(q_i,q_j) = \operatorname{vol} \ q_i A_i \cap q_j A_j$$

Construct the indicator on A

$$\mathbf{1}_{A}(x) = \left\{ \begin{array}{ll} 1 & \text{if } x \in A \\ 0 & \text{otherwise} \end{array} \right.$$

Observe:

$$\mathbf{1}_{A_i\cap A_j}(x)=\mathbf{1}_{A_i}(x)\mathbf{1}_{A_j}(x)$$
 vol $A_i=\int\limits_{\mathbb{R}^d}\mathbf{1}_{A_i}(x)dx$

So:

$$C_{i,j}(q_i,q_j) = \int_{\mathbb{D}^d} \mathbf{1}_{A_i}(q_i^{-1}x)\mathbf{1}_{A_j}(q_j^{-1}x)dx$$

$$C_{i,j}(q_i,q_j) = \int\limits_{\mathbb{D} d} \mathbf{1}_{A_i}(q_i^{-1}x)\mathbf{1}_{A_j}(q_j^{-1}x)dx$$

$$C_{i,j}(q_i,q_j) = \int\limits_{\mathbb{R}^d} \mathbf{1}_{A_i}(q_i^{-1}x)\mathbf{1}_{A_j}(q_j^{-1}x)dx$$

Push terms to one side:

$$\int\limits_{\mathbb{R}^d} \mathbf{1}_{A_i}(x) \mathbf{1}_{A_j}(q_j^{-1}q_i x) dx$$

$$C_{i,j}(q_i,q_j) = \int\limits_{\mathbb{R}^d} \mathbf{1}_{A_i}(q_i^{-1}x)\mathbf{1}_{A_j}(q_j^{-1}x)dx$$

Push terms to one side:

$$\int\limits_{\mathbb{R}^d} \mathbf{1}_{A_i}(x) \mathbf{1}_{A_j}(q_j^{-1}q_i x) dx$$

Substitute $q_j^{-1}q_ix\mapsto Rx-y$ and let $\widetilde{\mathbf{1}_{A_j}}(x)=\mathbf{1}_{A_j}(-x)$:

$$\int_{\mathbb{R}^d} \mathbf{1}_{A_i}(x) \widetilde{\mathbf{1}}_{A_j}(y - Rx) dx = \int_{\mathbb{R}^d} \mathbf{1}_{A_i}(R^{-1}x) \widetilde{\mathbf{1}}_{A_j}(y - x) dx$$

$$C_{i,j}(q_i,q_j) = \int\limits_{\mathbb{R}^d} \mathbf{1}_{A_i}(q_i^{-1}x)\mathbf{1}_{A_j}(q_j^{-1}x)dx$$

Push terms to one side:

$$\int\limits_{\mathbb{R}^d} \mathbf{1}_{A_i}(x) \mathbf{1}_{A_j}(q_j^{-1}q_i x) dx$$

Substitute $q_j^{-1}q_ix\mapsto Rx-y$ and let $\widetilde{\mathbf{1}_{A_j}}(x)=\mathbf{1}_{A_j}(-x)$:

$$\int_{\mathbb{R}^d} \mathbf{1}_{A_i}(x) \widetilde{\mathbf{1}}_{A_j}(y - Rx) dx = \int_{\mathbb{R}^d} \mathbf{1}_{A_i}(R^{-1}x) \widetilde{\mathbf{1}}_{A_j}(y - x) dx$$

So,

$$C_{i,j}(q_i,q_j) = ((\mathbf{1}_{A_i} \circ R^{-1}) \star \widetilde{\mathbf{1}_{A_j}})(y)$$

Convolution?

$$C_{i,j}(q_i,q_j) = ((\mathbf{1}_{A_i} \circ R^{-1}) \star \widetilde{\mathbf{1}_{A_j}})(y)$$

Convolution? Take a Fourier transform!

$$C_{i,j}(q_i,q_j) = ((\mathbf{1}_{A_i} \circ R^{-1}) \star \widehat{\mathbf{1}_{A_j}})(y) = \mathcal{F}^{-1}\left((\widehat{\mathbf{1}_{A_i}} \circ R^{-1})\overline{\widehat{\mathbf{1}_{A_j}}}\right)(y)$$

Convolution? Take a Fourier transform!

$$C_{i,j}(q_i,q_j) = ((\mathbf{1}_{A_i} \circ R^{-1}) \star \widetilde{\mathbf{1}_{A_j}})(y) = \mathcal{F}^{-1}\left((\widehat{\mathbf{1}_{A_i}} \circ R^{-1})\overline{\widehat{\mathbf{1}_{A_j}}}\right)(y)$$

What about gradients? (ie $\frac{\partial C_{i,j}(q_i,q_j)}{\partial q_i}$)

Convolution? Take a Fourier transform!

$$C_{i,j}(q_i,q_j) = ((\mathbf{1}_{A_i} \circ R^{-1}) \star \widetilde{\mathbf{1}_{A_j}})(y) = \mathcal{F}^{-1}\left((\widehat{\mathbf{1}_{A_i}} \circ R^{-1})\overline{\widehat{\mathbf{1}_{A_j}}}\right)(y)$$

What about gradients? (ie $\frac{\partial C_{i,j}(q_i,q_j)}{\partial q_i}$)

Fix parameters $q_i = (R_i, t_i)$,

$$q_i x = R_i x + t_i$$

$$q_i^{-1} = (R_i^{-1}, -R_i^{-1}t_i)$$

$$q_j q_i^{-1} x = Rx - y$$

Convolution? Take a Fourier transform!

$$C_{i,j}(q_i,q_j) = ((\mathbf{1}_{A_i} \circ R^{-1}) \star \widetilde{\mathbf{1}_{A_j}})(y) = \mathcal{F}^{-1}\left((\widehat{\mathbf{1}_{A_i}} \circ R^{-1})\overline{\widehat{\mathbf{1}_{A_j}}}\right)(y)$$

What about gradients? (ie $\frac{\partial C_{i,j}(q_i,q_j)}{\partial q_i}$)

Fix parameters
$$q_i = (R_i, t_i)$$
,

$$q_i x = R_i x + t_i$$

$$q_i^{-1} = (R_i^{-1}, -R_i^{-1}t_i)$$

$$q_j q_i^{-1} x = Rx - y$$

Solve for R, v.

$$R = R_j R_i^{-1}$$

$$y = t_j - R_j R_i^{-1} t_i$$

Convolution? Take a Fourier transform!

$$C_{i,j}(q_i,q_j) = ((\mathbf{1}_{A_i} \circ R^{-1}) \star \widetilde{\mathbf{1}_{A_j}})(y) = \mathcal{F}^{-1}\left((\widehat{\mathbf{1}_{A_i}} \circ R^{-1})\overline{\widehat{\mathbf{1}_{A_j}}}\right)(y)$$

What about gradients? (ie $\frac{\partial C_{i,j}(q_i,q_j)}{\partial q_i}$)

Fix parameters
$$q_i = (R_i, t_i)$$
, Solve for R, y ,
$$q_i x = R_i x + t_i$$

$$R = R_j R_i^{-1}$$

$$q_i^{-1} = (R_i^{-1}, -R_i^{-1} t_i)$$

$$q_i q_i^{-1} x = Rx - y$$

$$y = t_j - R_j R_i^{-1} t_i$$

Need to compute
$$\frac{\partial C_{i,j}(R_i,t_i,R_j,t_j)}{\partial R_i}$$
, $\frac{\partial C_{i,j}(R_i,t_i,R_j,t_j)}{\partial t_i}$
Or by symmetry: $C_{i,j}(q_i,q_j)=C_{j,i}(q_j,q_i)$

Start with the translational case first.

Let t_j^k denote the k^{th} component of t_j ,

Start with the translational case first.

Let t_i^k denote the k^{th} component of t_j , then

$$\frac{\partial C_{i,j}}{\partial t_j^k} = \frac{\partial}{\partial t_i^j} \left(\int_{\mathbb{R}^d} \widehat{\mathbf{1}_{A_i}} (R_i R_j^{-1} \omega) \overline{\widehat{\mathbf{1}_{A_j}}} (\omega) e^{2\pi i \langle \omega, t_j - R_j R_i^{-1} t_i \rangle} d\omega \right)$$

Start with the translational case first.

Let t_i^k denote the k^{th} component of t_j , then

$$\frac{\partial C_{i,j}}{\partial t_{j}^{k}} = \frac{\partial}{\partial t_{i}^{j}} \left(\int_{\mathbb{R}^{d}} \widehat{\mathbf{1}_{A_{i}}} (R_{i}R_{j}^{-1}\omega) \overline{\widehat{\mathbf{1}_{A_{j}}}}(\omega) e^{2\pi i \langle \omega, t_{j} - R_{j}R_{i}^{-1}t_{i} \rangle} d\omega \right) \\
= \int_{\mathbb{R}^{d}} 2\pi i \langle \omega, v^{k} \rangle \widehat{\mathbf{1}_{A_{i}}} (R_{i}R_{j}^{-1}\omega) \overline{\widehat{\mathbf{1}_{A_{j}}}}(\omega) e^{2\pi i \langle \omega, t_{j} - R_{j}R_{i}^{-1}t_{i} \rangle} d\omega$$

Where v^k denotes the k^{th} basis vector

Start with the translational case first.

Let t_j^k denote the k^{th} component of t_j , then

$$\frac{\partial C_{i,j}}{\partial t_{j}^{k}} = \frac{\partial}{\partial t_{i}^{j}} \left(\int_{\mathbb{R}^{d}} \widehat{\mathbf{1}_{A_{i}}} (R_{i}R_{j}^{-1}\omega) \overline{\widehat{\mathbf{1}_{A_{j}}}}(\omega) e^{2\pi i \langle \omega, t_{j} - R_{j}R_{i}^{-1}t_{i} \rangle} d\omega \right) \\
= \int_{\mathbb{R}^{d}} 2\pi i \langle \omega, v^{k} \rangle \widehat{\mathbf{1}_{A_{i}}} (R_{i}R_{j}^{-1}\omega) \overline{\widehat{\mathbf{1}_{A_{j}}}}(\omega) e^{2\pi i \langle \omega, t_{j} - R_{j}R_{i}^{-1}t_{i} \rangle} d\omega$$

Where v^k denotes the k^{th} basis vector

Conclusion: Translational gradient is just a multiplier

Parameterize $R_j = \exp(\mathfrak{r})$, where $\mathfrak{r} \in \mathfrak{so}(d)$ In otherwords $d \times d$ skew symmetric matrices, $\mathfrak{r}_{k,l} = -\mathfrak{r}_{l,k}$

Parameterize $R_j = \exp(\mathfrak{r})$, where $\mathfrak{r} \in \mathfrak{so}(d)$ In otherwords $d \times d$ skew symmetric matrices, $\mathfrak{r}_{k,l} = -\mathfrak{r}_{l,k}$

$$\frac{\partial C_{i,j}}{\partial \mathfrak{r}_{k,l}} = \frac{\partial}{\partial \mathfrak{r}_{k,l}} \left(\int_{\mathbb{R}^d} \widehat{\mathbf{1}_{A_i}} (R_i \exp(-\mathfrak{r}) \omega) \widehat{\overline{\mathbf{1}_{A_j}}} (\omega) e^{2\pi i \langle \omega, t_j - \exp(\mathfrak{r}) R_i^{-1} t_i \rangle} d\omega \right)$$

Parameterize $R_j = \exp(\mathfrak{r})$, where $\mathfrak{r} \in \mathfrak{so}(d)$ In otherwords $d \times d$ skew symmetric matrices, $\mathfrak{r}_{k,l} = -\mathfrak{r}_{l,k}$

$$\frac{\partial C_{i,j}}{\partial \mathfrak{r}_{k,l}} = \frac{\partial}{\partial \mathfrak{r}_{k,l}} \left(\int_{\mathbb{R}^d} \widehat{\mathbf{1}_{A_i}} (R_i \exp(-\mathfrak{r})\omega) \widehat{\overline{\mathbf{1}_{A_j}}}(\omega) e^{2\pi i \langle \omega, t_j - \exp(\mathfrak{r})R_i^{-1}t_i \rangle} d\omega \right)
\dots = \int_{\mathbb{R}^d} \widehat{\mathbf{1}_{A_i}}(\omega) e^{2\pi i \langle \omega, y \rangle} \left(-\left\langle \overline{\nabla \widehat{\mathbf{1}_{A_j}}}(R\omega), R\mathfrak{r}_{k,l}\omega \right\rangle \right.
+ \left. \widehat{\overline{\mathbf{1}_{A_j}}}(R\omega) 2\pi i \left\langle R\mathfrak{r}_{k,l}\omega, t_j \right\rangle \right) d\omega$$

Parameterize $R_j = \exp(\mathfrak{r})$, where $\mathfrak{r} \in \mathfrak{so}(d)$ In otherwords $d \times d$ skew symmetric matrices, $\mathfrak{r}_{k,l} = -\mathfrak{r}_{l,k}$

$$\frac{\partial C_{i,j}}{\partial \mathfrak{r}_{k,l}} = \frac{\partial}{\partial \mathfrak{r}_{k,l}} \left(\int_{\mathbb{R}^d} \widehat{\mathbf{1}_{A_i}} (R_i \exp(-\mathfrak{r})\omega) \overline{\widehat{\mathbf{1}_{A_j}}}(\omega) e^{2\pi i \langle \omega, t_j - \exp(\mathfrak{r})R_i^{-1}t_i \rangle} d\omega \right)
\dots = \int_{\mathbb{R}^d} \widehat{\mathbf{1}_{A_i}}(\omega) e^{2\pi i \langle \omega, y \rangle} \left(-\left\langle \overline{\nabla \widehat{\mathbf{1}_{A_j}}}(R\omega), R\mathfrak{r}_{k,l}\omega \right\rangle \right.
+ \overline{\widehat{\mathbf{1}_{A_j}}(R\omega)} 2\pi i \left\langle R\mathfrak{r}_{k,l}\omega, t_j \right\rangle \right) d\omega$$

Get two terms:

Parameterize $R_j = \exp(\mathfrak{r})$, where $\mathfrak{r} \in \mathfrak{so}(d)$ In otherwords $d \times d$ skew symmetric matrices, $\mathfrak{r}_{k,l} = -\mathfrak{r}_{l,k}$

$$\frac{\partial C_{i,j}}{\partial \mathfrak{r}_{k,l}} = \frac{\partial}{\partial \mathfrak{r}_{k,l}} \left(\int_{\mathbb{R}^d} \widehat{\mathbf{1}_{A_i}} (R_i \exp(-\mathfrak{r})\omega) \widehat{\overline{\mathbf{1}_{A_j}}}(\omega) e^{2\pi i \langle \omega, t_j - \exp(\mathfrak{r})R_i^{-1}t_i \rangle} d\omega \right) \\
\dots = \int_{\mathbb{R}^d} \widehat{\mathbf{1}_{A_i}}(\omega) e^{2\pi i \langle \omega, y \rangle} \left(-\left\langle \overline{\nabla \widehat{\mathbf{1}_{A_j}}}(R\omega), R\mathfrak{r}_{k,l}\omega \right\rangle \right. \\
\left. + \overline{\widehat{\mathbf{1}_{A_j}}(R\omega)} 2\pi i \left\langle R\mathfrak{r}_{k,l}\omega, t_j \right\rangle \right) d\omega$$

Get two terms: a multiplier (easy),

Parameterize $R_j = \exp(\mathfrak{r})$, where $\mathfrak{r} \in \mathfrak{so}(d)$ In otherwords $d \times d$ skew symmetric matrices, $\mathfrak{r}_{k,l} = -\mathfrak{r}_{l,k}$

$$\frac{\partial C_{i,j}}{\partial \mathfrak{r}_{k,l}} = \frac{\partial}{\partial \mathfrak{r}_{k,l}} \left(\int_{\mathbb{R}^d} \widehat{\mathbf{1}_{A_i}} (R_i \exp(-\mathfrak{r})\omega) \widehat{\overline{\mathbf{1}_{A_j}}}(\omega) e^{2\pi i \langle \omega, t_j - \exp(\mathfrak{r})R_i^{-1}t_i \rangle} d\omega \right) \\
\dots = \int_{\mathbb{R}^d} \widehat{\mathbf{1}_{A_i}}(\omega) e^{2\pi i \langle \omega, y \rangle} \left(-\left\langle \overline{\nabla \widehat{\mathbf{1}_{A_j}}}(R\omega), R\mathfrak{r}_{k,l}\omega \right\rangle \right. \\
+ \left. \widehat{\overline{\mathbf{1}_{A_j}}}(R\omega) 2\pi i \left\langle R\mathfrak{r}_{k,l}\omega, t_j \right\rangle \right) d\omega$$

Get two terms: a multiplier (easy), a gradient (can be precomputed).

Parameterize $R_j = \exp(\mathfrak{r})$, where $\mathfrak{r} \in \mathfrak{so}(d)$ In otherwords $d \times d$ skew symmetric matrices, $\mathfrak{r}_{k,l} = -\mathfrak{r}_{l,k}$

$$\frac{\partial C_{i,j}}{\partial \mathfrak{r}_{k,l}} = \frac{\partial}{\partial \mathfrak{r}_{k,l}} \left(\int_{\mathbb{R}^d} \widehat{\mathbf{1}_{A_i}} (R_i \exp(-\mathfrak{r})\omega) \overline{\widehat{\mathbf{1}_{A_j}}}(\omega) e^{2\pi i \langle \omega, t_j - \exp(\mathfrak{r}) R_i^{-1} t_i \rangle} d\omega \right)
\dots = \int_{\mathbb{R}^d} \widehat{\mathbf{1}_{A_i}}(\omega) e^{2\pi i \langle \omega, y \rangle} \left(-\left\langle \overline{\nabla \widehat{\mathbf{1}_{A_j}}}(R\omega), R\mathfrak{r}_{k,l}\omega \right\rangle \right.
+ \overline{\widehat{\mathbf{1}_{A_j}}}(R\omega) 2\pi i \left\langle R\mathfrak{r}_{k,l}\omega, t_j \right\rangle \right) d\omega$$

Get two terms: a multiplier (easy), a gradient (can be precomputed).

Computationally not too bad, but still pretty messy in *d*-dimensional space.

