

```
-- 1. View Databases
show databases
-- 2. Use Database
use office_db
-- 3. Create Collection
db.createCollection("employee")
-- 4. View Collections
show collections
-- 5. Insert Initial Data
db.employee.insertMany([
{
name:"neha",
salary:50000,
age:25,
city:"chennai",
dept:"hr"
},
{
name:"priya",
salary:60000,
age:20,
city:"chennai",
dept:"it"
},
{
name:"varun",
salary:20000,
age:22,
city:"bangalore",
dept:"sales"
},
{
name:"ashwini",
salary:15000,
age:23,
city:"mumbai",
dept:"hr"
},
{
name:"rahul",
salary:70000,
age:30,
city:"delhi",
dept:"it"
}
])
-- 6. Retrieve ALL Documents
db.employee.find()
-- 7. Count Documents
db.employee.countDocuments()
-- 8. Find Specific Documents
db.employee.find({name:"varun"})
db.employee.find({name:"neha"})
```

```
-- 9. Sorting
db.employee.find().sort({salary:1})
db.employee.find().sort({salary:-1})
-- 10. Limit
db.employee.find().limit(2)
db.employee.find().sort({salary:-1}).limit(1)
-- 11. Comparison Operators
db.employee.find({salary:{$gt:30000}})
db.employee.find({salary:{$lt:30000}})
db.employee.find({salary:{$eq:50000}})
-- 12. Update Operations
db.employee.updateOne(
  {name:"varun"},
  {$set:{age:40}}
)

db.employee.updateMany(
  {salary:{$lt:30000}},
  {$set:{country:"India"}}
)
-- 13. Delete Operation
db.employee.deleteOne({name:"varun"})
-- 14. Logical Operators
db.employee.find({
  $and:[
    {salary:{$gt:50000}},
    {dept:"it"}
  ]
})

db.employee.find({
  $or:[
    {dept:"hr"},
    {dept:"sales"}
  ]
})

db.employee.find({
  $nor:[
    {dept:"hr"}
  ]
})
-- 15. Aggregation
db.employee.aggregate([
  {$group: {_id:"$dept", avg_salary:{$avg:"$salary"}}}
])

db.employee.aggregate([
  {$group: {_id:"$dept", total_salary:{$sum:"$salary"}}}
])

db.employee.aggregate([
  {$group: {_id:"$dept", max_salary:{$max:"$salary"}}}
])

db.employee.aggregate([
```

```
    {$group: {_id: "$dept", min_salary: {$min: "$salary"}}}  
  ])  
  
db.employee.aggregate([  
  {$group: {_id: "$dept", total_count: {$sum: 1}}}  
])  
-- 16. Final Display  
db.employee.find()
```

In []: