
Full Stack Development
Containers, Microservices and UI
6. Code Management

Version Control



Local Version Control



Centralized Version Control



Distributed Version Control



Git Version Model



Other systems



Git

Source: Git book

Git & Github Workflow

blog.jr0cket.co.uk



Code Management Branches



Git History

- Prior to 2005: Linux using BitKeeper
- 2005: BitKeeper unfriends Linux
- Linus Torvalds and team design git (named for an uncouth person)
  - Speed
  - Simple design
  - Support for non-linear development
  - Distributed (you can work on the plane)
  - Handle large projects efficiently (speed and data size)
- Not intended to serve as repository for large binary files
  - Main purpose is as code management repository

Terminology

- Repository
- Working Copy
- Index/Staging area
- Blobs, Trees
- Cloning
- Remotes
- Pulling + Pushing
- Local history vs. Public history

Repository

- A set of files and directories
- Historical record of changes in the repository
- A set of commit objects
- A set of references to commit objects, called heads
- Let us give examples of what qualifies as a repository
  - A copy of a project directory?
  - CVS? Subversion?
- Git is a complete repository, either local and remote

Working Copy

- A.k.a “working directory,” is a single checkout of one version of the project

Hands-on: analyze the git directory (.git)

Can you have multiple working copies?

Source: Git book



Index and Staging areas

- Index and Staging area are the same
- It is a simple file in the Git directory
- Stores information about the next commit


Basic git Operations
Demo

Working Copy

- Git is a key-value data store
  - You can store a value and get back a key
  - All we need to know is “tree” and “blob”



Put and get values

- Put value, observe the key you get in return

```
[rod@exgnosis test]$ git init
Initialized empty Git repository in /home/rod/workspaces/test/.git/
[rod@exgnosis test]$ ls
[rod@exgnosis test]$ echo "Git test file" >> test.txt
[rod@exgnosis test]$  git hash-object -w test.txt
a46b6477ad8a5c24c403e155bfdf5ef58de44c86
[rod@exgnosis test]$ git cat-file -p a46b6477ad8a5c24c403e155bfdf5ef58de44c86
Git test file
[rod@exgnosis test]$
```

Cloning and Remotes

- Getting a copy of the existing get repository
  - How? git clone <url>
  - Also supported by most IDEs
- Remotes are versions of a project that are hosted on the Internet or network for collaboration:
  - There can be multiple remotes
  - Remotes can read only or read-write
  - List remotes for a repository with “git remote -v”
  - The origin remote is where the repo is cloned from

```
D:\classes\FSDNov28-Student>git remote -v
origin  https://github.com/ExgnosisClasses/FSDNov28-Student.git (fetch)
origin  https://github.com/ExgnosisClasses/FSDNov28-Student.git (push)
```

Pulling + Pushing

- Pulling – from a branch on a remote
- Fetching – all that you don't have yet
- Pushing – back to the branch on a remote



Local history vs. Public history

- Local history is on your computer and allows you to
  - Change commits
  - Change commit messages
  - Reorder
  - Squash
- However, be careful pushing this to the public history
  - Other developers may end up having to merge

Making a commit

- Commit is a record of your changes in a Git directory (repository)
- Making a commit is moving the branch point (master in this case) to the next snapshot



Commit features

- Permanence
  - Commit leaves a record
  - Commit goes into the Git area
  - Commit can be further recorded in a remote
- Impermanence
  - Commits can be taken back (undone locally or reverted)
  - Commits can be erased (rebase)


Basic git Commands
Demo

Branching and Merging



Git checkout tom -b



Git commit -a



Work on hotfix

git checkout -b hotfix
git commit -a -m 'urgent fix'



Merge hotfix

git checkout master
git merge hotfix



Cleanup

git branch -d hotfix



Pushing your change

git push <remote> <branch>



Branching and Merging

Demo

Branching Strategies

- A branching workflow is how developers:
  - Work in parallel on separate tasks and
  - Integrate their work into a codebase
- These are implementations of development models
  - All development on main branch; or
  - All development on feature branches
- All rely on branch and merge events
  - Generally, merges are the events that initiate a CICD pipeline
- There are three main flows used
  - GitHub flow
  - Git flow
  - GitLab flow

Git Flow



GitHub Flow



GitLab Flow


V2.0
Production Branch
Merge Request
Main Branch
Feature Branch
Merge Request
Testing

Feature Branch Workflow

- The main branch is protected
  - Only authorized members can push or merge
- To do any work, create a feature branch
  - These branches should not be created in a remote repository
- Clone the main branch to a local directory
  - Create the feature branch
  - Make changes, commit to the feature branch
  - Push the feature branch to the origin
  - The feature branch will remain until it is merged into the main branch

Feature Branch Merge

- The feature branch has to be merged into main by creating a merge request
- The feature branch can be deleted after the merge is done
- Feature branches should never be long lived


Questions?

Class Project Discussion


End Module