

```

#include <GL/glut.h>
float rt = 0.0f;
void init(int Width, int Height){
glClearColor(1.1, 1.1, 1.1, 1.1);
glMatrixMode(GL_PROJECTION);
gluPerspective(45.0f,(GLfloat)Width/(GLfloat)Height,0.1f,50.0f);
//specifies a viewing frustum into the world coordinate system
glMatrixMode(GL_MODELVIEW); //sets the current matrix mode}
float ballX = -0.5f;
float ballY = 0.0f;
float ballZ = 0.0f;
void Draw()
{
glClear(GL_COLOR_BUFFER_BIT | GL_DEPTH_BUFFER_BIT);
glLoadIdentity();
glTranslatef(rt,0.0f,-8.0f); //produces the translation specified by (x,y,z)
glBegin(GL_POLYGON);
glColor3f(1.0,0.0,0.0);
glVertex3f(-1.0f, 1.0f, 0.0f); //glVertex3f that means you have three floating point
//values
glVertex3f(0.2f, 1.0f, 0.0f);
glVertex3f(1.0f, 0.4f, 0.0f);
glColor3f(0.0,0.0,0.0);
glVertex3f(1.0f,0.0f, 0.0f);
glColor3f(0.0,0.0,0.0);
glVertex3f(-1.0f,0.0f, 0.0f);
glEnd();
glColor3f(1.0, 1.0, 0.0);
glTranslatef(ballX,ballY,ballZ);
glutSolidSphere (0.3, 20, 20);
//glColor3f(1.0, 0.0, 0.0);
glTranslatef(ballX+1.5,ballY,ballZ);
glutSolidSphere (0.3, 20, 20);
rt+=0.0001f;
glutSwapBuffers(); //swaps the buffers of the current window if double buffered}
int main(int argc, char **argv)
{
glutInit(&argc, argv);
glutInitDisplayMode(GLUT_RGBA | GLUT_SINGLE );
glutInitWindowSize(640, 480);
glutInitWindowPosition(0, 0);
glutCreateWindow("Moving Vehicle");
glutDisplayFunc(Draw);
glutIdleFunc(Draw);/*sets the global idle callback to be func so a GLUT program can
perform background processing tasks or continuous animation when window system
events are not being received*/
init(640,480);
glutMainLoop();
return 0;}

```