

```

#include<GL/glut.h>

void display() {
    glClear(GL_COLOR_BUFFER_BIT);//glClear actually clears the buffer,
    glColor3f(1.0, 0.0, 0.0);//used to give each vertex its own color
    glBegin(GL_POINTS);
    glVertex2f(10.0, 10.0);// specifies the x and y coordinates of the vertex,
    glVertex2f(150.0, 80.0);
    glVertex2f(100.0, 20.0);
    glVertex2f(200.0, 100.0);
    glEnd();
    glFlush();//all issued commands to be executed as quickly as they are accepted
}

void myinit() {
    glClearColor(1.0, 1.0, 1.0, 1.0);//specifies the red, green, blue, and alpha values
    //used by glClear to clear the color buffers.
    glColor3f(1.0, 0.0, 0.0);//Sets the current color
    glPointSize(10.0);
    gluOrtho2D(0.0, 499.0, 0.0, 499.0);
}

int main(int argc, char** argv) {
    glutInit(&argc, argv);
    glutInitDisplayMode(GLUT_SINGLE | GLUT_RGB);
    glutInitWindowSize(500, 500);
    glutInitWindowPosition(0, 0);
    glutCreateWindow("Points");
    glutDisplayFunc(display);
    myinit();
    glutMainLoop();
}

```