

The Informational Content of Geographical Indications

JEAN-SAUVEUR AY*
INRA UMR CESAER

Reproducibility file Version 0.1 : April 13, 2019

Abstract

This file contents the R codes associated with the paper "The informational content of geographical indications" AAWWE Working Paper No XXX. The data used are under licence XX, available on the INRA dataverse website: <https://data.inra.fr>. R functions used are reported in the appendix to preserve the visibility of codes. Additional elements are in the French version available from the following Github repository: .

Contents

1 Descriptive Statistics	2	6 Models for 1936 GIs	11
		6.1 Descriptive stats	11
2 Models of GI designation	3	6.2 Estimation	11
2.1 Parametric ordered logit	3	6.3 Significance	12
2.2 Ordered generalized additive	3	6.4 Goodness of fit	12
3 Diagnostics	4	6.5 Omitted variable	13
3.1 Significance	4	6.6 Specification	13
3.2 Goodness of fit	5	6.7 Marginal effects	14
3.3 Omitted variable	5	6.8 Commune effects	14
3.4 Specification	6	6.9 Dynamic Communes	15
4 Marginal effects	7	7 Counterfactual decomposition	15
4.1 Parametric ordered logit	7	7.1 Decomposition 1936 GIs	15
4.2 Ordered generalized additive	7	7.2 Alternative GI designations	17
4.3 Ordinal superiority figure	7	8 Session information	20
4.4 Correlation between Communes	9	A Functions	21
5 Decomposition	10	A.1 Surrogate	21
		A.2 Decomposition	24

*jsay@inra.fr at UMR CESAER, AgroSup, INRA, Univ. Bourgogne Franche-Comté, 26 bd Dr Petitjean, 21000 Dijon (FR).

1 Descriptive Statistics

Include stat des about sample selection

```
library(sp) ; load("Inter/PolyVny.Rda")
Reg.Rank <- subset(PolyVny,
                  PolyVny$PAOC!= 0 & !is.na(PolyVny$DEM) & !is.na(PolyVny$LIBCOM))
Reg.Rank$AOCc <- ifelse(Reg.Rank$GCRU== 1, 5,
                      ifelse(Reg.Rank$PCRU== 1, 4,
                            ifelse(Reg.Rank$VILL== 1 | Reg.Rank$COMM== 1, 3,
                                  ifelse(Reg.Rank$BOUR== 1, 2, 1))))
tst <- Reg.Rank@data[, 12:17]
tst$COMM <- ifelse(tst$VILL== 1 | tst$COMM== 1, 1, 0)
tst$VILL <- 0
table(rowSums(tst), Reg.Rank$AOCc)

tmp <- Reg.Rank$LIBCOM[order(Reg.Rank$YCHF, decreasing= TRUE)]
Reg.Rank$LIBCOM <- factor(Reg.Rank$LIBCOM, levels= unique(tmp))
Reg.Rank$RAYAT <- with(Reg.Rank@data, (SOLAR- mean(SOLAR))/ sd(SOLAR))
Reg.Rank$EXPO <- cut(Reg.Rank$ASPECT,
                    breaks= c(-2, 45, 90, 135, 180, 225, 270, 315, 360))
sapply(Reg.Rank@data, function(x) sum(is.na(x)))
#table(Reg.Old$LIBCOM, Reg.Old$AOCc)
```

PAR2RAS	IDU	CODECOM	AREA	PERIM	MAXDIST
0	0	0	0	0	0
PAOC	ALIG	BPTG	CREM	MOUS	BGOR
0	0	0	0	0	0
BOUR	VILL	COMM	PCRU	GCRU	XL93
0	0	0	0	0	0
YL93	NOMOS	URBAN	FOREST	WATER	DEM
0	0	0	0	0	0
SLOPE	ASPECT	SOLAR	PERMEA	CODE	NOTATION
0	0	0	0	0	0
DESCR	TYPE_GEOL	AP_LOCALE	TYPE_AP	GEOL_NAT	ISOPIQUE
0	0	80	80	0	0
AGE_DEB	ERA_DEB	SYS_DEB	LITHOLOGIE	DURETE	ENVIRONMT
0	0	0	0	10	0
GEOCHIMIE	LITHO_COM	NOUC	NO_UC	NO_ETUDE	SURFUC
0	10	658	658	658	658
TARG	TSAB	TLIM	TEXTAG	EPAIS	TEG
658	658	658	658	658	658
TMO	RUE	RUD	NOUS	OCCUP	DESCRp
658	658	658	658	658	658
AOC36lab	AOC36lv1	LIEUDIT	CLDVIN	LIBCOM	XCHF
18	18	152	152	152	152
YCHF	ALTCOM	SUPCOM	POPCOM	CODECANT	REGION
152	152	152	152	152	152
X	Y	AOCc	RAYAT	EXPO	
0	0	0	0	0	

2 Models of GI designation

2.1 Parametric ordered logit

Benchmark parametric ordered logistic model

```
library(MASS)
por1 <- polr(factor(AOCc)~ 0+ LIBCOM+ EXPO
             + poly(DEM, 2)+ poly(SLOPE, 2)+ poly(RAYAT, 2)
             + poly(X, 3)* poly(Y, 3), data= Reg.Rank, Hess= TRUE)
por1a <- polr(factor(AOCc)~ 0 + EXPO
              + poly(DEM, 2)+ poly(SLOPE, 2)+ poly(RAYAT, 2)
              + poly(X, 3)* poly(Y, 3), data= Reg.Rank, Hess= TRUE)
por1b <- polr(factor(AOCc)~ 0+ LIBCOM+ EXPO
              + poly(DEM, 2)+ poly(SLOPE, 2)+ poly(RAYAT, 2)
              , data= Reg.Rank, Hess= TRUE)
```

Warning messages:

- 1: In polr(factor(AOCc) ~ 0 + LIBCOM + EXPO + poly(DEM, 2) + poly(SLOPE, :
une coordonnée à l'origine est nécessaire et assumée
- 2: In polr(factor(AOCc) ~ 0 + LIBCOM + EXPO + poly(DEM, 2) + poly(SLOPE, :
le plan ne semble pas de rang plein, des coefs seront ignorés

Why warning message can be omitted.

2.2 Ordered generalized additive

The loop that allow to create the gamod object, the results of the models. I advice to not run the loop but to pick some value for the maximum degree of freedom and run the models individually.

```
library(mgcv)
listk <- c(50, 100, 200, 300, 400, 500, 600, 700, 800, 900)
gamod <- vector("list", length(listk))
system.time(
for (i in 1: length(listk)){
  gamod[[ i]] <- gam(AOCc~ 0+ LIBCOM+ EXPO+ s(DEM)+ s(SLOPE)+ s(RAYAT)
                    + s(X, Y, k= listk[ i])
                    , data= Reg.Rank, family= ocat(R= 5))
})
names(gamod) <- paste0("gam", listk)
save(gamod, file= "Inter/gamod.Rda")

gammod <- vector("list", length(listk))
system.time(
for (i in 1: length(listk)){
  gammod[[ i]] <- gam(AOCc~ 0+ EXPO+ s(DEM)+ s(SLOPE)+ s(RAYAT)
                     + s(X, Y, k= listk[ i])
                     , data= Reg.Rank, family= ocat(R= 5))
})
names(gammod) <- paste0("gam", listk)
save(gammod, file= "Inter/gammod.Rda")
```

utilisateur	système	écoulé
56177.4	384.9	56565
utilisateur	système	écoulé
42413.2	262.8	42679.6

3 Diagnostics

3.1 Significance

```
library(car)
resla <- anova(por1, por1b)
(res1 <- Anova(por1))
```

Analysis of Deviance Table (Type II tests)

Response: factor(AOCc)

	LR	Chisq	Df	Pr(>Chisq)
LIBCOM	14625	31		<2e-16 ***
EXPO	1212	7		<2e-16 ***
poly(DEM, 2)	5334	2		<2e-16 ***
poly(SLOPE, 2)	385	2		<2e-16 ***
poly(RAYAT, 2)	1921	2		<2e-16 ***
poly(X, 3)	2478	3		<2e-16 ***
poly(Y, 3)	639	3		<2e-16 ***
poly(X, 3):poly(Y, 3)	9555	9		<2e-16 ***

codes: 0 '***' 0.001 '**' 0.01 '*' 0.05 '.' 0.1 ' ' 1

```
load("Inter/gamod.Rda")
resume <- function(mod){
  tmp <- anova(mod)
  res <- c(as.vector(rbind(tmp$s.table[, 3], tmp$s.table[, 1])),
          as.vector(rbind(tmp$pTerms.tab[, 2], tmp$pTerms.tab[, 1])))
  names(res) <- c(as.vector(rbind(rownames(tmp$s.table), rep("", 4))),
                 as.vector(rbind(rownames(tmp$pTerms.tab), rep("", 2))))
  round(res, 1)
}
sapply(gamod[ 1: 5* 2], resume)
```

	gam100	gam300	gam500	gam700	gam900
s(DEM)	5020.2	2385.4	1677.7	1692.6	1766.8
	9.0	8.9	8.8	8.8	8.8
s(SLOPE)	1281.1	458.2	266.1	225.3	243.6
	8.5	8.5	8.5	8.4	8.4
s(RAYAT)	2491.6	1196.5	667.3	554.7	557.9

	8.3	8.2	7.7	7.6	7.5
s(X,Y)	41458.2	73705.5	94094.8	103941.0	107522.8
	98.7	295.2	483.1	666.7	844.7
LIBCOM	6793.2	6079.7	4594.7	3555.0	2894.5
	31.0	31.0	31.0	31.0	31.0
EXPO	110.3	123.2	222.3	153.5	160.8
	7.0	7.0	7.0	7.0	7.0

3.2 Goodness of fit

```
psR2 <- function(x) 1- (logLik(x)/ logLik(update(x, . ~ + 1)))
round(c(psR2(por1), AIC(por1)/ 1000,
        sum(diag(table(predict(por1), Reg.Rank$AOCc)))/nrow(Reg.Rank)), 2)
```

```
[1] 0.29 119.40 0.59
```

```
library(mgcv)
pcgp <- function(x){
  sum(diag(table(cut(x$line, c(-Inf, x$family$getTheta(TRUE), Inf)),
                    x$model[, 1])))/ nrow(x$model)* 100
}

rbind(sapply(gamod[ 1: 5* 2], pcgp), sapply(gamod[ 1: 5* 2], AIC))
#sapply(gamod, psR2)
```

```
      gam100  gam300  gam500  gam700  gam900
[1,]  73.89   79.94   84.23   86.94   89.15
[2,] 82412.10 64710.89 54941.54 48291.33 43535.14
```

3.3 Omitted variable

```
library(lmtest) ; library(sandwich) ; library(sure)
wall <- 0 ; nsim= 100
for (i in 1: nsim){
  tmp <- surrogate(por1a)- por1a$lp
  wall[ i] <- waldtest(lm(tmp~ Reg.Rank$LIBCOM), . ~ 1, vcov= vcovHC)$F[ 2]
}
quantile(wall, c(.05, .5, .95))
```

```
      5%   50%   95%
268.0 274.2 279.6
```

A passer en Reg.Rank, introduire la fonction sur les surrogate residuals des modèles gams en annexe.

```
load("Inter/gammod.Rda") ; source("myFcts.R")
omitVar <- function(mod, nsim= 100, old= F){
  usq <- 0
  if (!old) COM <- RRank$LIBCOM else COM <- SRank$LIBCOM
  for(i in 1: nsim) {
    if (!old) RES <- surlGAM(mod) else RES <- suroldGAM(mod)
    tmp <- lm(I(RES- mod$linear.pred)~ COM)
    usq[ i] <- waldtest(tmp, . ~ 1, vcov= vcovHC)$F[ 2]
  }
  usq
}
wal2 <- sapply(gammod, omitVar)
apply(wal2[, 1: 5* 2], 2, function(x) quantile(x, c(.05, .5, .95)))
```

	gam100	gam300	gam500	gam700	gam900
5%	17.38	6.060	3.377	2.004	1.704
50%	18.94	6.806	4.130	2.525	2.181
95%	20.15	7.746	4.864	3.060	2.760

```
library(lattice)
pltdat <- stack(data.frame(logit= wal1, wal2))
bwplot(values~ ind, data= pltdat, type=c("l","g"), horizontal= FALSE,
  xlab='Model of GI designation', ylab='Bootstraped F-statistics',
  par.settings = list(box.rectangle=list(col='black'),
    plot.symbol = list(pch='.', cex = 0.1)),
  scales=list(y= list(log= TRUE)),
  panel = function(..., box.ratio) {
    panel.grid(h= -1, v = -11)
    panel.violin(..., col = "lightblue",
      varwidth = FALSE, box.ratio = box.ratio)
    panel.bwplot(..., col='black',
      cex=0.8, pch='|', fill='gray', box.ratio = .1)
    panel.abline(h= log(1.47), col= "red", lty= 3)
    panel.text(2, log(1.55), "F= 1.47: critical value at 5%")})
```

3.4 Specification

Surrogate residuals can also be used to test specification, results not reported.

```
library(sure) ; library(ggplot2) ; library(gridExtra)
var <- c("DEM", "SLOPE", "RAYAT", "EXPO", "LIBCOM", "X", "Y")
plots <- lapply(var, function(.x)
  autoplot(por1, what= "covariate", x= RRank@data[, .x], xlab= .x))
(atp <- autoplot(por1, what= "qq"))
do.call(grid.arrange, c(list(atp), plots))
```

Introducing pltSURE function.

```
restmp <- surlGAM(gamod$gam900)- gamod$gam900$line
```




Figure 1: Effects of model XX

```
plot(qlogis(1: nrow(RRank)/ nrow(RRank), scale= 1), sort(restmp))
abline(0, 1)
par(mfrow= c(3, 3)) ; for (i in var) pltSURE(restmp, RRank@data[, i], i)
```

4 Marginal effects

4.1 Parametric ordered logit

```
library(effects)
plot(predictorEffects(por1, ~ DEM+ SLOPE+ RAYAT+ EXPO, latent= TRUE,
  xlevels=list(DEM= 200: 500,
    SLOPE= 0: 400/ 10, RAYAT= -60: 30/ 10)))
```

4.2 Ordered generalized additive

On voit bien que le lissage est le même que le papier.

```
plot(gamod$gam100, pages= 1, scale= 0)
```

4.3 Ordinal superiority figure




Figure 2: Effects of model XX




Figure 3: Effects of model XX

```

library(latticeExtra)
plogi <- function(x) exp(x/ sqrt(2))/ (1+ exp(x/ sqrt(2)))
xx <- data.frame(sapply(gamod, function(x)
  2* plogi(1(x$coeff[ 4: 31]- mean(x$coeff[ 4: 31]))- 1))
ww <- data.frame(xx,
  LIBCOM= substr(names(gamod[[1]]$coef[ 4: 31]), 7, 30),
  MIN= apply(xx[ 7: 10], 1, min),
  MAX= apply(xx[ 7: 10], 1, max),
  MEAN= apply(xx[ 7: 10], 1, mean))
segplot(reorder(factor(LIBCOM), MEAN)~ MIN+ MAX, length= 5, draw.bands= T,
  data= ww[order(ww$MEAN), ], center= MEAN, type= "o",
  unit = "mm", axis = axis.grid, col.symbol= "black", cex= 1,
  xlab= "Min, Mean and Max of Ordinal Superiority Measures")

```




Figure 4: Effects of model XX

4.4 Correlation between *Communes*

```

library(plyr) ; library(ggrepel)
yy <- ddply(RRank@data, .(LIBCOM),
  function(x) weighted.mean(x$AOCc, x$Area))
zz <- merge(ww, yy, by= "LIBCOM")
m <- lm(V1~ MEAN, data= zz)
a <- signif(coef(m)[1], digits = 2)
b <- signif(coef(m)[2], digits = 2)
c <- signif(summary(m)$r.sq, digits = 2)
textlab <- paste("y = ", a, " + ", b, " x ", " ", R2 = " ", c, sep= "")
ggplot(zz, aes(MEAN, V1, label= LIBCOM)) +

```

```
geom_smooth(method= lm, aes(MEAN, V1))+
geom_text_repel(point.padding = NA) +
annotate("text", x= -.75, y= 4, label= textlab, size= 4, parse= F)+
xlab("Reputation (ordinal superiority)") +
ylab("Average GI grade (between 0 and 5)")
```




Figure 5: Effects of model XX

5 Decomposition

see appendix for the code of decompositions, latent un peu long à tourner.

```
load("Inter/gamod.Rda") ; source("myFcts.R")
## latent <- sapply(gamod[ 1: 5* 2], function(x)
##   rowSums(predict(x, type= 'terms')[, -1]))
decomp <- apply(latent, 2, function(x)
  c(Signal= var(x), Noise= pi^2/ 3, jointSignal(x), jointNoise(x),
    rankSignal(x), rankResid(x), rankNoise(x),
    comSignal(x), comResid(x), comNoise(x)))
round(t(t(decomp)/ (pi^2/ 3+ decomp[1, ]))* 100, 1)
```

	gam100	gam300	gam500	gam700	gam900
Signal	84.8	94.7	95.9	96.8	97.6
Noise	15.2	5.3	4.1	3.2	2.4
Joint Signal	68.9	78.5	76.0	77.9	78.7
Joint Noise	16.0	16.2	20.0	18.9	18.9

Rank Signal	55.1	40.3	56.8	61.3	57.6
Rank Residual	13.8	38.2	19.2	16.5	21.2
Rank Noise	29.7	54.4	39.1	35.4	40.0
Com Signal	21.3	37.2	24.6	27.5	29.1
Com Residual	47.6	41.3	51.4	50.4	49.7
Com Noise	63.5	57.5	71.3	69.3	68.5

6 Models for 1936 GIs

6.1 Descriptive stats

```
Reg.Old <- subset(Reg.Rank, !is.na(Reg.Rank$AOC36lv1) &
  !Reg.Rank$LIBCOM %in%
  c("CHENOVE", "MARSANNAY-LA-COTE", "COUCHEY",
    "COMBLANCHIEN", "CORGOLOIN", "SAINT-ROMAIN"))
Reg.Old$LIBCOM <- factor(Reg.Old$LIBCOM)
Reg.Old$AOC <- as.numeric(ifelse(Reg.Old$AOC36lv1== "0", 1,
  ifelse(Reg.Old$AOC36lv1== "3", 2, 3)))
table(Reg.Old$AOC36lv1, Reg.Old$AOC)
#table(Reg.Old$LIBCOM, Reg.Old$AOC)
```

	1	2	3	4	5
0	7204	12605	4120	567	39
3	15	662	15378	8017	261
5	0	1	13	3	1604

6.2 Estimation

```
library(MASS)
por2 <- polr(factor(AOC)~ 0+ LIBCOM+ EXPO
  + poly(DEM, 2)+ poly(SLOPE, 2)+ poly(RAYAT, 2)
  + poly(X, 3)* poly(Y, 3), data= Reg.Old, Hess= T)
por2a <- polr(factor(AOC)~ 0+ EXPO
  + poly(DEM, 2)+ poly(SLOPE, 2)+ poly(RAYAT, 2)
  + poly(X, 3)* poly(Y, 3), data= Reg.Old, Hess= T)
por2b <- polr(factor(AOC)~ 0+ LIBCOM+ EXPO
  + poly(DEM, 2)+ poly(SLOPE, 2)+ poly(RAYAT, 2)
  , data= Reg.Old, Hess= T)
```

```
library(mgcv)
listk <- c(50, 75, 100, 150, 200, 250, 300)
gamold <- vector("list", length(listk))
system.time(
  for (i in 1: length(listk)){
    gamold[[ i]] <- gam(AOC~ 0+ LIBCOM+ EXPO+ s(DEM)+ s(SLOPE)+ s(RAYAT)
      + s(X, Y, k= listk[ i])
      , data= Reg.Old, family= ocat(R= 3))
```

```

})
names(gamold) <- paste0("gam", listk)
save(gamold, file= "Inter/gamold.Rda")

gammold <- vector("list", length(listk))
system.time(
for (i in 1: length(listk)){
  gammold[[ i]] <- gam(A0Co~ 0+ EXPO+ s(DEM)+ s(SLOPE)+ s(RAYAT)
    + s(X, Y, k= listk[ i])
    , data= Reg.Old, family= ocat(R= 3))
})
names(gammold) <- paste0("gam", listk)
save(gammold, file= "Inter/gammold.Rda")

```

utilisateur	système	écoulé
12259.5	144.1	12405.5
utilisateur	système	écoulé
9582.37	78.69	9661.62

6.3 Significance

```

load("Inter/gamold.Rda")
res2a <- anova(por2, por2b)
res2 <- Anova(por2)
sapply(gamold[ 3: 7], resume)

```

	gam100	gam150	gam200	gam250	gam300
s(DEM)	499.8	647.4	702.3	541.9	344.5
	8.5	8.2	8.8	8.4	7.7
s(SLOPE)	387.3	314.0	254.4	244.3	153.0
	8.7	8.7	8.6	8.6	8.3
s(RAYAT)	242.0	160.1	127.1	122.9	105.2
	8.5	8.3	8.1	5.0	5.9
s(X, Y)	17520.5	20194.2	22301.7	23507.2	23801.4
	98.3	146.3	194.4	239.8	286.6
LIBCOM	2782.5	1843.0	1642.4	1283.0	1049.4
	25.0	25.0	25.0	25.0	25.0
EXPO	119.8	91.8	91.9	96.1	90.2
	7.0	7.0	7.0	7.0	7.0

6.4 Goodness of fit

```

round(c(psR2(por2), AIC(por2)/ 1000,
  sum(diag(table(predict(por2), Reg.Old$A0Co)))/ nrow(Reg.Old)), 2)
rbind(sapply(gamold, pcgp), sapply(gamold, AIC))
#sapply(gamold, psR2)

```

```
[1] 0.38 51.29 0.79
      gam50  gam75  gam100  gam150  gam200  gam250  gam300
[1,] 84.34  85.9  87.08  89.26  90.28  91.4  92.54
[2,] 40789.58 36833.3 33810.36 30271.01 27574.12 24526.6 22482.20
```

6.5 Omitted variable

```
library(lmtest) ; library(sandwich) ; library(sure)
wal3 <- 0 ; nsim= 100
for (i in 1: nsim){
  tmp <- surrogate(por2a)- por2a$lp
  wal3[ i] <- waldtest(lm(tmp~ Reg.Old$LIBCOM), . ~ 1, vcov= vcovHC)$F[ 2]
}
load("Inter/gammold.Rda") ; source("myFcts.R")
wal4 <- sapply(gammold, function(x) omitVar(x, old= T))
wold <- data.frame(logit= wal3, wal4)
apply(wold, 2, function(x) quantile(x, c(.05, .5, .95)))
```

```
      logit gam50  gam75 gam100 gam150 gam200 gam250 gam300
5%  168.1 7.408  7.340  4.714  3.498  2.057  1.178  1.091
50%  173.6 8.553  8.843  5.894  4.310  2.709  1.832  1.488
95%  179.8 9.958 10.501  6.858  5.396  3.851  2.495  2.057
```

```
library(lattice)
poldat <- stack(wold)
bwplot(values~ ind, data= poldat, type=c("l","g"), horizontal= FALSE,
  xlab='Model of GI designation', ylab='Bootstraped F-statistics',
  par.settings = list(box.rectangle=list(col='black'),
    plot.symbol = list(pch='.', cex = 0.1)),
  scales=list(y= list(log= TRUE)),
  panel = function(..., box.ratio) {
    panel.grid(h= -1, v = -11)
    panel.violin(..., col = "lightblue",
      varwidth = FALSE, box.ratio = box.ratio)
    panel.bwplot(..., col='black',
      cex=0.8, pch='|', fill='gray', box.ratio = .1)
    panel.abline(h= log(1.47), col= "red", lty= 3)
    panel.text(2, log(1.55), "F= 1.47: critical value at 5%")})
```

6.6 Specification

results not reported

```
library(sure) ; library(ggplot2) ; library(gridExtra)
var <- c("DEM", "SLOPE", "RAYAT", "EXPO", "LIBCOM", "X", "Y")
plots <- lapply(var, function(.x)
  autoplot(por2, what= "covariate", x= Reg.Old@data[, .x], xlab= .x))
(atp <- autoplot(por2, what= "qq"))
```




Figure 6: Effects of model XX

```
do.call(grid.arrange, c(list(atp), plots))
```

```
restmp <- suroldGAM(gamold$gam300)- gamold$gam300$line
plot(qlogis(1: nrow(SRank)/ nrow(SRank), scale= 1), sort(restmp))
abline(0, 1)
var <- c("DEM", "SLOPE", "RAYAT", "EXPO", "LIBCOM", "X", "Y")
par(mfrow= c(3, 3)) ; for (i in var) pltSURE(restmp, SRank@data[, i], i)
```

6.7 Marginal effects

```
library(effects)
plot(predictorEffects(por2, ~ DEM+ SLOPE+ RAYAT+ EXPO, latent= TRUE,
  xlevels=list(DEM= 200: 500,
    SLOPE= 0: 400/ 10, RAYAT= -60: 30/ 10)))
plot(gamold$gam300, pages= 1, scale= 0)
```

6.8 Commune effects

```
xxx <- data.frame(sapply(gamold, function(x)
  2* plogi(I(x$coeff[ 1: 25]- mean(x$coeff[ 1: 25]))- 1))
www <- data.frame(xxx,
  LIBCOM= substr(names(gamold[[ 1]]$coef[ 1: 25]), 7, 30),
```




Figure 7: Effects of model XX

```

MIN= apply(xxx[ 6: 7], 1, min),
MAX= apply(xxx[ 6: 7], 1, max),
MEAN= apply(xxx[ 6: 7], 1, mean))
segplot(reorder(factor(LIBCOM), MEAN)~ MIN+ MAX, length= 5, draw.bands= T,
data= www[order(www$MEAN), ], center= MEAN, type= "o",
unit = "mm", axis = axis.grid, col.symbol= "black", cex= 1,
xlab= "Min, Mean and Max of Ordinal Superiority Measures")

```

6.9 Dynamic Communes

```

zzz <- merge(ww, www, by= "LIBCOM")
segplot(reorder(factor(LIBCOM), MEAN.x)~ MEAN.y+ MEAN.x, data= zzz,
segments.fun = panel.arrows, length = 2, unit = "mm",
draw.bands= F, axis = axis.grid,
xlab= "Rate of variation for ordinal superiority")

```

7 Counterfactual decomposition

7.1 Decomposition 1936 GIs

```

load("Inter/gamold.Rda") ; source("myFcts.R")
latold <- sapply(gamold, function(x)
rowSums(predict(x, type= 'terms')[, -1]))
decold <- apply(latold, 2, function(x)
c(Signal= var(x), Noise= pi^2/ 3,
jointSignal2(x, vert= "AOCc", dat= SRank@data),
jointNoise2(x, vert= "AOCc", dat= SRank@data),
rankSignal2(x, vert= "AOCc", dat= SRank@data),

```




Figure 8: Effects of model XX




Figure 9: Effects of model XX


```

rankResid2(x, vert= "AOCO", dat= SRank@data),
rankNoise2(x, vert= "AOCO", dat= SRank@data),
comSignal2(x, dat= SRank@data),
comResid2(x, dat= SRank@data), comNoise2(x, dat= SRank@data)))
round(t(t(decold)/ (pi^2/ 3+ decold[1, ]))* 100, 1)

```

	gam50	gam75	gam100	gam150	gam200	gam250	gam300
Signal	95.6	93.1	95.4	98.7	98.1	99.5	99.5
Noise	4.4	6.9	4.6	1.3	1.9	0.5	0.5
Joint Signal	78.7	63.2	55.3	75.2	47.9	75.0	45.1
Joint Noise	16.9	29.9	40.2	23.5	50.3	24.5	54.5
Rank Signal	5.8	18.1	24.1	16.4	20.6	14.9	22.7
Rank Noise	89.8	75.0	71.3	82.4	77.5	84.6	76.8
Rank Residual	72.9	45.1	31.2	58.8	27.3	60.1	22.4
Com Signal	67.5	39.6	29.4	62.3	24.0	62.7	22.6
Com Noise	28.1	53.5	66.0	36.4	74.1	36.8	77.0
Com Residual	16.0	33.3	43.7	20.9	35.3	20.6	43.7

7.2 Alternative GI designations

```

# prdd <- predict(gamod$gam900, type= 'terms')
thsld <- c(-Inf, gamod$gam900$family$getTheta(TRUE), Inf)
ltt0 <- mean(prdd[, 1])+ rowSums(prdd[, -1])-
  (surlGAM(gamod$gam900)- gamod$gam900$line)
ltt1 <- rowSums(prdd)
ltt2 <- mean(prdd[, 1])+ rowSums(prdd[, -1])-
  (surlGAM(gamod$gam800)- gamod$gam800$line)
ltt3 <- mean(prdd[, 1])+ rowSums(prdd[, -1])
Simu <- data.frame(RRank, OLD= RRank$AOCavt, S0= cut(ltt0, thsld),
  SI= cut(ltt1, thsld), SII= cut(ltt2, thsld),
  SIII= cut(ltt3, thsld))
table(Simu$AOCc, Simu$S0) ; table(Simu$AOCc, Simu$SI)
table(Simu$AOCc, Simu$SII) ; table(Simu$AOCc, Simu$SIII)

```

	OLD	CF1	CF2	CF3	CF4	CF5	CF6
Signal	97.1	97.1	97.1	97.1	97.1	97.1	97.1
Noise	2.9	2.9	2.9	2.9	2.9	2.9	2.9
Joint Signal	51.4	80.1	81.2	82.2	79.4	80.0	79.2
Joint Noise	45.8	17.1	15.9	15.0	17.7	17.1	18.0
Rank Signal	38.9	70.7	64.5	73.5	62.2	62.8	62.0
Rank Noise	58.2	26.4	32.6	23.6	34.9	34.3	35.1
Rank Residual	12.5	9.4	16.7	8.7	17.2	17.2	17.2
Com Signal	28.5	28.5	28.5	28.5	28.5	28.5	28.5
Com Noise	68.6	68.6	68.6	68.6	68.6	68.6	68.6
Com Residual	22.9	51.6	52.7	53.7	50.9	51.5	50.7

```

thrldBOUR <- mean(ltt1[RRank$AOCc== 2])
thrldVILL <- mean(ltt1[RRank$AOCc== 3])
thrldPCRU <- mean(ltt1[RRank$AOCc== 4])
Simv <- data.frame(Simu,
  SIV= ifelse(RRank$AOCc< 2, RRank$AOCc,
    ifelse(RRank$AOCc== 2 & ltt< thrldBOUR, 2,
      ifelse(RRank$AOCc== 2 & ltt>= thrldBOUR, 3,
        RRank$AOCc+ 1))),
  SV = ifelse(RRank$AOCc< 3, RRank$AOCc,
    ifelse(RRank$AOCc== 3 & ltt< thrldVILL, 3,
      ifelse(RRank$AOCc== 3 & ltt>= thrldVILL, 4,
        RRank$AOCc+ 1))),
  SVI= ifelse(RRank$AOCc< 4, RRank$AOCc,
    ifelse(RRank$AOCc== 4 & ltt< thrldPCRU, 4,
      ifelse(RRank$AOCc== 4 & ltt>= thrldPCRU, 5,
        RRank$AOCc+ 1))))
table(Simv$AOCc, Simv$SIV)
table(Simv$AOCc, Simv$SV) ; table(Simv$AOCc, Simv$SVI)

```

	1	2	3	4	5	6
1	9759	0	0	0	0	0
2	0	8931	6577	0	0	0
3	0	0	0	24151	0	0
4	0	0	0	0	8577	0
5	0	0	0	0	0	1906

	1	2	3	4	5	6
1	9759	0	0	0	0	0
2	0	15508	0	0	0	0
3	0	0	13275	10876	0	0
4	0	0	0	0	8577	0
5	0	0	0	0	0	1906

	1	2	3	4	5	6
1	9759	0	0	0	0	0
2	0	15508	0	0	0	0
3	0	0	24151	0	0	0
4	0	0	0	4970	3607	0
5	0	0	0	0	0	1906

```

decf <- sapply(names(Simv)[ 100: 107], function(x)
  c(Signal= var(rowSums(prdd[, -1])), Noise= pi^2/ 3,
    jointSignal2(rowSums(prdd[, -1]), vert= x, dat= Simv),
    jointNoise2(rowSums(prdd[, -1]), vert= x, dat= Simv),
    rankSignal2(rowSums(prdd[, -1]), vert= x, dat= Simv),
    rankResid2(rowSums(prdd[, -1]), vert= x, dat= Simv),
    comSignal2(rowSums(prdd[, -1]), dat= Simv),
    comResid2(rowSums(prdd[, -1]), vert= x, dat= Simv),
    comNoise2(rowSums(prdd[, -1]), dat= Simv)))

```

```
(tabpap <- round(t(t(decf)/ (pi^2/ 3+ decf[1, ]))* 100, 1))
```

	OLD	S0	SI	SII	SIII	SIV	SV	SVI
Signal	97.6	97.6	97.6	97.6	97.6	97.6	97.6	97.6
Noise	2.4	2.4	2.4	2.4	2.4	2.4	2.4	2.4
Joint Signal	43.3	81.1	80.7	81.2	82.8	79.2	79.6	79.0
Joint Noise	54.3	16.4	16.8	16.4	14.8	18.4	18.0	18.6
Rank Signal	17.8	70.7	59.8	70.7	73.1	58.0	58.5	57.9
Rank Residual	25.4	10.4	21.0	10.5	9.7	21.1	21.0	21.1
Rank Noise	79.7	26.8	37.8	26.8	24.5	39.5	39.0	39.7
Com Signal	29.1	29.1	29.1	29.1	29.1	29.1	29.1	29.1
Com Residual	14.2	52.1	51.7	52.1	53.7	50.1	50.5	49.9
Com Noise	68.5	68.5	68.5	68.5	68.5	68.5	68.5	68.5

8 Session information

```
sessionInfo()
```

```
R version 3.5.3 (2019-03-11)
```

```
Platform: x86_64-pc-linux-gnu (64-bit)
```

```
Running under: Ubuntu 18.04.2 LTS
```

```
Matrix products: default
```

```
BLAS: /usr/lib/x86_64-linux-gnu/blas/libblas.so.3.7.1
```

```
LAPACK: /usr/lib/x86_64-linux-gnu/lapack/liblapack.so.3.7.1
```

```
locale:
```

```
[1] LC_CTYPE=fr_FR.UTF-8      LC_NUMERIC=C
[3] LC_TIME=fr_FR.UTF-8      LC_COLLATE=fr_FR.UTF-8
[5] LC_MONETARY=fr_FR.UTF-8  LC_MESSAGES=fr_FR.UTF-8
[7] LC_PAPER=fr_FR.UTF-8     LC_NAME=C
[9] LC_ADDRESS=C             LC_TELEPHONE=C
[11] LC_MEASUREMENT=fr_FR.UTF-8 LC_IDENTIFICATION=C
```

```
attached base packages:
```

```
[1] stats4      stats      graphics  grDevices  utils      datasets
[7] methods     base
```

```
other attached packages:
```

```
[1] gridExtra_2.3      xtable_1.8-3      ggrepel_0.8.0
[4] ggplot2_3.1.0      plyr_1.8.4        latticeExtra_0.6-28
[7] RColorBrewer_1.1-2 effects_4.0-3      lattice_0.20-38
[10] truncdist_1.0-2    evd_2.3-3         sure_0.2.0
[13] sandwich_2.5-0     lmtest_0.9-36     zoo_1.8-4
[16] mgcv_1.8-28        nlme_3.1-137      car_3.0-2
[19] carData_3.0-1      MASS_7.3-51.1     sp_1.3-1
```

```
loaded via a namespace (and not attached):
```

```
[1] Rcpp_1.0.0          assertthat_0.2.0  R6_2.3.0
[4] cellranger_1.1.0    survey_3.33-2     pillar_1.3.0
[7] rlang_0.3.0.1       lazyeval_0.2.1    curl_3.2
[10] readxl_1.1.0        minqa_1.2.4       data.table_1.11.4
[13] nloptr_1.0.4        Matrix_1.2-17     labeling_0.3
[16] splines_3.5.3       rgdal_1.3-6       lme4_1.1-18-1
[19] foreign_0.8-71      munsell_0.5.0     compiler_3.5.3
[22] pkgconfig_2.0.2     nnet_7.3-12       tidyselect_0.2.5
[25] tibble_1.4.2        rio_0.5.10        crayon_1.3.4
[28] dplyr_0.7.8         withr_2.1.2       grid_3.5.3
[31] gtable_0.2.0        magrittr_1.5      scales_1.0.0
[34] zip_1.0.0           bindrcpp_0.2.2    openxlsx_4.1.0
```

```
[37] tools_3.5.3      forcats_0.3.0    glue_1.3.0
[40] purrr_0.2.5      hms_0.4.2        abind_1.4-5
[43] survival_2.43-3  colorspace_1.3-2 bindr_0.1.1
[46] haven_1.1.2
```

A Functions

A.1 Surrogate

```
pltSURE <- function(resid, xvar, lab){
  plot(xvar, resid, xlab= lab, main= paste("Surrogate Analysis", lab))
  abline(h= 0, col= "red", lty= 3, lwd= 2)
  lines(smooth.spline(resid ~ xvar), lwd= 3, col= "blue")
}
```

1. function

```
sur1OLR <- function(mod, newd= NULL){
  if (mod$method!= "logistic") stop("Logistic required")
  gg <- as.numeric(mod$zeta)
  if (is.null(newd)){
    g1 <- unname(as.integer(model.response(model.frame(mod))))
    g6 <- mod$lp
  } else {
    g1 <- as.integer(newd[, "AOCc"])
    g6 <- gg[ 1]-qlogis(predict(mod, newdata= newd, type= 'probs')[, 1])
  }
  nn <- length(g1)
  suls <- sapply(g1, switch,
    "1"= c(-Inf , gg[ 1]), "2"= c(gg[ 1], gg[ 2]),
    "3"= c(gg[ 2], gg[ 3]), "4"= c(gg[ 3], gg[ 4]),
    "5"= c(gg[ 4], Inf ))
  sls <- data.frame(unlist(t(suls)))
  rtrunc(nn, spec= "logis", a= sls[, 1], b= sls[, 2],
    location= g6, scale= 1)
}
```

2. test

```
summary(por1)
```

```
library(sure)
library(truncdist)
surpOLR <- function(mod, newd= NULL){
  if (mod$method!= "probit") stop("Probit required")
  gg <- as.numeric(mod$zeta)
  if (is.null(newd)){
    g1 <- unname(as.integer(model.response(model.frame(mod))))
```

```

      g6 <- mod$lp
    } else {
      g1 <- as.integer(newd[, "AOCc"])
      g6 <- gg[ 1]-qnorm(predict(mod, newdata= newd, type= 'probs')[, 1])
    }
    nn <- length(g1)
    suls <- sapply(g1, switch,
      "1"= c(-Inf , gg[ 1]), "2"= c(gg[ 1], gg[ 2]),
      "3"= c(gg[ 2], gg[ 3]), "4"= c(gg[ 3], gg[ 4]),
      "5"= c(gg[ 4], Inf ))
    sls <- data.frame(unlist(t(suls)))
    rtrunc(nn, spec= "norm", a= sls[, 1], b= sls[, 2],
      mean= g6, sd= sqrt(1+ var(g6)))
  }

```

```

kk <- surrogate(por1)+ por1$zeta[ 1]
hh <- surpOLR(por1)
plot(kk, hh)
abline(h= gg)
abline(v= gg)
abline(0, 1, col= "blue")

```

```

ll <- surrogate(por1)+ gg[ 1]
plot(kk, ll)
abline(h= gg)
abline(v= gg)
abline(0, 1, col= "blue")

```

```

oo <- surpOLR(por1, newd= RegRank)
plot(oo, ll)
abline(h= gg)
abline(v= gg)
abline(0, 1, col= "blue")

```

```

surlGAM <- function(mod, newd= NULL){
  gg <- as.numeric(mod$family$getTheta(TRUE))
  if (is.null(newd)){
    g1 <- as.integer(mod$y)
    g6 <- mod$linear.predictors
  } else {
    g1 <- as.integer(newd[, "AOCc"])
    g6 <- predict(mod, newdata= newd)
  }
  nn <- length(g1)
  suls <- sapply(g1, switch,
    "1"= c(-Inf , gg[ 1]), "2"= c(gg[ 1], gg[ 2]),
    "3"= c(gg[ 2], gg[ 3]), "4"= c(gg[ 3], gg[ 4]),
    "5"= c(gg[ 4], Inf ))
  sls <- data.frame(unlist(t(suls)))
  rtrunc(nn, spec= "logis", a= sls[, 1], b= sls[, 2], location= g6)
}
surolGAM <- function(mod, newd= NULL){
  gg <- as.numeric(mod$family$getTheta(TRUE))
  if (is.null(newd)){
    g1 <- as.integer(mod$y)

```

```

      g6 <- mod$linear.predictors
    } else {
      g1 <- as.integer(newd[, "AOCavt"])
      g6 <- predict(mod, newdata= newd)
    }
    nn <- length(g1)
    suls <- sapply(g1, switch,
      "1"= c(-Inf , gg[ 1]), "2"= c(gg[ 1], gg[ 2]),
      "3"= c(gg[ 2], Inf ))
    sls <- data.frame(unlist(t(suls)))
    rtrunc(nn, spec= "logis", a= sls[, 1], b= sls[, 2], location= g6)
  }

```

```

fit.ogam <- gam(AOCc~ poly(DEM, 2)+ poly(SLOPE, 2)
  + poly(RAYAT, 2)+ poly(ASPECT, 2)+ poly(PERMEABILITY, 2)
  , family= ocat(R= 5), data= RegRank)
fit.oglm <- polr(factor(AOCc)~ poly(DEM, 2)+ poly(SLOPE, 2)
  + poly(RAYAT, 2)+ poly(ASPECT, 2)+ poly(PERMEABILITY, 2)
  , method= "logistic", data= RegRank)
plot(fit.ogam$line, fit.oglm$lp-fit.oglm$zeta[1]- 1)
abline(0, 1)

hh <- surrogate(fit.oglm)+ fit.oglm$zeta[ 1]+ 1
gg <- surlGAM(fit.ogam)
plot(gg, hh)
abline(v= fit.ogam$family$getTheta(TRUE))
abline(h= fit.oglm$zeta+ 1)
abline(0, 1, col= "blue")
kk <- surlGAM(fit.ogam, newd= RegRank)
plot(kk, hh)
abline(v= fit.ogam$family$getTheta(TRUE))
abline(h= fit.oglm$zeta+ 1)
abline(0, 1, col= "blue")

```

3. function

```

surlGLM <- function(mod, newd= NULL){
  if (mod$family$link!= "logit") stop("Logit required")
  if (is.null(newd)){
    g1 <- as.integer(mod$y)
    g6 <- mod$linear.predictors
  } else {
    g1 <- as.integer(newd[, "AOCc"])
    g6 <- predict(mod, newdata= newd, type= "link")
  }
  nn <- length(g1)
  ifelse(g1== 0,
    rtrunc(nn, spec= "logis", a= -Inf, b= 0, location= g6,
      scale= 1),
    rtrunc(nn, spec= "logis", a= 0, b= Inf, location= g6,
      scale= 1))
}

```

4. test

```

surpGLM <- function(mod, newd= NULL){
  if (mod$family$link!= "probit") stop("Probit required")
  if (is.null(newd)){
    g1 <- as.integer(mod$y)
    g6 <- mod$linear.predictors
  } else {
    g1 <- as.integer(newd[, "AOCc"])
    g6 <- predict(mod, newdata= newd, type= "link")
  }
  nn <- length(g1)
  ifelse(g1== 0, rtrunc(nn, spec= "norm", a= -Inf, b= 0, mean= g6),
    rtrunc(nn, spec= "norm", a= 0, b= Inf, mean= g6))
}

```

A.2 Decomposition

```

jointNoise <- function(latent, DAT= RegRank){
  jN <- 0
  for (i in 1: 5){
    for (j in levels(DAT$LIBCOM)){
      tmp <- latent[DAT$AOCc== i & DAT$LIBCOM== j]
      if (length(tmp)> 0)
        jN <- jN+ var(tmp)* mean(DAT$AOCc== i & DAT$LIBCOM== j)
    }
  }
  c("Joint Noise"= jN)
}

jointNoise2 <- function(latent, vert= "AOCc", horiz= "LIBCOM", dat= RRank){
  jN <- 0
  for (i in levels(factor(dat[, vert]))){
    for (j in levels(factor(dat[, horiz]))){
      tmp <- latent[dat[, vert]== i & dat[, horiz]== j]
      if (length(tmp)> 1)
        jN <- jN+
          var(tmp)* mean(dat[, vert]== i & dat[, horiz]== j)
    }
  }
  c("Joint Noise"= jN)
}

```

```

jointSignal <- function(latent, DAT= RegRank){
  jS <- rep(0, nrow(DAT))
  for (i in 1: 5){
    for (j in levels(DAT$LIBCOM)){
      jS[DAT$AOCc== i & DAT$LIBCOM== j] <-
        mean(latent[DAT$AOCc== i & DAT$LIBCOM== j])
    }
  }
  c("Joint Signal"= var(jS))
}

jointSignal2 <- function(latent, vert="AOCc", horiz="LIBCOM", dat= RRank){
  jS <- rep(0, nrow(dat))

```



```

    for (i in levels(factor(dat[, vert]))) {
      for (j in levels(factor(dat[, horiz]))) {
        ind <- dat[, vert] == i & dat[, horiz] == j
        jS[ind] <- mean(latent[ind])
      }
    }
  }
  c("Joint Signal" = var(jS))
}

```

```

rankSignal <- function(latent, DAT= RegRank){
  rS <- var(ifelse(DAT$AOCc== 1, mean(latent[DAT$AOCc== 1]),
    ifelse(DAT$AOCc== 2, mean(latent[DAT$AOCc== 2]),
    ifelse(DAT$AOCc== 3, mean(latent[DAT$AOCc== 3]),
    ifelse(DAT$AOCc== 4, mean(latent[DAT$AOCc== 4]),
    mean(latent[DAT$AOCc== 5])))))
  c("Rank Signal" = rS)
}
rankSignal2 <- function(latent, vert= "AOCc", horiz= "LIBCOM", dat= RRank){
  rS <- rep(NA, nrow(dat))
  for (i in levels(factor(dat[, vert]))) {
    rS[ dat[, vert] == i ] <- mean(latent[dat[, vert] == i])
  }
  c("Rank Signal" = var(rS))
}

```

```

rankNoise <- function(latent, DAT= RegRank){
  rN <- var(latent[DAT$AOCc== 1]) * mean(DAT$AOCc== 1) +
    var(latent[DAT$AOCc== 2]) * mean(DAT$AOCc== 2) +
    var(latent[DAT$AOCc== 3]) * mean(DAT$AOCc== 3) +
    var(latent[DAT$AOCc== 4]) * mean(DAT$AOCc== 4) +
    var(latent[DAT$AOCc== 5]) * mean(DAT$AOCc== 5)
  c("Rank Noise" = rN)
}
rankNoise2 <- function(latent, vert= "AOCc", dat= RRank){
  rN <- 0
  for (i in levels(factor(dat[, vert]))) {
    rN <- rN + var(latent[dat[, vert] == i]) * mean(dat[, vert] == i)
  }
  c("Rank Noise" = rN)
}

```

```

rankResid <- function(latent, DAT= RegRank){
  sig <- rep(0, nrow(DAT))
  for (i in 1: 5){
    for (j in levels(DAT$LIBCOM)){
      sig[DAT$AOCc== i & DAT$LIBCOM== j] <-
        mean(latent[DAT$AOCc== i & DAT$LIBCOM== j])
    }
  }
  rR <- (var(sig[DAT$AOCc== 1]) * mean(DAT$AOCc== 1) +
    var(sig[DAT$AOCc== 2]) * mean(DAT$AOCc== 2) +
    var(sig[DAT$AOCc== 3]) * mean(DAT$AOCc== 3) +
    var(sig[DAT$AOCc== 4]) * mean(DAT$AOCc== 4) +

```

```

        var(sig[DAT$AOCc== 5])* mean(DAT$AOCc== 5))
c("Rank Residual"= rR)
}
rankResid2 <- function(latent, vert= "AOCc", horiz= "LIBCOM", dat= RRank){
  sig <- rep(0, nrow(dat)) ; rR <- 0
  for (i in levels(factor(dat[, vert]))){
    for (j in levels(factor(dat[, horiz]))){
      ind <- dat[, vert]== i & dat[, horiz]== j
      sig[ind] <- mean(latent[ind])
    }
  }
  for (i in levels(factor(dat[, vert]))){
    rR <- rR+ var(sig[dat[, vert]== i])* mean(dat[, vert]== i)
  }
  c("Rank Residual"= rR)
}

```

```

comSignal <- function(latent, DAT= RegRank){
  cS <- rep(0, nrow(DAT))
  for (j in levels(DAT$LIBCOM)){
    cS[ DAT$LIBCOM== j] <- mean(latent[DAT$LIBCOM== j])
  }
  c("Com Signal"= var(cS))
}
comSignal2 <- function(latent, horiz= "LIBCOM", dat= RRank){
  cS <- rep(0, nrow(dat))
  for (j in levels(factor(dat[, "LIBCOM"]))) {
    cS[ dat[, "LIBCOM"]== j] <- mean(latent[dat[, "LIBCOM"]== j])
  }
  c("Com Signal"= var(cS))
}

```

```

comNoise <- function(latent, DAT= RegRank){
  cN <- 0
  for (j in levels(DAT$LIBCOM)){
    cN <- cN+ (var(latent[DAT$LIBCOM== j])* mean(DAT$LIBCOM== j))
  }
  c("Com Noise"= cN)
}
comNoise2 <- function(latent, horiz= "LIBCOM", dat= RRank){
  cN <- 0
  for (j in levels(factor(dat[, horiz]))){
    cN <- cN+ (var(latent[dat[, horiz]== j])* mean(dat[, horiz]== j))
  }
  c("Com Noise"= cN)
}

```

```

comResid <- function(latent, DAT= RegRank){
  sig <- rep(0, nrow(DAT))
  for (i in 1: 5){
    for (j in levels(DAT$LIBCOM)){
      sig[DAT$AOCc== i & DAT$LIBCOM== j] <-
        mean(latent[DAT$AOCc== i & DAT$LIBCOM== j])
    }
  }
}

```

```

    }
  }
  cR <- 0
  for (j in levels(DAT$LIBCOM)){
    cR <- cR+ var(sig[DAT$LIBCOM== j])* mean(DAT$LIBCOM== j)
  }
  c("Com Residual"= cR)
}
comResid2 <- function(latent, vert= "AOCc", horiz= "LIBCOM", dat= RRank){
  sig <- rep(0, nrow(dat))
  for (i in levels(factor(dat[, vert]))){
    for (j in levels(factor(dat[, horiz]))){
      sig[dat[, vert]== i & dat[, horiz]== j] <-
        mean(latent[dat[, vert]== i & dat[, horiz]== j])
    }
  }
  cR <- 0
  for (j in levels(factor(dat[, horiz]))){
    cR <- cR+ var(sig[dat[, horiz]== j])* mean(dat[, horiz]== j)
  }
  c("Com Residual"= cR)
}

```
