Interpretable Discovery from Unstructured Data: A High-Dimensional Approach

Jacob Carlson
Harvard University*

First Draft: October 2025
This Draft: October 2026

Please click here for the latest version

Abstract

We propose an automatic, general-purpose framework for making discoveries from unstructured data (e.g., text data from open-ended surveys of economic beliefs). The framework leverages recent methods from the literature on AI interpretability to transform unstructured datasets into high-dimensional, structured datasets of interpretable concept measurements; specifies concept-by-concept parameters and null hypotheses based on this transformed dataset; tests these hypotheses using algorithms validated by new results in high-dimensional multiple testing, producing a selected set ("discoveries"); and both generates and evaluates human-interpretable natural language descriptions of these discoveries. The proposed framework has few researcher degrees of freedom, is robust to data snooping, mitigates under-exploration, and facilitates fast and inexpensive sensitivity analysis and replication. We revisit applications to recent descriptive and causal analyses of unstructured data in empirical economics, and find this framework is able to automatically replicate existing discoveries, add nuance to others, and make entirely new discoveries as well.

1 Introduction

Unstructured data provide opportunities to measure economic phenomena that would be otherwise unmeasurable. In some settings, unstructured data enable high quality, scalable

*Email: jacob_carlson@g.harvard.edu. I am grateful to Isaiah Andrews, Melissa Dell, Neil Shephard, Rahul Singh, Elie Tamer, Davide Viviano, and participants in the Harvard econometrics workshop for their feedback and suggestions. I thank Harvey Barnhard, Andrew Kao, and Karthik Tadepalli for early feedback and encouragement. There are no relevant financial relationships or other potential conflicts of interest to disclose that relate to the research described in this paper. A previous version of this paper was circulated under the title "Making Interpretable Discoveries from Unstructured Data: A High-Dimensional Multiple Hypothesis Testing Approach." I thank Claude for research assistance in literature review, proof checking, and code generation.

measurement of an economic feature that theory or prior empirical research suggested was important. For example, satellite data may be used for high-frequency measurement of changes in local economic activity [Khachiyan et al., 2022]. In other settings, unstructured data enable researchers to measure *novel* features of economic interest—previously uncaptured by both theory and structured data collection—which can serve as inputs to downstream econometric analysis and facilitate new economic *discoveries*.[1] For example, consider the following three settings, motivated by real applications in recent empirical economics research.

Example 1 (Information treatment RCT, e.g., Bursztyn et al. [2023], Andre et al. [2026])**.** A researcher is interested in running a randomized controlled trial (RCT) with an information treatment. A key outcome of the experiment is the participant's reaction to the information treatment, and the researcher would like to discover any systematic differences in reactions across the treatment and control groups. The full space of economically meaningful reactions is unknown to the researcher ex-ante. As such, for all participants, the researcher collects text responses to open-ended questions eliciting reactions to the experimental intervention, and is interested in learning any relevant causal effects on the presence of concepts surfaced in these text responses. △

Example 2 (Descriptive survey analysis, e.g., Andre et al. [2022], Stantcheva [2024])**.** A researcher is interested in understanding the attitudes of some population of interest towards some particular (economic) policy. To learn about diverse population attitudes without priming respondents to discuss particular topics, the researcher runs a survey on a representative sample from the population of interest that asks many open-ended questions about attitudes and beliefs, to which survey respondents reply freely in text. The researcher is interested in describing any frequently discussed concepts that are surfaced from this open-ended survey, as well as how concept frequencies differ across various subgroups in the sample. △

Example 3 (Labor RCT on human-AI productivity, e.g., Noy and Zhang [2023])**.** A researcher is interested in understanding the causal effects of AI adoption on worker productivity and creativity. As such, the researcher runs an experiment in which participants are asked to complete a short professional writing task, with half of participants randomly receiving access to a frontier LLM (the treatment group) and the other half receiving no aid (the control group). The researcher is interested in discovering any interpretable features of the writing that differ systematically across treatment and control. △

To address these examples—among many others—this paper proposes an automatic, general-purpose framework. At a high level, the framework consists of transforming an unstructured dataset into a high-dimensional, structured dataset of interpretable concept measurements and then analyzing this transformed dataset using new methods for multiple

[1] For some other recent examples of analysis of unstructured data in economics, consider: speech recordings from FOMC meetings used to better understand monetary policy [Gorodnichenko et al., 2023]; videos of start-up pitches used to study entrepreneurship and investment [Hu and Ma, 2025]; mug shots used to study judicial decisionmaking [Ludwig and Mullainathan, 2024]; visual art and written narratives used to infer long-run living standards [Gorin et al., 2025, Lagakos et al., 2025]; and qualitative interviews used to better understand the impacts of RCT treatments [Bergman et al., 2024, Krause et al., 2025, Ahmadi et al., 2026].




Figure 1: The proposed framework for discovery from unstructured data.

hypothesis testing. More specifically, the framework can be broken down into the following four steps, which are also depicted in the schematic in Figure 1.

1. Creating concept embeddings: each unstructured data point is mapped to a "concept embedding," which is a binary vector.[2] Each element of the vector is intended as an indicator for the presence of a particular human-interpretable feature—or, informally, a "concept"—expressed in the unstructured data point. Though many choices of concept embedding are compatible with the framework, a default recommendation is to use a pretrained *sparse dictionary learning* model (newly popular in the AI interpretability literature) as a concept embedding method. By construction, concept embedding vectors are *high-dimensional*, aiming to catalog a vast number of human-interpretable concepts and thus broaden the scope for making novel, economically meaningful discoveries later on.

Example 1 (Continued). Each experimental participant's post-treatment text response is passed through an LLM equipped with pretrained sparse autoencoder (SAE), a popular implementation of a sparse dictionary learning model [Bricken et al., 2023].[3] The SAE's feature activations are pooled and thresholded at zero to serve as a concept embedding. There is one concept embedding of each text response (and one text response per experimental participant), each of which is of dimension $p \approx 10^4$. The set of concepts measured by this

[2]The name "concept embedding" is chosen to be consistent with other parts of the CS and AI interpretability literatures that make use of similar objects, e.g., Bhalla et al. [2024], Jiang et al. [2025].

[3]See, e.g., the blogpost https://www.goodfire.com/blog/a-practical-guide-to-saes for a more thorough introduction.

SAE-derived concept embedding approximates the huge set of interpretable text features that the LLM is capable of "thinking about" upon reading a text. For example, concept number 1 in the concept embedding may indicate the presence of exclamation points, concept number 2 may indicate discussion of politics, concept number 3 may signal discussion of health issues, and so on. △

2. Specifying concept-level parameters and hypotheses: the researcher, using their new dataset of concept embeddings, specifies p concept-specific hypothesis tests based on p concept-level parameters of interest—one for each concept cataloged in the concept embedding. The researcher has great flexibility in designing meaningful concept-level parameters, hypotheses, and test statistics at this stage of the framework, which may employ data sources beyond the concept embeddings themselves (e.g., covariates from structured data sources).

Example 1 (Continued). The researcher computes a difference in means across treatment and control groups for each *concept indicator* (a binary entry in the concept embedding) to test a total of p null hypotheses of zero average treatment effect (ATE) on the probability of a given concept appearing in a text response. The p parameters of interest are the p concept-by-concept ATEs. △

3. High-dimensional multiple testing: all p concept-specific hypotheses are tested using statistical procedures with high-dimensional, generalized familywise error guarantees validated by novel results in high-dimensional multiple hypothesis testing and central limit theory. In particular, these results prove that the algorithms of Romano and Wolf [2007] for controlling the k familywise error rate (k-FWER)—the probability of making k or more false rejections—are valid in high-dimensions under mild regularity conditions. Control of the k-FWER for $k > 1$ is less conservative than simple FWER control—control over the probability of making *any* false rejections[4]—leading to more powerful tests. Moreover, the researcher may invert these tests to form *generalized simultaneous confidence intervals*: the probability that k or more parameters fall outside the simultaneous random intervals is less than or equal to a desired level α.

Example 1 (Continued). An algorithm based on the procedures of Romano and Wolf [2007] is deployed to simultaneously test each of the p null hypotheses of no average treatment effect, guaranteeing k-FWER control at level α (in large samples) for a researcher chosen value of k, even though $p \gg n$ (inference is "high-dimensional"). Critical values produced by the algorithm may also be used to form generalized simultaneous confidence intervals for the difference-in-means point estimates of the p concept-by-concept ATEs. △

4. Local automatic interpretation: the output of the framework so far is a selected set of rejected, concept-level null hypotheses (as well as corresponding generalized simultaneous confidence intervals and point estimates), a.k.a., "discoveries." However—much like the "topics" learned by LDA models [Blei et al., 2003]—the "concepts" encoded by sparse dictionary learning methods do not come with natural language descriptions at first. That is, we know, e.g., the first entry of the concept embedding encodes a human-interpretable concept, and that we rejected the null hypothesis associated with it, but we do not yet

[4]Note that FWER is equivalent to k-FWER when $k = 1$.

have an English description for what that concept is. As such, in the final stage of the framework, the researcher generates natural language descriptions of the concepts in the concept embedding using a variant of a popular *automatic interpretation* (or "autointerp") method that is tailored to the unstructured data distribution being explored.[5] A new statistical formalization of a workhorse autointerp evaluation method from Paulo et al. [2024] is used to infer the quality of these "local" autointerp descriptions for the data distribution being analyzed.

Example 1 (Continued). The researcher now has in hand some subset of the p null hypotheses that have been rejected: a set of indices associated with particular elements of the concept embeddings. In order to provide an English language description for each of the selected concepts, a dedicated "explainer LLM" (which may be closed- or open-source) reads examples of texts in the researcher's dataset for which a given feature is (highly) present and generates an English description for what concept is encoded. The credibility of this LLM-derived description of the concept is then evaluated with a specially designed classification task on a held-out evaluation sample of the researcher's unstructured dataset. △

The final output of the proposed framework is a set of concept-level discoveries (rejections of nulls) that come with generalized familywise error rate guarantees (or, point estimates for associated parameters of interest and generalized simultaneous confidence intervals); natural language descriptions of those discoveries; and scores measuring the quality of those descriptions.

Example 1 (Continued). The researcher discovers that the null of no average treatment effect is rejected for concepts indexed $\{2, 101, 5030, ...\}$. Concept 2 is described by an explainer LLM as activating on "mentions of politics" and this description is estimated as having a high "quality" score, i.e., the information treatment credibly causes increased discussion of politics; and so on. △

The proposed framework for discovery has several distinct scientific benefits. Firstly, the proposed framework is fully *automatic* in execution, requiring no "human-in-the-loop" to guide discovery. As such, it has very few *researcher degrees of freedom* and facilitates inexpensive[6] and practical *replication and sensitivity analysis*.[7] This stands in contrast to conventional approaches for discovery from unstructured economic data (including both "hand-coding" approaches [Haaland et al., 2024] and more modern "hypothesis generation"

[5]Many pretrained sparse dictionary learning models come with "off-the-shelf" feature descriptions, but they are usually of poor quality when transported to DGPs the SAE was not trained on, and thus benefit from refinement based on information in the dataset of interest. This is discussed further in Section 3.4.

[6]All empirical examples in this paper were computed on Google Colab notebooks using a single A100 GPU, access to which only costs $10 per month (and is free for students and academic faculty), and takes approximately one hour to run using this hardware.

[7]The few choices a researcher must make in the proposed framework, such as a choice of concept embedding, can also easily be preregistered, further hampering the possibility that a researcher applies this framework with many different models to select on favorable results. Even without preregistration, cherry-picking across sparse dictionary learning models for the purposes of reverse engineering a desired result is unlikely to succeed given that, e.g., SAE features tend to exhibit some degree of universality across architectures (c.f., Wang et al. [2025])—another reason we advocate their default adoption as concept embeddings.

approaches [Ludwig and Mullainathan, 2024]), which typically require researcher discretion and intervention over which measurements to take (hand-coding) or test (hypothesis generation). Such researcher degrees of freedom, in turn, open up room for cherry-picking "desirable" features to measure and/or test; create opportunities for conscious or unconscious data snooping (breaking the "firewall" of statistically independent generation and testing [Mullainathan and Spiess, 2017]); and make reproducibility and sensitivity analysis challenging (or infeasible, when discretionary choices are never documented or formalized). As new advances in AI tools (e.g., AI interviewers [Geiecke and Jaravel, 2024]) make it easier than ever for researchers to collect unstructured datasets, controlling researcher degrees of freedom and reproducibility in econometric methods for analyzing unstructured data may only become more important.

Secondly, the proposed framework suggests methods for *high-dimensional* measurement and testing. This also stands in contrast to conventional approaches to discovery in economics, which usually artificially delimit the scope of interpretable measurements to take or hypotheses to test, leading to *under-exploration* of the unstructured data and "incompleteness" of economic insights or explanations [Fudenberg et al., 2022, Modarressi et al., 2025]. That is, by keeping measurement and testing high-dimensional, the proposed framework is better able to help researchers see past the "streetlight" of their own economic intuitions for what might be important to measure and test with their unstructured datasets, broadening the possibilities for making truly surprising discoveries.[8] The ability to take many interesting and interpretable measurements and test them all with meaningful power under a generalized Type I error guarantee—even with access to only a small dataset of several hundred observations—is a direct result of the contributions made within this framework.

More specifically, the proposed framework is supported by distinct contributions to econometric theory, computational economics, and AI interpretability, which themselves may be of independent interest, including:

1. Extensions of two frontier econometric toolkits—extending the high-dimensional "many approximate means" framework of Belloni et al. [2018] to the study of the k-th largest coordinate of sums of independent random vectors, and extending the application of the k-FWER controlling procedures of Romano and Wolf [2007] to the high-dimensional setting.

2. A new approach to (and software implementation for) doing *high-dimensional* hypothesis generation with *small* datasets, which leverages pretrained sparse dictionary learning models of LLM residual streams and a "local" automatic interpretation procedure, complementing frameworks such as Movva et al. [2025].

3. A new statistical inference-based formalization of a popular framework for evaluating automatically generated SAE feature interpretations from Paulo et al. [2024], and associated estimation and inference results.

The remainder of this paper is structured as follows: Section 2 discusses related literature; Section 3 describes the framework in detail; Section 4 applies the framework to three recent

[8]The "streetlight effect" describes the cognitive bias that occurs when researchers only think to measure that which is easiest or most obvious to measure: idiomatically speaking, the researcher is "only searching for their lost keys where the light is shining." The same problem is sometimes cast as failing to measure or discover important "unknown unknowns."

papers making use of unstructured data for discovery [Andre et al., 2026, Bursztyn et al., 2023, Noy and Zhang, 2023]; and Section 5 concludes.

2 Related Literature

The framework proposed in this paper is related to recent works from literatures spanning economics, statistics, and computer science.

Econometric methods for unstructured data. Motivated by the capabilities of modern AI/ML methods for extracting structure from unstructured economic data (see, e.g., Mullainathan and Spiess [2017], Gentzkow et al. [2019a], Ash and Hansen [2023], Dell [2025]), new econometric and statistical frameworks have been developed to facilitate principled statistical inference on low-dimensional features (predictions) learned from unstructured datasets under supervision, e.g., Angelopoulos et al. [2023], Ludwig et al. [2024], Carlson and Dell [2025], Rambachan et al. [2024]. This most recent wave of econometric literature emphasizes nonparametric frameworks compatible with black-box AI models and centers debiasing methods, as opposed to model-based approaches, e.g., Gentzkow et al. [2019b], Battaglia et al. [2024]. Though the framework presented in this paper is similarly concerned with rigorous inference on unstructured data without making parametric assumptions, its goal is primarily to pursue high-dimensional inference on machine learned features to facilitate unsupervised discovery, as opposed to pursuing low-dimensional inference on known features of interest measured with AI predictions.

The proposed framework is most similar to existing works such as Ludwig et al. [2017], Modarressi et al. [2025], both of which provide formal econometric frameworks for discovery from high-dimensional economic data. Both of these works focus specifically on causal inference in RCTs, unlike the proposed framework, which generally treats any inference question that can be posed as a hypothesis test (including causal inference based on RCT data). Both Ludwig et al. [2017] and Modarressi et al. [2025] employ the intuition of a "reverse regression" to formally test whether a distribution of (high-dimensional) outcomes is the same across treatment and control groups as a method for discovery. However, both papers note that such a coarse test is often insufficient for developing scientific insight into the causal effects of treatment, motivating methods for probing *what* changed across the outcome distributions. Modarressi et al. [2025] specifically explores this idea for (unstructured) text data, suggesting a semi-automated framework based on a human-LLM hybrid pipeline that hypothesizes a low-dimensional set of "causal themes" that differ across treatment and control and then scores texts per these themes to evaluate ATEs in a held-out sample.

High-dimensional multiple testing. There is an extensive literature on multiple hypothesis testing (or "selective inference" more broadly) in statistics, biostatistics, and economics (see, e.g., Romano et al. [2010] for a review in econometrics). The methods in this literature span asymptotic and finite sample valid frameworks, and low- and high-dimensional settings. In particular, for the problem considered in this paper, the literature on asymptotically valid, high-dimensional selective inference is most relevant, as such methods permit making very few assumptions about the data (c.f., assuming independence or a known flavor of

dependence [Benjamini and Hochberg, 1995, Fithian and Lei, 2022]); readily incorporate resampling methods that improve power (relative to guarding against worst-case dependence, c.f., Bonferroni corrections or the method of Benjamini and Yekutieli [2001]); and do not prescribe particular hypothesis tests of interest or make assumptions about distributions of individual random variables (c.f., the literature on "knockoffs" [Barber and Candès, 2015, Candès et al., 2018, Barber and Candès, 2019, Janson and Su, 2016]).

The new results for high-dimensional central limit theory and multiple hypothesis testing appearing in this paper are derived by combining and extending recent work on high-dimensional central limit theory and Gaussian multiplier bootstraps for order statistics [Belloni et al., 2018, Chernozhuokov et al., 2022, Ding et al., 2025]. The formal results on high-dimensional central limit theory in this paper are best viewed as extensions of some core results of the "many approximate means" framework of Belloni et al. [2018], moving the framework from the study of the maximal order statistic to the study of the *largest* order statistics by leveraging new results from a recent high-dimensional probability literature [Ding et al., 2025, Feng, 2026].

These high-dimensional CLTs in turn support new high-dimensional ($p \gg n$) analysis of the k-FWER controlling step-down procedures of Romano and Wolf [2007], Romano et al. [2008]—which were originally studied in a low-dimensional (fixed p) setting—leading to theorems that show such procedures remain valid for asymptotic k-FWER control in high-dimensions under several important technical conditions (chiefly, that k is fixed, or "sufficiently small"). These results in asymptotic high-dimensional k-FWER control complement existing methods for asymptotic high-dimensional control of the FWER [Belloni et al., 2018] and asymptotic high-dimensional control of the FDR under weak dependence [Liu and Shao, 2014, Belloni et al., 2018].

Hypothesis generation. There is a growing literature in economics and computer science on "hypothesis generation" [Ludwig and Mullainathan, 2024, Zhong et al., 2023]—that is, using AI/ML frameworks to systematically generate and measure research-relevant, interpretable features from unstructured data [Dell and Rambachan, 2026]. From the perspective of this literature, the proposed framework can be seen as advocating for *high-dimensional* hypothesis generation, paired with high-dimensional hypothesis evaluation (testing). More specifically, concept embeddings can be viewed as the result of applying a hypothesis generator to some unstructured evaluation sample, the result of which is subjected to formal statistical analysis. Correspondingly, then, the new methods in high-dimensional multiple testing in this paper can also be seen as a new technique for evaluating many generated hypotheses.

Sparse autoencoders have recently been proposed and applied as hypothesis generators for social science research questions [Movva et al., 2025, Peng et al., 2025, Wang et al., 2026]. From the perspective of this hypothesis generation sub-literature, one can consider that the hypothesis generation procedure associated with the proposed SAE-based concept embeddings was that of the original self-supervised training of the SAE model in an external corpus. The application of SAE as hypothesis generator in this paper is based on a model *pretrained* on an LLM's residual stream, eschewing the need for a large SAE training corpus and thereby accommodating analysis with small datasets. That said, the proposed framework would likewise be compatible with SAEs trained from scratch (based on dense embeddings

or otherwise, c.f., Movva et al. [2025]). Furthermore, unlike other works in this space, SAE features are not filtered by their ability to predict some outcome or treatment. Filtering is not pursued in the proposed framework because filtering through supervision can: (1) artificially reduce the breadth of interpretable measurements taken by the SAE; (2) introduce another lever for researcher discretion/intervention; and (3) inappropriately prune features that, e.g., have large associated causal effects but do not explain much variation in treatment.[9] That said, using structured covariates to supervise the dimensionality reduction of a concept embedding is theoretically compatible with the proposed framework (under appropriate sample splitting) and may have important applications in settings considered beyond this paper's empirical examples.

AI interpretability. There is a large literature in computer science on machine learning interpretability (see, e.g., Doshi-Velez and Kim [2017]). The machine learning interpretability methods leveraged by the present framework originate from a nascent though highly active literature known as "mechanistic interpretability," which seeks to develop methods for interpreting LLM behavior via quantitative analyses of model internals (e.g., activations, weights). In particular, the sparse dictionary learning methods for LLM interpretability implemented in this framework are called "sparse autoencoders" (SAEs), and were developed in Bricken et al. [2023], Templeton et al. [2024].[10] [11] Other sparse dictionary learning methods that have been proposed as competitors to SAEs (e.g., transcoders [Paulo et al., 2025]) may similarly serve as concept embedding methods. The proposed framework is also related to recent independent efforts in "data-centric interpretability," such as Jiang et al. [2025], who leverage SAE activations to create interpretable concept embeddings of text in order to facilitate (purely descriptive) analysis of datasets relevant to LLM behavior.

SAEs and similar methods learn quantitative measures of interpretable concepts, but do not on their own generate natural language (e.g., English) descriptions for these learned concepts. As such, a related literature on "automatic interpretability" (or "autointerp") methods has become active, which seeks to coherently use LLMs to describe the features discovered by sparse dictionary learning methods at scale. Recent important papers in this literature include: Bills et al. [2023], Shaham et al. [2024], Paulo et al. [2024], Rajamanoharan et al. [2024]. Specifically, the autointerp framework proposed in this paper adapts and formalizes insights from the "detection scoring" method of Paulo et al. [2024].

Though the empirical examples considered in this paper handle one of the most popular

[9] "Many true [causal] hypotheses need not be visible in raw correlations... Other procedures would be required to surface those. Our focus here is on searching for true hypotheses that are visible in raw correlations" [Ludwig and Mullainathan, 2024].

[10] SAEs are very wide autoencoders inserted at various layers of an LLM that are trained to intercept and reconstruct activations from model internals (such as the residual stream, MLPs or the like) under a sparsity-inducing penalization on a reconstruction loss. Under the "linear representation hypothesis" and "superposition hypothesis" (see, e.g., Bricken et al. [2023] for more discussion), these sparse autoencoders are thought to act as an overcomplete basis of the space of concepts in text leveraged by an LLM to make next token predictions, encouraging learned autoencoder latents to have monosemantic interpretations.

[11] There has been much debate about the success of SAEs in pursuit of AI interpretability (e.g., Leask et al. [2025]), though most criticisms still support the notion that SAEs and other sparse dictionary learning methods have a comparative advantage in discovering as opposed to detecting concepts of interest in text [Peng et al., 2025]—which is how they are applied in this framework.

unstructured data types—text—for which sparse dictionary learning-based interpretability methods are the most mature, sparse dictionary learning techniques have been successfully applied to many other modalities, including audio and images [Abdulaal et al., 2024, Bhalla et al., 2024, Fry, 2024, Daujotas, 2024, Pluth et al., 2025, Fel et al., 2026]. Future work would seek to apply the proposed framework to unstructured datasets in these other data modalities.

3 Framework

We now consider each step of the proposed framework in detail. In what follows, we define $[p] := \{1, \ldots, p\}$, and let $x \mapsto \log x$ be the natural logarithm. Further, for any vector $s \in \mathbb{R}^p$ and a subset of indices $K \subseteq [p]$, let $s_K \in \mathbb{R}^{|K|}$ denote the subvector indexed by K, such that $(s_K)_q = s_{j_q}$ for $j_q \in K$ and $j_1 < j_2 < \cdots < j_{|K|}$. We use $s \mapsto s_{[k]}$ as notation for the function that selects the k-th *largest* coordinate of the vector s.

3.1 Creating Concept Embeddings

We consider that the researcher has access to a dataset of size n, $\{(W_i, Z_i)\}_{i=1}^n$, which is sampled i.i.d. from some population of interest represented by distribution P.[12] The $Z_i \in \mathcal{Z}$ are unstructured data points and the $W_i \in \mathcal{W}$ are any other observed covariates of interest. The space $\mathcal{Z}$ is typically high-dimensional but semantically shallow, e.g., if each Z_i was a 224×224 pixel image, $\mathcal{Z}$ might then be the space of all $3 \times 224 \times 224$ arrays of RGB values, or if Z_i was text that was truncated up to some maximum length, $\mathcal{Z}$ might be the space of all binary matrices of a certain dimensionality, which are concatenated one-hot encodings for each word, term, or token in the text with respect to a specific pre-defined vocabulary.

Example 1 (Continued). The Z_i is a text response elicited for experimental participant i; the $W_i \in \mathcal{W} = \{0, 1\}$ is a treatment status indicator for experimental participant i. △

The first stage of the framework relies on the researcher having access to a function which creates high-dimensional, human-interpretable concept embeddings from unstructured data points, which we may denote as $h : \mathcal{Z} \to \{0, 1\}^p$.[13] The researcher has freedom to implement any high-dimensional concept embedding strategy of interest, so long as it is constructed in a way that is statistically independent of the dataset $\{(W_i, Z_i)\}_{i=1}^n$. However, as a computationally practical and widely applicable default, we suggest computing concept embeddings using pretrained *sparse dictionary learning* models.[14] In practice, this is

[12] That is, the fundamental source of uncertainty in this framework is sampling uncertainty, driven by an underlying sampling experiment in which units are sampled i.i.d. from P, and each unit is associated with a measurement (W_i, Z_i).

[13] Note that, consistent with the hypothesis generation literature, h can be thought of as the measurement function resulting from some learned, *high-dimensional* "hypothesis generator." It can also be thought of as a *high-dimensional* "codebook function" in the conceptual framework of Egami et al. [2022].

[14] Alternative examples of concept embeddings include: a concept embedding where each index records the presence or absence of particular n-gram (cheap computation, but not very rich measurement) or one where each index indicates absence or presence of a Wikipedia category (`https://en.wikipedia.org/wiki/Wikipedia:Contents/Categories`) operationalized with zero-shot LLM classification à la Asirvatham et al. [2026] (computation is expensive, but measurement is very rich).

accomplished by passing an unstructured data point to a deep neural network equipped with a pretrained sparse dictionary learning model (e.g., an LLM equipped with pretrained SAE when Z_i are texts); recording the feature activations from the SAE; and then aggregating these SAE feature activations (across tokens) to form a vector of indicators for the presence of each feature measured by the SAE, indexed $j \in [p]$.

There are many possible ways for a researcher to design a concept embedding based on a sparse dictionary learning model, though an especially straightforward choice is to record the SAE activations at a single layer of the deep neural network, setting the j-th entry of the concept embedding equal to 1 if the j-th SAE feature activated on any token of the input text, and 0 otherwise:

$$h(z)_j := \begin{cases} 1 \text{ if SAE feature } j \text{ at layer } l \text{ activates on any token of } z, \\ 0 \text{ otherwise.} \end{cases}$$

Concrete choices for the SAE architecture and layer l will be discussed in the empirical examples in Section 4.

We define $Y_i := h(Z_i) \in \{0,1\}^p$ as the concept embedding of an unstructured data point Z_i. Each "concept indicator" $Y_{ij} \in \{0,1\}$ has the natural interpretation that a particular concept j appeared in the unstructured data point Z_i.[15]

Example 1 (Continued). Each text response Z_i is passed through an open-source LLM equipped with a pretrained SAE. The SAE activations for each token of Z_i at the l-th layer of the LLM are max-pooled (i.e., the maximum token activation is used as the activation summary for the entire text) and then thresholded at zero, yielding a $p \approx 10^4$-dimensional binary vector Y_i for each experimental participant i. Each $Y_{ij} \in \{0,1\}$ is a binary indicator of a particular concept being expressed in experimental participant i's text response, e.g., Y_{i7} could indicate whether or not experimental participant i's text response contains phrases indicating uncertainty. △

Application of the h function can be thought of as effectively producing a new, semantically rich, high-dimensional, and interpretable dataset of concept measurements with associated covariates $\{(Y_i, W_i)\}_{i=1}^n$ from the original unstructured dataset $\{(Z_i, W_i)\}_{i=1}^n$. The crux of the proposed framework is that simultaneous inference on parameters derived from each concept indicator Y_{ij}—or each (Y_{ij}, W_i) pair—is desirable because:

1. Each Y_{ij} is intended to indicate the presence of a rich, *human-interpretable* concept, and therefore parameters derived from Y_{ij} for any given j (and associated hypotheses) inherit this interpretability, e.g., $E_P[Y_{ij}]$ is the probability of human-interpretable concept j appearing in an unstructured data observation in population P. In practice,

[15] SAE feature activations are typically positively valued scalars, where magnitude is thought to correspond to some notion of intensity of activation. Other works in mechanistic interpretability consider using these raw activation values directly, perhaps with max or average pooling across tokens. However, presently, magnitude of activation is not a well-understood or highly interpretable quantitative property of sparse dictionary learning methods, and as such the default h function advocated for in the proposed framework does not incorporate this information. That said, leveraging feature activation intensity is empirically shown to be useful for deriving good autointerpretation generation strategies; see Section 3.4 for more on this.

for concept embeddings based on pretrained SAEs, the concepts measured might not capture entirely mutually exclusive concepts in unstructured data—leading to some redundancy in hypotheses—but still provide meaningful *coverage* of distinct concepts, i.e., jointly, SAE features can be shown to tile manifolds that constitute the meaningful concepts an LLM "thinks about" upon reading a text, in a relevant activation space [Bhalla et al., 2026a].

2. Collectively, the p indicators in Y_i for any given observation i catalog a vast space of interpretable concepts. Again, for SAEs, this catalog is intended to span the huge set of concepts that a frontier LLM uses for reasoning while doing next token prediction (or other pre-/mid-/post-training tasks) in internet-scale datasets. As such, simultaneous inference on parameters derived from all of these concept indicators greatly reduces the possibility that a researcher misses out on measuring important "unknown unknowns" in their unstructured data, mitigating *under-exploration* and expanding the scope for making truly surprising discoveries. The fact that these concept measures were curated in a data-independent way further shields inference from scientific and statistical problems associated with *data snooping*.

Towards exploiting this wealth of interpretable information created through concept embedding, we turn to specifying formal hypothesis tests of parameters of interest in the next step of the framework.

3.2 Specifying Concept-Level Parameters and Hypotheses

With an interpretable dataset of concept embeddings and associated covariates $\{(Y_i, W_i)\}_{i=1}^n$, we may consider defining p "one-sided" concept-level hypotheses $\{\tilde{H}_{0,j}\}_{j\in[p]}$, where

$$\tilde{H}_{0,j} : \theta_j(P) := E_P[X_{ij}] \leq 0, \quad X_{ij} = g(W_i, Y_{ij}),$$

for some measurable function g, or, alternatively, a set of "two-sided" hypotheses of interest $\{H_{0,j}\}_{j\in[p]}$ given by

$$H_{0,j} : \theta_j(P) := E_P[X_{ij}] = 0.$$

As shorthand, we will denote $X := \{X_i\}_{i=1}^n$. Letting the concept-level parameter of interest $\theta_j(P)$ be an expectation of some flexible function g of a concept indicator and covariates accommodates many natural estimands of interest in the social sciences, though extensions to a wider class of parameters that are only associated with *asymptotically linear* estimators will be discussed in detail in Section 3.3.4.

Example 1 (Continued). To infer average treatment effects on concept indicators, for treatment indicator W_i, fixed probability of treatment π (bounded away from zero and one), and potential outcomes $Y_{ij}(w)$ under SUTVA,

$$H_{0,j} : E[Y_{ij}(1) - Y_{ij}(0)] = E[X_{ij}] = E\left[\frac{W_i - \pi}{\pi(1-\pi)} Y_{ij}\right] = 0.$$

In other words, we set $X_{ij} = g(W_i, Y_{ij}) := \frac{W_i - \pi}{\pi(1-\pi)} Y_{ij}$, a Horvitz–Thompson transformation for computing a difference in means. △

We may form test statistics for such hypotheses as

$$T_{n,j} := \frac{1}{\sqrt{n}} \sum_{i=1}^{n} X_{ij}, \quad T_n := \frac{1}{\sqrt{n}} \sum_{i=1}^{n} X_i,$$

and taking absolute values, as appropriate.

Though inference on all p hypotheses facilitates rich, interpretable exploration of our unstructured dataset, inference in this setting is also challenging because:

1. The p is large, so simultaneous inference on (testing hypotheses for) all $j \in [p]$ parameters is a setting where we want *multiple hypothesis testing* guarantees. To see this, for the running Example 1, consider that of the $p \approx 10^4$ concepts we measure, we may anticipate that the presence of only 100 or so are causally affected by treatment. However, we do not know the identities of these concepts ex-ante, so we must search through all p concepts for them. If each concept-level hypothesis is tested at the standard 5% level, even in the ideal case that we conclude all 100 truly affected concepts are significant, we also expect to label 5% of the 9,900 unaffected concepts as significant, leading to a selected set of about $100 + (0.05 \times 9900) = 595$ concepts, of which $0.05 \times 9900/595 \approx 83\%$ are false discoveries. Multiple testing methods exactly aim to control error rates regarding the false discoveries a researcher makes after running many tests.

2. Not only is p large, but for most social science applications of interest $p \gg n$ (e.g., the experiment from Example 1 contains a few hundred participants, but the concept embedding contains tens of thousands of concept indicators), so simultaneous inference on all parameters is a *high-dimensional* multiple hypothesis testing problem.

3. Each estimator, test statistic, or p-value formed from the Y_{ij} for each $j \in [p]$ for the purposes of inference is plausibly statistically *dependent* on every other in a complicated way, ruling out multiple hypothesis testing approaches that assume independence or specific, known forms of dependence (e.g., PRDS [Benjamini and Yekutieli, 2001]).

4. The intent of the analysis is discovery, so the desired form of selective (familywise) error control is ideally *not too conservative*—similar to the original motivation for controlling selective error rates like the FDR [Benjamini and Hochberg, 1995] (discussed further in Section 3.3.5) instead of the FWER (probability of making *any* false rejections).

What is needed, then, for principled simultaneous inference on parameters based on all Y_{ij} is a *dependence-agnostic, high-dimensional multiple testing procedure with control over a generalized familywise error rate*. To be as well-powered as possible, we want testing procedures that employ resampling methods for estimating the true covariance across test statistics, such that conservative protection against worst-case dependence is not required. To keep things as general as possible, we also want to allow for only asymptotically valid test statistics and p-values, as is common in much of econometric analysis. In the following section, theory and corresponding statistical procedures are developed to achieve exactly these aims.

3.3 High-Dimensional Multiple Hypothesis Testing

We now state and prove the validity of statistical procedures that provide high-dimensional k-FWER control asymptotically, i.e., in the large sample limit, control of the probability of making k or more rejections of true nulls under distribution P:

$$k\text{-FWER}_P := P\{\text{reject at least } k \text{ hypotheses } H_{0,j} : j \in I(P)\}$$

for $I(P)$ the set of indices of true null hypotheses under distribution P. Naturally, k-FWER control for $k = 1$ is control of the FWER, and larger choices of k power making more discoveries.

3.3.1 Background and Motivation

The fundamental challenge of high-dimensional statistical inference, characterized by settings where $p \gg n$, is that classic statistical theory no longer applies: classical asymptotic statistics treats p as fixed in the relevant asymptotic thought experiment as n grows large, whereas in high-dimensional settings the p is growing (much) faster than n in the relevant asymptotic thought experiment. As such, many classic results fail in high-dimensional settings, and new high-dimensional statistical theory must be developed—a literature that has grown popular in response to increasing interest in the statistical analysis of "big data."[16] Multiple hypothesis testing (or selective inference, more broadly) in high-dimensions has received considerable attention in recent years, with methods now available that provide asymptotic high-dimensional control of the FWER under mild conditions [Belloni et al., 2018], and asymptotic high-dimensional control of the FDR under weak dependence across test statistics [Liu and Shao, 2014, Belloni et al., 2018]. Though valid in high-dimensions, these methods are quite conservative, or involve assumptions about the dependence structure of the data that are implausible in many settings (including the present one), respectively.

These existing high-dimensional multiple hypothesis testing results are supported by advances in high-dimensional central limit theory. Most existing high-dimensional CLT results naturally handle the case of controlling the FWER, which is facilitated by learning the quantiles of the distribution of the *maximum* coordinate of a scaled sum of independent random vectors in high-dimensions, but are invalid for studying the behavior of workhorse methods for controlling the k-FWER, which require modeling the distribution of the *k-th largest* coordinate of a scaled sum of independent random vectors in high-dimensions. Fortunately, recent work in high-dimensional central limit theory (e.g., Ding et al. [2025], Feng [2026]) has developed new theoretical tools suited to understanding the behavior of exactly these objects in high-dimensions, under assumptions of varying strength, as well as associated bootstrap procedures. We apply such tools to study and ultimately validate the asymptotic k-FWER control of the Romano and Wolf [2007] procedures in high-dimensions; we then extend tools from Ding et al. [2025] specifically, developing new high-dimensional CLTs that support more general high-dimensional multiple hypothesis testing procedures.

The following subsections state formal assumptions and results in high-dimensional central limit theory and multiple hypothesis testing. All formal results are stated as generally

[16] Concretely, challenges with developing statistical methods in high-dimensions include the lack of explicit limit distributions and complex dependence structures (see, e.g., Chernozhukov et al. [2023] for more).

as possible, holding for data that is independent but not identically distributed (i.n.i.d.), which nests the setting of interest based on discovery from i.i.d. sampled unstructured data. Readers not interested in theoretical details and formal statements may skip to Section 3.4.

3.3.2 Assumptions

Let $n \geq 3$ and $p \geq 3$. Let us further define

$$S_{n,j} := \frac{1}{\sqrt{n}} \sum_{i=1}^{n} (X_{ij} - E[X_{ij}]), \quad S_n := \frac{1}{\sqrt{n}} \sum_{i=1}^{n} (X_i - E[X_i]).$$

We will denote $\Sigma := E\left[S_n S_n^{\mathsf{T}}\right] = n^{-1} \sum_{i=1}^{n} E[(X_i - E[X_i])(X_i - E[X_i])^{\mathsf{T}}]$, which simplifies to $\Sigma = E[(X_i - E[X_i])(X_i - E[X_i])^{\mathsf{T}}]$ under i.i.d. data.

Then we make the following assumptions.

Assumption M. Let $b_1 > 0$ and $b_2 > 0$ be some constants such that $b_1 \leq b_2$. For all $i \in [n]$, $j \in [p]$, assume there exists a sequence of constants $B_n > 1$ (which may diverge) such that: (i) $E\left[\exp\left(|X_{ij} - E[X_{ij}]| / B_n\right)\right] \leq 2$; (ii) $b_1^2 \leq \frac{1}{n} \sum_{i=1}^{n} E[(X_{ij} - E[X_{ij}])^2]$; and (iii) $\frac{1}{n} \sum_{i=1}^{n} E[(X_{ij} - E[X_{ij}])^4] \leq B_n^2 b_2^2$.

These are mild conditions on the tails and moments of the data X_{ij}, which are stated in a way that accommodates data that are i.n.i.d. Part (i) of Assumption M simply requires that X_{ij} be subexponential, or, equivalently, have an Orlicz norm in Ψ_1 bounded by B_n. The B_n is indexed by n to accommodate growing tail thickness within the subexponential regime as $p = p_n$ grows in the asymptotic thought experiment with i.n.i.d. data. Part (ii) of Assumption M insists that the second (centered) moments of the data be bounded away from zero, appropriately stated for i.n.i.d. data. Part (iii) insists on bounded fourth (centered) moments in a similar fashion. Though these results are stated to handle i.n.i.d. data (in the interest of supporting applications beyond those considered in this paper), for i.i.d. data—the case considered in the applications of this framework—we may simply require for some fixed $B < \infty$ and fixed b_1, b_2 with $b_1 \leq b_2$: (i) $E\left[\exp\left(|X_{ij} - E[X_{ij}]| / B\right)\right] \leq 2$; (ii) $b_1^2 \leq E[(X_{ij} - E[X_{ij}])^2]$; and (iii) $E[(X_{ij} - E[X_{ij}])^4] \leq B^2 b_2^2$. Note that, in many use cases of interest based on concept indicators, the X_{ij} will be both bounded (almost surely) and studentized, making these assumptions highly plausible.

Remark 1 (Degenerate features). Some fraction of concept indicators may be degenerate at zero for any given dataset (they are "dead" [Bricken et al., 2023]). Assumption M foreshadows that the high-dimensional CLTs underlying the upcoming high-dimensional multiple hypothesis testing results are only valid for understanding the k-th largest coordinate of the (in-population) non-degenerate coordinates of S_n, which we may label S_n^+. Of course, degenerate concepts in distribution P are not of interest for the purposes of discovery, and so modeling the distribution of $S_{n,[k]}^+$ is precisely of scientific interest, in alignment with Assumption M. The researcher knows the in-sample degenerate coordinates, which is a superset of the in-population degenerate coordinates. We recommend dropping the in-sample degenerate coordinates to form a vector we may label $\check{S}_n$, and proceeding with analysis based on $\check{S}_n$ (noting that, by contrast, in finite samples, entries of S_n^+ may be zero, even if in the

large sample limit they would not be). Whenever the $S^+_{n,j}$ for all non-degenerate j are strictly positive with probability 1, then $\check{S}_{n,[k]} = S^+_{n,[k]}$ with probability 1 as well, and looking at the data to drop degenerate coordinates is both useful and benign. This commonly occurs: for example, when $|S^+_n|$ is of interest in two-sided testing and X_{ij} has no atoms or X_{ij} is binary (such as when $X_{ij} = Y_{ij}$).[17] The Gaussian multiplier bootstrap quantity that will be discussed later on, under two-sided testing, will also satisfy this property under the data-conditional law. Otherwise, whenever k or more coordinates of S^+_n are strictly positive with very high probability, so too is $\check{S}_{n,[k]} = S^+_{n,[k]}$ with very high probability, and this will almost always be the case in conventional datasets of concept embeddings (that feature many thousands of non-degenerate concepts). ◇

Assumption R. Assume that $B_n^2 \log^5(pn) = o(n)$.

This is the key rate condition needed for (uniform) Gaussian or bootstrap approximation error to go to zero asymptotically under the high-dimensional CLTs discussed in both the works of Ding et al. [2025] and Chernozhuokov et al. [2022]. Rewritten, it says that

$$\frac{B_n^2 \log^5(pn)}{n} = o(1)$$

which permits p growing very fast with n in the asymptotic thought experiment. In fact, p may be growing nearly exponentially in n, e.g., $p = e^{n^{1/6}}$ for fixed B_n. That this rate condition permits $p \gg n$ is an important positive result in high-dimensional central limit theory [Chernozhukov et al., 2017, 2023].

Remark 2 (State-of-the-art assumptions). Both Assumptions M and R are the state-of-the-art in the high-dimensional central limit theory from which this framework draws [Chernozhuokov et al., 2022, Ding et al., 2025]. Indeed, these conditions are the exact same as those used in both Chernozhuokov et al. [2022] and Ding et al. [2025]. Notably, these assumptions do not require non-degeneracy of Σ, another important positive result in this literature [Chernozhukov et al., 2023]. Under assumptions of non-degenerate Σ, improved rate conditions may be used in place of Assumption R. ◇

3.3.3 High-dimensional k-FWER Control

We will focus on the Gaussian multiplier bootstrap as our high-dimensional bootstrap method, which is both computationally light and theoretically suited to the setting at hand. We define the Gaussian multiplier bootstrap quantity

$$S_n^B := \frac{1}{\sqrt{n}} \sum_{i=1}^n \xi_i \left(X_i - \bar{X}_n \right),$$

where $\xi_i \overset{iid}{\sim} N(0,1)$ and $\bar{X}_n := n^{-1} \sum_{i=1}^n X_i$. For the purposes of bootstrapping, we will denote the data-conditional probability measure $P^B(\cdot) := P(\cdot \mid X)$.

[17] So long as, technically, $nE[Y_{ij}]$ is not *exactly* an integer.

With these assumptions and notations in place, we can now state results that certify the application of the step-down algorithms of Romano and Wolf [2007] (Algorithms 2.1 and 2.2) for controlling the k-FWER in large samples in high-dimensions. Recall that Algorithm 2.1 of Romano and Wolf [2007] begins by assuming that the researcher can compute appropriate critical values given by $\hat{c}_{n,K}(1-\alpha,k)$ for any $K \subset \{1,...,p\}$, which in the present case will be given by the $1-\alpha$ quantile of $S^B_{n,K,[k]}$ under P^B. The algorithm proceeds by first rejecting all $H_{0,j}$ such that $T_{n,j} > \hat{c}_{n,\{1,...,p\}}(1-\alpha,k)$, and ends if there are no rejections for any j, in which case all hypotheses are "accepted" (so far, this is equivalent to the entirety of a single-step procedure). If there are less than k rejections, then the algorithm halts; otherwise, heuristically, the next step of the algorithm uses information about the previously rejected hypotheses to inform a choice of K that yields a $\hat{c}_{n,K}(1-\alpha,k)$ that is then compared to the test statistics for the remaining hypotheses, leading to more rejections and another step (just like the previous) or halting if there are no more rejections. Algorithms 2.1 and 2.2 only differ on how they construct K after the first step, with Algorithm 2.2 offering a more computationally streamlined approach. (For completeness, both algorithms are reproduced in full in Appendix Section 6.6.)

Theorem 1 (High-dimensional k-FWER control for small k, one-sided)**.** *Consider the method of Algorithm 2.1 in Romano and Wolf [2007] with test statistics T_n of hypotheses $\{\tilde{H}_{0,j}\}_{j\in[p]}$ and critical values $\hat{c}_{n,K}(1-\alpha,k)$ given by the $1-\alpha$ quantile of $S^B_{n,K,[k]}$ under P^B. Assume that k is fixed (i.e., not growing with n,p). Then under Assumptions M and R, this method ensures:*

(i) $\limsup_{n,p\to\infty} k\text{-}FWER_P \leq \alpha$.

(ii) If $\tilde{H}_{0,j}$ is false and $\theta_j(P) \gg B_n\sqrt{\log p/n}$, then the probability that the step-down method rejects $\tilde{H}_{0,j}$ tends to 1.

(iii) If $\min_{j\notin I(P)} \theta_j(P) \gg B_n\sqrt{\log p/n}$, then conclusions (i) and (ii) also hold when Algorithm 2.1 is replaced by Algorithm 2.2 of Romano and Wolf [2007].

This result is the natural high-dimensional analog of Theorem 3.1 (as well as Theorem 3.3) of Romano and Wolf [2007]. Theorems 3.1 and 3.3 of Romano and Wolf [2007]—as well as all formal results in that paper—are implicitly analyzed with fixed p asymptotics. Theorem 1 says that so long as k is fixed (small in the relevant asymptotic sense), Algorithm 2.1 of Romano and Wolf [2007] may be used to asymptotically achieve control of the k-FWER at any desired level α even in high-dimensional settings, where p can grow much faster than n, and moreover that Algorithm 2.1 is consistent against local alternatives that are not shrinking towards zero too quickly[18] (i.e., intuitively, in sufficiently large samples, we are able to appropriately reject a false null so long as $\theta_j(P) = E_P[X_{ij}]$ is not very close to zero). Result (i) of Theorem 1 resembles result (i) of Theorem 3.1 of Romano and Wolf [2007], but where now p is growing as fast as allowed by Assumption R; result (ii) of Theorem 1 resembles result (ii) of Theorem 3.1 of Romano and Wolf [2007], but now $\theta_j(P) \gg B_n\sqrt{\log p/n}$ appears instead of $\theta_j(P) > 0$.[19] Result (iii) says that the streamlined Algorithm 2.2 of Romano and

[18] Under Assumption R, note that $B_n\sqrt{\log p/n} = o(1)$.

[19] Formally, by $\theta_j(P) \gg B_n\sqrt{\log p/n}$ we mean that $\theta_j(P)/(B_n\sqrt{\log p/n}) \to \infty$.

Wolf [2007] also provides high-dimensional k-FWER control and is consistent against local alternatives when a natural (though perhaps not always granted) separation condition holds.

The proof of this result is available in Appendix Section 6.9, and, as previously alluded to, relies on the insight that the low-dimensional k-FWER controlling algorithms of Romano and Wolf [2007] can be adapted to and analyzed in the high-dimensional setting using new results in high-dimensional central limit theory for order statistics [Chernozhuokov et al., 2022, Ding et al., 2025]. In the following theorem, we state the sibling procedure for high-dimensional control of the k-FWER in two-sided testing settings; it is the high-dimensional analog of Theorem 3.2 of Romano and Wolf [2007].

Theorem 2 (High-dimensional k-FWER control for small k, two-sided)**.** *Consider the method of Algorithm 2.1 in Romano and Wolf [2007] with test statistics $|T_n|$ of hypotheses $\{H_{0,j}\}_{j\in[p]}$ and critical values $\hat{c}_{n,K}(1-\alpha,k)$ given by the $1-\alpha$ quantile of $|S^B_{n,K}|_{[k]}$ under P^B. Assume that k is fixed (i.e., not growing with n,p). Then under Assumptions M and R, this method ensures:*

(i) $\limsup_{n,p\to\infty} k\text{-}FWER_P \leq \alpha$.

(ii) If $H_{0,j}$ is false and $|\theta_j(P)| \gg B_n\sqrt{\log p/n}$, then the probability that the step-down method rejects $H_{0,j}$ tends to 1.

(iii) If $\min_{j\notin I(P)}|\theta_j(P)| \gg B_n\sqrt{\log p/n}$, then conclusions (i) and (ii) also hold when Algorithm 2.1 is replaced by Algorithm 2.2 of Romano and Wolf [2007].

Remark 3 (Small k). To comment explicitly on why the procedures of Theorems 1 and 2 are only theoretically valid for "small" k, note that the sup-norm bootstrap or Gaussian approximation error in the high-dimensional CLTs for the k-th largest coordinate introduced in Ding et al. [2025] only goes to zero if

$$\frac{k^8 B_n^2 \log^5(pn)}{n} = o(1),$$

meaning that k must be fixed or must grow incredibly slowly. That is, k needs to be quite "small" in theory. ◇

Remark 4 (Choosing k in practice). The k in a k-FWER controlling procedure is intended as an ex-ante hyperparameter choice. In practice, researchers might consider choosing a "small" k based on the real scientific costs of investigating false discoveries, a back-of-the-envelope calculation that takes into account the researcher's prior for the count of true discoveries and/or total rejections, or calibrations based on external (independent) datasets. Researchers may also consider pre-specifying a small fixed grid of k values, e.g., $k \in \{1, 5, 10\}$, and running the k-FWER controlling algorithm based on each element of the grid. Because the algorithms explored in this paper yield critical values that are monotonically decreasing in the value of k, researchers can simply report all the rejections for the largest k in the grid, and, for each of those rejections, the first k in the grid at which that rejection is made. All of this is subject to the largest k in the grid still being sufficiently "small"—see Remarks 3 and 5. ◇

Remark 5 (Maximal k and placebo tests). Though the high-dimensional central limit theory underlying Theorems 1 and 2 makes clear that k must be "small," this does not immediately suggest what a maximal choice of k would look like in any finite sample. To evaluate if a researcher chosen k is "small" enough, researchers may consider running tests of true global nulls in relevant settings. For example, in an experimental setting such as Example 1, researchers may generate placebo treatment assignments for units (independently of the data), and run the algorithm suggested by Theorem 1 at increasing $k \in \{1, 2, ...\}$. The first k in this sequence that yields many rejections of the null relative to that k—which the researcher knows to be false rejections by placebo design—suggests that k has become so large that control of the k-FWER has begun to fail. ◇

3.3.4 Many Approximate Means and k-FWER Control

So far, we have validated the algorithms of Romano and Wolf [2007] in high-dimensions (with important caveats) using new theoretical tools for studying the k-th largest coordinate of S_n from Ding et al. [2025]. However, these results were only based on hypotheses of means: the parameters of interest were written exactly as $\theta_j(P) = E_P[X_{ij}]$ for some interpretable X_{ij}, and estimators $\hat{\theta}_j$ were simply sample means (with $T_{n,j} = \sqrt{n}\hat{\theta}_j$). Though this is a common setting, researchers often want to test hypotheses for parameters which have estimators (and test statistics) that are not exactly expressible as averages of the observed data, yet "approximately" behave like means in large samples. Important examples include t-stats,[20] or when the parameters of interest are linear regression coefficients estimated with OLS. Thus, we also want k-FWER control for hypothesis testing based on "many approximate means" (MAM) in the parlance of Belloni et al. [2018]. To achieve this, we will extend the high-dimensional CLTs introduced in Ding et al. [2025] (which are only valid for the "exact" means previously studied) to the setting of MAM, and thereby unlock high-dimensional k-FWER control for tests based on a wider class of estimators of parameters of practical interest.

To begin, note that many estimators $\hat{\theta}_j$ of parameters $\theta_j(P)$ will have the asymptotically linear representation

$$\sqrt{n}(\hat{\theta}_j - \theta_j(P)) = \frac{1}{\sqrt{n}} \sum_{i=1}^{n} \psi_{ij} + R_{n,j}, \quad \sqrt{n}(\hat{\theta} - \theta(P)) = \frac{1}{\sqrt{n}} \sum_{i=1}^{n} \psi_i + R_n, \tag{1}$$

where $\hat{\theta} := (\hat{\theta}_1, \hat{\theta}_2, ..., \hat{\theta}_p)^\intercal$, $\theta(P) := (\theta_1(P), \theta_2(P), ..., \theta_p(P))^\intercal$, $\psi_i := (\psi_{i1}, \psi_{i2}, ..., \psi_{ip})^\intercal$ is the collection of influence functions ψ_{ij} at observation i for $\theta_j(P)$, and the $R_{n,j}$ are small remainder terms ("linearization errors"). This setup nests the previous hypothesis testing setup based on "exact" means, for which $\theta_j(P) = E_P[X_{ij}]$ and

$$\psi_{ij} = X_{ij} - E_P[X_{ij}], \quad R_n = 0.$$

[20] Multiple hypothesis testing with studentized statistics is often important for the purposes of "balance": that all hypothesis tests considered are similarly powered, contributing to selective error control similarly (see, e.g., Romano and Wolf [2010] for a more formal characterization of balance in this setting). For example, when $X_{ij} = Y_{ij} \in \{0, 1\}$, more frequently occurring concept indicators are higher variance features, and we are typically interested in powering discoveries beyond just these frequently occurring concepts.

Based on this observation, going forward we will simply relabel the data X_{ij} as the influence function ψ_{ij}, such that

$$S_n = \frac{1}{\sqrt{n}} \sum_{i=1}^{n} \psi_i, \quad \tilde{S}_n := \sqrt{n}(\hat{\theta} - \theta(P)) = S_n + R_n,$$

recalling that, by definition, influence functions are mean zero, i.e., $E[\psi_{ij}] = 0$, and thus $\Sigma = n^{-1} \sum_{i=1}^{n} E[\psi_i \psi_i^{\intercal}]$, and we treat Assumption M as holding for data ψ_{ij}. With this new notation in place, we can now state a high-dimensional CLT that accommodates the case of small linearization errors R_n, the so-called setting of "many approximate means."

Theorem 3 (High-dimensional CLT for the small k-max coordinate, MAM)**.** *Let $\tilde{S}_n := S_n + R_n$, and assume that $\|R_n\|_\infty = o_P(1/\sqrt{\log(pn)})$. Further assume that k is fixed (i.e., does not grow with n, p). If Assumptions M and R hold, then as $n, p \to \infty$*

$$\sup_{t \in \mathbb{R}} \left| P\left(\tilde{S}_{n,[k]} \leq t\right) - P\left(N(0, \Sigma)_{[k]} \leq t\right) \right| \to 0.$$

This theorem is both a natural generalization of Lemma A.6 of Ding et al. [2025], which proves the special case for $R_n = 0$, and an extension of Theorem 2.1 of Belloni et al. [2018], which concerns uniform approximations over (hyper)rectangular events (like the max statistic falling below t) for "many approximate means."[21] This theorem indicates that, for small k, in the large sample limit, the distribution of the k-th largest coordinate of a scaled sum of independent random vectors is (uniformly) well-approximated by the distribution of the k-th largest coordinate of a Gaussian random vector with variance matrix Σ *whether or not* there is a small linearization error R_n. In Appendix Section 6.7, we state an analogous theorem for the analogous (multiplier) bootstrap quantity under the relevant bootstrap law P^B.

Leveraging these high-dimensional CLTs for MAM, in Appendix Section 6.7 we also state high-dimensional CLTs that explicitly allow for studentization, recognizing that studentization with estimated variances can be cast as analyzing a particular $\tilde{S}_n$. These results can in turn be used to prove the following high-dimensional k-FWER result; a two-sided version can similarly be stated, but is omitted for brevity.[22]

Theorem 4 (High-dimensional k-FWER control for small k, studentized, one-sided)**.** *Assume that $X_i \overset{iid}{\sim} P$. Define $\widehat{\Sigma}_{jj} := n^{-1} \sum_{i=1}^{n} (X_{ij} - \bar{X}_{n,j})^2$ and $\widehat{\Lambda} := \text{diag}\{\widehat{\Sigma}_{11}, \ldots, \widehat{\Sigma}_{pp}\}$. Consider the method of Algorithm 2.1 in Romano and Wolf [2007] with test statistics $\hat{\Lambda}^{-1/2} T_n$ of hypotheses $\{\tilde{H}_{0,j}\}_{j \in [p]}$ and critical values $\hat{c}_{n,K}(1 - \alpha, k)$ given by the $1 - \alpha$ quantile of $(\hat{\Lambda}^{-1/2} S_n^B)_{K,[k]}$ under P^B. Assume that k is fixed (i.e., not growing with n, p). Then under Assumptions M and R, so long as $B_n = O(1)$, this method ensures:*

(i) $\limsup_{n,p \to \infty} k\text{-FWER}_P \leq \alpha$.

[21] Note that the k-th largest coordinate falling below some t for $k = 1$ is an event where $\tilde{S}_n$ falls in a (hyper)rectangular set, and for $k > 1$ is a *union* of rectangles.

[22] It is also the case that we may safely only work on the event $\{\min_{j \leq p} \widehat{\Sigma}_{jj} \geq b_1^2/2\}$ in this theorem, so we incur no existence issues, as this event occurs with probability tending to 1 in the large sample limit given Assumption M.

(ii) If $\tilde{H}_{0,j}$ is false and $\theta_j(P) \gg \sqrt{\log p/n}$, then the probability that the step-down method rejects $\tilde{H}_{0,j}$ tends to 1.

(iii) If $\min_{j \notin I(P)} \theta_j(P) \gg \sqrt{\log p/n}$, then conclusions (i) and (ii) also hold when Algorithm 2.1 is replaced by Algorithm 2.2 of Romano and Wolf [2007].

The evaluated influence functions ψ_{ij} are typically not fully observed in the data, and instead must be estimated. This becomes important when bootstrapping, because the bootstrap must be based on quantities that we can actually compute with the observed data. The following theorem states that, when the influence functions are sufficiently well-estimated with observed data, the high-dimensional multiplier bootstrap remains effective.[23]

Assumption A. Assume that $\max_{j \in [p]} \left(n^{-1} \sum_{i=1}^{n} (\hat{\psi}_{ij} - \psi_{ij})^2 \right)^{1/2} = o_P(1/\log(pn))$.

Theorem 5 (High-dimensional bootstrap for the small k-max coordinate with estimated influence function)**.** *Define*

$$\tilde{S}_n^B := \frac{1}{\sqrt{n}} \sum_{i=1}^{n} \xi_i \hat{\psi}_i.$$

Further assume that k is fixed (i.e., does not grow with n, p). If Assumptions M, R, and A hold, then as $n, p \to \infty$

$$\sup_{t \in \mathbb{R}} \left| P^B \left(\tilde{S}^B_{n,[k]} \leq t \right) - P \left(N(0, \Sigma)_{[k]} \leq t \right) \right| \xrightarrow{P} 0.$$

This theorem is the natural analog to Theorem 2.2 of Belloni et al. [2018]. It uses the same sufficient condition for the asymptotic approximation quality of the influence function—Assumption A—as Belloni et al. [2018] (equation 2.3), which is derived from an implication of the Borell-Sudakov-Tsirelson inequality.

The following result then leverages Theorem 5, among others, to permit high-dimensional multiple hypothesis testing with k-FWER control in the MAM setting when influence functions must be estimated. Again, a two-sided result is omitted simply for brevity, and would introduce no new technical issues.

Theorem 6 (High-dimensional k-FWER control for small k, MAM, one-sided)**.** *Consider the method of Algorithm 2.1 in Romano and Wolf [2007] with test statistics $\sqrt{n}\hat{\theta}_j$ of null hypotheses $\tilde{H}_{0,j} : \theta_j(P) \leq 0$ for all $j \in [p]$, and critical values $\hat{c}_{n,K}(1-\alpha, k)$ given by the $1-\alpha$ quantile of $\tilde{S}^B_{n,K,[k]}$ under P^B. Assume that k is fixed (i.e., not growing with n, p) and that for all $j \in [p]$ the asymptotically linear representation of equation (1) holds with $\|R_n\|_\infty = o_P(1/\sqrt{\log(pn)})$. Then under Assumptions M, R, and A, this method ensures:*

(i) $\limsup_{n,p \to \infty} k\text{-}FWER_P \leq \alpha$.

[23] Note that, even in the case of exact means, the influence function is not directly observed, because $E_P[X_{ij}]$ is not directly observed; nonetheless, the results proven earlier permit $E_P[X_{ij}]$ to be approximated with a sample average, as part of S_n^B. Theorem 5 provides a more abstracted approximation condition to generalize this plug-in result.

(ii) *If $\tilde{H}_{0,j}$ is false and $\theta_j(P) \gg B_n\sqrt{\log p/n}$, then the probability that the step-down method rejects $\tilde{H}_{0,j}$ tends to 1.*

(iii) *If $\min_{j\notin I(P)} \theta_j(P) \gg B_n\sqrt{\log p/n}$, then conclusions (i) and (ii) also hold when Algorithm 2.1 is replaced by Algorithm 2.2 of Romano and Wolf [2007].*

Theorem 6 embeds a practical bootstrapping procedure for estimators of parameters that are only asymptotically linear: derive the influence functions for the parameters of interest, estimate them if they are not directly observed, and then implement a multiplier bootstrap based on the data-conditional law of $\tilde{S}_n^B$.

An important application of these results is the empirical setting where each $\theta_j(P)$ is a linear regression coefficient based on a separate regression of a concept indicator on some regressor(s) of interest, estimated with a corresponding OLS coefficient $\hat{\theta}_j$. Here, $\sqrt{n}(\hat{\theta}_j - \theta_j(P))$ will have only an asymptotically linear representation, and the data-evaluated influence functions must be estimated. In the following example, we walk through the derivation of the bootstrapping procedure for testing many regression coefficients.

Example 4 (Bootstrap for many linear regression coefficients)**.** Consider the dataset given by $\{(Y_i, T_i, D_i)\}_{i=1}^n$, drawn i.i.d. from distribution P, where $Y_i = (Y_{i1}, \ldots, Y_{ip})^\intercal \in \mathbb{R}^p$ are concept indicators, $T_i \in \mathbb{R}$ is a treatment of interest, and $D_i \in \mathbb{R}^d$ are controls for some small (fixed) d that includes a constant. The researcher is interested in making discoveries based on the coefficient on T from the linear regression of Y_j on (T, D), which we denote $\theta_j(P)$, and which is formally defined via the optimization problem

$$(\theta_j(P), \vartheta_j(P)) := \arg\min_{b,g} E_P[(Y_j - Tb - D^\intercal g)^2].$$

By the Frisch-Waugh-Lovell theorem, we can write

$$H_{0,j} : \theta_j(P) = \Omega(P)^{-1} E_P[\widetilde{T}\,\widetilde{Y}_j] = 0$$

where $L_P[\cdot \mid \cdot]$ denotes the population linear projection operator, and by defining $\widetilde{T} := T - L_P[T \mid D]$ and $\widetilde{Y}_j := Y_j - L_P[Y_j \mid D]$, letting $\Omega(P) := E_P[\widetilde{T}^2]$ for shorthand. Defining the population residual $\widetilde{U}_j := \widetilde{Y}_j - \theta_j(P)\widetilde{T}$, the influence function for $\theta_j(P)$ at observation i is given by

$$\psi_{ij} := \Omega(P)^{-1}\widetilde{T}_i\widetilde{U}_{ij}.$$

For the expectation under the empirical distribution $E_n[\cdot]$ (i.e., the sample average), we can define feasible sample analogs as

$$\widehat{\gamma}_T := E_n[D_iD_i^\intercal]^{-1}E_n[D_iT_i], \qquad \widehat{\gamma}_{Y_j} := E_n[D_iD_i^\intercal]^{-1}E_n[D_iY_{ij}],$$
$$\widehat{\widetilde{T}}_i := T_i - D_i^\intercal\widehat{\gamma}_T, \qquad \widehat{\widetilde{Y}}_{ij} := Y_{ij} - D_i^\intercal\widehat{\gamma}_{Y_j},$$
$$\widehat{\Omega} := E_n[\widehat{\widetilde{T}}_i^2], \qquad \widehat{\theta}_j := \widehat{\Omega}^{-1}E_n[\widehat{\widetilde{T}}_i\,\widehat{\widetilde{Y}}_{ij}], \qquad \widehat{\widetilde{U}}_{ij} := \widehat{\widetilde{Y}}_{ij} - \widehat{\theta}_j\widehat{\widetilde{T}}_i, \qquad \widehat{\psi}_{ij} := \widehat{\Omega}^{-1}\widehat{\widetilde{T}}_i\widehat{\widetilde{U}}_{ij},$$

noting that $\hat{\theta}_j$ is just the usual OLS coefficient. We may now write out the asymptotically linear representation of each of the $j \in [p]$ regression coefficients as

$$\sqrt{n}(\hat{\theta}_j - \theta_j(P)) = \frac{1}{\sqrt{n}}\sum_{i=1}^n \psi_{ij} + R_{n,j}.$$

The appropriate law for facilitating k-FWER control via Theorem 6 is then given by

$$\tilde{S}_n^B := \frac{1}{\sqrt{n}} \sum_{i=1}^{n} \xi_i \hat{\psi}_i = \widehat{\Omega}^{-1} \frac{1}{\sqrt{n}} \sum_{i=1}^{n} \xi_i \widehat{\widetilde{T}}_i \widehat{\widetilde{U}}_i$$

under P^B, where $\widehat{\widetilde{U}}_i$ stacks all $\widehat{\widetilde{U}}_{ij}$ as a vector. That $\hat{\psi}_i$ is a sufficiently good approximation of ψ_i and that R_n is sufficiently small (in large samples) is proven in Propositions 2 and 3, as stated in Appendix Section 6.8, under certain sufficient conditions (e.g., all data is subgaussian tailed). △

3.3.5 High-dimensional FDX Control

In practice, researchers may also be interested in control of false discovery exceedance (FDX). Control of FDX at (γ, α) is defined as

$$P(\text{FDP} > \gamma) \leq \alpha$$

where FDP $:= F/(R \vee 1)$ and where F is the number of false rejections made by some multiple testing procedure and R is the total number of rejections made. Control of the FDX is sometimes preferred to control of the FDR (control that grants $E[\text{FDP}] \leq \alpha$), as control of the FDR can still permit large deviations of the FDP from its mean with high probability, whereas with FDX control the probability of such large deviations is bounded [Genovese and Wasserman, 2006].

In practice, successful control of the FDX is usually implemented as a "meta-procedure" built on top of a valid k-FWER controlling procedure [Janson and Su, 2016]. This is also true of the large sample FDX controlling Algorithm 4.1 of Romano and Wolf [2007], which is a wrapper around their k-FWER controlling Algorithms 2.1 or 2.2. However, the asymptotic argument that justifies using Algorithm 4.1 of Romano and Wolf [2007] would require that, in the high-dimensional asymptotic thought experiment, k also grows[24]—in other words, k could be "large," which is contradicted by the assumptions made to achieve *high-dimensional* k-FWER control under the assumption-lean results of Ding et al. [2025].[25]

Alternatively, however, we may still achieve FDX control in high-dimensions with an "augmentation" approach, which we state in the following two results.

Theorem 7 (High-dimensional FDX control via augmentation)**.** *Consider running the high-dimensional k-FWER controlling procedure of Theorem 6 at level α, and then augmenting the output set of rejections $\mathcal{R}$ by the set of null hypotheses with next q largest test statistics to form the new rejection set $\mathcal{R}_{\text{aug}}$, where $0 \leq q \leq p - |\mathcal{R}|$ and q may be data-dependent. Then this augmented procedure based on $\mathcal{R}_{\text{aug}}$, under the assumptions of Theorem 6, achieves*

$$\limsup_{n,p \to \infty} P\left\{ \text{FDP} > \frac{k - 1 + q}{(|\mathcal{R}| + q) \vee 1} \right\} \leq \alpha.$$

[24] See the proof of Theorem 4.1 in Romano and Wolf [2007].

[25] In theory, one could make very strong signal sparsity-style assumptions to try to recover high-dimensional k-FWER control with growing ("large") k, but such assumptions would be difficult to parse the validity of in practice.

Proof. Let F be the number of false rejections made by the k-FWER controlling procedure at level α, and $\mathcal{R}$ be the set of rejected nulls made by this procedure alone. Let $\tilde{F}$ be the number of false rejections made by the k-FWER controlling procedure at level α augmented by rejecting the previously unrejected null hypotheses with the next q largest test statistics.

Consider the event $\{F \leq k-1\}$. On this "good" event, no matter how we choose q, $\tilde{F} \leq k-1+q$, which is the pessimistic case that all additionally rejected hypotheses are true nulls. That is

$$\{F \leq k-1\} \subseteq \{\tilde{F} \leq k-1+q\} \subseteq \left\{ \frac{\tilde{F}}{(|\mathcal{R}|+q) \vee 1} \leq \frac{k-1+q}{(|\mathcal{R}|+q) \vee 1} \right\} := \left\{ \text{FDP} \leq \frac{k-1+q}{(|\mathcal{R}|+q) \vee 1} \right\}.$$

Then by Theorem 6 (i), we have that

$$\limsup_{n,p\to\infty} P\left\{ \text{FDP} > \frac{k-1+q}{(|\mathcal{R}|+q) \vee 1} \right\} \leq \limsup_{n,p\to\infty} P\{F \geq k\} = \limsup_{n,p\to\infty} k\text{-FWER}_P \leq \alpha,$$

completing the proof. □

This is a natural extension of Theorem 3 of Genovese and Wasserman [2006] to the high-dimensional setting.[26] Because q can be chosen in any (even data-dependent) way, we can also state the following corollary that achieves FDX control at a specific researcher chosen (γ, α) based on an underlying (high-dimensional) k-FWER controlling procedure.

Corollary 1 (High-dimensional FDX control at γ via augmentation)**.** *Consider running the augmented high-dimensional k-FWER controlling procedure of Theorem 7, but where if $\gamma|\mathcal{R}| < (k-1)$, set $\mathcal{R}_{\text{aug}} = \emptyset$, and otherwise choose q to be the largest integer such that*

$$\frac{k-1+q}{(|\mathcal{R}|+q) \vee 1} \leq \gamma.$$

Then the augmented procedure based on $\mathcal{R}_{\text{aug}}$ achieves

$$\limsup_{n,p\to\infty} P\{\text{FDP} > \gamma\} \leq \alpha.$$

Proof. If $\mathcal{R}_{\text{aug}}$ is the empty set, then FDX control at (γ, α) holds vacuously. When $\mathcal{R}_{\text{aug}}$ is not the empty set, by the result of Theorem 7, the conclusion is immediate. □

Note that, in practice, solving out the above, we may set q to simply be the smaller of $p - |\mathcal{R}|$ and $\lfloor (\gamma|\mathcal{R}| - (k-1))/(1-\gamma) \rfloor$. Further note that (asymptotic) FDX control at (γ, α) implies (asymptotic) FDR control at level $\gamma(1-\alpha)+\alpha$ (e.g., if $\alpha = 0.05$ and $\gamma = 0.1$, then FDR is controlled at 0.145); see, e.g., Romano and Shaikh [2006] for more on the connections between FDX and FDR control.

[26] Note that this theorem can be generalized to consider rejecting *any* disjoint set of previously unrejected hypotheses of size q, though the above implementation is resistant to data-mining and is plausibly the most ex-ante powerful choice.

3.4 Local Automatic Interpretation

By applying the statistical procedures discussed in Section 3.3, the researcher obtains a selected set of rejected null hypotheses, or "discoveries." Concretely, these discoveries are recorded as a set of coordinates $\hat{J} \subseteq [p]$ indexing the rejected nulls.

Though the machine learning theory that motivates sparse dictionary learning supposes that each hypothesis $\hat{\jmath} \in \hat{J}$ has a human-interpretable meaning, sparse dictionary learning methods themselves do not generate *natural language descriptions* of what each human-interpretable meaning may be—analogous to the way in which "topics" discovered by LDA topic models do not come with natural language descriptions [Blei et al., 2003]. We now discuss a set of procedures for both automatically generating and evaluating the quality of natural language feature descriptions, emphasizing the importance of statistical inference with respect to the actual data distribution of interest, P.

Remark 6 (Why do we need automatic interpretation?). Human judgment alone could be deployed as a means of giving natural language descriptions to concept indicators, e.g., the researcher could inspect many of the text examples that activate (highly) for a given SAE feature in order to arrive at a plausible English language description for the concept signaled by that feature. However, such a process suffers from (1) problems related to motivated reasoning and data snooping (e.g., the researcher could simply come up with a concept description that is reverse engineered from a conclusion they wanted to find in the data); and (2) problems related to the scale of interpretation and associated interpretation effort/cost (e.g., there may be many hundreds of concepts discovered, all requiring interpretation; interpreting all p concepts would require even more labor). Automatic interpretation pipelines solve both of these problems. They automate the process of creating and scoring natural language descriptions of concept indicators by leveraging a dedicated "explainer LLM" to reason about interpretations inexpensively at scale.[27] Of course, the researcher can look directly at the highly activating unstructured data points to develop their own interpretations, in parallel. ◇

3.4.1 Local Automatic Generation

We adopt the canonical autointerp generation strategy pioneered in Bricken et al. [2023] for this framework: we pass text samples from the researcher's unstructured dataset that activate highly on a particular feature to an explainer LLM—annotating these exemplar texts with information about where and how strongly the feature activates—and ask for an English description of the possible meaning of the feature.[28]

By drawing on text samples from the researcher's unstructured dataset of interest, this generation strategy is *local*—it is tailored to the distribution P. Though off-the-shelf feature descriptions are sometimes available for pretrained sparse dictionary learning models, these descriptions were necessarily learned on a different distribution of data (e.g., some large and opaque swath of the internet). As such, these descriptions are liable to be of lower quality

[27] The terminology "explainer LLM" is chosen to be consistent with related works in the AI interpretability literature, e.g., Jiang et al. [2025].

[28] This exact generation strategy, which only looks at "top activating" examples, is also used in and argued for in, e.g., Choi et al. [2024].

than those based on the researcher's own dataset. The specific prompts implementing this strategy for the empirical applications considered later are detailed in Appendix Section 6.4.

Example 1 (Continued). The null hypothesis of no average treatment effect is rejected for concept 4. Using the raw SAE feature activations (necessary to compute in the process of evaluating the h function), the researcher is able to rank text responses from experimental participants by largest activations for concept 4 on any token ("max pooling"). The researcher takes the top 10 highest activating text examples and annotates each of them to indicate the highest activating token(s) in each response. These exemplar responses are then passed to an explainer LLM that reasons about and then outputs the concise English phrase "discussion of politics" to describe concept 4. △

3.4.2 Local Automatic Evaluation

Autointerp pipelines ideally not only specify how to generate descriptions for concept indicators, but also *evaluate* the quality of these descriptions. We now consider a new statistical formalization of a mainstream autointerp evaluation technique called "detection scoring."

The fundamental principle of detection scoring is that "an interpretation should serve as a binary classifier distinguishing activating from nonactivating contexts" [Paulo et al., 2024]. In other words: description of a concept can be treated like a classification problem, one where the natural language description itself (harnessed in an LLM prompt) is the classifier, the input is a specific text example, and the label to be predicted is derived from the ground truth of the presence or absence of a SAE feature's activation in that text example (which is always known to the researcher using their h function). Under this framing, binary classifier performance metrics like accuracy, precision, and recall characterize the quality of the description.

To formalize this autointerp strategy, consider a "held-out" unstructured dataset of size m drawn independently from the same distribution of interest P. (This held-out dataset may be created, for example, by partitioning an original unstructured dataset drawn i.i.d. from P into two disjoint datasets via indices chosen at random, independently of all the data.) Let us denote the set of indices of unstructured data points in the main sample as $\mathcal{I}^{\text{estim}}$, and those in the held-out dataset as $\mathcal{I}^{\text{eval}}$.[29]

Using the data points with indices in $\mathcal{I}^{\text{estim}}$, we extract exemplar unstructured data points to be used to create an autointerp explanation of concept j, which we denote $\hat{\eta}_j$. For all $i \in \mathcal{I}^{\text{eval}}$, we define the random variable $\hat{Y}_{ij} \in \{0, 1\}$ as

$$\hat{Y}_{ij} := \texttt{CLS}(Z_i, \hat{\eta}_j),$$

where the function $\texttt{CLS}(\cdot)$ is a fixed choice of LLM and classification prompt fed both an unstructured data point Z_i and the learned autointerp explanation $\hat{\eta}_j$. The $\hat{Y}_{ij}$ is the classifier output, a prediction of whether or not the unstructured data point Z_i contains a concept with description $\hat{\eta}_j$.[30]

[29] In empirical settings featuring a randomized experiment, for the sake of preserving power, it may be useful for researchers to create the held-out dataset split from the larger treatment arm, if one exists.

[30] Note that, even if a sample splitting implementation of this autointerp evaluation strategy is pursued,

For the purposes of evaluating autointerp descriptions, we define the canonical "detection score" estimand as

$$\theta_j^{\text{acc}}(\hat{\eta}_j; P) := E_P\left[S_{ij} \mid \hat{\eta}_j\right] = P(\{Y_{ij} = \hat{Y}_{ij}\} \mid \hat{\eta}_j) = P\left(\{Y_{ij} = \texttt{CLS}(Z_i, \hat{\eta}_j)\} \mid \hat{\eta}_j\right)$$

where $S_{ij} := \mathbf{1}\{Y_{ij} = \hat{Y}_{ij}\}$, i.e., $\theta_j^{\text{acc}}(\hat{\eta}_j; P)$ is the accuracy of the classifier. Conditioning on $\hat{\eta}_j$ in the estimand of interest should be thought of as evaluating a fixed autointerp description. Importantly, as the notation emphasizes, the $\theta_j^{\text{acc}}(\hat{\eta}_j; P)$ tells us exactly the quality of the description $\hat{\eta}_j$ for the population of interest P, unlike other autointerp evaluation methods for which the underlying distribution that implicitly defines the evaluation score is highly opaque (c.f., simulation scoring [Bills et al., 2023]). In this way, evaluation is also *local*.

We can easily construct a plug-in estimator of the autointerp detection score estimand; its unbiasedness, consistency, and asymptotic normality under the $\hat{\eta}_j$-conditional law are established in the following proposition.

Proposition 1 (Conditional inference on detection score)**.** *Let $m := |\mathcal{I}^{eval}|$. Define the detection score estimator for concept indicator j as*

$$\hat{\theta}_j^{acc} := \frac{1}{m} \sum_{i \in \mathcal{I}^{eval}} S_{ij}, \quad S_{ij} = \mathbf{1}\{Y_{ij} = \hat{Y}_{ij}\} = \mathbf{1}\{Y_{ij} = \texttt{CLS}(Z_i, \hat{\eta}_j)\}.$$

Assume there exists a constant $\delta \in (0, 1/2)$ such that $P(S_{ij} = 1 \mid \hat{\eta}_j) \in [\delta, 1-\delta]$ almost surely. Then we have that $E_P\left[\hat{\theta}_j^{acc} \mid \hat{\eta}_j\right] = \theta_j^{acc}(\hat{\eta}_j; P)$ almost surely, and that as $m \to \infty$

$$\sup_{t \in \mathbb{R}} \left| P\left(\sqrt{m}(\hat{\theta}_j^{acc} - \theta_j^{acc}(\hat{\eta}_j; P)) \le t \mid \hat{\eta}_j\right) - P(N(0, \text{Var}(S_{ij} \mid \hat{\eta}_j)) \le t \mid \hat{\eta}_j) \right| \xrightarrow{a.s.} 0.$$

It is immediate from Proposition 1 then that the empirical variance estimator $\hat{V}_j^{\text{acc}} := m^{-1} \sum_{i \in \mathcal{I}^{\text{eval}}} (S_{ij} - m^{-1} \sum_i S_{ij})^2$ permits construction of valid large sample frequentist confidence intervals for $\hat{\theta}_j^{\text{acc}}$ under the $\hat{\eta}_j$-conditional law of the data.

Example 1 (Continued). The null hypothesis of no average treatment effect is rejected for concept 4, and the autointerp generation strategy implemented by the researcher describes concept 4 as activating on "discussion of politics." To evaluate the quality of this description, the researcher runs an LLM-based classifier over a held-out dataset of experimental participant text responses. The LLM classifier is given the prompt "Does the following text example indicate discussion of politics? Return 1 or 0 for yes or no:" followed by a text response from the held-out dataset. The researcher then uses the output of the LLM classifier to compute the detection score, which measures the accuracy of this autointerp description-based classifier at predicting the presence of concept 4 in the held-out dataset. △

cross-fitting is inappropriate, because there is little reason to think, given the sample sizes available to researchers, that $\hat{\eta}_j$ would be stable across folds. As such, when sample splitting is employed, an uneven split is recommended, e.g., only 15% of the data is used for the held-out evaluation sample.

Remark 7 (Oracle detection scores). Towards better understanding the information communicated to the researcher by the detection score, it is useful to consider the function $\texttt{CLS}^*(\cdot)$, which we can define implicitly as

$$\bar{\theta}_j^{\text{acc}}(\hat{\eta}_j; P) := \sup_{f \in \mathcal{F}} P\left(\{Y_{ij} = f(Z_i, \hat{\eta}_j)\} \mid \hat{\eta}_j\right) = P\left(\{Y_{ij} = \texttt{CLS}^*(Z_i, \hat{\eta}_j)\} \mid \hat{\eta}_j\right),$$

where $\mathcal{F}$ is the space of all viable classification prompts and LLMs able to execute them. That is, $\texttt{CLS}^*(\cdot)$ is the "oracle" detection scoring model setup, which when evaluated produces the highest interpretative accuracy score possible under a given description $\hat{\eta}_j$ under distribution P. Arguably, $\bar{\theta}_j^{\text{acc}}(\hat{\eta}_j; P)$ is more informative to the researcher than $\theta_j^{\text{acc}}(\hat{\eta}_j; P)$ about the quality of $\hat{\eta}_j$, as $\bar{\theta}_j^{\text{acc}}(\hat{\eta}_j; P)$ purely quantifies the quality of $\hat{\eta}_j$, without the wedge introduced by classification failures stemming from $\texttt{CLS}(\cdot)$ itself. Because any feasible choice of $\texttt{CLS}(\cdot)$ yields

$$P\left(\{Y_{ij} = \texttt{CLS}(Z_i, \hat{\eta}_j)\} \mid \hat{\eta}_j\right) \leq P\left(\{Y_{ij} = \texttt{CLS}^*(Z_i, \hat{\eta}_j)\} \mid \hat{\eta}_j\right)$$

one can reasonably interpret $\hat{\theta}_j^{\text{acc}}$ as a conservative (under)estimate of the more informative quantity $\bar{\theta}_j^{\text{acc}}(\hat{\eta}_j; P)$. ◇

We may also define additional detection score estimands with respect to either the precision or recall of the autointerp classifier:

$$\theta_j^{\text{prec}}(\hat{\eta}_j) := P\left(Y_{ij} = 1 \mid \hat{Y}_{ij} = 1, \hat{\eta}_j\right) = \frac{E[\mathbf{1}\{Y_{ij} = 1\}\mathbf{1}\{\hat{Y}_{ij} = 1\} \mid \hat{\eta}_j]}{E[\mathbf{1}\{\hat{Y}_{ij} = 1\} \mid \hat{\eta}_j]},$$
$$\theta_j^{\text{rec}}(\hat{\eta}_j) := P\left(\hat{Y}_{ij} = 1 \mid Y_{ij} = 1, \hat{\eta}_j\right) = \frac{E[\mathbf{1}\{Y_{ij} = 1\}\mathbf{1}\{\hat{Y}_{ij} = 1\} \mid \hat{\eta}_j]}{E[\mathbf{1}\{Y_{ij} = 1\} \mid \hat{\eta}_j]}.$$

As above, these estimands may be consistently estimated with appropriate asymptotically valid confidence intervals under the $\hat{\eta}_j$-conditional law using the natural plug-in estimators and the delta method. That said, for the purposes of the empirical applications in the following section, we focus on estimating the canonical detection score based on accuracy, following the common practice in the relevant literature [Paulo et al., 2024].

Further, recall that we are not typically interested in autointerp evaluation for a fixed j, but instead for a particular data-driven choice $\hat{\jmath} \in \hat{J}$ suggested by a high-dimensional selective inference procedure.[31] However, so long as discovery is also performed using the main estimation sample indexed by $\mathcal{I}^{\text{estim}}$, the researcher may treat each $\hat{\jmath}$ as fixed for the purposes of evaluation inference. Formally, for all $j \in [p]$,

$$E_P\left[S_{i\hat{\jmath}} \mid \hat{\eta}_{\hat{\jmath}}, \hat{\jmath} = j\right] = E_P\left[S_{ij} \mid \hat{\eta}_j, \hat{\jmath} = j\right] = E_P\left[S_{ij} \mid \hat{\eta}_j\right]$$

where the last equality follows because, under the proposed independently held-out data scheme,

$$[\mathbf{1}\{Y_{ij} = \texttt{CLS}(Z_i, \hat{\eta}_j)\} \perp\!\!\!\perp \hat{\jmath}] \mid \hat{\eta}_j.$$

[31] Autointerpretation typically incurs non-negligible compute costs, and, as such, researchers will often only be interested in forming meaningful autointerpretations for the subset of discovered concepts.

Remark 8 (Inference on the best interpretation). If a researcher is interested in inference on the best performing autointerp description across multiple generation prompts or strategies—say among a set $\{\hat{\eta}_{j,1}, \hat{\eta}_{j,2}, \dots\}$ for any j of interest—then the evaluation performance should be estimated with appropriate "inference on winners" corrections such as those discussed in Andrews et al. [2024]. ◇

Remark 9 (Evaluation of human-generated descriptions). It is worth noting that this autointerp evaluation strategy can also serve as a general-purpose description evaluation technology, e.g., for carefully crafted human descriptions of concept indicators in settings where there is a small number of discoveries. The scientific benefit of evaluation in such a setting is also clear: even if there is concern that human-made descriptions are reverse-engineered to support a presupposed conclusion, any description (human made or machine made, motivated or not) that is not supported by the data will be surfaced through the evaluation scores. In this way, description evaluation can be seen as even more critical when automatic methods are not employed by the researcher to generate descriptions. ◇

3.5 Pseudocode and Code

In Appendix Section 6.5, we state a simple version of the entire framework for interpretable discovery from unstructured data as a single pseudocode algorithm. We focus on an implementation with text data, sample splitting, two-sided testing, single-step hypothesis testing (i.e., just the first step of Algorithm 2.1 of Romano and Wolf [2007]), and autointerp evaluation via accuracy-based detection scoring. Full implementation code is also available: see the link in Appendix Section 6.1.

4 Empirical Applications

As an illustration of the framework proposed in this paper, we now reanalyze several recent works in empirical economics related to discovery from unstructured data, and show how new, principled, and interpretable discoveries may be made using the same exact data.

4.1 Reanalyzing Andre et al. [2026]

An inspiration for Example 1, Andre et al. [2026] study household narratives about the surge in inflation circa 2021-2022 in the United States. In particular, Andre et al. [2026] elicit household narratives about inflation using surveys with open-ended text responses. Among the many analyses they pursue, Andre et al. [2026] conduct several survey experiments in order to measure the causal effects of being exposed to "expert" narratives on respondents' own narrative beliefs and expectations for inflation.

In their primary experiment, Andre et al. [2026] recruit a representative sample of hundreds of households and randomly expose one-third of respondents to a written "expert" narrative attributing rising inflation throughout 2021-2022 to "pent-up demand" and forced savings during the COVID-19 pandemic (with another third exposed to a different expert narrative on energy crises, and the last third acting as a control). In a follow-up survey

the next day, the authors then elicit respondents' own inflation narrative through open text—one of the core outcomes of the experiment.[32] In order to quantitatively measure the narratives that appear in the open text, the authors hand-code 16 distinct "narrative factor" indicators, crafted per a discretionary, manual process.[33] The primary finding of this experiment is that the presence of the "pent-up demand" hand-coded concept increases by 37.8 percentage points in the "pent-up demand" treatment group relative to the control—signaling a very high "elasticity to the provision of new information"—and the hand-coded concept for "energy crisis" decreases by 7.9 p.p. in the pent-up demand treatment group relative to the control—a "crowding out" phenomenon that the authors do not interpret further.

Do we *automatically* replicate these findings with the proposed framework? Do we expand on them? To investigate, we implement a concept embedding based on the Temporal Sparse Autoencoder (T-SAE) [Bhalla et al., 2026b], itself based on layer 12 of a Gemma family LLM [Lieberum et al., 2024]. We implement an autointerp pipeline detailed in Section 6.4 using as explainer LLMs Anthropic's Claude Sonnet (High) for generation and Google's lightweight Gemma 4 31B for evaluation.[34] A small held-out evaluation dataset is created by sample splitting, using just 15% of the original experimental dataset in Andre et al. [2026].

The hypotheses tested are of the form discussed in Example 4,

$$H_{0,j} : \theta_j(P) = E_P[\widetilde{T}_i^2]^{-1} E_P[\widetilde{T}_i \, \widetilde{Y}_{ij}] = 0,$$

where $\widetilde{Y}_{ij}$ is an indicator for concept j in the concept embedding and $\widetilde{T}_i$ is the "pent-up demand" treatment indicator, both residualized with the same controls used in the regression specification that produced the primary results of the original study (i.e., a linear regression specification with controls as documented in Table 4 of Andre et al. [2026]). This yields a dataset with $n = 758$ and $p = 5420$ (non-degenerate features—see Remark 1).

We begin by considering 5-FWER controlled multiple testing with $\alpha = 0.05$ based on the result of Theorem 6, and make 162 interpretable discoveries—that is, we reject the null of an average treatment effect equal to zero on 162 concepts encoded by the concept embedding. In Figure 2, we display the 10 largest (by $|\hat{\theta}_j|$) of the *well-interpreted* discoveries, which we define as discoveries with a point estimate for the detection accuracy score greater than 0.75.[35] Furthermore, for presentational purposes, we suppress plotting discoveries with autointerp descriptions that are highly semantically similar to many others—the total number of similarly interpreted discoveries being indicated in a parenthetical when there is more than one.[36] Such a plot can be thought of as a concise summary of the outputs

[32] The authors' rationale for collecting open-ended text responses is explicitly to "offer a lens into people's spontaneous thoughts," as open-ended elicitation "leaves individuals' answers unrestricted and does not prime them on any particular issue."

[33] See Table 1 of Andre et al. [2026] for a list of these hand-coded "narrative factors."

[34] Gemma 4 is open-source, and as such evaluations of generated descriptions remain readily reproducible, conditional on generated descriptions.

[35] This is a benchmark derived from the median Claude detection score reported in Paulo et al. [2024] for autointerp on large-scale, open-source text corpora.

[36] In particular, we embed all autointerp generated descriptions with `all-mpnet-base-v2`, and perform agglomerative clustering with a threshold given by the 99th percentile cosine similarity of these dense embeddings; for each cluster, only the concept with the highest detection accuracy score is plotted.

of the entirety of the discovery framework. The next 10 largest well-interpreted discoveries are plotted in Figure 3, and the remaining well-interpreted discoveries can be viewed in Appendix Section 6.3.

The discoveries made with the proposed framework automatically replicate the finding that the "pent-up demand" narrative increases prominently in the treatment group. Concept 1174, described as "words like 'consumer,' 'demand,' 'spending,' " increases by nearly the same amount as the original, manually coded pent-up demand feature. Many other concepts (in the top 20 alone) reference demand, spending, or pandemic recovery, echoing highly specific elements of the treatment narrative[37] and making it appear plausible that respondents are acting in part due to some social desirability bias.[38]

The original finding that a narrative about an "energy crisis" decreases in the treatment group is qualified by running the proposed framework: no specific SAE concepts regarding energy decrease in presence in the treatment group, but many concepts about the Russia-Ukraine War (1885, 2854, 8502, 1676) and international or global actors (1198, 532, 4906) do. As the authors note, "At the time of the experiment, the energy crisis had just been exacerbated by Russia's invasion of Ukraine," suggesting that the true effect of the treatment narrative about pent-up demand in the U.S. post-pandemic may have been to dampen respondents' broader beliefs about the role of international forces in contributing to rising inflation (a "global-to-local" narrative belief shift).

Lastly, there are several discoveries made by the proposed framework that seem to characterize a new class of treatment effects missed by the original hand-coding scheme, which one might label "narrative amplification." These include large treatment effects on concepts 5613 ("words expressing greed, excess desire, or entitlement") and 1754 ("phrases about Biden taking/becoming office"), both of which are common inflation narratives held by non-experts.[39] This is to say that a U.S.-specific treatment narrative may have reinforced some respondents' plausibly pre-existing narratives centered around domestic U.S. political factors.

If we instead apply (1-)FWER controlled multiple testing at the same $\alpha = 0.05$, the framework only yields 65% of these discoveries, in particular missing some of the "narrative amplification" discoveries discussed above.[40]

A complementary survey experiment run by Andre et al. [2026] (detailed in Appendix G.1) studies to what extent respondents adopt narratives they encounter in "endogenously chosen" (self-selected) news media content. In this experiment, respondents in the treatment group are instructed to spend 5 minutes reading a newspaper article of their choice about U.S. inflation, whereas respondents in the control group are asked to do the same for an article on a topic unrelated to inflation (specifically, "tourist attractions in Miami"), with both groups being provided a small monetary incentive to summarize the articles. Then, in a follow-up survey, respondents' narratives for the recent surge in inflation are elicited with an open-text response. The result is a nearly 7 p.p. increase in the presence of a hand-coded "residual demand" factor and nearly 10 p.p. increases in the presence of both the hand-coded

[37] See Appendix Section H.3 of Andre et al. [2026] for the exact statement.

[38] As speculated, but not confirmed, in footnote 21 of Andre et al. [2026].

[39] See Section 4.1 of Andre et al. [2026].

[40] That is, 106 discoveries are made with FWER control, which is only slightly better than a Bonferroni correction, which results in 97 discoveries being made.




Figure 2: Well-Interpreted Discoveries for the First Narrative Provision Experiment of Andre et al. [2026], Rank 1-10.

"pandemic" narrative factor and "residual supply" narrative factor.[41]

For this experiment, using the same concept embedding and explainer LLM setup as discussed above with a 10% held-out evaluation set yields a dataset for analysis with $n = 673$ and $p = 5548$. Testing analogously formed null hypotheses, implementing a high-dimensional (1-)FWER controlled multiple testing procedure with $\alpha = 0.05$ only returns 3 discoveries, none of which yield any deep insight (e.g., concept 770 is "the word 'a/an' before 'result,"' and none of these discoveries have descriptions that pass the formally described criterion for being well-interpreted).[42] However, implementing 5-FWER control at $\alpha = 0.05$ upturns 17 discoveries. That is, by large sample guarantee of Theorem 6, the probability of making 5 or more false rejections with this procedure is at most 5% across repeated samples, and so, informally speaking, we would have high (frequentist) confidence that *at least* 13 of these 17 discoveries are genuine. Well-interpreted discoveries are plotted in Figure 4, and suggest that endogenous uptake of news-based inflation narratives significantly increases respondent narratives involving notions of supply and demand (an automatic replication of the discoveries from the original analysis) as well as consumer spending, specific economics jargon (suggesting parroting of the media content), and labor supply shortages (previously undocumented).

All of this analysis was performed automatically, in a handful of minutes, on a single A100

[41] See Appendix Figure B.10 of Andre et al. [2026].

[42] Bonferroni correction applied in this setting returns the same 3 discoveries.




Figure 3: Well-Interpreted Discoveries for the First Narrative Provision Experiment of Andre et al. [2026], Rank 11-20.

GPU in Google Colab (accessed for free, as a student or university affiliate). The API calls to Claude cost only cents, and could also be replaced with open-source model generations for free. Though this analysis was not preregistered, it is possible to cheaply and automatically replicate these results, and assess their sensitivity to different autointerpretation strategies, concept embedding implementations, and testing hyperparameters. Notably, the space of possible concepts was not pruned in any way prior to this analysis. Discoveries and their interpretations were made without human intervention, with no room for data snooping.

4.2 Reanalyzing Bursztyn et al. [2023]

Another inspiration for Example 1, Bursztyn et al. [2023] study how the provision of "social cover" affects willingness to publicly dissent to socially stigmatized causes, and the perception of this dissent. As a key application of their theory, Bursztyn et al. [2023] run an information treatment experiment (Experiment 2) in which participants are told they have been matched with another (fictional) respondent that chose to join a campaign to *oppose defunding the police* (a plausible expression of dissent in liberal American politics at the time the experiment was conducted), and are then shown a tweet that the matched respondent is said to have posted. This tweet has been randomized to either provide or not provide some "social cover" for the fictional matched respondent's plausibly contentious statement, namely whether or not the tweet indicated that the matched respondent joined the campaign before reading




Figure 4: Well-Interpreted Discoveries for the Media Narrative Provision Experiment of Andre et al. [2026].

an evidence-based article in support of it (the no social cover condition) or after (the social cover condition).[43]

A key outcome collected by this experiment is the participant's open-ended text response to the question "Why do you think your matched respondent chose to join the campaign to oppose defunding the police?" This open-ended text response is meant to capture the causal effect of social cover on the perception of dissent. Towards this goal, Bursztyn et al. [2023] compute a Pearson's χ^2 statistic for all phrases of up to three words per Gentzkow and Shapiro [2010], which they use as an index to rank the phrases that are most differentially expressed in each condition's open-ended responses.[44] The richness of the results of this analysis is, naturally, hindered by the coarseness of the featurization of the text as three word phrases, as well as the fact that there are no obvious estimands or inferential guarantees. The only qualitative conclusion gleaned by Bursztyn et al. [2023] from this quantitative exercise is: "we find that respondents in the Cover condition are more likely to use phrases related to the article or the associated evidence—for example, 'article,' 'read,' 'convincing,' or 'increase in crime.' "[45]

[43]See Online Appendix Figure B.3 of Bursztyn et al. [2023] for a schematic of the experimental design.

[44]Specifically, it is a Pearson's χ^2 statistic for a null hypothesis that the propensity to use a given phrase is equal across conditions, per Gentzkow and Shapiro [2010]. We interpret these statistics as simply forming an index, however, because the results of these hypothesis tests are not reported, and no multiple hypothesis testing corrections are implemented.

[45]The Online Appendix Table B.11 of Bursztyn et al. [2023] contains the top ten characteristic phrases in

Do we make more (and more interpretable) discoveries with the framework proposed in this paper? To investigate, we apply the same concept embedding and explainer LLM setup as in Section 4.1. A small held-out evaluation dataset is created by sample splitting, using just 15% of the original dataset in Bursztyn et al. [2023].

The hypotheses of interest are, for all $j \in [p]$,

$$H_{0,j} : \theta_j(P) = E[Y_{ij}(1) - Y_{ij}(0)] = E\left[\frac{W_i - \pi}{\pi(1-\pi)} Y_{ij}\right] = 0,$$

for $\pi = 0.5$, and where the event $\{W_i = 1\}$ indicates the social cover condition. This yields a dataset for analysis where $n = 879$ and $p = 4697$.

We can again consider whether or not controlling the (1-)FWER would be too conservative for the purposes of meaningful discovery in this setting. To explore this, we set $k = 1$ and $\alpha = 0.05$,[46] and we obtain just 5 rejections of nulls from high-dimensional multiple testing. These include: a 14.8 percentage point causal effect on the presence of concept 1786; a 14.8 p.p. causal effect on the presence of concept 8565; an 8.9 p.p. causal effect on concept 3869; a 12.5 p.p. causal effect on concept 4335; and a 11.1 p.p. causal effect on concept 1503. The automatic interpretations of these concepts corroborate the original qualitative findings of Bursztyn et al. [2023]: concept 1786 is described as activating on mentions of "references to the Washington Post as a cited source"; concept 8565 on "the word 'article' referring to a cited source"; concept 3869 on "reading or encountering an article with information"; concept 4335 on "references to articles or editorials as persuasive sources"; and concept 1503 on "verbs and phrases describing what an article says or implies." However, we only discover 5 significant causal effects, and again do not gain much new insight relative to the original analysis—even if the discovery and interpretation of these concepts was transparent, principled, and automatic.

We now apply the discovery framework setting $k = 5$, still with $\alpha = 0.05$, per the method of Theorem 4.[47] Just with 5-FWER control, we obtain 15 rejections of the null, or 15 discoveries. Again, by large sample guarantee of Theorem 4, the probability of making 5 or more false rejections with this procedure is at most 5% across repeated samples, and so, informally, in the frequentist sense, we would have high confidence that *at least* 11 of these 15 discoveries are genuine.[48]

In Figure 5, we again display the 10 largest well-interpreted discoveries. The remaining well-interpreted discoveries can be viewed in Appendix Section 6.3. In this plot, the previous concepts discovered with (1-)FWER control appear, as well as others absent from both that analysis and the original analysis in Bursztyn et al. [2023].

Though there is some conceptual redundancy in the discoveries—which we may have anticipated, based on earlier discussion related to, e.g., Bhalla et al. [2026a]—in totality

each condition based on the χ^2 index.

[46] Equivalently, we implement the high-dimensional FWER controlling procedure of Belloni et al. [2018].

[47] In practice, placebo tests reveal that high-dimensional k-FWER control *in this particular example* seems reliable even at fairly large k, i.e., k can be over 1700 before encountering more rejections than should be permitted.

[48] To get a better sense for which discoveries are plausibly true, informally, one might consider re-running the algorithm of Theorem 4 at increasing values of k, and noting at which k each hypothesis enters the selected set.




Figure 5: Well-Interpreted Discoveries for Experiment 2 of Bursztyn et al. [2023], Rank 1-10.

these discoveries recover many findings in Bursztyn et al. [2023] that otherwise required full additional experiments to learn. For example, concept 2443 responds to "academic credentials and scholarly authority" and increases by nearly 10 percentage points in the treatment group, indicating that—exactly as Bursztyn et al. [2023] posit, and run a separate experiment to further probe—the social cover mechanism plausibly relies on the perceived credibility of the article cited. Concept 7927 (the 13th largest well-interpreted discovery, viewable in Appendix Figure 16) responds to "being persuaded or convinced by arguments," and its probability of activation is increased by just over 7 percentage points in the treatment group. This is direct validation of the authors' manipulation leading to "the (implicit) justification that they joined the campaign because they were persuaded by the article's claims"—exactly as intended, but something that Bursztyn et al. [2023] otherwise needed to run Auxiliary Experiment 4 to confirm.

4.3 Reanalyzing Noy and Zhang [2023]

An inspiration for Example 3, Noy and Zhang [2023] are interested in studying the causal effects of AI assistance on task-level productivity. Specifically, they run an RCT where midlevel professional writing tasks are assigned to hundreds of college-educated professionals, and access to ChatGPT (GPT 3.5) is randomly provided to half of the participants. In practice, in the ChatGPT-exposed treatment arm, there is 80% adoption of the AI tool for completing the writing assignment. The headline findings of the original experiment (Figure

1) are that average time spent on the writing task decreases by 40%, and a human-assessed quality "grade" (scored from 1-7) increases by 18%.

Perceived quality of the writing increased, but why? Can we discover interpretable causal effects of AI assistance on writing using the written outputs themselves? To investigate this, we apply the discovery framework to a subset of the experimental sample consisting of HR professionals and managers, all of whom were given the same writing task: drafting a company-wide email on a sensitive topic. Again, we use the same concept embedding and explainer LLM setup as in Section 4.2 and a held-out evaluation sample consisting of 20% of the original (email task) dataset. Task outputs are truncated to a maximum length of 1500 characters.

The hypotheses tested are again of the form discussed in Example 4,

$$H_{0,j} : \theta_j(P) = E_P[\widetilde{T}_i^2]^{-1} E_P[\widetilde{T}_i \, \widetilde{Y}_{ij}] = 0,$$

where $\widetilde{Y}_{ij}$ is an indicator for concept j in the concept embedding and $\widetilde{T}_i$ is the treatment indicator, both residualized with the same controls used in the participant-level regression specification that produced the primary results of the original study (i.e., the specification S.1 in the supplemental appendix of Noy and Zhang [2023]). This yields a dataset with $n = 138$ and $p = 5435$ non-degenerate features. We again apply 5-FWER control with $\alpha = 0.05$, based on the result of Theorem 6, and we make 128 interpretable discoveries.[49] In Figure 6, we again plot the 10 largest well-interpreted discoveries, and in Figure 7 the next 10 largest, with the remaining well-interpreted discoveries viewable in Appendix Section 6.3.

The discoveries made suggest that ChatGPT assistance has large causal effects on the inclusion and exclusion of specific phrases and words. Concepts 4179, 1060, and 3320 pick up on GenAI causing emails to use the specific phrase "I hope this email finds you well." The causal effect on concept 5073 indicates the removal of "Good..." as an email salutation. A large causal effect on concept 3644 indicates the words "finds" and "found" go up in treatment; similarly for the phrase "want to" (concept 2861) and "we believe" (concept 4234) and "concerned" (concept 5208) and the transitional phrases "in addition" or "additionally" (concept 4465). Broadly, these findings corroborate a growing literature in human-computer interaction documenting that AI assistance on tasks homogenizes outputs, narrowing creative diversity [Jo and Raghavan, 2026].

Concepts 4299, 2689, 9037, 7200, and 1811 all increase significantly in the treatment group, and map to usage of language indicating understanding, (re)assurance, and collaboration—that is, positively valenced, empathetic language. Other discoveries, such as the negative causal effects on concepts 2147, 908, 6462, 4029, and 2431 suggest that ChatGPT exposure reduces rhetorical/linguistic/grammatical informality, e.g., reducing sentence-ending exclamation points and informal use of words like "so," "get," and "go." Collectively, these insights hint at possible mechanisms for the perceived increase in email quality.

5 Conclusion

Literatures across empirical economics and econometrics have increasingly suggested the importance of discovery from high-dimensional or unstructured data (e.g., Ludwig et al.

[49] With (1-)FWER control, only 46 discoveries are made.




Figure 6: Well-Interpreted Discoveries for Noy and Zhang [2023], Rank 1-10.

[2017], Ludwig and Mullainathan [2024], Chernozhukov et al. [2025], Haaland et al. [2024], Dell and Rambachan [2026]). The framework proposed in this paper shows how newly validated statistical procedures for high-dimensional multiple testing, when combined with measurement techniques based on the latest innovations in AI interpretability, can facilitate such discovery with higher practicality and higher fidelity than previously possible.

It is worth noting that problems surrounding post-selection inference, researcher degrees of freedom, and motivated data mining have been taken very seriously in other literatures, such as the analysis of RCTs in economics, where these concerns motivated the creation of preanalysis plans (PAPs) for experiments. One analogy for the proposed framework, then, is that it provides similar value to a PAP for the setting of discovery from unstructured data. Just like a PAP, the proposed framework can be accompanied by contingent, complementary analyses of the unstructured dataset, so long as these analyses are evaluated by readers with the appropriate skepticism [Banerjee et al., 2020]. However, unlike writing a comprehensive PAP for an experiment, the proposed framework places very little burden on the researcher: the same default template for analysis (the concepts measured by the SAE) can be reused across many diverse empirical settings. In fact, the credibility of analysis is bolstered by not deviating from a default choice of SAE.[50]

Having a well-defined and intuitive quantitative method for evaluating concept description

[50]When the unstructured data being analyzed literally comes from an experiment, preregistration of the proposed framework in an actual PAP is also easily declared (it simply involves stipulating a particular choice of explainer LLM and SAE under the default proposed concept embedding strategy).




Figure 7: Well-Interpreted Discoveries for Noy and Zhang [2023], Rank 11-20.

quality is important in the context of the proposed framework, as it is these descriptions on which the scientific conclusions of discovery ultimately rest. By formulating autointerp evaluation as a statistical inference problem, the importance of evaluation with respect to the actual population of interest P becomes salient ("locality"); the need for assembling an independent hold-out dataset (e.g., via sample splitting) becomes clear; the role for confidence intervals becomes legible by appeal to sampling uncertainty (c.f., Miller [2024]); and we further unlock useful connections to the literature on post-selection inference, such that we may discipline settings evaluating a multiplicity of interpretations (c.f., Andrews et al. [2024]).

It is important to reiterate that the proposed framework is compatible with many possible high-dimensional measurement technologies of concepts. The use of sparse dictionary learning models, and SAEs in particular, is viewed as a powerful *default* recommendation for creating high-dimensional concept embeddings: even if prone to some noise and redundancy, it is both rich and broad as a measurement technology, as well as compute-efficient. That said, alternative choices of high-dimensional concept embedding may be more appealing depending on the use case of interest—ranging from a high-dimensional collection of data-independently curated zero-shot classifiers to alternative interpretability models like Predictive Concept Decoders [Huang et al., 2025]. An important future direction of work might also involve engineering a new "social science default" concept embedding that is tailored to a large

space of highly social science relevant concepts.[51]

The proposed framework is most naturally viewed as one tool of many in the empirical researcher's toolkit for making discoveries from unstructured data. In practice, applying this framework alongside others could produce complementary scientific insights, or otherwise serve to enrich a researcher's understanding of their unstructured dataset.

[51] We thank Jenny S. Wang for this suggestion.

References

Arman Khachiyan, Anthony Thomas, Huye Zhou, Gordon Hanson, Alex Cloninger, Tajana Rosing, and Amit K. Khandelwal. Using Neural Networks to Predict Microspatial Economic Growth. *American Economic Review: Insights*, 4(4):491–506, December 2022. ISSN 2640-205X, 2640-2068. doi: 10.1257/aeri.20210422. URL https://pubs.aeaweb.org/doi/10.1257/aeri.20210422.

Yuriy Gorodnichenko, Tho Pham, and Oleksandr Talavera. The Voice of Monetary Policy. *American Economic Review*, 113(2):548–584, February 2023. ISSN 0002-8282. doi: 10.1257/aer.20220129. URL https://pubs.aeaweb.org/doi/10.1257/aer.20220129.

Allen Hu and Song Ma. Persuading Investors: A Video-Based Study. *The Journal of Finance*, 80(5):2639–2688, October 2025. ISSN 0022-1082, 1540-6261. doi: 10.1111/jofi.13471. URL https://onlinelibrary.wiley.com/doi/10.1111/jofi.13471.

Jens Ludwig and Sendhil Mullainathan. Machine Learning as a Tool for Hypothesis Generation. *The Quarterly Journal of Economics*, 139(2):751–827, March 2024. ISSN 0033-5533, 1531-4650. doi: 10.1093/qje/qjad055. URL https://academic.oup.com/qje/article/139/2/751/7515309.

Clément Gorin, Stephan Heblich, and Yanos Zylberberg. State of the Art: Economic Development Through the Lens of Paintings. Technical Report w33976, National Bureau of Economic Research, Cambridge, MA, June 2025. URL http://www.nber.org/papers/w33976.pdf.

David Lagakos, Stelios Michalopoulos, and Hans-Joachim Voth. American Life Histories. Technical Report w33373, National Bureau of Economic Research, Cambridge, MA, January 2025. URL http://www.nber.org/papers/w33373.pdf.

Peter Bergman, Raj Chetty, Stefanie DeLuca, Nathaniel Hendren, Lawrence F. Katz, and Christopher Palmer. Creating Moves to Opportunity: Experimental Evidence on Barriers to Neighborhood Choice. *American Economic Review*, 114(5):1281–1337, May 2024. ISSN 0002-8282. doi: 10.1257/aer.20200407. URL https://pubs.aeaweb.org/doi/10.1257/aer.20200407.

Patrick Krause, Elizabeth Rhodes, Sarah Miller, Alexander Bartik, David Broockman, and Eva Vivalt. The Impact of Unconditional Cash Transfers on Parenting and Children. Technical Report w34040, National Bureau of Economic Research, Cambridge, MA, July 2025. URL http://www.nber.org/papers/w34040.pdf.

Majid Ahmadi, Imrul Huda, John A. List, Arnoldo Müller-Molina, Julie Pernaudet, Ajay Sailopal, and Dana Suskind. Leveraging Artificial Intelligence and Field Experiments to Explore Novel Features of Parental Speech and Foster Child Development, 2026. URL https://www.ssrn.com/abstract=6902758.

Leonardo Bursztyn, Georgy Egorov, Ingar Haaland, Aakaash Rao, and Christopher Roth. Justifying Dissent. *The Quarterly Journal of Economics*, 138(3):1403–1451, June 2023.

ISSN 0033-5533, 1531-4650. doi: 10.1093/qje/qjad007. URL https://academic.oup.com/qje/article/138/3/1403/7000850.

Peter Andre, Ingar Haaland, Christopher Roth, Mirko Wiederholt, and Johannes Wohlfart. Narratives about the Macroeconomy. *Review of Economic Studies*, page rdag014, February 2026. ISSN 0034-6527, 1467-937X. doi: 10.1093/restud/rdag014. URL https://academic.oup.com/restud/advance-article/doi/10.1093/restud/rdag014/8489219.

Peter Andre, Carlo Pizzinelli, Christopher Roth, and Johannes Wohlfart. Subjective Models of the Macroeconomy: Evidence From Experts and Representative Samples. *The Review of Economic Studies*, 89(6):2958–2991, November 2022. ISSN 0034-6527, 1467-937X. doi: 10.1093/restud/rdac008. URL https://academic.oup.com/restud/article/89/6/2958/6531988.

Stefanie Stantcheva. Why Do We Dislike Inflation? Technical Report w32300, National Bureau of Economic Research, Cambridge, MA, April 2024. URL http://www.nber.org/papers/w32300.pdf.

Shakked Noy and Whitney Zhang. Experimental evidence on the productivity effects of generative artificial intelligence. *Science*, 381(6654):187–192, July 2023. ISSN 0036-8075, 1095-9203. doi: 10.1126/science.adh2586. URL https://www.science.org/doi/10.1126/science.adh2586.

Usha Bhalla, Alex Oesterling, Suraj Srinivas, Flavio P. Calmon, and Himabindu Lakkaraju. Interpreting CLIP with Sparse Linear Concept Embeddings (SpLiCE), 2024. URL https://arxiv.org/abs/2402.10376. Version Number: 2.

Nick Jiang, Xiaoqing Sun, Lisa Dunlap, Lewis Smith, and Neel Nanda. Interpretable Embeddings with Sparse Autoencoders: A Data Analysis Toolkit, 2025. URL https://arxiv.org/abs/2512.10092. Version Number: 1.

Trenton Bricken, Adly Templeton, Joshua Batson, Brian Chen, Adam Jermyn, Tom Conerly, Nick Turner, Cem Anil, Carson Denison, Amanda Askell, Robert Lasenby, Yifan Wu, Shauna Kravec, Nicholas Schiefer, Tim Maxwell, Nicholas Joseph, Zac Hatfield-Dodds, Alex Tamkin, Karina Nguyen, Brayden McLean, Josiah E Burke, Tristan Hume, Shan Carter, Tom Henighan, and Christopher Olah. Towards monosemanticity: Decomposing language models with dictionary learning. *Transformer Circuits Thread*, 2023. https://transformer-circuits.pub/2023/monosemantic-features/index.html.

Joseph P. Romano and Michael Wolf. Control of generalized error rates in multiple testing. *The Annals of Statistics*, 35(4), August 2007. ISSN 0090-5364. doi: 10.1214/009053606000001622. URL https://projecteuclid.org/journals/annals-of-statistics/volume-35/issue-4/Control-of-generalized-error-rates-in-multiple-testing/10.1214/009053606000001622.full.

David M Blei, Andrew Y Ng, and Michael I Jordan. Latent dirichlet allocation. *Journal of Machine Learning Research*, 3(Jan):993–1022, 2003.

Gonçalo Paulo, Alex Mallen, Caden Juang, and Nora Belrose. Automatically Interpreting Millions of Features in Large Language Models, 2024. URL https://arxiv.org/abs/2410.13928. Version Number: 3.

Junxuan Wang, Xuyang Ge, Wentao Shu, Qiong Tang, Yunhua Zhou, Zhengfu He, and Xipeng Qiu. Towards universality: Studying mechanistic similarity across language model architectures. In *The Thirteenth International Conference on Learning Representations*, 2025. URL https://openreview.net/forum?id=2J18i8T0oI.

Ingar Haaland, Christopher Roth, Stefanie Stantcheva, and Johannes Wohlfart. Understanding Economic Behavior Using Open-ended Survey Data. Technical Report w32421, National Bureau of Economic Research, Cambridge, MA, May 2024. URL http://www.nber.org/papers/w32421.pdf.

Sendhil Mullainathan and Jann Spiess. Machine Learning: An Applied Econometric Approach. *Journal of Economic Perspectives*, 31(2):87–106, May 2017. ISSN 0895-3309. doi: 10.1257/jep.31.2.87. URL https://pubs.aeaweb.org/doi/10.1257/jep.31.2.87.

Friedrich Geiecke and Xavier Jaravel. Conversations at Scale: Robust AI-led Interviews with a Simple Open-Source Platform , 2024. URL https://www.ssrn.com/abstract=4974382.

Drew Fudenberg, Jon Kleinberg, Annie Liang, and Sendhil Mullainathan. Measuring the Completeness of Economic Models. *Journal of Political Economy*, 130(4):956–990, April 2022. ISSN 0022-3808, 1537-534X. doi: 10.1086/718371. URL https://www.journals.uchicago.edu/doi/10.1086/718371.

Iman Modarressi, Jann Spiess, and Amar Venugopal. Causal Inference on Outcomes Learned from Text, 2025. URL https://arxiv.org/abs/2503.00725. Version Number: 1.

Alexandre Belloni, Victor Chernozhukov, Denis Chetverikov, Christian Hansen, and Kengo Kato. High-Dimensional Econometrics and Regularized GMM, 2018. URL https://arxiv.org/abs/1806.01888. Version Number: 2.

Rajiv Movva, Kenny Peng, Nikhil Garg, Jon Kleinberg, and Emma Pierson. Sparse Autoencoders for Hypothesis Generation, 2025. URL https://arxiv.org/abs/2502.04382. Version Number: 3.

Matthew Gentzkow, Bryan Kelly, and Matt Taddy. Text as Data. *Journal of Economic Literature*, 57(3):535–574, September 2019a. ISSN 0022-0515. doi: 10.1257/jel.20181020. URL https://pubs.aeaweb.org/doi/10.1257/jel.20181020.

Elliott Ash and Stephen Hansen. Text Algorithms in Economics. *Annual Review of Economics*, 15(1):659–688, September 2023. ISSN 1941-1383, 1941-1391. doi: 10.1146/annurev-economics-082222-074352. URL https://www.annualreviews.org/content/journals/10.1146/annurev-economics-082222-074352.

Melissa Dell. Deep Learning for Economists. *Journal of Economic Literature*, 63(1):5–58, March 2025. ISSN 0022-0515, 2328-8175. doi: 10.1257/jel.20241733. URL https://pubs.aeaweb.org/doi/10.1257/jel.20241733.

Anastasios N. Angelopoulos, Stephen Bates, Clara Fannjiang, Michael I. Jordan, and Tijana Zrnic. Prediction-powered inference. *Science*, 382(6671):669–674, November 2023. doi: 10.1126/science.adi6000. URL https://www.science.org/doi/10.1126/science.adi6000. Publisher: American Association for the Advancement of Science.

Jens Ludwig, Sendhil Mullainathan, and Ashesh Rambachan. Large Language Models: An Applied Econometric Framework, December 2024. URL http://arxiv.org/abs/2412.07031. arXiv:2412.07031 [econ].

Jacob Carlson and Melissa Dell. A Unifying Framework for Robust and Efficient Inference with Unstructured Data, 2025. URL https://arxiv.org/abs/2505.00282. Version Number: 2.

Ashesh Rambachan, Rahul Singh, and Davide Viviano. Program Evaluation with Remotely Sensed Outcomes, 2024. URL https://arxiv.org/abs/2411.10959. Version Number: 2.

Matthew Gentzkow, Jesse M. Shapiro, and Matt Taddy. Measuring Group Differences in High-Dimensional Choices: Method and Application to Congressional Speech. *Econometrica*, 87(4):1307–1340, 2019b. ISSN 0012-9682. doi: 10.3982/ECTA16566. URL https://www.econometricsociety.org/doi/10.3982/ECTA16566.

Laura Battaglia, Timothy Christensen, Stephen Hansen, and Szymon Sacher. Inference for Regression with Variables Generated by AI or Machine Learning, 2024. URL https://arxiv.org/abs/2402.15585. Version Number: 5.

Jens Ludwig, Sendhil Mullainathan, and Jann Spiess. Machine-Learning Tests for Effects on Multiple Outcomes, 2017. URL https://arxiv.org/abs/1707.01473. Version Number: 2.

Joseph P. Romano, Azeem M. Shaikh, and Michael Wolf. Hypothesis Testing in Econometrics. *Annual Review of Economics*, 2(1):75–104, September 2010. ISSN 1941-1383, 1941-1391. doi: 10.1146/annurev.economics.102308.124342. URL https://www.annualreviews.org/doi/10.1146/annurev.economics.102308.124342.

Yoav Benjamini and Yosef Hochberg. Controlling the False Discovery Rate: A Practical and Powerful Approach to Multiple Testing. *Journal of the Royal Statistical Society. Series B (Methodological)*, 57(1):289–300, 1995. ISSN 00359246. URL http://www.jstor.org/stable/2346101. Publisher: [Royal Statistical Society, Oxford University Press].

William Fithian and Lihua Lei. Conditional calibration for false discovery rate control under dependence. *The Annals of Statistics*, 50(6), December 2022. ISSN 0090-5364. doi: 10.1214/21-AOS2137. URL https://projecteuclid.org/journals/annals-of-statistics/volume-50/issue-6/

Conditional-calibration-for-false-discovery-rate-control-under-dependence/10.1214/21-AOS2137.full.

Yoav Benjamini and Daniel Yekutieli. The Control of the False Discovery Rate in Multiple Testing under Dependency. *The Annals of Statistics*, 29(4):1165–1188, 2001. ISSN 00905364, 21688966. URL http://www.jstor.org/stable/2674075. Publisher: Institute of Mathematical Statistics.

Rina Foygel Barber and Emmanuel J. Candès. Controlling the false discovery rate via knockoffs. *The Annals of Statistics*, 43(5), October 2015. ISSN 0090-5364. doi: 10.1214/15-AOS1337. URL https://projecteuclid.org/journals/annals-of-statistics/volume-43/issue-5/Controlling-the-false-discovery-rate-via-knockoffs/10.1214/15-AOS1337.full.

Emmanuel Candès, Yingying Fan, Lucas Janson, and Jinchi Lv. Panning for Gold: 'Model-X' Knockoffs for High Dimensional Controlled Variable Selection. *Journal of the Royal Statistical Society Series B: Statistical Methodology*, 80(3):551–577, June 2018. ISSN 1369-7412, 1467-9868. doi: 10.1111/rssb.12265. URL https://academic.oup.com/jrsssb/article/80/3/551/7048447.

Rina Foygel Barber and Emmanuel J. Candès. A knockoff filter for high-dimensional selective inference. *The Annals of Statistics*, 47(5), October 2019. ISSN 0090-5364. doi: 10.1214/18-AOS1755. URL https://projecteuclid.org/journals/annals-of-statistics/volume-47/issue-5/A-knockoff-filter-for-high-dimensional-selective-inference/10.1214/18-AOS1755.full.

Lucas Janson and Weijie Su. Familywise error rate control via knockoffs. *Electronic Journal of Statistics*, 10(1), January 2016. ISSN 1935-7524. doi: 10.1214/16-EJS1129. URL https://projecteuclid.org/journals/electronic-journal-of-statistics/volume-10/issue-1/Familywise-error-rate-control-via-knockoffs/10.1214/16-EJS1129.full.

Victor Chernozhuokov, Denis Chetverikov, Kengo Kato, and Yuta Koike. Improved central limit theorem and bootstrap approximations in high dimensions. *The Annals of Statistics*, 50(5), October 2022. ISSN 0090-5364. doi: 10.1214/22-AOS2193. URL https://projecteuclid.org/journals/annals-of-statistics/volume-50/issue-5/Improved-central-limit-theorem-and-bootstrap-approximations-in-high-dimensions/10.1214/22-AOS2193.full.

Yixi Ding, Qizhai Li, Yuke Shi, and Liuquan Sun. Gaussian Multiplier Bootstrap Procedure for the k-th Largest Coordinate of High-Dimensional Statistics, 2025. URL https://arxiv.org/abs/2508.14400v1. Version Number: 1.

Long Feng. High Dimensional Bootstrap and Asymptotic Expansion for the k-th Largest Coordinate, April 2026. URL http://arxiv.org/abs/2604.04785. arXiv:2604.04785 [math.ST].

Joseph P. Romano, Azeem M. Shaikh, and Michael Wolf. FORMALIZED DATA SNOOPING BASED ON GENERALIZED ERROR RATES. *Econometric Theory*, 24 (02), April 2008. ISSN 0266-4666, 1469-4360. doi: 10.1017/S0266466608080171. URL http://www.journals.cambridge.org/abstract_S0266466608080171.

Weidong Liu and Qi-Man Shao. Phase transition and regularized bootstrap in large-scale t-tests with false discovery rate control. *The Annals of Statistics*, 42 (5), October 2014. ISSN 0090-5364. doi: 10.1214/14-AOS1249. URL https://projecteuclid.org/journals/annals-of-statistics/volume-42/issue-5/Phase-transition-and-regularized-bootstrap-in-large-scale-t-tests/10.1214/14-AOS1249.full.

Ruiqi Zhong, Peter Zhang, Steve Li, Jinwoo Ahn, Dan Klein, and Jacob Steinhardt. Goal Driven Discovery of Distributional Differences via Language Descriptions, 2023. URL https://arxiv.org/abs/2302.14233. Version Number: 2.

Melissa Dell and Ashesh Rambachan. The Measurement Revolution? Credible Measurement and Inference in the Age of AI. Technical Report w35744, National Bureau of Economic Research, Cambridge, MA, September 2026. URL http://www.nber.org/papers/w35744.pdf.

Kenny Peng, Rajiv Movva, Jon Kleinberg, Emma Pierson, and Nikhil Garg. Use Sparse Autoencoders to Discover Unknown Concepts, Not to Act on Known Concepts, 2025. URL https://arxiv.org/abs/2506.23845. Version Number: 1.

Jenny S Wang, Aliya Saperstein, and Emma Pierson. In your own words: computationally identifying interpretable themes in free-text survey data, 2026. URL https://arxiv.org/abs/2603.26930. Version Number: 2.

Finale Doshi-Velez and Been Kim. Towards A Rigorous Science of Interpretable Machine Learning, 2017. URL https://arxiv.org/abs/1702.08608. Version Number: 2.

Adly Templeton, Tom Conerly, Jonathan Marcus, Jack Lindsey, Trenton Bricken, Brian Chen, Adam Pearce, Craig Citro, Emmanuel Ameisen, Andy Jones, Hoagy Cunningham, Nicholas L Turner, Callum McDougall, Monte MacDiarmid, C. Daniel Freeman, Theodore R. Sumers, Edward Rees, Joshua Batson, Adam Jermyn, Shan Carter, Chris Olah, and Tom Henighan. Scaling monosemanticity: Extracting interpretable features from claude 3 sonnet. *Transformer Circuits Thread*, 2024. URL https://transformer-circuits.pub/2024/scaling-monosemanticity/index.html.

Patrick Leask, Bart Bussmann, Michael Pearce, Joseph Bloom, Curt Tigges, Noura Al Moubayed, Lee Sharkey, and Neel Nanda. Sparse Autoencoders Do Not Find Canonical Units of Analysis, February 2025. URL http://arxiv.org/abs/2502.04878. arXiv:2502.04878 [cs].

Gonçalo Paulo, Stepan Shabalin, and Nora Belrose. Transcoders Beat Sparse Autoencoders for Interpretability, 2025. URL https://arxiv.org/abs/2501.18823. Version Number: 2.

Steven Bills, Nick Cammarata, Dan Mossing, Henk Tillman, Leo Gao, Gabriel Goh, Ilya Sutskever, Jan Leike, Jeff Wu, and William Saunders. Language models can explain neurons in language models. https://openaipublic.blob.core.windows.net/neuron-explainer/paper/index.html, 2023.

Tamar Rott Shaham, Sarah Schwettmann, Franklin Wang, Achyuta Rajaram, Evan Hernandez, Jacob Andreas, and Antonio Torralba. A Multimodal Automated Interpretability Agent, 2024. URL https://arxiv.org/abs/2404.14394. Version Number: 2.

Senthooran Rajamanoharan, Tom Lieberum, Nicolas Sonnerat, Arthur Conmy, Vikrant Varma, János Kramár, and Neel Nanda. Jumping Ahead: Improving Reconstruction Fidelity with JumpReLU Sparse Autoencoders, 2024. URL https://arxiv.org/abs/2407.14435. Version Number: 3.

Ahmed Abdulaal, Hugo Fry, Nina Montaña-Brown, Ayodeji Ijishakin, Jack Gao, Stephanie Hyland, Daniel C. Alexander, and Daniel C. Castro. An X-Ray Is Worth 15 Features: Sparse Autoencoders for Interpretable Radiology Report Generation, 2024. URL https://arxiv.org/abs/2410.03334. Version Number: 1.

Hugo Fry. Towards multimodal interpretability: Learning sparse interpretable features in vision transformers, Apr 2024. URL https://www.lesswrong.com/posts/iYFuZo9BMvr6GgMs5/case-study-interpreting-manipulating-and-controlling-clip. Accessed: 2024-05-16.

Gytis Daujotas. Case study: Interpreting, manipulating, and controlling clip with sparse autoencoders, Aug 2024. URL https://www.lesswrong.com/posts/iYFuZo9BMvr6GgMs5/case-study-interpreting-manipulating-and-controlling-clip. Accessed: 2025-10-03.

Daniel Pluth, Yu Zhou, and Vijay K. Gurbani. Sparse Autoencoder Insights on Voice Embeddings, 2025. URL https://arxiv.org/abs/2502.00127. Version Number: 1.

Thomas Fel, Matthew Kowal, Mozes Jacobs, Dron Hazra, Usha Bhalla, Lee Sharkey, Lucius Bushnaq, Satchel Grant, Tal Haklay, Thomas Icard, Can Rager, Michael Pearce, Daniel Wurgaft, Aiden Swann, Fenil Doshi, Siddharth Boppana, Curt Tigges, Nick Cammarata, Thomas Serre, Vasudev Shyam, Owen Lewis, Thomas McGrath, Jack Merullo, Ekdeep Singh Lubana, and Atticus Geiger. Structuring Sparsity: Block-Sparse Featurizers Capture Visual Concept Manifolds, 2026. URL https://arxiv.org/abs/2606.25234. Version Number: 1.

Naoki Egami, Christian J. Fong, Justin Grimmer, Margaret E. Roberts, and Brandon M. Stewart. How to make causal inferences using texts. *Science Advances*, 8(42):eabg2652, October 2022. ISSN 2375-2548. doi: 10.1126/sciadv.abg2652. URL https://www.science.org/doi/10.1126/sciadv.abg2652.

Hemanth Asirvatham, Elliott Mokski, and Andrei Shleifer. GPT as a Measurement Tool. Technical Report w34834, National Bureau of Economic Research, Cambridge, MA, February 2026. URL http://www.nber.org/papers/w34834.pdf.

Usha Bhalla, Thomas Fel, Can Rager, Sheridan Feucht, Tal Haklay, Daniel Wurgaft, Siddharth Boppana, Matthew Kowal, Vasudev Shyam, Jack Merullo, Atticus Geiger, and Ekdeep Singh Lubana. Do Sparse Autoencoders Capture Concept Manifolds?, 2026a. URL https://arxiv.org/abs/2604.28119. Version Number: 1.

Victor Chernozhukov, Denis Chetverikov, Kengo Kato, and Yuta Koike. High-Dimensional Data Bootstrap. *Annual Review of Statistics and Its Application*, 10(1):427–449, March 2023. ISSN 2326-8298, 2326-831X. doi: 10.1146/annurev-statistics-040120-022239. URL https://www.annualreviews.org/doi/10.1146/annurev-statistics-040120-022239.

Victor Chernozhukov, Denis Chetverikov, and Kengo Kato. Central limit theorems and bootstrap in high dimensions. *The Annals of Probability*, 45(4), July 2017. ISSN 0091-1798. doi: 10.1214/16-AOP1113. URL https://projecteuclid.org/journals/annals-of-probability/volume-45/issue-4/Central-limit-theorems-and-bootstrap-in-high-dimensions/10.1214/16-AOP1113.full.

Joseph P. Romano and Michael Wolf. Balanced control of generalized error rates. *The Annals of Statistics*, 38(1), February 2010. ISSN 0090-5364. doi: 10.1214/09-AOS734. URL https://projecteuclid.org/journals/annals-of-statistics/volume-38/issue-1/Balanced-control-of-generalized-error-rates/10.1214/09-AOS734.full.

Christopher R Genovese and Larry Wasserman. Exceedance Control of the False Discovery Proportion. *Journal of the American Statistical Association*, 101(476):1408–1417, December 2006. ISSN 0162-1459, 1537-274X. doi: 10.1198/016214506000000339. URL https://www.tandfonline.com/doi/full/10.1198/016214506000000339.

Joseph P. Romano and Azeem M. Shaikh. Stepup procedures for control of generalizations of the familywise error rate. *The Annals of Statistics*, 34(4), August 2006. ISSN 0090-5364. doi: 10.1214/009053606000000461. URL https://projecteuclid.org/journals/annals-of-statistics/volume-34/issue-4/Stepup-procedures-for-control-of-generalizations-of-the-familywise-error/10.1214/009053606000000461.full.

Dami Choi, Vincent Huang, Kevin Meng, Daniel D Johnson, Jacob Steinhardt, and Sarah Schwettmann. Scaling automatic neuron description. https://transluce.org/neuron-descriptions, October 2024.

Isaiah Andrews, Toru Kitagawa, and Adam McCloskey. Inference on Winners. *The Quarterly Journal of Economics*, 139(1):305–358, January 2024. ISSN 0033-5533, 1531-4650. doi: 10.1093/qje/qjad043. URL https://academic.oup.com/qje/article/139/1/305/7276491.

Usha Bhalla, Alex Oesterling, Claudio Mayrink Verdun, Himabindu Lakkaraju, and Flavio Calmon. Temporal sparse autoencoders: Leveraging the sequential nature of language for interpretability. In *The Fourteenth International Conference on Learning Representations*, 2026b. URL https://openreview.net/forum?id=bojVI4l9Kn.

Tom Lieberum, Senthooran Rajamanoharan, Arthur Conmy, Lewis Smith, Nicolas Sonnerat, Vikrant Varma, János Kramár, Anca Dragan, Rohin Shah, and Neel Nanda. Gemma Scope: Open Sparse Autoencoders Everywhere All At Once on Gemma 2, 2024. URL https://arxiv.org/abs/2408.05147. Version Number: 2.

Matthew Gentzkow and Jesse M. Shapiro. What Drives Media Slant? Evidence From U.S. Daily Newspapers. *Econometrica*, 78(1):35–71, January 2010. ISSN 0012-9682. doi: 10.3982/ECTA7195. URL https://doi.org/10.3982/ECTA7195. Publisher: John Wiley & Sons, Ltd.

Nathanael Jo and Manish Raghavan. Incentives shape how humans co-create with generative AI, 2026. URL https://arxiv.org/abs/2604.03529. Version Number: 1.

Victor Chernozhukov, Mert Demirer, Esther Duflo, and Iván Fernández-Val. Fisher–Schultz Lecture: Generic Machine Learning Inference on Heterogeneous Treatment Effects in Randomized Experiments, With an Application to Immunization in India. *Econometrica*, 93(4):1121–1164, 2025. ISSN 0012-9682. doi: 10.3982/ECTA19303. URL https://www.econometricsociety.org/doi/10.3982/ECTA19303.

Abhijit Banerjee, Esther Duflo, Amy Finkelstein, Lawrence Katz, Benjamin Olken, and Anja Sautmann. In Praise of Moderation: Suggestions for the Scope and Use of Pre-Analysis Plans for RCTs in Economics. Technical Report w26993, National Bureau of Economic Research, Cambridge, MA, April 2020. URL http://www.nber.org/papers/w26993.pdf.

Evan Miller. Adding Error Bars to Evals: A Statistical Approach to Language Model Evaluations, 2024. URL https://arxiv.org/abs/2411.00640. Version Number: 1.

Vincent Huang, Dami Choi, Daniel D Johnson, Sarah Schwettmann, and Jacob Steinhardt. Predictive concept decoders: Training scalable end-to-end interpretability assistants, 2025. URL https://arxiv.org/abs/2512.15712.

Beatrice Ferrario and Stefanie Stantcheva. Eliciting People's First-Order Concerns: Text Analysis of Open-Ended Survey Questions. *AEA Papers and Proceedings*, 112:163–169, May 2022. ISSN 2574-0768, 2574-0776. doi: 10.1257/pandp.20221071. URL https://pubs.aeaweb.org/doi/10.1257/pandp.20221071.

Leo Gao, Stella Biderman, Sid Black, Laurence Golding, Travis Hoppe, Charles Foster, Jason Phang, Horace He, Anish Thite, Noa Nabeshima, Shawn Presser, and Connor Leahy. The Pile: An 800GB Dataset of Diverse Text for Language Modeling, 2021. URL https://arxiv.org/abs/2101.00027. Version Number: 1.

Adam Karvonen, Can Rager, Johnny Lin, Curt Tigges, Joseph Bloom, David Chanin, Yeu-Tong Lau, Eoin Farrell, Callum McDougall, Kola Ayonrinde, Demian Till, Matthew

Wearden, Arthur Conmy, Samuel Marks, and Neel Nanda. SAEBench: A Comprehensive Benchmark for Sparse Autoencoders in Language Model Interpretability, 2025. URL https://arxiv.org/abs/2503.09532. Version Number: 4.

Roman Vershynin. *High-Dimensional Probability: An Introduction with Applications in Data Science*. Cambridge University Press, 1 edition, September 2018. ISBN 978-1-108-23159-6 978-1-108-41519-4. doi: 10.1017/9781108231596. URL https://www.cambridge.org/core/product/identifier/9781108231596/type/book.

Arun Kumar Kuchibhotla and Abhishek Chakrabortty. Moving beyond sub-Gaussianity in high-dimensional statistics: applications in covariance estimation and linear regression. *Information and Inference: A Journal of the IMA*, 11(4):1389–1456, December 2022. ISSN 2049-8772. doi: 10.1093/imaiai/iaac012. URL https://academic.oup.com/imaiai/article/11/4/1389/6612958.

Huiming Zhang and Haoyu Wei. Sharper Sub-Weibull Concentrations. 2021. doi: 10.48550/ARXIV.2102.02450. URL https://arxiv.org/abs/2102.02450. Version Number: 3.

6 Appendix

6.1 Replication

The results from the empirical applications section of this paper can be replicated using the open-source replication data from Andre et al. [2026], Bursztyn et al. [2023], Stantcheva [2024], and Noy and Zhang [2023], respectively, in addition to the GitHub repository: https://github.com/jscarlson/hdmht-discovery.

6.2 Reanalyzing Stantcheva [2024]

An inspiration for Example 2, Stantcheva [2024] conducts surveys with representative samples of the United States population investigating attitudes towards inflation. These surveys include open-ended text responses to a variety of questions, with the goal of discovering attitudes and opinions that the researcher should not (for concern about priming respondents) or could not (for lack of imagination) manually pre-specify.[52]

An important open-ended prompt that Stantcheva [2024] solicits an answer to is "High inflation is caused by..." This prompt is specifically highlighted by the Brookings Institution paper summary of Stantcheva [2024], signaling its policy relevance.[53] In the original analysis, Stantcheva [2024] codes open-ended responses with a discretionary keyword-based method introduced in Ferrario and Stantcheva [2022].[54] The result of applying this analytic technique to the open-ended responses to the above prompt yields Figure 3 in Stantcheva [2024], which finds, among other things, that mentions of "Biden and the administration," "Greed," "Monetary policy," "Fiscal policy," "War and foreign policy," "Demand vs supply," and "Supply-side mechanisms (other than input prices)" appear in more than 5% of all responses. Discussion of "input prices," "energy prices," "demand-side mechanisms," "people earning higher incomes," "government debt," and "COVID-19" appear in more than 2% of responses.

Do we make the same discoveries automatically if we apply the proposed framework instead? Do we make more and new interpretable discoveries? To find out, we use the same concept embedding and explainer LLM setup as in Section 4.2, but reduce the space of SAE features by half, filtering out all features that, in the corpus on which the SAE was trained, had greater than median empirical token activation frequency. This choice of dimensionality reduction is meant to screen out features that activate in many texts across domains, e.g., features related to common grammatical features of text, which was handled implicitly in the previous causal analysis by virtue of differencing. (Ideally, such a dimensionality reduction choice would be preregistered, to prevent cherry-picking by filtering, but could also easily be analyzed for sensitivity.) Again we split the sample randomly to form a held-out evaluation dataset consisting of 15% of the original dataset analyzed in Stantcheva [2024].

We now test hypotheses $H_{0,j} : \theta_j(P) = E[Y_{ij}] = P(Y_{ij} = 1) = 0$; naturally, in this setting where probabilities are being tested, of actual scientific interest is the dual of this testing

[52] See, e.g., Haaland et al. [2024] for more discussion of the benefits of open-ended survey questions for understanding economic behavior.

[53] See https://www.brookings.edu/articles/why-do-we-dislike-inflation/.

[54] The method suggests that the researcher create a list of topics and associated keywords that denote their presence via anything from "manual to semi-supervised or unsupervised" means.

procedure, i.e., the point estimates for the probability of discussion along with generalized simultaneous confidence intervals. This yields a dataset with $n = 428$ and $p = 1173$ non-degenerate features. We now apply 5-FWER control with $\alpha = 0.05$ based on the result in Theorem 4, and we make 186 interpretable discoveries. In Figure 8, as in Figure 5, we plot the 10 largest well-interpreted discoveries; in Figure 9 we plot the next 10 largest. The remaining well-interpreted discoveries can be similarly viewed in Appendix Section 6.3.

Notably, among the full 186 well-interpreted discoveries made, we recover many of the features coded from the original analysis in Stantcheva [2024] without any human discretion or intervention: concept 2493 is "blaming government or Biden for inflation"; concept 2189 is "'Greed' as a concept or word"; concept 3551 is "Federal Reserve and monetary policy concepts"; concept 3029 is "government fiscal mismanagement or overspending"; concept 1009 is "excess demand outpacing supply"; concept 3121 is "'supply chain' and physical goods/commodities"; concept 2105 is "fuel, oil, and gas prices"; concept 453 is "'consumer' and 'demand' in economic contexts"; concept 3672 is "wages, labor costs, and worker pay increases"; concept 949 is "national debt and government borrowing"; and concept 96 is "global and international scale references."[55]

Many additional discovered concepts add nuance to these broad categories, e.g., for greed, concept 3498 is "corporate greed and capitalist wealth," or for blaming the Biden administration, concept 697 is "misplaced priorities or focus directed elsewhere." Furthermore, many of these well-interpreted discoveries contribute to some entirely new insights. Concept 221 is described as "first-person expressions of uncertainty or ignorance" and appears in over *one-third* of the responses—a strong signal that is not coded in the original analysis, and what one might call an important "unknown unknown." Discovered concepts 20, 925, 323, 574, 802, and 3904, among others, are all characterized by discussion of uncertainty or hedging language, further reinforcing the interpretation that many Americans are simply unsure of (or confused about) the causes of inflation, as opposed to subscribers of a particular pet theory. Concept 415 is "commas and conjunctions separating listed causes or factors," which, among others, indicates that many surveyed have multiple factors in mind.

Beyond filtering out greater than median activating concepts, no other choices were made to delimit the space of possible discoveries, or focus them in some way on the space of economic- or inflation-relevant concepts; the exact same explainer LLMs and SAE that yielded the results of Section 4.2 yielded the results in this section.

[55] Concept 1138 corresponds to "economic crisis, recession, and COVID-related economic causes"; it has a detection score point estimate of 0.723 and so just misses the cutoff for "well-interpreted."




Figure 8: Well-Interpreted Discoveries for Responses to Prompt "High inflation is caused by..." in Stantcheva [2024], Rank 1-10.




Figure 9: Well-Interpreted Discoveries for Responses to Prompt "High inflation is caused by..." in Stantcheva [2024], Rank 11-20.

6.3 Additional Plots




Figure 10: Well-Interpreted Discoveries for First Narrative Provision Experiment of Andre et al. [2026], Rank 21-30.




Figure 11: Well-Interpreted Discoveries for First Narrative Provision Experiment of Andre et al. [2026], Rank 31-40.




Figure 12: Well-Interpreted Discoveries for First Narrative Provision Experiment of Andre et al. [2026], Rank 41-50.




Figure 13: Well-Interpreted Discoveries for First Narrative Provision Experiment of Andre et al. [2026], Rank 51-60.




Figure 14: Well-Interpreted Discoveries for First Narrative Provision Experiment of Andre et al. [2026], Rank 61-70.




Figure 15: Well-Interpreted Discoveries for First Narrative Provision Experiment of Andre et al. [2026], Rank 71-.




Figure 16: Well-Interpreted Discoveries for Experiment 2 of Bursztyn et al. [2023], Rank 11-.




Figure 17: Well-Interpreted Discoveries for Responses to Prompt "High inflation is caused by..." in Stantcheva [2024], Rank 21-30.




Figure 18: Well-Interpreted Discoveries for Responses to Prompt "High inflation is caused by..." in Stantcheva [2024], Rank 31-40.




Figure 19: Well-Interpreted Discoveries for Responses to Prompt "High inflation is caused by..." in Stantcheva [2024], Rank 41-50.




Figure 20: Well-Interpreted Discoveries for Responses to Prompt "High inflation is caused by..." in Stantcheva [2024], Rank 51-60.




Figure 21: Well-Interpreted Discoveries for Responses to Prompt "High inflation is caused by..." in Stantcheva [2024], Rank 61-70.




Figure 22: Well-Interpreted Discoveries for Responses to Prompt "High inflation is caused by..." in Stantcheva [2024], Rank 71-80.




Figure 23: Well-Interpreted Discoveries for Responses to Prompt "High inflation is caused by..." in Stantcheva [2024], Rank 81-90.




Figure 24: Well-Interpreted Discoveries for Responses to Prompt "High inflation is caused by..." in Stantcheva [2024], Rank 91-.




Figure 25: Well-Interpreted Discoveries for Noy and Zhang [2023], Rank 21-30.




Figure 26: Well-Interpreted Discoveries for Noy and Zhang [2023], Rank 31-.

6.4 Implementation Details

6.4.1 Concept Embedding

We use the T-SAE [Bhalla et al., 2026b] as the basis for a concept embedding, preferring it to alternatives due to its "temporal loss" modification helping to separate out semantic from syntactic features in the learning process—leading to greater interpretability in theory and in practice. Because off-the-shelf feature descriptions are available for the T-SAE, we use them to inform a simple filtering procedure that generates the final concept embedding: if multiple features have the exact same off-the-shelf description up to whitespace and casing, they are max-pooled for the purposes of indicating the presence of the (putatively same) underlying concept. This filtering thereby reduces the dimensionality of the concept embedding.

6.4.2 Local Autointerp

Building autointerp pipelines for scalable description of features produced from sparse dictionary learning methods is an active area of AI/ML research. Most best practices rely on leveraging LLMs themselves to interpret the features and later score these interpretations, per the pioneering work of Bills et al. [2023].

Heuristically, most of these pipelines operate by collecting text samples on which a given feature activates the most in a particular corpus (as well as perhaps sampling additional text samples across the empirical distribution of activation strengths) and weaving information about these activations—alongside the activating text—into prompts that LLMs are asked to interpret. Though autointerp descriptions are available for the T-SAE and some other SAEs, these descriptions are learned based on the distribution of the SAE's pretraining data (the Pile [Gao et al., 2021] for the T-SAE), and as such benefit from being refined through a *local* autointerpretation strategy that uses text samples from the unstructured dataset distribution P.

For the purposes of generation, we take cues from the methods of Paulo et al. [2024], Bills et al. [2023], Karvonen et al. [2025] to arrive at a prompt of the form:

```
{"role": "system", "content": """
You are a meticulous AI researcher studying the internal
representations of language models. Your task is to produce short,
precise descriptions of what a neuron responds to. Descriptions must
be specific enough that a reader could accurately predict which new
texts would activate the neuron.
"""},
{"role": "user", "content": f"""
A particular neuron most activated on the following examples when a
corpus of texts was passed through a language model. Tokens that
triggered the neuron are wrapped in << ... >> and annotated with
their activation strength as <<token(v)>>, where v is an integer
from 1 (weakly activating) to 10 (the neuron's strongest response).
Higher-numbered tokens are the most informative; weight them
accordingly, and note that some examples activate the neuron more
```

```
strongly overall than others. Unmarked tokens did not activate the
neuron but provide context.

Write a single short phrase (ideally 3-8 words) describing the
specific concept, topic, or linguistic pattern this neuron responds
to, e.g., `news articles and formal reports' or `verbs and nouns
related to actions'. This pattern/description should be abstracted
away from the broad topic of the corpus itself, which will be
consistent across all of the examples. Delimit your answer as
[[description here]].

The << >>( ) glyphs are annotations, not part of the text; base
your description on which tokens they mark and how strongly.

Examples:
{numbered_texts}
"""}
```

where `numbered_texts` is an enumerated concatenation of L exemplar texts—modified as the prompt suggests—associated with the tokens that activated most highly on a given feature in the main sample of the researcher's unstructured dataset. We use $L = 10$ in the empirical examples of this paper, and Anthropic's Claude Sonnet (high reasoning effort, June 2026), to perform interpretations. In practice, we employ a floor of 25% of an exemplar text's maximum token activation strength for the feature for annotation. Activation strength annotations `v` are determined by

$$\frac{\text{activation strength} \times 10}{\max(\text{activation strength across } L \text{ exemplars})}$$

rounded to the nearest integer. For an exact implementation, see code at https://github.com/jscarlson/hdmht-discovery.

For the purposes of evaluation, we again adapt the detection scoring prompting strategy of Paulo et al. [2024], using prompts of the form:

```
{"role": "system", "content": """
You are an intelligent and meticulous linguistics researcher.
You will be provided a certain latent attribute of text, such as
``male pronouns'' or ``text with negative sentiment''.
You will then be given a text example. Your task
is to determine if the example possesses the latent attribute.
Return 1 if the text possesses the latent attribute,
and return 0 otherwise. Return only this number.
"""
},
{"role": "user", "content": f"""
LATENT ATTRIBUTE: {description}
```

```
TEXT EXAMPLE: {text}
"""
}
```

where `description` is an autointerp description being evaluated and `text` is a text sample being analyzed for the presence of the relevant feature. We use the open-source model Gemma 4 31B to perform evaluations, for the sake of reproducibility and cost effectiveness.

6.5 Pseudocode Algorithm

Algorithm 1 Interpretable Discovery from Text Data with k-FWER Control (Simplified)

Require: Data $\{(W_i, Z_i)\}_{i=1}^{n+m}$ drawn i.i.d. from distribution P; concept embedding function $h : \mathcal{Z} \to \{0,1\}^{\tilde{p}}$; map $g : \mathcal{W} \times \{0,1\} \to \mathbb{R}$; level α; error control k; explainer LLM $\mathcal{E}$; eval dataset size m; bootstrap iterations $\mathfrak{B}$.

Require: $k \ll \tilde{p}$.

Split sample

Randomly split $[n+m]$ into $\mathcal{I}^{\text{estim}}$ and $\mathcal{I}^{\text{eval}}$ with $|\mathcal{I}^{\text{estim}}| = n$ and $|\mathcal{I}^{\text{eval}}| = m$.

Create concept embeddings

for $i = 1, \ldots, n+m$ **do**

  $Y_i \leftarrow h(Z_i) \in \{0,1\}^{\tilde{p}}$.

end for

Drop degenerate features

Initialize $\mathcal{J} \leftarrow \emptyset$.

for $j = 1, \ldots, \tilde{p}$ **do**

  If $\exists\, i$ such that $Y_{ij} \neq 0$, $\mathcal{J} \leftarrow \mathcal{J} \cup \{j\}$.

end for

$p \leftarrow |\mathcal{J}|$.

Compute concept-level estimates and t-stats

for $j \in \mathcal{J}$ **do**

  For $i \in \mathcal{I}^{\text{estim}}$: $X_{ij} \leftarrow g(W_i, Y_{ij})$.

  $\hat{\theta}_j \leftarrow \frac{1}{n}\sum_{i \in \mathcal{I}^{\text{estim}}} X_{ij}$; $\hat{\Sigma}_{jj} \leftarrow \frac{1}{n}\sum_{i \in \mathcal{I}^{\text{estim}}} (X_{ij} - \hat{\theta}_j)^2$.

  $T_{n,j} \leftarrow \sqrt{n}\,\hat{\theta}_j / \sqrt{\hat{\Sigma}_{jj}}$.

end for

$\hat{\Lambda} \leftarrow \text{diag}(\hat{\Sigma}_{11}, \ldots, \hat{\Sigma}_{pp})$.

High-dimensional selective inference

Critical value $\hat{c}_n(1-\alpha, k) \leftarrow 1-\alpha$ quantile of $\left|\hat{\Lambda}^{-1/2} S_n^B\right|_{[k]}$ under bootstrap law, approx. using $\mathfrak{B}$ multiplier bootstrap iterations with $\{X_i\}_{i \in \mathcal{I}^{\text{estim}}}$.

Selected set $\hat{J} \leftarrow \{j : |T_{n,j}| > \hat{c}_n(1-\alpha, k)\} \subseteq [p]$.

For $j \in [p]$: gen. sim. CI $\mathcal{C}_j \leftarrow \left[\hat{\theta}_j - \hat{c}_n(1-\alpha,k)\sqrt{\frac{\hat{\Sigma}_{jj}}{n}}, \hat{\theta}_j + \hat{c}_n(1-\alpha,k)\sqrt{\frac{\hat{\Sigma}_{jj}}{n}}\right] \in \mathbb{R}^2$.

Autointerpretation

Initialize `CLS` using $\mathcal{E}$ and fixed classification prompt.

for $\hat{\jmath} \in \hat{J}$ **do**

  Generate descriptions $\hat{\eta}_{\hat{\jmath}} \leftarrow \mathcal{E}(\{Z_i\}_{i \in \mathcal{I}^{\text{estim}}})$ (e.g., implemented per App. Sec. 6.4).

  for $i \in \mathcal{I}^{\text{eval}}$ **do**

    $\hat{Y}_{i\hat{\jmath}} \leftarrow \texttt{CLS}(Z_i, \hat{\eta}_{\hat{\jmath}}) \in \{0,1\}$; $S_{i\hat{\jmath}} \leftarrow \mathbf{1}\{Y_{i\hat{\jmath}} = \hat{Y}_{i\hat{\jmath}}\}$.

  end for

  Detection score $\hat{\theta}^{\text{acc}}_{\hat{\jmath}} \leftarrow \frac{1}{m}\sum_{i \in \mathcal{I}^{\text{eval}}} S_{i\hat{\jmath}}$.

  Optionally: form CI for $\theta^{\text{acc}}_{\hat{\jmath}}(\hat{\eta}_{\hat{\jmath}})$ using plug-in estimators under $(\hat{\eta}_{\hat{\jmath}}, \hat{\jmath})$-conditional law.

end for

Output: $\{(j, \hat{\theta}_j, \mathcal{C}_j) : j \in [p]\}$ and $\{(\hat{\jmath}, \hat{\eta}_{\hat{\jmath}}, \hat{\theta}^{\text{acc}}_{\hat{\jmath}}) : \hat{\jmath} \in \hat{J}\}$.

6.6 Romano and Wolf [2007] Algorithms

We reproduce Algorithms 2.1 and 2.2 in Romano and Wolf [2007] in full here for completeness, using the notation of this paper.

Algorithm 2 Romano and Wolf [2007] Algorithm 2.1

1. Let $A_1 = \{1, \ldots, p\}$. If $\max\left(T_{n,j} : j \in A_1\right) \leq \hat{c}_{n,A_1}(1-\alpha, k)$, then accept all hypotheses and stop; otherwise, reject any $H_{0,j}$ for which $T_{n,j} > \hat{c}_{n,A_1}(1-\alpha, k)$ and continue.
2. Let R_2 be the indices j of hypotheses $H_{0,j}$ previously rejected, and let A_2 be the indices of the remaining hypotheses. If $|R_2| < k$, then stop. Otherwise, let

$$\hat{d}_{n,A_2}(1-\alpha, k) = \max_{I \subset R_2, |I|=k-1} \left\{\hat{c}_{n,K}(1-\alpha, k) : K = A_2 \cup I\right\}.$$

Then, reject any $H_{0,j}$ with $j \in A_2$ satisfying $T_{n,j} > \hat{d}_{n,A_2}(1-\alpha, k)$. If there are no further rejections, stop.

$\vdots$

ℓ. Let R_ℓ be the indices j of hypotheses $H_{0,j}$ previously rejected, and let A_ℓ be the indices of the remaining hypotheses. Let

$$\hat{d}_{n,A_\ell}(1-\alpha, k) = \max_{I \subset R_\ell, |I|=k-1} \left\{\hat{c}_{n,K}(1-\alpha, k) : K = A_\ell \cup I\right\}.$$

Then, reject any $H_{0,j}$ with $j \in A_\ell$ satisfying $T_{n,j} > \hat{d}_{n,A_\ell}(1-\alpha, k)$. If there are no further rejections, stop.

$\vdots$

And so on.

Algorithm 3 Romano and Wolf [2007] Algorithm 2.2

The algorithm is analogous to Algorithm 2.1. The only difference is that in any step $\ell > 1$ the critical value

$$\hat{d}_{n,A_\ell}(1-\alpha, k) = \max_{I \subset R_\ell, |I|=k-1} \left\{\hat{c}_{n,K}(1-\alpha, k) : K = A_\ell \cup I\right\}$$

is replaced by the critical value

$$\tilde{d}_{n,A_\ell}(1-\alpha, k) = \hat{c}_{n,K}(1-\alpha, k),$$
$$\text{where } K = \left\{r_{(|R_\ell|-k+2)}, r_{(|R_\ell|-k+1)}, \ldots, r_{(p)}\right\}.$$

6.7 Additional Results

Theorem 8 (High-dimensional bootstrap for the small k-max coordinate of approximate means)**.** *Let $\tilde{S}_n^B := S_n^B + R_n$, and assume that $\|R_n\|_\infty = o_P(1/\sqrt{\log(pn)})$. Further assume that k is fixed (i.e., does not grow with n, p). If Assumptions M and R hold, then as $n, p \to \infty$*

$$\sup_{t \in \mathbb{R}} \left| P^B\left(\tilde{S}_{n,[k]}^B \leq t\right) - P\left(N(0,\Sigma)_{[k]} \leq t\right)\right| \xrightarrow{P} 0.$$

Define the diagonal matrix of asymptotic variances $\Lambda := \mathrm{diag}(\Sigma)$, as well as the corresponding correlation matrix $\Sigma_0 := \Lambda^{-1/2}\Sigma\Lambda^{-1/2}$. Let plug-in estimates be $\widehat{\Sigma}_{jj} := n^{-1}\sum_{i=1}^{n}\left(X_{ij} - \bar{X}_{n,j}\right)^2$ and $\widehat{\Lambda} := \mathrm{diag}\left\{\widehat{\Sigma}_{11}, \ldots, \widehat{\Sigma}_{pp}\right\}$.

Theorem 9 (High-dimensional CLT for the small k-max studentized coordinate)**.** *Assume $X_i \overset{iid}{\sim} P$. If Assumptions M and R hold, $B_n = O(1)$, and k is fixed (i.e., does not grow with n, p), then, by application of Theorem 3, as $n, p \to \infty$*

$$\sup_{t\in\mathbb{R}}\left|P\left(\left(\hat{\Lambda}^{-1/2}S_n\right)_{[k]} \le t\right) - P\left(N(0,\Sigma_0)_{[k]} \le t\right)\right| \to 0.$$

Theorem 10 (High-dimensional bootstrap for the small k-max studentized coordinate)**.** *Assume $X_i \overset{iid}{\sim} P$. If Assumptions M and R hold, $B_n = O(1)$, and k is fixed (i.e., does not grow with n, p), then, by application of Theorem 8, as $n, p \to \infty$*

$$\sup_{t\in\mathbb{R}}\left|P^B\left(\left(\hat{\Lambda}^{-1/2}S_n^B\right)_{[k]} \le t\right) - P\left(N(0,\Sigma_0)_{[k]} \le t\right)\right| \xrightarrow{P} 0.$$

Corollary 2 (Generalized simultaneous confidence intervals)**.** *Under the conditions of the two-sided analog of Theorem 4, let $\hat{c} := \hat{c}_{n,[p]}(1-\alpha, k)$ be the single-step critical value, i.e., the $1-\alpha$ quantile of $|\hat{\Lambda}^{-1/2}S_n^B|_{[k]}$ under P^B, and define, for $j \in [p]$,*

$$\mathcal{C}_j := \left[\hat{\theta}_j - \hat{c}\sqrt{\hat{\Sigma}_{jj}/n},\ \hat{\theta}_j + \hat{c}\sqrt{\hat{\Sigma}_{jj}/n}\right].$$

Then

$$\liminf_{n,p\to\infty} P\Big(\big|\{j \in [p] : \theta_j(P) \notin \mathcal{C}_j\}\big| < k\Big) \ \ge\ 1-\alpha.$$

Proof. The event that k or more parameters fall outside their intervals is exactly the event $\left(|\hat{\Lambda}^{-1/2}S_n|\right)_{[k]} > \hat{c}$, where $S_{n,j} = \sqrt{n}(\hat{\theta}_j - \theta_j(P))$. The proof of (the two-sided analog of) Theorem 4, applied with $K = [p]$, establishes $\limsup_{n,p\to\infty} P\big((|\hat{\Lambda}^{-1/2}S_n|)_{[k]} > \hat{c}_{n,[p]}(1-\alpha, k)\big) \le \alpha$, which is the claim. □

6.8 Many Linear Regressions

We now state two propositions associated with Example 4.

Proposition 2 (Influence function approximation for many linear regressions)**.** *Let $\{(Y_i, T_i, D_i)\}_{i=1}^n$ be drawn i.i.d. from distribution P, where $Y_i = (Y_{i1}, \ldots, Y_{ip})^\intercal \in \mathbb{R}^p$, $T_i \in \mathbb{R}$, and $D_i \in \mathbb{R}^d$ with fixed d, and D_i includes a constant. Let $L_P[\cdot \mid \cdot]$ denote the linear projection operator. Define population quantities*

$$\widetilde{T} := T - L_P[T \mid D], \qquad \widetilde{Y}_j := Y_j - L_P[Y_j \mid D], \qquad \Omega := E_P[\widetilde{T}^2], \qquad \theta_j := \Omega^{-1}E_P[\widetilde{T}\,\widetilde{Y}_j],$$
$$\widetilde{U}_j := \widetilde{Y}_j - \theta_j\widetilde{T}, \qquad \psi_{ij} := \Omega^{-1}\widetilde{T}_i\widetilde{U}_{ij}.$$

Define feasible sample analog quantities as

$$\widehat{\gamma}_T := E_n[D_i D_i^{\mathsf{T}}]^{-1} E_n[D_i T_i], \qquad \widehat{\gamma}_{Y_j} := E_n[D_i D_i^{\mathsf{T}}]^{-1} E_n[D_i Y_{ij}],$$
$$\widehat{\widetilde{T}}_i := T_i - D_i^{\mathsf{T}} \widehat{\gamma}_T, \qquad \widehat{\widetilde{Y}}_{ij} := Y_{ij} - D_i^{\mathsf{T}} \widehat{\gamma}_{Y_j},$$
$$\widehat{\Omega} := E_n[\widehat{\widetilde{T}}_i^2], \qquad \widehat{\theta}_j := \widehat{\Omega}^{-1} E_n[\widehat{\widetilde{T}}_i \widehat{\widetilde{Y}}_{ij}], \qquad \widehat{\widetilde{U}}_{ij} := \widehat{\widetilde{Y}}_{ij} - \widehat{\theta}_j \widehat{\widetilde{T}}_i, \qquad \widehat{\psi}_{ij} := \widehat{\Omega}^{-1} \widehat{\widetilde{T}}_i \widehat{\widetilde{U}}_{ij}.$$

Assume:

(ND) $\Sigma_D := E_P[DD^{\mathsf{T}}]$ *is nonsingular and* $0 < C_1 \leq \Omega \leq C_2 < \infty$.

(SG) There exists $C_3 < \infty$ *such that* $\|T\|_{\psi_2} \leq C_3$, $\max_{\ell \leq d} \|D_\ell\|_{\psi_2} \leq C_3$, $\max_{j \leq p} \|Y_j\|_{\psi_2} \leq C_3$.

Then, if Assumption R *holds,*

$$\max_{j \in [p]} \sqrt{E_n\left[(\widehat{\psi}_{ij} - \psi_{ij})^2\right]} = o_P\left(\frac{1}{\log(pn)}\right).$$

Proposition 3 (Linearization error for many linear regressions)**.** *Assume the same setup as Proposition 2. Let*

$$\sqrt{n}(\hat{\theta}_j - \theta_j) = \frac{1}{\sqrt{n}} \sum_{i=1}^{n} \psi_{ij} + R_{n,j}$$

where

$$R_{n,j} = (\widehat{\Omega}^{-1} - \Omega^{-1}) \sqrt{n} E_n[\widetilde{T}\, \widetilde{U}_j] + \widehat{\Omega}^{-1} \sqrt{n} E_n[(\widehat{\widetilde{T}} - \widetilde{T}) \widetilde{U}_j].$$

Let $R_n := (R_{n,1}, \ldots, R_{n,p})^{\mathsf{T}}$. *Then, under Assumption* R*,*

$$\|R_n\|_\infty = o_P\left(1/\sqrt{\log(pn)}\right).$$

6.9 Proofs

Before stating proofs of the results in the main text, we state several additional useful lemmas.

Lemma 1. *For a sequence of random variables* U_n *and for a deterministic sequence* r_n*,*

$$U_n = o_P(r_n) \iff P^B(|U_n/r_n| \geq \varepsilon) = o_P(1) \text{ for any } \varepsilon > 0.$$

Proof. Note that, by definition, we have that $U_n = o_P(r_n)$ if for any $\varepsilon > 0$ that

$$\lim_{n \to \infty} P(|U_n/r_n| \geq \varepsilon) = \lim_{n \to \infty} E[Z_{n,\varepsilon}] = 0$$

where $Z_{n,\varepsilon} := P(|U_n/r_n| \geq \varepsilon \mid X)$, as by the law of total expectation $P(|U_n/r_n| \geq \varepsilon) = E[Z_{n,\varepsilon}]$. By Markov's inequality, because $Z_{n,\varepsilon}$ is always positive, for any $\delta > 0$,

$$P(Z_{n,\varepsilon} \geq \delta) \leq \frac{E[Z_{n,\varepsilon}]}{\delta}.$$

Thus we have that

$$0 \leq \lim_{n\to\infty} P(Z_{n,\varepsilon} \geq \delta) \leq \frac{\lim_{n\to\infty} E[Z_{n,\varepsilon}]}{\delta} = 0$$

and $\lim_{n\to\infty} P(|Z_{n,\varepsilon}| \geq \delta) = 0$ for any $\varepsilon, \delta > 0$. As such, $P(|U_n/r_n| \geq \varepsilon \mid X) = P^B(|U_n/r_n| \geq \varepsilon) = o_P(1)$ for any $\varepsilon > 0$ if $U_n = o_P(r_n)$.

For the other direction, note further that if $P(|U_n/r_n| \geq \varepsilon \mid X) = o_P(1)$ then the boundedness of $Z_{n,\varepsilon}$ permits using the bounded convergence theorem[56] to show for any $\varepsilon > 0$

$$P(|U_n/r_n| \geq \varepsilon) = o(1).$$

□

Lemma 2. *If for $\delta_n \searrow 0, \nu_n \searrow 0$, and sequence of functions $d_n : \mathcal{X}_n \to \mathbb{R}$, for $X_n \in \mathcal{X}_n$*

$$P(d_n(X_n) \geq \delta_n) \leq \nu_n$$

then

$$d_n(X_n) = o_P(1).$$

Proof. We want to show that, for any fixed $\delta > 0$,

$$\lim_{n\to\infty} P(d_n(X_n) \geq \delta) = 0$$

(the definition of convergence in probability). Note that, given the definition $\delta_n = o(1)$, for some n^*, for all $n \geq n^*$ we have that $\delta_n < \delta$. Thus, define the events:

$$A_n := \{d_n(X_n) \geq \delta\}, \quad B_n := \{d_n(X_n) \geq \delta_n\}$$

For all $n \geq n^*$, $A_n \subseteq B_n$. Thus, for all $n \geq n^*$

$$P\{d_n(X_n) \geq \delta\} \leq P\{d_n(X_n) \geq \delta_n\}.$$

Notice that then, using that $\nu_n = o(1)$,

$$0 \leq \lim_{n\to\infty} P\{d_n(X_n) \geq \delta\} \leq \lim_{n\to\infty} P\{d_n(X_n) \geq \delta_n\} = 0.$$

Because this holds for any choice of $\delta > 0$, we have proven the stated result. □

Lemma 3. *For $\{X_i\}_{i\in[n]}$ independent subexponential random vectors of dimension p, with each $\|X_{ij} - E[X_{ij}]\|_{\psi_1} \leq B_n$ for $i \in [n]$ and $j \in [p]$, then, under Assumption R,*

$$\|S_n\|_\infty = \left\| \frac{1}{\sqrt{n}} \sum_{i=1}^{n} (X_i - E[X_i]) \right\|_\infty = O_P\left(B_n \sqrt{\log p}\right).$$

[56] See, e.g., Lemma 10.7 at this link: https://people.math.wisc.edu/~roch/teaching_files/275b.1.12w/lect10-web.pdf.

Proof. We start by noting Proposition 2.9.2 of Vershynin [2018], which implies here that

$$P\left\{\left|\frac{1}{n}\sum_{i=1}^{n}(X_{ij}-E[X_{ij}])\right|\geq t\right\}\leq 2\exp\left[-c\min\left(\frac{nt^2}{B_n^2},\frac{nt}{B_n}\right)\right].$$

Thus by the union bound,

$$P\left\{\max_{j\in[p]}\left|\frac{1}{n}\sum_{i=1}^{n}(X_{ij}-E[X_{ij}])\right|\geq t\right\}\leq 2p\exp\left[-c\min\left(\frac{nt^2}{B_n^2},\frac{nt}{B_n}\right)\right].$$

Defining that

$$\varepsilon:=2p\exp\left[-c\min\left(\frac{nt^2}{B_n^2},\frac{nt}{B_n}\right)\right]$$

then we have that for $\tilde{c}=1/c$

$$\tilde{c}\frac{\log(2p/\varepsilon)}{n}=\min\left\{t^2/B_n^2,t/B_n\right\}$$

and therefore

$$t=\tilde{c}B_n\frac{\log(2p/\varepsilon)}{n}\vee\tilde{c}B_n\sqrt{\frac{\log(2p/\varepsilon)}{n}},$$

meaning that

$$P\left\{\max_{j\in[p]}\left|\frac{1}{n}\sum_{i=1}^{n}(X_{ij}-E[X_{ij}])\right|\geq\tilde{c}B_n\left(\frac{\log(2p/\varepsilon)}{n}\vee\sqrt{\frac{\log(2p/\varepsilon)}{n}}\right)\right\}\leq\varepsilon.$$

As such, we have

$$P\left\{\max_{j\in[p]}\left|\frac{1}{\sqrt{n}}\sum_{i=1}^{n}(X_{ij}-E[X_{ij}])\right|\geq\tilde{c}B_n\left(\frac{\log(2p/\varepsilon)}{\sqrt{n}}\vee\sqrt{\log(2p/\varepsilon)}\right)\right\}\leq\varepsilon.$$

However, under Assumption R, $\log(p)/\sqrt{n}=o(1)$, so the Gaussian tail term dominates for large n, and thus for large n we may set $M_\varepsilon:=\tilde{c}\sqrt{\frac{\log(2/\varepsilon)}{\log 3}+1}$ and observe that

$$P\left\{\frac{\max_{j\in[p]}\left|\frac{1}{\sqrt{n}}\sum_{i=1}^{n}(X_{ij}-E[X_{ij}])\right|}{B_n\sqrt{\log p}}\geq M_\varepsilon\right\}\leq\varepsilon.$$

We then conclude using the definition of stochastic boundedness that

$$\left\|\frac{1}{\sqrt{n}}\sum_{i=1}^{n}(X_i-E[X_i])\right\|_\infty=O_P\left(B_n\sqrt{\log p}\right)$$

as claimed. □

Lemma 4. *Under Assumptions M and R,*

$$\|S_n^B\|_\infty = O_P(B_n\sqrt{\log p}).$$

Proof. Using Assumptions M and R, the proof of Lemma 3 implies that

$$P\left\{\|S_n\|_\infty \geq \tilde{c}B_n\left(\frac{\log(2p/\varepsilon)}{\sqrt{n}} \vee \sqrt{\log(2p/\varepsilon)}\right)\right\} \leq \varepsilon.$$

Using Lemma 4.6 of Chernozhuokov et al. [2022] and Lemma 2, notice that

$$b_n(X) := P\left(\|S_n^B\|_\infty > \tilde{c}B_n\left(\frac{\log(2p/\varepsilon)}{\sqrt{n}} \vee \sqrt{\log(2p/\varepsilon)}\right) \mid X\right) \leq \varepsilon + o_P(1). \tag{2}$$

Define the event $A_n := \{b_n(X) > \varepsilon + \eta\}$ for any $\eta > 0$. Then the earlier statement implies that $P(A_n) = o(1)$. Now, by the law of total expectation and the law of total probability,

$$\begin{aligned}
&P\left(\|S_n^B\|_\infty > \tilde{c}B_n\left(\frac{\log(2p/\varepsilon)}{\sqrt{n}} \vee \sqrt{\log(2p/\varepsilon)}\right)\right) \\
&= E[b_n(X)] \\
&= E[b_n(X) \mid A_n]P(A_n) + E[b_n(X) \mid A_n^c]P(A_n^c) \\
&= E[b_n(X) \mid A_n^c] + o(1) && \text{(Set } \eta = o(1)\text{)} \\
&\leq \varepsilon + o(1).
\end{aligned}$$

It then follows, using the same logic as in Lemma 3, along with Assumption R, that

$$\|S_n^B\|_\infty = O_P(B_n\sqrt{\log p}).$$

□

Lemma 5. *Suppose Assumptions M (treating the influence functions ψ_{ij} as data), R, and A hold. Then*

$$\|\tilde{S}_n^B\|_\infty = O_P(B_n\sqrt{\log p}).$$

Proof. First, we will decompose $\tilde{S}_n^B = G_n + \Delta_n$, where $G_n := n^{-1/2}\sum_{i=1}^n \xi_i\psi_i$ and $\Delta_n := n^{-1/2}\sum_{i=1}^n \xi_i(\hat{\psi}_i - \psi_i)$.

Conditional on X, $G_{n,j}$ is centered Gaussian with variance $\hat{\sigma}_j^2 := n^{-1}\sum_{i=1}^n \psi_{ij}^2$. By Assumption M(iii) and Jensen's inequality, $n^{-1}\sum_{i=1}^n E[\psi_{ij}^2] \leq (n^{-1}\sum_{i=1}^n E[\psi_{ij}^4])^{1/2} \leq B_n b_2$. Moreover, ψ_{ij}^2 is sub-Weibull of order 1/2 with $\|\psi_{ij}^2\|_{\psi_{1/2}} \lesssim B_n^2$, so Theorem 3.4 of Kuchibhotla and Chakrabortty [2022] together with a union bound over $j \in [p]$ gives

$$\max_{j\in[p]}\left|\hat{\sigma}_j^2 - n^{-1}\sum_{i=1}^n E[\psi_{ij}^2]\right| = O_P\left(B_n\sqrt{\frac{\log p}{n}} + \frac{B_n^2\log^2(2n)\log^2(p)}{n}\right) = o_P(B_n^2)$$

where the last equality follows from Assumption R, and so $\max_{j\in[p]}\hat{\sigma}_j = O_P(B_n)$ (recalling $B_n > 1$). The Borell-TIS inequality (as per [Belloni et al., 2018])—applied as in the proof of Theorem 5—yields, for any $\varepsilon \in (0,1)$, almost surely,

$$P^B\left(\|G_n\|_\infty > \max_{j\in[p]}\hat{\sigma}_j\left(\sqrt{2\log(2p)} + \sqrt{2\log(1/\varepsilon)}\right)\right) \leq 2\varepsilon,$$

and applying the un-conditioning argument exactly as in the proof of Lemma 4 (via the law of total probability on the event $\{\max_j \hat{\sigma}_j \leq MB_n\}$ for some $M < \infty$, whose probability can be made arbitrarily close to one) delivers $\|G_n\|_\infty = O_P(B_n\sqrt{\log p})$.

Then, conditional on X, note that $\Delta_{n,j}$ is a centered Gaussian with variance $n^{-1}\sum_{i=1}^n(\hat{\psi}_{ij} - \psi_{ij})^2$, so by the same inequality as above, with P^B-probability at least $1 - 2\varepsilon$,

$$\|\Delta_n\|_\infty \leq \max_{j\in[p]}\Big(n^{-1}\sum_{i=1}^n(\hat{\psi}_{ij} - \psi_{ij})^2\Big)^{1/2}\big(\sqrt{2\log(2p)} + \sqrt{2\log(1/\varepsilon)}\big).$$

Choosing $\varepsilon = 1/(2n)$ and applying Assumption A, the right-hand side is $o_P(1/\log(pn))O(\sqrt{\log(pn)}) = o_P(1)$; un-conditioning again (as above) gives $\|\Delta_n\|_\infty = o_P(1)$.

Combining these results, it is immediate that $\|\tilde{S}_n^B\|_\infty = O_P(B_n\sqrt{\log p})$.

□

We now prove the results from the main text. For any set of real numbers A with $|A| > k$, we use the notation k-max(A) to denote the k-th largest element of A, following Romano and Wolf [2007].

Theorem 1 (High-dimensional k-FWER control for small k, one-sided)**.** *Consider the method of Algorithm 2.1 in Romano and Wolf [2007] with test statistics T_n of hypotheses $\{\tilde{H}_{0,j}\}_{j\in[p]}$ and critical values $\hat{c}_{n,K}(1-\alpha,k)$ given by the $1-\alpha$ quantile of $S^B_{n,K,[k]}$ under P^B. Assume that k is fixed (i.e., not growing with n, p). Then under Assumptions M and R, this method ensures:*

(i) $\limsup_{n,p\to\infty} k\text{-}FWER_P \leq \alpha$.

(ii) *If $\tilde{H}_{0,j}$ is false and $\theta_j(P) \gg B_n\sqrt{\log p/n}$, then the probability that the step-down method rejects $\tilde{H}_{0,j}$ tends to 1.*

(iii) *If $\min_{j\notin I(P)}\theta_j(P) \gg B_n\sqrt{\log p/n}$, then conclusions (i) and (ii) also hold when Algorithm 2.1 is replaced by Algorithm 2.2 of Romano and Wolf [2007].*

Proof. To start, we may assume $|I(P)| \geq k$: otherwise at most $|I(P)| < k$ true null hypotheses can be falsely rejected, so that k-FWER$_P = 0 \leq \alpha$ holds trivially, and parts (ii) and (iii) are unaffected. (This will also be implicitly assumed in subsequent proofs of the Romano and Wolf [2007] algorithms' validity in high-dimensions.)

Now consider Algorithm 2.1 from Romano and Wolf [2007], which at each stage takes as inputs critical values $\hat{c}_{n,K}(1-\alpha,k)$ and a vector of test statistics T_n; we denote this as `RW-2.1`$(T_n, \hat{c}_{n,K}(1-\alpha,k))$.

The choice of critical values we will use is based on a bootstrap of the $1-\alpha$ quantile of the k-max:

$$\hat{c}_{n,K}(1-\alpha,k) := 1-\alpha \text{ quantile of } S^B_{n,K,[k]} \mid X.$$

As in Romano and Wolf [2007], define $I(P)$ to be the set of indices of true null hypotheses under P. Note that, for any $K \supset I(P)$,

$$\hat{c}_{n,K}(1-\alpha,k) \geq \hat{c}_{n,I(P)}(1-\alpha,k)$$

because for any $K \supset I(P)$, and under any distribution, $S^B_{n,K,[k]} \geq S^B_{n,I(P),[k]}$ almost surely (i.e., the k-max statistic can only get larger if we include more test statistics without dropping the others). As such, Theorem 2.1 (i) holds, and we conclude that `RW-2.1`$(T_n, \hat{c}_{n,K}(1-\alpha, k))$ delivers:

$$k\text{-FWER}_P \leq P\left\{k\text{-max}\left(T_{n,j} : j \in I(P)\right) > \hat{c}_{n,I(P)}(1-\alpha, k)\right\}.$$

Specifically, then, it is sufficient to show that

$$\limsup_{n,p} P\left\{k\text{-max}\left(T_{n,j} : j \in I(P)\right) > \hat{c}_{n,I(P)}(1-\alpha, k)\right\} \leq \alpha.$$

To continue to use the notation of Romano and Wolf [2007], let $\hat{\theta}_{n,j} := \bar{X}_{n,j}$. Since $\theta_j(P) \leq 0$ for $j \in I(P)$, it follows that, almost surely,

$$\begin{aligned} k\text{-max}\left(T_{n,j} : j \in I(P)\right) &= k\text{-max}\left(\sqrt{n}\hat{\theta}_{n,j} : j \in I(P)\right) \\ &\leq k\text{-max}\left(\sqrt{n}\left[\hat{\theta}_{n,j} - \theta_j(P)\right] : j \in I(P)\right) \\ &= k\text{-max}\left(S_{n,j} : j \in I(P)\right) \end{aligned}$$

and therefore

$$\begin{aligned} &P\left\{k\text{-max}\left(T_{n,j} : j \in I(P)\right) > \hat{c}_{n,I(P)}(1-\alpha, k)\right\} \\ \leq &P\left\{k\text{-max}\left(S_{n,j} : j \in I(P)\right) > \hat{c}_{n,I(P)}(1-\alpha, k)\right\}. \end{aligned}$$

If we can show that the limit of the quantity on the right-hand side is no greater than α, the proof is complete. However, Theorem 2.2 of Ding et al. [2025] delivers exactly that, for any K,

$$P\left\{S_{n,K,[k]} > \hat{c}_{n,K}\left(1-\alpha, k\right)\right\} \leq \alpha + o(1)$$

under Assumptions M and R. So, chaining inequalities, we note that

$$k\text{-FWER}_P \leq P\left\{S_{n,I(P),[k]} > \hat{c}_{n,I(P)}\left(1-\alpha, k\right)\right\} \leq \alpha + o(1)$$

and so

$$\limsup_{n,p\to\infty} k\text{-FWER}_P \leq \alpha$$

which is precisely what we wanted to show.

To prove the second statement, consider the $\tilde{H}_{0,j}$ corresponding to all $\theta_j(P) > 0$. Note that, for the Gaussian multiplier bootstrap, using Assumptions M and R, by the tail inequality Equation 2 in the proof of Lemma 4,

$$\hat{c}_{n,[p]}\left(1-\alpha, k\right) \leq \hat{c}_{n,[p]}\left(1-\alpha, 1\right) = O_P\left(B_n\sqrt{\log p}\right).$$

Furthermore, each $S_{n,j} = \sqrt{n}\left[\hat{\theta}_{n,j} - \theta_j(P)\right]$ is tight, so

$$T_{n,j} = \sqrt{n}\hat{\theta}_{n,j} = \sqrt{n}(\hat{\theta}_{n,j} - \theta_j(P)) + \sqrt{n}\theta_j(P) \xrightarrow{P} \infty.$$

However, because $\sqrt{n}$ grows faster than $B_n\sqrt{\log p}$ by Assumption R, we have that also

$$\frac{T_{n,j}}{B_n\sqrt{\log p}} \xrightarrow{P} \infty.$$

Therefore, with probability tending to one, $T_{n,j} > \hat{c}_{n,[p]}(1-\alpha, k)$, resulting in the rejection of $\tilde{H}_{0,j}$ in the first step of Algorithm 2.1, so long as $\theta_j(P)$ is fixed or approaches zero slower than a rate of $B_n\sqrt{\log p/n}$.

To prove the third statement, the asymptotic validity of the streamlined Algorithm 2.2 follows from the separation assumption

$$\min_{j \notin I(P)} \theta_j(P) \gg B_n\sqrt{\log p/n}$$

using the same logic as for the proof of the second statement and the argument of proof of Theorem 3.3 of Romano and Wolf [2007], i.e., $\min\left(T_{n,j} : j \notin I(P)\right)$ is diverging at rate $\sqrt{n}$, and if any $\theta_j(P) = 0$ then $\max\left(T_{n,j} : j \in I(P)\right) = O_P(B_n\sqrt{\log p})$. □

Theorem 2 (High-dimensional k-FWER control for small k, two-sided)**.** *Consider the method of Algorithm 2.1 in Romano and Wolf [2007] with test statistics $|T_n|$ of hypotheses $\{H_{0,j}\}_{j\in[p]}$ and critical values $\hat{c}_{n,K}(1-\alpha,k)$ given by the $1-\alpha$ quantile of $|S^B_{n,K}|_{[k]}$ under P^B. Assume that k is fixed (i.e., not growing with n, p). Then under Assumptions M and R, this method ensures:*

(i) $\limsup_{n,p\to\infty} k\text{-}FWER_P \leq \alpha$.

(ii) If $H_{0,j}$ is false and $|\theta_j(P)| \gg B_n\sqrt{\log p/n}$, then the probability that the step-down method rejects $H_{0,j}$ tends to 1.

(iii) If $\min_{j\notin I(P)} |\theta_j(P)| \gg B_n\sqrt{\log p/n}$, then conclusions (i) and (ii) also hold when Algorithm 2.1 is replaced by Algorithm 2.2 of Romano and Wolf [2007].

Proof. We again start by considering Algorithm 2.1 from Romano and Wolf [2007], which at each stage takes as inputs critical values $\hat{c}_{n,K}(1-\alpha,k)$ and a vector of test statistics $|T_n|$; we denote this as `RW-2.1`$(|T_n|, \hat{c}_{n,K}(1-\alpha,k))$.

The choice of critical values we will use is based on a bootstrap of the $1-\alpha$ quantile of the k-max of absolute values:

$$\hat{c}_{n,K}(1-\alpha,k) := 1-\alpha \text{ quantile of } |S^B_{n,K}|_{[k]} \mid X.$$

As in Romano and Wolf [2007], define $I(P)$ to be the set of indices of true null hypotheses under P. Note that, for any $K \supset I(P)$,

$$\hat{c}_{n,K}(1-\alpha,k) \geq \hat{c}_{n,I(P)}(1-\alpha,k)$$

because for any $K \supset I(P)$, and under any distribution, $|S^B_{n,K}|_{[k]} \geq |S^B_{n,I(P)}|_{[k]}$ almost surely (i.e., the k-max statistic can only get larger if we include more test statistics without dropping the others). As such, Theorem 2.1 (i) holds, and we conclude that `RW-2.1`$(|T_n|, \hat{c}_{n,K}(1-\alpha,k))$ delivers:

$$k\text{-FWER}_P \leq P\left\{k\text{-max}\left(|T_{n,j}| : j \in I(P)\right) > \hat{c}_{n,I(P)}(1-\alpha,k)\right\}.$$

Specifically, then, it is sufficient to show that

$$\limsup_{n,p} P\left\{k\text{-max}\left(|T_{n,j}| : j \in I(P)\right) > \hat{c}_{n,I(P)}(1-\alpha,k)\right\} \leq \alpha.$$

To continue to use the notation of Romano and Wolf [2007], let $\hat{\theta}_{n,j} := \bar{X}_{n,j}$. Since $\theta_j(P) = 0$ for $j \in I(P)$, it follows that, almost surely,

$$\begin{aligned} k\text{-max}\left(|T_{n,j}| : j \in I(P)\right) &= k\text{-max}\left(\sqrt{n}|\hat{\theta}_{n,j}| : j \in I(P)\right) \\ &= k\text{-max}\left(\sqrt{n}\left|\hat{\theta}_{n,j} - \theta_j(P)\right| : j \in I(P)\right) \\ &= k\text{-max}\left(|S_{n,j}| : j \in I(P)\right) \end{aligned}$$

and therefore

$$\begin{aligned} &P\left\{k\text{-max}\left(|T_{n,j}| : j \in I(P)\right) > \hat{c}_{n,I(P)}(1-\alpha,k)\right\} \\ =&P\left\{k\text{-max}\left(|S_{n,j}| : j \in I(P)\right) > \hat{c}_{n,I(P)}(1-\alpha,k)\right\}. \end{aligned}$$

If we can show that the limit of the quantity on the right-hand side is no greater than α, the proof is complete. However, Theorem 2.2 and Remark 2 of Ding et al. [2025] delivers exactly that, for any K,

$$P\left\{|S_{n,K}|_{[k]} > \hat{c}_{n,K}\left(1-\alpha,k\right)\right\} \leq \alpha + o(1)$$

under Assumptions M and R. So, chaining inequalities, we note that

$$k\text{-FWER}_P \leq P\left\{|S_{n,I(P)}|_{[k]} > \hat{c}_{n,I(P)}\left(1-\alpha,k\right)\right\} \leq \alpha + o(1)$$

and so

$$\limsup_{n,p\to\infty} k\text{-FWER}_P \leq \alpha$$

which is precisely what we wanted to show.

To prove the second statement, note that, for the Gaussian multiplier bootstrap, using Assumptions M and R, by the tail inequality Equation 2 in the proof of Lemma 4, and using the insight from Remark 2 of Ding et al. [2025] that quantiles for absolute values are identical to quantiles for a related $2p$ dimensional problem without absolute values,

$$\hat{c}_{n,[p]}\left(1-\alpha,k\right) \leq \hat{c}_{n,[p]}\left(1-\alpha,1\right) = O_P\left(B_n\sqrt{\log p}\right).$$

Now notice that each $S_{n,j} = \sqrt{n}\left[\hat{\theta}_{n,j} - \theta_j(P)\right]$ is tight, so consider that for the $H_{0,j}$ corresponding to all $\theta_j(P) > 0$ that

$$T_{n,j} = \sqrt{n}\hat{\theta}_{n,j} = \sqrt{n}(\hat{\theta}_{n,j} - \theta_j(P)) + \sqrt{n}\theta_j(P) \xrightarrow{P} \infty$$

and that for the $H_{0,j}$ corresponding to all $\theta_j(P) < 0$ that

$$T_{n,j} = \sqrt{n}\hat{\theta}_{n,j} = \sqrt{n}(\hat{\theta}_{n,j} - \theta_j(P)) + \sqrt{n}\theta_j(P) \xrightarrow{P} -\infty.$$

However, because $\sqrt{n}$ grows faster than $B_n\sqrt{\log p}$ by Assumption R, we have that also for all $H_{0,j}$ for which $\theta_j(P) \neq 0$

$$\frac{|T_{n,j}|}{B_n\sqrt{\log p}} \xrightarrow{P} \infty.$$

Therefore, with probability tending to one, $|T_{n,j}| > \hat{c}_{n,[p]}(1-\alpha, k)$, resulting in the rejection of $H_{0,j}$ in the first step of Algorithm 2.1, so long as $|\theta_j(P)|$ is fixed or approaches zero slower than a rate of $B_n\sqrt{\log p/n}$.

To prove the third statement, the asymptotic validity of the streamlined Algorithm 2.2 follows from the separation assumption

$$\min_{j \notin I(P)} |\theta_j(P)| \gg B_n\sqrt{\log p/n}$$

using the same logic as for the proof of the second statement and the argument of proof of Theorem 3.3 of Romano and Wolf [2007], i.e., $\min(|T_{n,j}| : j \notin I(P))$ is diverging at rate $\sqrt{n}$, and if any $\theta_j(P) = 0$ then $\max(|T_{n,j}| : j \in I(P)) = O_P(B_n\sqrt{\log p})$. □

Before proceeding to proofs of the high-dimensional CLTs, we define the following deterministic sequences:

$$\nu_n := 2n^{-1} + 3\sqrt{\frac{B_n^2 \log^3(pn)}{n}}, \qquad \beta_n := k^2\left(\frac{B_n^2 \log^5(pn)}{n}\right)^{1/4}$$

where both $\nu_n = o(1)$ and $\beta_n = o(1)$ under Assumption R.

Theorem 3 (High-dimensional CLT for the small k-max coordinate, MAM)**.** *Let $\tilde{S}_n := S_n + R_n$, and assume that $\|R_n\|_\infty = o_P(1/\sqrt{\log(pn)})$. Further assume that k is fixed (i.e., does not grow with n, p). If Assumptions M and R hold, then as $n, p \to \infty$*

$$\sup_{t\in\mathbb{R}} \left| P\left(\tilde{S}_{n,[k]} \leq t\right) - P\left(N(0,\Sigma)_{[k]} \leq t\right)\right| \to 0.$$

Proof. The proof of this lemma proceeds following the strategy of Chernozhukov et al. [2023].

First, recall that the function $t \mapsto t_{[k]}$ is 1-Lipschitz wrt to the sup-norm, meaning almost surely

$$\left|\tilde{S}_{n,[k]} - S_{n,[k]}\right| = \left|(S_n + R_n)_{[k]} - S_{n,[k]}\right| \leq \|R_n\|_\infty.$$

Consider the event $\{\|R_n\|_\infty \leq \epsilon\}$, as well as the event $\{(S_n + R_n)_{[k]} \leq t\}$. Then observe that

$$\{\|R_n\|_\infty \leq \epsilon\} \cap \{(S_n + R_n)_{[k]} \leq t\} \subseteq \{S_{n,[k]} \leq t + \epsilon\}$$

As such notice that

$$\{(S_n+R_n)_{[k]} \leq t\} = (\{(S_n+R_n)_{[k]} \leq t\} \cap \{\|R_n\|_\infty \leq \epsilon\}) \cup (\{(S_n+R_n)_{[k]} \leq t\} \cap \{\|R_n\|_\infty > \epsilon\})$$

and so

$$P(\tilde{S}_{n,[k]} \leq t) = P((S_n + R_n)_{[k]} \leq t) \leq P(S_{n,[k]} \leq t + \epsilon) + P(\|R_n\|_\infty > \epsilon).$$

We now need to apply an anti-concentration result, which can be found as embedded in Lemma A.7 of Ding et al. [2025]. It implies, for any t, for a C_1 depending on only b_1, b_2,

$$P\left(\tilde{S}_{n,[k]} \leq t\right) \leq P\left(S_{n,[k]} \leq t\right) + C_1 k\epsilon\sqrt{1 \vee \log(p/\epsilon)} + 2C_1\beta_n + P\left(\|R_n\|_\infty > \epsilon\right).$$

We then have, using Assumptions M and R in addition to the high-dimensional CLT for the k largest coordinate of Lemma A.6 in Ding et al. [2025] (which requires Assumption M):

$$\begin{aligned} P\left(\tilde{S}_{n,[k]} \leq t\right) &\leq P\left(S_{n,[k]} \leq t\right) + C_1 k\epsilon\sqrt{1 \vee \log(p/\epsilon)} + 2C_1\beta_n + P\left(\|R_n\|_\infty > \epsilon\right) \\ &\leq P\left(N(0,\Sigma)_{[k]} \leq t\right) + C_1 k\epsilon\sqrt{1 \vee \log(p/\epsilon)} + C_2\beta_n + P\left(\|R_n\|_\infty > \epsilon\right). \end{aligned}$$

Since $\sqrt{\log(pn)}\,\|R_n\|_\infty = o_P(1)$, there exists a deterministic sequence $\delta_n \searrow 0$ such that $P\big(\sqrt{\log(pn)}\,\|R_n\|_\infty > \delta_n\big) \to 0$. If we choose

$$\epsilon = \epsilon_n := \max\left\{\delta_n/\sqrt{\log(pn)},\ (pn)^{-1}\right\},$$

then $P(\|R_n\|_\infty > \epsilon_n) \to 0$, and since $\epsilon_n \geq (pn)^{-1}$ implies $\log(p/\epsilon_n) \leq \log(p^2 n) \leq 2\log(pn)$, we have, for fixed k,

$$k\,\epsilon_n\sqrt{1 \vee \log(p/\epsilon_n)} \ \leq\ \sqrt{2}\,k\,\max\left\{\delta_n,\ \tfrac{\sqrt{\log(pn)}}{pn}\right\} \ \to\ 0.$$

It follows that

$$P\left(\tilde{S}_{n,[k]} \leq t\right) \leq P\left(N(0,\Sigma)_{[k]} \leq t\right) + \rho_n + C_2\beta_n$$

where $\rho_n := C_1 k\epsilon_n\sqrt{1 \vee \log(p/\epsilon_n)} + P\left(\|R_n\|_\infty > \epsilon_n\right) = o(1)$ is deterministic.

From the reverse direction, note that

$$\left\{\|R_n\|_\infty \leq \epsilon\right\} \cap \left\{S_{n,[k]} \leq t - \epsilon\right\} \subseteq \left\{(S_n + R_n)_{[k]} \leq t\right\}$$

so it also holds that similarly, partitioning $\{S_{n,[k]} \leq t - \epsilon\}$ using $\{\|R_n\|_\infty \leq \epsilon\}$ and its complement, that

$$P\left(\tilde{S}_{n,[k]} \leq t\right) \geq P\left(S_{n,[k]} \leq t - \epsilon\right) - P\left(\|R_n\|_\infty > \epsilon\right),$$

and so using identical arguments as above we conclude that, uniformly in t,

$$\left|P\left(\tilde{S}_{n,[k]} \leq t\right) - P\left(N(0,\Sigma)_{[k]} \leq t\right)\right| \leq C_2\beta_n + \rho_n = o(1),$$

proving the stated result. □

Theorem 8 (High-dimensional bootstrap for the small k-max coordinate of approximate means)**.** *Let $\tilde{S}_n^B := S_n^B + R_n$, and assume that $\|R_n\|_\infty = o_P(1/\sqrt{\log(pn)})$. Further assume that k is fixed (i.e., does not grow with n, p). If Assumptions M and R hold, then as $n, p \to \infty$*

$$\sup_{t\in\mathbb{R}}\left|P^B\left(\tilde{S}^B_{n,[k]} \leq t\right) - P\left(N(0,\Sigma)_{[k]} \leq t\right)\right| \xrightarrow{P} 0.$$

Proof. The proof of this lemma proceeds following the strategy of Theorem 3. Using the same logic as the proof of Theorem 3, note that almost surely

$$P^B(\tilde{S}^B_{n,[k]} \leq t) = P^B((S^B_n + R_n)_{[k]} \leq t) \leq P^B(S^B_{n,[k]} \leq t + \epsilon) + P^B(\|R_n\|_\infty > \epsilon).$$

Observe that, from Ding et al. [2025] Lemma A.6 and Lemma A.8, using Assumptions M and R and the triangle inequality, with probability at least $1 - \nu_n$

$$\sup_{t \in \mathbb{R}} \left| P^B\left(S^B_{n,[k]} \leq t\right) - P\left(S_{n,[k]} \leq t\right) \right| \leq C_3 \beta_n,$$

and thus with probability at least $1 - \nu_n$

$$P^B(\tilde{S}^B_{n,[k]} \leq t) = P^B((S^B_n + R_n)_{[k]} \leq t) \leq P\left(S_{n,[k]} \leq t + \epsilon\right) + C_3\beta_n + P^B(\|R_n\|_\infty > \epsilon).$$

Then again using Lemma A.7 and Lemma A.6 of Ding et al. [2025] we get that with probability at least $1 - \nu_n$

$$P^B(\tilde{S}^B_{n,[k]} \leq t) \leq P\left(N(0,\Sigma)_{[k]} \leq t\right) + C_4\beta_n + \rho^B_n$$

where $\rho^B_n := C_1 k\epsilon\sqrt{1 \vee \log(p/\epsilon)} + P^B\left(\|R_n\|_\infty > \epsilon\right)$. The reverse direction proceeds similarly just as in Theorem 3, yielding still with probability at least $1-\nu_n$ (as in the reverse direction the "bad" event is the same)

$$|P^B(\tilde{S}^B_{n,[k]} \leq t) - P\left(N(0,\Sigma)_{[k]} \leq t\right)| \leq C_4\beta_n + \rho^B_n$$

uniformly in t. We may re-write this as, with probability at least $1 - \nu_n$,

$$|P^B(\tilde{S}^B_{n,[k]} \leq t) - P\left(N(0,\Sigma)_{[k]} \leq t\right)| - \rho^B_n \leq C_4\beta_n$$

and so using Lemma 2, uniformly in t,

$$|P^B(\tilde{S}^B_{n,[k]} \leq t) - P\left(N(0,\Sigma)_{[k]} \leq t\right)| - \rho^B_n = o_P(1).$$

By Lemma 1, $\sqrt{\log(pn)}\,\|R_n\|_\infty = o_P(1)$ implies $P^B\left(\sqrt{\log(pn)}\,\|R_n\|_\infty > u\right) = o_P(1)$ for every fixed $u > 0$; a standard diagonalization argument then yields a deterministic sequence $\delta_n \searrow 0$ with $P^B\left(\sqrt{\log(pn)}\,\|R_n\|_\infty > \delta_n\right) = o_P(1)$. Setting $\epsilon = \epsilon_n := \max\{\delta_n/\sqrt{\log(pn)}, (pn)^{-1}\}$ as in the proof of Theorem 3, we obtain $\log(p/\epsilon_n) \leq 2\log(pn)$ and hence $C_1 k\epsilon_n\sqrt{1 \vee \log(p/\epsilon_n)} = o(1)$ for fixed k, so that

$$\rho^B_n = C_1 k\epsilon_n\sqrt{1 \vee \log(p/\epsilon_n)} + P^B\left(\|R_n\|_\infty > \epsilon_n\right) = o(1) + o_P(1) = o_P(1).$$

This means that

$$|P^B(\tilde{S}^B_{n,[k]} \leq t) - P\left(N(0,\Sigma)_{[k]} \leq t\right)| = o_P(1)$$

uniformly in t, completing the proof. □

Theorem 9 (High-dimensional CLT for the small k-max studentized coordinate)**.** *Assume $X_i \overset{iid}{\sim} P$. If Assumptions M and R hold, $B_n = O(1)$, and k is fixed (i.e., does not grow with n, p), then, by application of Theorem 3, as $n, p \to \infty$*

$$\sup_{t \in \mathbb{R}} \left| P\left(\left(\hat{\Lambda}^{-1/2} S_n\right)_{[k]} \leq t\right) - P\left(N(0,\Sigma_0)_{[k]} \leq t\right) \right| \to 0.$$

Proof. Let $\tilde{S}_n := \hat{\Lambda}^{-1/2} S_n$. Then we may write $\tilde{S}_n = \Lambda^{-1/2} S_n + R_n$, and note that

$$R_n = \hat{\Lambda}^{-1/2} S_n - \Lambda^{-1/2} S_n = (\hat{\Lambda}^{-1/2} - \Lambda^{-1/2}) S_n,$$

and thus we can use the machinery of Theorem 3 to prove the desired result so long as we can show that $\|R_n\|_\infty = o_P(1/\sqrt{\log(pn)})$.

Note that, by the sub-multiplicative induced matrix norm inequality,

$$\left\| \left(\widehat{\Lambda}^{-1/2} - \Lambda^{-1/2} \right) S_n \right\|_\infty \leq \|\widehat{\Lambda}^{-1/2} - \Lambda^{-1/2}\|_\infty \, \|S_n\|_\infty = \|\widehat{\Lambda}^{-1/2} - \Lambda^{-1/2}\|_{\max} \, \|S_n\|_\infty$$

where the last equality follows from the fact that the max elementwise norm is equal to the induced operator ∞-norm for diagonal matrices.

To control the first term on the right-hand side, we may turn to Kuchibhotla and Chakrabortty [2022], Theorem 4.2, which shows that if X_{ij} are sub-Weibull with parameter $\alpha = 1$ (i.e., subexponential, granted by Assumption M), then Assumption R ensures that

$$\|\widehat{\Lambda} - \Lambda\|_{\max} = o_P(1/\log(pn)).$$

To see this, note that Theorem 4.2 of Kuchibhotla and Chakrabortty [2022] (spelled out in Remark 4.1) implies that

$$\|\hat{\Sigma} - \Sigma\|_{\max} = O_P\left(\sqrt{\frac{\log p}{n}} \vee \frac{(\log p)^2 (\log n)^2}{n} \right)$$

if $B_n = O(1)$ (where $\|\cdot\|_{\max}$ is the maximum elementwise norm), which we assume. As a consequence, Assumption R also delivers that $\|\widehat{\Lambda} - \Lambda\|_{\max} \leq \|\hat{\Sigma} - \Sigma\|_{\max} = o_P\left(1/\log(pn)\right)$, and thus $\|\widehat{\Lambda}^{-1/2} - \Lambda^{-1/2}\|_{\max} = o_P\left(1/\log(pn)\right)$ as well using a Taylor expansion argument and part (ii) of Assumption M.[57]

For the second term, note that, using Lemma 3 via Assumptions M and R, that $\|S_n\|_\infty = O_P(B_n\sqrt{\log p}) = O_P(\sqrt{\log p})$, where the last equality follows because $B_n = O(1)$ by assumption. Putting everything together then, we conclude

$$\left\| \left(\widehat{\Lambda}^{-1/2} - \Lambda^{-1/2} \right) S_n \right\|_\infty \leq o_P\left(1/\log(pn)\right) O_P(\sqrt{\log p}) = o_P(1/\sqrt{\log(pn)}).$$

□

Theorem 10 (High-dimensional bootstrap for the small k-max studentized coordinate)**.** *Assume $X_i \overset{iid}{\sim} P$. If Assumptions M and R hold, $B_n = O(1)$, and k is fixed (i.e., does not grow with n, p), then, by application of Theorem 8, as $n, p \to \infty$*

$$\sup_{t \in \mathbb{R}} \left| P^B \left(\left(\hat{\Lambda}^{-1/2} S_n^B \right)_{[k]} \leq t \right) - P\left(N(0, \Sigma_0)_{[k]} \leq t \right) \right| \xrightarrow{P} 0.$$

[57] Since $\widehat{\Lambda}$ and Λ are invariant under a common location shift of the data, we may apply the cited result to the centered array $X_i - E[X_i]$, whose marginal ψ_1-norms are bounded by B_n under Assumption M(i).

Proof. The proof of this theorem proceeds just as the proof of Theorem 9. Let $\tilde{S}_n^B := \hat{\Lambda}^{-1/2} S_n^B$ and

$$R_n = \hat{\Lambda}^{-1/2} S_n^B - \Lambda^{-1/2} S_n^B = (\hat{\Lambda}^{-1/2} - \Lambda^{-1/2}) S_n^B,$$

and thus we can use Theorem 8 to prove the desired result so long as we can show that, sufficiently, $\|R_n\|_\infty = o_P(1/\sqrt{\log(pn)})$.

Note then that almost surely, as in Theorem 9,

$$\left\| \left(\widehat{\Lambda}^{-1/2} - \Lambda^{-1/2} \right) S_n^B \right\|_\infty \leq \|\widehat{\Lambda}^{-1/2} - \Lambda^{-1/2}\|_{\max} \left\| S_n^B \right\|_\infty .$$

Using the same arguments as in the proof of Theorem 9, we conclude that $\|\widehat{\Lambda}^{-1/2} - \Lambda^{-1/2}\|_\infty = o_P(1/\log(pn))$. By Lemma 4 we have that $\|S_n^B\|_\infty = O_P(B_n \sqrt{\log p})$, and under $B_n = O(1)$ then $\|S_n^B\|_\infty = O_P(\sqrt{\log p})$. Thus, we complete the proof as in Theorem 9. □

Theorem 4 (High-dimensional k-FWER control for small k, studentized, one-sided)**.** *Assume that* $X_i \overset{iid}{\sim} P$. *Define* $\widehat{\Sigma}_{jj} := n^{-1} \sum_{i=1}^n (X_{ij} - \bar{X}_{n,j})^2$ *and* $\widehat{\Lambda} := \mathrm{diag}\{\widehat{\Sigma}_{11}, \ldots, \widehat{\Sigma}_{pp}\}$. *Consider the method of Algorithm 2.1 in Romano and Wolf [2007] with test statistics* $\hat{\Lambda}^{-1/2} T_n$ *of hypotheses* $\{\tilde{H}_{0,j}\}_{j \in [p]}$ *and critical values* $\hat{c}_{n,K}(1-\alpha, k)$ *given by the* $1-\alpha$ *quantile of* $(\hat{\Lambda}^{-1/2} S_n^B)_{K,[k]}$ *under* P^B. *Assume that* k *is fixed (i.e., not growing with* n, p*). Then under Assumptions M and R, so long as* $B_n = O(1)$*, this method ensures:*

(i) $\limsup_{n,p \to \infty} k\text{-}FWER_P \leq \alpha$.

(ii) If $\tilde{H}_{0,j}$ *is false and* $\theta_j(P) \gg \sqrt{\log p/n}$*, then the probability that the step-down method rejects* $\tilde{H}_{0,j}$ *tends to 1.*

(iii) If $\min_{j \notin I(P)} \theta_j(P) \gg \sqrt{\log p/n}$*, then conclusions (i) and (ii) also hold when Algorithm 2.1 is replaced by Algorithm 2.2 of Romano and Wolf [2007].*

Proof. We consider Algorithm 2.1 from Romano and Wolf [2007], which at each stage takes as inputs critical values $\hat{c}_{n,K}(1-\alpha, k)$ and a vector of test statistics T_n; we denote this as `RW-2.1`$(T_n, \hat{c}_{n,K}(1-\alpha, k))$.

The choice of critical values we will use is based on a bootstrap of the $1-\alpha$ quantile of the k-max:

$$\hat{c}_{n,K}(1-\alpha, k) := 1-\alpha \text{ quantile of } (\hat{\Lambda}^{-1/2} S_n^B)_{K,[k]} \mid X.$$

As in Romano and Wolf [2007], define $I(P)$ to be the set of indices of true null hypotheses under P. Note that, for any $K \supset I(P)$,

$$\hat{c}_{n,K}(1-\alpha, k) \geq \hat{c}_{n,I(P)}(1-\alpha, k)$$

because for any $K \supset I(P)$, and under any distribution, $(\hat{\Lambda}^{-1/2} S_n^B)_{K,[k]} \geq (\hat{\Lambda}^{-1/2} S_n^B)_{I(P),[k]}$ almost surely (i.e., the k-max statistic can only get larger if we include more test statistics without dropping the others).

As such, Theorem 2.1 (i) holds, and we conclude that `RW-2.1`$(\hat{\Lambda}^{-1/2} T_n, \hat{c}_{n,K}(1-\alpha, k))$ delivers:

$$k\text{-FWER}_P \leq P\left\{ k\text{-max}\left(\hat{\Lambda}_{jj}^{-1/2} T_{n,j} : j \in I(P) \right) > \hat{c}_{n,I(P)}(1-\alpha, k) \right\}.$$

Specifically, then, it is sufficient to show that

$$\limsup_{n,p} P\left\{k\text{-max}\left(\hat{\Lambda}_{jj}^{-1/2}T_{n,j} : j \in I(P)\right) > \hat{c}_{n,I(P)}(1-\alpha,k)\right\} \leq \alpha.$$

To continue to use the notation of Romano and Wolf [2007], let $\hat{\theta}_{n,j} := \bar{X}_{n,j}$. Since $\theta_j(P) \leq 0$ for $j \in I(P)$, it follows that, almost surely,

$$\begin{aligned} k\text{-max}\left(\hat{\Lambda}_{jj}^{-1/2}T_{n,j} : j \in I(P)\right) &= k\text{-max}\left(\hat{\Lambda}_{jj}^{-1/2}\sqrt{n}\hat{\theta}_{n,j} : j \in I(P)\right) \\ &\leq k\text{-max}\left(\hat{\Lambda}_{jj}^{-1/2}\sqrt{n}\left[\hat{\theta}_{n,j} - \theta_j(P)\right] : j \in I(P)\right) \\ &= k\text{-max}\left(\hat{\Lambda}_{jj}^{-1/2}S_{n,j} : j \in I(P)\right) \end{aligned}$$

and therefore

$$\begin{aligned} &P\left\{k\text{-max}\left(\hat{\Lambda}_{jj}^{-1/2}T_{n,j} : j \in I(P)\right) > \hat{c}_{n,I(P)}(1-\alpha,k)\right\} \\ \leq &P\left\{k\text{-max}\left(\hat{\Lambda}_{jj}^{-1/2}S_{n,j} : j \in I(P)\right) > \hat{c}_{n,I(P)}(1-\alpha,k)\right\}. \end{aligned}$$

If we can show that the limit of the quantity on the right-hand side is no greater than α, the proof is complete.

Recall, however, that Theorem 9 (via Theorem 3) gives us that, for any viable K,

$$\sup_{t\in\mathbb{R}}\left|P\left(\left(\hat{\Lambda}^{-1/2}S_n\right)_{K,[k]} \leq t\right) - P\left(N(0,\Sigma_0)_{K,[k]} \leq t\right)\right| \leq C_2\beta_n + \rho_n$$

and Theorem 10 (via Theorem 8) that, with probability at least $1-\nu_n$,

$$\sup_{t\in\mathbb{R}}\left|P^B\left(\left(\hat{\Lambda}^{-1/2}S_n^B\right)_{K,[k]} \leq t\right) - P\left(N(0,\Sigma_0)_{K,[k]} \leq t\right)\right| \leq C_4\beta_n + \rho_n^B$$

and so by the triangle inequality, with probability at least $1-\nu_n$,

$$\sup_{t\in\mathbb{R}}\left|P\left(\left(\hat{\Lambda}^{-1/2}S_n\right)_{K,[k]} \leq t\right) - P^B\left(\left(\hat{\Lambda}^{-1/2}S_n^B\right)_{K,[k]} \leq t\right)\right| \leq C_5\beta_n + \rho_n + \rho_n^B.$$

Now let $c_{1-\gamma}$ be the $1-\gamma$ quantile of $\left(\hat{\Lambda}^{-1/2}S_n\right)_{K,[k]}$, and use $c_{1-\gamma}^B = \hat{c}_{n,K}(1-\gamma,k)$ for shorthand. Since $\rho_n^B = o_P(1)$, fix a deterministic sequence $w_n \searrow 0$ such that $P(\rho_n^B > w_n) = o(1)$, and define the deterministic sequences

$$\check{\beta}_n := C_5\beta_n + \rho_n + w_n, \qquad \tilde{\beta}_n := 2(C_2+C_5)\beta_n + 4\rho_n + 2w_n,$$

so that $c_{1-\alpha+\check{\beta}_n}$ and $c_{1-\alpha-\tilde{\beta}_n}$ are well-defined population quantiles (for all n large enough that $\check{\beta}_n < 1-\alpha$ and $\tilde{\beta}_n < \alpha$). Work on the intersection of the event on which the uniform comparison of the previous display holds and the event $\{\rho_n^B \leq w_n\}$; this intersection has

probability at least $1 - \nu_n - P(\rho_n^B > w_n)$, and on it the uniform comparison holds with the deterministic bound $C_5\beta_n + \rho_n + w_n$. Consequently, on this event, both

$$P^B\left(\left(\hat{\Lambda}^{-1/2}S_n^B\right)_{K,[k]} \le c_{1-\alpha+\check{\beta}_n}\right) \ge P\left(\left(\hat{\Lambda}^{-1/2}S_n\right)_{K,[k]} \le c_{1-\alpha+\check{\beta}_n}\right) - (C_5\beta_n + \rho_n + w_n) \ge 1 - \alpha$$

and

$$\begin{aligned} P^B\left(\left(\hat{\Lambda}^{-1/2}S_n^B\right)_{K,[k]} \le c_{1-\alpha-\tilde{\beta}_n}\right) &\le P\left(\left(\hat{\Lambda}^{-1/2}S_n\right)_{K,[k]} \le c_{1-\alpha-\tilde{\beta}_n}\right) + C_5\beta_n + \rho_n + w_n \\ &\le (1 - \alpha - \tilde{\beta}_n) + 2C_2\beta_n + 2\rho_n + C_5\beta_n + \rho_n + w_n \\ &< 1 - \alpha, \end{aligned}$$

where the second inequality comes from the fact that

$$P\left(\left(\hat{\Lambda}^{-1/2}S_n\right)_{K,[k]} \le t + \epsilon\right) \le P\left(\left(\hat{\Lambda}^{-1/2}S_n\right)_{K,[k]} \le t\right) + C_1 k\epsilon\sqrt{1 \vee \log(p/\epsilon)} + 2(C_2\beta_n + \rho_n)$$

using the argument of Lemma A.7 of Ding et al. [2025] via Theorem 3 (letting $t = c_{1-\alpha-\tilde{\beta}_n} - \epsilon$ and taking $\epsilon \searrow 0$), and the final inequality holds because $\tilde{\beta}_n > (2C_2 + C_5)\beta_n + 3\rho_n + w_n$.

This in turn implies that

$$P(c_{1-\alpha-\tilde{\beta}_n} < c_{1-\alpha}^B \le c_{1-\alpha+\check{\beta}_n}) \ge 1 - \nu_n - P(\rho_n^B > w_n).$$

This in turn implies that both

$$\begin{aligned} P((\hat{\Lambda}^{-1/2}S_n)_{K,[k]} > c_{1-\alpha}^B) &\le P((\hat{\Lambda}^{-1/2}S_n)_{K,[k]} > c_{1-\alpha-\tilde{\beta}_n}) + (\nu_n + P(\rho_n^B > w_n)) \\ &\le \alpha + \tilde{\beta}_n + (\nu_n + P(\rho_n^B > w_n)) \end{aligned}$$

and, using Lemma A.7 of Ding et al. [2025] via Theorem 3 again,

$$\begin{aligned} P((\hat{\Lambda}^{-1/2}S_n)_{K,[k]} > c_{1-\alpha}^B) &\ge P((\hat{\Lambda}^{-1/2}S_n)_{K,[k]} > c_{1-(\alpha-\check{\beta}_n)}) - (\nu_n + P(\rho_n^B > w_n)) \\ &\ge \alpha - \check{\beta}_n - 2(C_2\beta_n + \rho_n) - (\nu_n + P(\rho_n^B > w_n)). \end{aligned}$$

These two statements then jointly imply that

$$|P((\hat{\Lambda}^{-1/2}S_n)_{K,[k]} > \hat{c}_{n,K}(1-\alpha, k)) - \alpha| \le o(1).$$

So, chaining inequalities, we arrive at

$$k\text{-FWER}_P \le P\left\{(\hat{\Lambda}^{-1/2}S_n)_{I(P),[k]} > \hat{c}_{n,I(P)}\,(1-\alpha, k)\right\} \le \alpha + o(1)$$

and so

$$\limsup_{n,p\to\infty} k\text{-FWER}_P \le \alpha$$

which is precisely what we wanted to show.

To prove the second statement, consider the $\tilde{H}_{0,j}$ corresponding to all $\theta_j(P) > 0$. Note that, for the Gaussian multiplier bootstrap, using Assumptions M and R, by the tail inequality Equation 2 in the proof of Lemma 4 we can conclude that (because $B_n = O(1)$)

$$\hat{c}_{n,[p]}\left(1-\alpha, k\right) \leq \hat{c}_{n,[p]}\left(1-\alpha, 1\right) = O_P\left(\sqrt{\log p}\right)$$

(noting that premultiplication by $\hat{\Lambda}^{-1/2}$ under the data conditional law is just a particular choice of normalization). Furthermore, each $S_{n,j} = \sqrt{n}\left[\hat{\theta}_{n,j} - \theta_j(P)\right]$ is tight, and the conventional Lindeberg-Levy CLT and non-degeneracy and bounded fourth moments from Assumption M yields $|\hat{\Lambda}_{jj}^{-1/2} - \Lambda_{jj}^{-1/2}| = O_P(n^{-1/2})$, so

$$\begin{aligned}
\hat{\Lambda}_{jj}^{-1/2} T_{n,j} &= \hat{\Lambda}_{jj}^{-1/2}\sqrt{n}\hat{\theta}_{n,j} \\
&= (\Lambda_{jj}^{-1/2} + O_P(n^{-1/2}))\sqrt{n}(\hat{\theta}_{n,j} - \theta_j(P)) + O_P(n^{-1/2})\sqrt{n}\theta_j(P) + \Lambda_{jj}^{-1/2}\sqrt{n}\theta_j(P) \\
&= \Lambda_{jj}^{-1/2} O_P(1) + O_P(n^{-1/2}) + O_P(1)\theta_j(P) + \Lambda_{jj}^{-1/2}\sqrt{n}\theta_j(P) \xrightarrow{P} \infty
\end{aligned}$$

because the last term is diverging. However, because $\sqrt{n}$ grows faster than $\sqrt{\log p}$ when $B_n = O(1)$ by Assumption R, we have that also

$$\frac{\hat{\Lambda}_{jj}^{-1/2} T_{n,j}}{\sqrt{\log p}} \xrightarrow{P} \infty.$$

Therefore, with probability tending to one, $T_{n,j} > \hat{c}_{n,[p]}\left(1-\alpha, k\right)$, resulting in the rejection of $\tilde{H}_{0,j}$ in the first step of Algorithm 2.1, so long as $\theta_j(P)$ is fixed or approaches zero slower than a rate of $\sqrt{\log p/n}$.

To prove the third statement, the asymptotic validity of the streamlined Algorithm 2.2 follows from the separation assumption

$$\min_{j \notin I(P)} \theta_j(P) \gg B_n\sqrt{\log p/n}$$

using the same logic as for the proof of the second statement and the argument of proof of Theorem 3.3 of Romano and Wolf [2007], i.e., $\min\left(\hat{\Lambda}_{jj}^{-1/2} T_{n,j} : j \notin I(P)\right)$ is diverging at rate $\sqrt{n}$, and if any $\theta_j(P) = 0$ then $\max\left(\hat{\Lambda}_{jj}^{-1/2} T_{n,j} : j \in I(P)\right) = O_P(B_n\sqrt{\log p}) = O_P(\sqrt{\log p})$. □

Theorem 5 (High-dimensional bootstrap for the small k-max coordinate with estimated influence function)**.** *Define*

$$\tilde{S}_n^B := \frac{1}{\sqrt{n}}\sum_{i=1}^n \xi_i \hat{\psi}_i.$$

Further assume that k is fixed (i.e., does not grow with n, p). If Assumptions M, R, and A hold, then as $n, p \to \infty$

$$\sup_{t \in \mathbb{R}} \left| P^B\left(\tilde{S}_{n,[k]}^B \leq t\right) - P\left(N(0,\Sigma)_{[k]} \leq t\right)\right| \xrightarrow{P} 0.$$

Proof. We follow the proof strategy of Belloni et al. [2018], Theorem 2.2.

Because of Assumption A, as per Belloni et al. [2018], there exist two deterministic sequences $\delta_n \searrow 0, v_n \searrow 0$ that satisfy

$$P\left(\max_{j\in[p]} \frac{1}{n}\sum_{i=1}^{n}\left[\left(\hat{\psi}_{ij}-\psi_{ij}\right)^2\right] > \delta_n^2/\log^2(pn)\right) \leq v_n,$$

Set $\Delta_n := \delta_n/\sqrt{\log(pn)}$, and observe that, under the bootstrap law P^B, that $\frac{1}{\sqrt{n}}\sum_{i=1}^{n}\xi_i\left(\hat{\psi}_{ij}-\psi_{ij}\right)$ is a zero-mean Gaussian with variance $n^{-1}\sum_{i=1}^{n}\left(\hat{\psi}_{ij}-\psi_{ij}\right)^2$. Thus by the Borell-TIS inequality, for any $\alpha \in (0,1)$,

$$P^B\left(\max_{j\in[p]}\left|\frac{1}{\sqrt{n}}\sum_{i=1}^{n}\xi_i\left(\hat{\psi}_{ij}-\psi_{ij}\right)\right| > \max_{j\in[p]}\sqrt{n^{-1}\sum_{i=1}^{n}\left[\left(\hat{\psi}_{ij}-\psi_{ij}\right)^2\right]}\left(\sqrt{2\log(2p)}+\sqrt{2\log(1/\alpha)}\right)\right) \leq 2\alpha.$$

Using Assumption A and setting $\alpha = \delta_n/2 \geq 1/(2n)$, we then have that

$$P^B\left(\max_{j\in[p]}\left|\frac{1}{\sqrt{n}}\sum_{i=1}^{n}\xi_i\left(\hat{\psi}_{ij}-\psi_{ij}\right)\right| > C_7\Delta_n\right) \leq \delta_n$$

with probability $1-v_n$ for some universal constant C_7. So far, these arguments are identical to Belloni et al. [2018].

Now consider the event $\left\{\max_{j\in[p]}\left|\frac{1}{\sqrt{n}}\sum_{i=1}^{n}\xi_i\left(\hat{\psi}_{ij}-\psi_{ij}\right)\right| > C_7\Delta_n\right\}$ for any p, n and $t > 0$ and $k \geq 1$ and notice that

$$\begin{aligned}
&\left\{\max_{j\in[p]}\left|\frac{1}{\sqrt{n}}\sum_{i=1}^{n}\xi_i\left(\hat{\psi}_{ij}-\psi_{ij}\right)\right| > C_7\Delta_n\right\} \\
&\supseteq \left\{\left|k\text{-}\max_{j\in[p]}\frac{1}{\sqrt{n}}\sum_{i=1}^{n}\xi_i\hat{\psi}_{ij} - k\text{-}\max_{j\in[p]}\frac{1}{\sqrt{n}}\sum_{i=1}^{n}\xi_i\psi_{ij}\right| > C_7\Delta_n\right\} \\
&\supseteq \left\{k\text{-}\max_{j\in[p]}\frac{1}{\sqrt{n}}\sum_{i=1}^{n}\xi_i\psi_{ij} - k\text{-}\max_{j\in[p]}\frac{1}{\sqrt{n}}\sum_{i=1}^{n}\xi_i\hat{\psi}_{ij} > C_7\Delta_n\right\} \\
&\supseteq \left\{k\text{-}\max_{j\in[p]}\frac{1}{\sqrt{n}}\sum_{i=1}^{n}\xi_i\psi_{ij} > t + C_7\Delta_n\right\} \cap \left\{k\text{-}\max_{j\in[p]}\frac{1}{\sqrt{n}}\sum_{i=1}^{n}\xi_i\hat{\psi}_{ij} \leq t\right\}.
\end{aligned}$$

where the second line follows by noting that the k-max function is L_∞ Lipschitz. Then notice that, almost surely, by a Boole-Fréchet inequality,

$$\begin{aligned}
&P^B\left(\left\{k\text{-}\max_{j\in[p]}\frac{1}{\sqrt{n}}\sum_{i=1}^{n}\xi_i\psi_{ij} > t + C_7\Delta_n\right\} \cap \left\{k\text{-}\max_{j\in[p]}\frac{1}{\sqrt{n}}\sum_{i=1}^{n}\xi_i\hat{\psi}_{ij} \leq t\right\}\right) \\
\geq &P^B\left(\left\{k\text{-}\max_{j\in[p]}\frac{1}{\sqrt{n}}\sum_{i=1}^{n}\xi_i\hat{\psi}_{ij} \leq t\right\}\right) - P^B\left(\left\{k\text{-}\max_{j\in[p]}\frac{1}{\sqrt{n}}\sum_{i=1}^{n}\xi_i\psi_{ij} \leq t + C_7\Delta_n\right\}\right),
\end{aligned}$$

meaning that still with probability $1 - v_n$

$$P^B\left(k\text{-}\max_{j\in[p]} \frac{1}{\sqrt{n}}\sum_{i=1}^{n} \xi_i \hat{\psi}_{ij} \le t\right) \le P^B\left(k\text{-}\max_{j\in[p]} \frac{1}{\sqrt{n}}\sum_{i=1}^{n} \xi_i \psi_{ij} \le t + C_7\Delta_n\right) + \delta_n.$$

However, we also have, using equation (34) (which invokes anti-concentration result Corollary A.1) and Proposition 2.4 from Ding et al. [2025] and the triangle inequality,

$$P^B\left(k\text{-}\max_{j\in[p]} \frac{1}{\sqrt{n}}\sum_{i=1}^{n} \xi_i \hat{\psi}_{ij} \le t\right) \le P\left(N(0,\Sigma)_{[k]} \le t\right) + \delta_n + C_8\beta_n$$

with a probability $1 - 1/\left(2n^4\right) - 1/n - 3\nu_n - v_n = 1 - o(1)$ with some constant C_8 that only depends on b_1, b_2.

The lower bound can be proven using nearly identical arguments and setting a threshold of $t - C_7\Delta_n$; because these arguments hold for any t, we thus conclude, for fixed k, with probability at least $1 - 1/\left(2n^4\right) - 1/n - 3\nu_n - v_n$,

$$\sup_{t\in\mathbb{R}} \left| P^B\left(\tilde{S}^B_{n,[k]} \le t\right) - P\left(N(0,\Sigma)_{[k]} \le t\right)\right| \le \delta_n + C_8\beta_n.$$

Application of Lemma 2 then completes the proof.

□

Theorem 6 (High-dimensional k-FWER control for small k, MAM, one-sided)**.** *Consider the method of Algorithm 2.1 in Romano and Wolf [2007] with test statistics $\sqrt{n}\hat{\theta}_j$ of null hypotheses $\tilde{H}_{0,j} : \theta_j(P) \le 0$ for all $j \in [p]$, and critical values $\hat{c}_{n,K}(1-\alpha, k)$ given by the $1-\alpha$ quantile of $\tilde{S}^B_{n,K,[k]}$ under P^B. Assume that k is fixed (i.e., not growing with n, p) and that for all $j \in [p]$ the asymptotically linear representation of equation (1) holds with $\|R_n\|_\infty = o_P(1/\sqrt{\log(pn)})$. Then under Assumptions M, R, and A, this method ensures:*

(i) $\limsup_{n,p\to\infty} k\text{-}FWER_P \le \alpha$.

(ii) If $\tilde{H}_{0,j}$ is false and $\theta_j(P) \gg B_n\sqrt{\log p/n}$, then the probability that the step-down method rejects $\tilde{H}_{0,j}$ tends to 1.

(iii) If $\min_{j\notin I(P)} \theta_j(P) \gg B_n\sqrt{\log p/n}$, then conclusions (i) and (ii) also hold when Algorithm 2.1 is replaced by Algorithm 2.2 of Romano and Wolf [2007].

Proof. We consider Algorithm 2.1 from Romano and Wolf [2007], which at each stage takes as inputs critical values $\hat{c}_{n,K}(1-\alpha, k)$ and a vector of test statistics T_n; we denote this as `RW-2.1`$(T_n, \hat{c}_{n,K}(1-\alpha, k))$.

The choice of critical values we will use is based on a bootstrap of the $1-\alpha$ quantile of the k-max:

$$\hat{c}_{n,K}(1-\alpha, k) := 1-\alpha \text{ quantile of } (\tilde{S}^B_n)_{K,[k]} \mid X.$$

As in Romano and Wolf [2007], define $I(P)$ to be the set of indices of true null hypotheses under P. Note that, for any $K \supset I(P)$,

$$\hat{c}_{n,K}(1-\alpha, k) \ge \hat{c}_{n,I(P)}(1-\alpha, k)$$

because for any $K \supset I(P)$, and under any distribution, $(\tilde{S}_n^B)_{K,[k]} \geq (\tilde{S}_n^B)_{I(P),[k]}$ almost surely (i.e., the k-max statistic can only get larger if we include more test statistics without dropping the others).

As such, Theorem 2.1 (i) holds, and we conclude that `RW-2.1`$(\sqrt{n}\hat{\theta}, \hat{c}_{n,K}(1-\alpha,k))$ delivers:

$$k\text{-FWER}_P \leq P\left\{k\text{-max}\left(\sqrt{n}\hat{\theta}_j : j \in I(P)\right) > \hat{c}_{n,I(P)}(1-\alpha,k)\right\}.$$

Specifically, then, it is sufficient to show that

$$\limsup_{n,p} P\left\{k\text{-max}\left(\sqrt{n}\hat{\theta}_j : j \in I(P)\right) > \hat{c}_{n,I(P)}(1-\alpha,k)\right\} \leq \alpha.$$

Since $\theta_j(P) \leq 0$ for $j \in I(P)$, it follows that, almost surely,

$$k\text{-max}\left(\sqrt{n}\hat{\theta}_j : j \in I(P)\right) \leq k\text{-max}\left(\sqrt{n}\left[\hat{\theta}_j - \theta_j(P)\right] : j \in I(P)\right)$$

and therefore

$$\begin{aligned}
&P\left\{k\text{-max}\left(\sqrt{n}\hat{\theta}_j : j \in I(P)\right) > \hat{c}_{n,I(P)}(1-\alpha,k)\right\} \\
\leq &P\left\{k\text{-max}\left(\sqrt{n}(\hat{\theta}_j - \theta_j(P)) : j \in I(P)\right) > \hat{c}_{n,I(P)}(1-\alpha,k)\right\} \\
= &P\left\{k\text{-max}\left(\tilde{S}_{n,j} : j \in I(P)\right) > \hat{c}_{n,I(P)}(1-\alpha,k)\right\}
\end{aligned}$$

where the last equality is simply notation. If we can show that the limit of the quantity on the right-hand side is no greater than α, the proof is complete.

Recall, however, that Theorem 3 gives us that, for any viable K,

$$\sup_{t\in\mathbb{R}}\left|P\left(\tilde{S}_{n,K,[k]} \leq t\right) - P\left(N(0,\Sigma)_{K,[k]} \leq t\right)\right| \leq C_2\beta_n + \rho_n$$

and Theorem 5 that, with probability at least $1-\tilde{\nu}_n$ (where $\tilde{\nu}_n := 1/(2n^4) + 1/n + 3\nu_n + v_n$),

$$\sup_{t\in\mathbb{R}}\left|P^B\left(\tilde{S}^B_{n,K,[k]} \leq t\right) - P\left(N(0,\Sigma)_{K,[k]} \leq t\right)\right| \leq \delta_n + C_8\beta_n$$

and so by the triangle inequality, with probability at least $1-\tilde{\nu}_n$,

$$\sup_{t\in\mathbb{R}}\left|P\left(\tilde{S}_{n,K,[k]} \leq t\right) - P^B\left(\tilde{S}^B_{n,K,[k]} \leq t\right)\right| \leq \delta_n + \rho_n + C_9\beta_n.$$

Now let $c_{1-\gamma}$ be the $1-\gamma$ quantile of $\tilde{S}_{n,K,[k]}$, and use $c^B_{1-\gamma} = \hat{c}_{n,K}(1-\gamma,k)$ for shorthand. Then, letting $\check{\beta}_n := \delta_n + \rho_n + C_9\beta_n$, with probability at least $1-\tilde{\nu}_n$ both

$$P^B\left(\tilde{S}^B_{n,K,[k]} \leq c_{1-\alpha+\check{\beta}_n}\right) \geq P\left(\tilde{S}_{n,K,[k]} \leq c_{1-\alpha+\check{\beta}_n}\right) - (\delta_n + \rho_n + C_9\beta_n) \geq 1-\alpha$$

and letting $\tilde{\beta}_n := (2C_2 + 2C_9)\beta_n + 4\rho_n + 2\delta_n$,

$$\begin{aligned} P^B\left(\tilde{S}^B_{n,K,[k]} \leq c_{1-\alpha-\tilde{\beta}_n}\right) &\leq P\left(\tilde{S}_{n,K,[k]} \leq c_{1-\alpha-\tilde{\beta}_n}\right) + \delta_n + \rho_n + C_9\beta_n \\ &\leq (1-\alpha-\tilde{\beta}_n) + 2C_2\beta_n + 2\rho_n + \delta_n + \rho_n + C_9\beta_n \\ &= (1-\alpha-\tilde{\beta}_n) + C_{10}\beta_n + 3\rho_n + \delta_n \\ &< 1-\alpha \end{aligned}$$

where again the second inequality comes from the fact that

$$P\left(\tilde{S}_{n,K,[k]} \leq t+\epsilon\right) \leq P\left(\tilde{S}_{n,K,[k]} \leq t\right) + C_1 k\epsilon\sqrt{1 \vee \log(p/\epsilon)} + 2(C_2\beta_n + \rho_n)$$

using Lemma A.7 of Ding et al. [2025] via Theorem 3 (and then, specifically, letting $t = c_{1-\alpha-\tilde{\beta}_n} - \epsilon$ and then taking $\epsilon \searrow 0$).

This in turn implies that

$$P(c_{1-\alpha-\tilde{\beta}_n} < c^B_{1-\alpha} \leq c_{1-\alpha+\check{\beta}_n}) \geq 1 - \tilde{\nu}_n.$$

This in turn implies that both

$$\begin{aligned} P(\tilde{S}_{n,K,[k]} > c^B_{1-\alpha}) &\leq P(\tilde{S}_{n,K,[k]} > c_{1-\alpha-\tilde{\beta}_n}) + \tilde{\nu}_n \\ &\leq \alpha + \tilde{\beta}_n + \tilde{\nu}_n \end{aligned}$$

and, using Lemma A.7 of Ding et al. [2025] via Theorem 3 again,

$$\begin{aligned} P(\tilde{S}_{n,K,[k]} > c^B_{1-\alpha}) &\geq P(\tilde{S}_{n,K,[k]} > c_{1-(\alpha-\check{\beta}_n)}) - \tilde{\nu}_n \\ &\geq \alpha - \check{\beta}_n - 2(C_2\beta_n + \rho_n) - \tilde{\nu}_n. \end{aligned}$$

These two statements then jointly imply that

$$|P(\tilde{S}_{n,K,[k]} > \hat{c}_{n,K}(1-\alpha)) - \alpha| \leq o(1).$$

So, chaining inequalities, we arrive at

$$k\text{-FWER}_P \leq P\left\{\tilde{S}_{n,I(P),[k]} > \hat{c}_{n,I(P)}\left(1-\alpha, k\right)\right\} \leq \alpha + o(1)$$

and so

$$\limsup_{n,p\to\infty} k\text{-FWER}_P \leq \alpha$$

which is precisely what we wanted to show.

To prove the second statement, consider the $\tilde{H}_{0,j}$ corresponding to all $\theta_j(P) > 0$. Note that the critical values are based on $\tilde{S}^B_n$, which is built from *estimated* influence functions; by Lemma 5 (which uses Assumptions M, R, and A), we have

$$\hat{c}_{n,[p]}\left(1-\alpha, k\right) \leq \hat{c}_{n,[p]}\left(1-\alpha, 1\right) = O_P\left(B_n\sqrt{\log p}\right)$$

because the two conditional bounds from this lemma imply that for every $\varepsilon > 0$ there exists $M < \infty$ such that, with unconditional probability tending to one, $P^B(\|\tilde{S}_n^B\|_\infty > MB_n\sqrt{\log p}) \leq \varepsilon$ (and taking $\varepsilon < \alpha$ yields $\hat{c}_{n,[p]}(1-\alpha, 1) \leq MB_n\sqrt{\log p}$ with probability tending to one, i.e., $\hat{c}_{n,[p]}(1-\alpha, k) = O_P(B_n\sqrt{\log p})$).

Furthermore, each $\tilde{S}_{n,j} = \sqrt{n}\left[\hat{\theta}_{n,j} - \theta_j(P)\right]$ is tight, and so

$$\sqrt{n}\hat{\theta}_j = \sqrt{n}(\hat{\theta}_j - \theta_j(P)) + \sqrt{n}\theta_j(P) \xrightarrow{P} \infty.$$

However, because $\sqrt{n}$ grows faster than $B_n\sqrt{\log p}$ by Assumption R, we have that also

$$\frac{\sqrt{n}\hat{\theta}_j}{B_n\sqrt{\log p}} \xrightarrow{P} \infty.$$

Therefore, with probability tending to one, $\sqrt{n}\hat{\theta}_j > \hat{c}_{n,[p]}(1-\alpha, k)$, resulting in the rejection of $\tilde{H}_{0,j}$ in the first step of Algorithm 2.1, so long as $\theta_j(P)$ is fixed or approaches zero slower than a rate of $B_n\sqrt{\log p/n}$.

To prove the third statement, the asymptotic validity of the streamlined Algorithm 2.2 follows from the separation assumption

$$\min_{j \notin I(P)} \theta_j(P) \gg B_n\sqrt{\log p/n}$$

using the same logic as for the proof of the second statement and the argument of proof of Theorem 3.3 of Romano and Wolf [2007], i.e., $\min\left(\sqrt{n}\hat{\theta}_j : j \notin I(P)\right)$ is diverging at rate $\sqrt{n}$, and if any $\theta_j(P) = 0$ then $\max\left(\sqrt{n}\hat{\theta}_j : j \in I(P)\right) = O_P(B_n\sqrt{\log p})$. □

Proposition 1 (Conditional inference on detection score)**.** *Let $m := |\mathcal{I}^{eval}|$. Define the detection score estimator for concept indicator j as*

$$\hat{\theta}_j^{acc} := \frac{1}{m}\sum_{i \in \mathcal{I}^{eval}} S_{ij}, \quad S_{ij} = \mathbf{1}\{Y_{ij} = \hat{Y}_{ij}\} = \mathbf{1}\{Y_{ij} = \texttt{CLS}(Z_i, \hat{\eta}_j)\}.$$

Assume there exists a constant $\delta \in (0, 1/2)$ such that $P(S_{ij} = 1 \mid \hat{\eta}_j) \in [\delta, 1-\delta]$ almost surely. Then we have that $E_P\left[\hat{\theta}_j^{acc} \mid \hat{\eta}_j\right] = \theta_j^{acc}(\hat{\eta}_j; P)$ almost surely, and that as $m \to \infty$

$$\sup_{t \in \mathbb{R}} \left| P\left(\sqrt{m}(\hat{\theta}_j^{acc} - \theta_j^{acc}(\hat{\eta}_j; P)) \leq t \mid \hat{\eta}_j\right) - P(N(0, \mathrm{Var}(S_{ij} \mid \hat{\eta}_j)) \leq t \mid \hat{\eta}_j) \right| \xrightarrow{a.s.} 0.$$

Proof. To show the conditional unbiasedness of the estimator, observe that

$$E_P\left[\hat{\theta}_j^{\mathrm{acc}} \mid \hat{\eta}_j\right] = \frac{1}{m}\sum_{i \in \mathcal{I}^{\mathrm{eval}}} E_P[S_{ij} \mid \hat{\eta}_j] = \theta_j^{\mathrm{acc}}(\hat{\eta}_j; P)$$

because S_{ij} is drawn i.i.d. under the $\hat{\eta}_j$-conditional law.

To show $\sqrt{m}$-consistency and asymptotic normality, we make use of Lemma 1 from Modarressi et al. [2025], a clean statement of a conditional Berry-Esseen theorem for i.n.i.d.

data. Noticing that for all $i \in \mathcal{I}^{\text{eval}}$ that $\zeta_{ij} := S_{ij} - \theta_j^{\text{acc}}(\hat{\eta}_j; P)$ are mean zero and independent, and that their third moments are bounded under the conditional law almost surely (as $S_{ij} \in \{0,1\}$ and $\theta_j^{\text{acc}}(\hat{\eta}_j; P) \in [0,1]$), using the assumption that $P(S_{ij} = 1 \mid \hat{\eta}_j) \in [\delta, 1-\delta]$, this lemma provides that

$$\sup_{t \in \mathbb{R}} \left| P\left(m^{-1/2} \sum_{i \in \mathcal{I}^{\text{eval}}} \zeta_{ij} \le t \mid \hat{\eta}_j \right) - P(N(0, \text{Var}(S_{ij} \mid \hat{\eta}_j)) \le t \mid \hat{\eta}_j) \right| \le C_0 \frac{\sum_{i \in \mathcal{I}^{\text{eval}}} E\left[|\zeta_{ij}|^3 \mid \hat{\eta}_j \right]}{\left(\sum_{i \in \mathcal{I}^{\text{eval}}} E\left[\zeta_{ij}^2 \mid \hat{\eta}_j \right] \right)^{3/2}}$$

for some universal constant $C_0 < \infty$, almost surely. The left-hand side of this inequality is exactly the left-hand side of the convergence statement in the proposition being proved. As for the right-hand side, note that then, given our previous observations and assumptions, $E\left[|\zeta_{ij}|^3 \mid \hat{\eta}_j \right] \le 1$ almost surely, and $E\left[\zeta_{ij}^2 \mid \hat{\eta}_j \right] = \text{Var}(S_{ij} \mid \hat{\eta}_j) \ge \delta(1-\delta) = C_1 > 0$, almost surely. Thus we have that

$$C_0 \frac{\sum_{i \in \mathcal{I}^{\text{eval}}} E\left[|\zeta_{ij}|^3 \mid \hat{\eta}_j \right]}{\left(\sum_{i \in \mathcal{I}^{\text{eval}}} E\left[\zeta_{ij}^2 \mid \hat{\eta}_j \right] \right)^{3/2}} \le C_0 \frac{m}{(C_1 m)^{3/2}} = \frac{C_0}{C_1^{3/2}} m^{-1/2} \asymp m^{-1/2}.$$

Taking $m \to \infty$ then proves the stated claim. □

Proposition 2 (Influence function approximation for many linear regressions)**.** *Let $\{(Y_i, T_i, D_i)\}_{i=1}^n$ be drawn i.i.d. from distribution P, where $Y_i = (Y_{i1}, \ldots, Y_{ip})^\intercal \in \mathbb{R}^p$, $T_i \in \mathbb{R}$, and $D_i \in \mathbb{R}^d$ with fixed d, and D_i includes a constant. Let $L_P[\cdot \mid \cdot]$ denote the linear projection operator. Define population quantities*

$$\widetilde{T} := T - L_P[T \mid D], \qquad \widetilde{Y}_j := Y_j - L_P[Y_j \mid D], \qquad \Omega := E_P[\widetilde{T}^2], \qquad \theta_j := \Omega^{-1} E_P[\widetilde{T}\,\widetilde{Y}_j],$$
$$\widetilde{U}_j := \widetilde{Y}_j - \theta_j \widetilde{T}, \qquad \psi_{ij} := \Omega^{-1} \widetilde{T}_i \widetilde{U}_{ij}.$$

Define feasible sample analog quantities as

$$\widehat{\gamma}_T := E_n[D_i D_i^\intercal]^{-1} E_n[D_i T_i], \qquad \widehat{\gamma}_{Y_j} := E_n[D_i D_i^\intercal]^{-1} E_n[D_i Y_{ij}],$$
$$\widehat{\widetilde{T}}_i := T_i - D_i^\intercal \widehat{\gamma}_T, \qquad \widehat{\widetilde{Y}}_{ij} := Y_{ij} - D_i^\intercal \widehat{\gamma}_{Y_j},$$
$$\widehat{\Omega} := E_n[\widehat{\widetilde{T}}_i^2], \qquad \widehat{\theta}_j := \widehat{\Omega}^{-1} E_n[\widehat{\widetilde{T}}_i \widehat{\widetilde{Y}}_{ij}], \qquad \widehat{\widetilde{U}}_{ij} := \widehat{\widetilde{Y}}_{ij} - \widehat{\theta}_j \widehat{\widetilde{T}}_i, \qquad \widehat{\psi}_{ij} := \widehat{\Omega}^{-1} \widehat{\widetilde{T}}_i \widehat{\widetilde{U}}_{ij}.$$

Assume:

(ND) $\Sigma_D := E_P[DD^\intercal]$ is nonsingular and $0 < C_1 \le \Omega \le C_2 < \infty$.

(SG) There exists $C_3 < \infty$ such that $\|T\|_{\psi_2} \le C_3$, $\max_{\ell \le d} \|D_\ell\|_{\psi_2} \le C_3$, $\max_{j \le p} \|Y_j\|_{\psi_2} \le C_3$.

Then, if Assumption R holds,

$$\max_{j \in [p]} \sqrt{E_n\left[(\widehat{\psi}_{ij} - \psi_{ij})^2 \right]} = o_P\left(\frac{1}{\log(pn)} \right).$$

Proof. Let $\|\cdot\|_p$ denote the usual ℓ^p norm for a finite-dimensional vector, and let $\|v\|_{p,n} := E_n[|v_i|^p]^{1/p}$ denote the L^p norm under the empirical measure. Lastly, let the L^p norm under probability measure P be $\|\cdot\|_{p,P}$. We note two inequalities used repeatedly: for n-dimensional vectors v, u, Hölder's inequality gives

$$\|vu\|_{2,n} \leq \|v\|_{4,n}\|u\|_{4,n},$$

and for conformable matrix A and vector v, $\|Av\|_2 \leq \|A\|_{\text{op}}\|v\|_2$.

Preliminaries. Write $\gamma_T := \Sigma_D^{-1}E_P[DT]$, so $\widetilde{T} = T - \gamma_T^\intercal D$. Since T and D are subgaussian and d is fixed, $\widetilde{T}$ is subgaussian. Hence $E_P[\widetilde{T}^4] < \infty$ and $\|\widetilde{T}\|_{4,n} = O_P(1)$ by the WLLN.

Let $\gamma_{Y_j} := \Sigma_D^{-1}E_P[DY_j]$. Then $\widetilde{Y}_j = Y_j - \gamma_{Y_j}^\intercal D$ and is subgaussian by the same argument, and $E_P[\widetilde{Y}_j^4] < \infty$.

Since d is fixed and $\max_{j\leq p}\|Y_j\|_{\psi_2} \leq C_3$, we have $\sup_{j\leq p} E_P[Y_j^2] \leq C < \infty$. By Cauchy-Schwarz,

$$\|E_P[DY_j]\|_2 \leq \sqrt{E_P[\|D\|_2^2]}\sqrt{E_P[Y_j^2]} \leq C,$$

uniformly in j because $\|D\|_2^2$ is subexponential. Therefore, using (ND),

$$\sup_{j\leq p}\|\gamma_{Y_j}\|_2 \leq \|\Sigma_D^{-1}\|_{\text{op}}\sup_{j\leq p}\|E_P[DY_j]\|_2 \leq C < \infty.$$

Similarly, by Cauchy-Schwarz and (ND),

$$|\theta_j| = \Omega^{-1}|E_P[\widetilde{T}\widetilde{Y}_j]| \leq \Omega^{-1}\sqrt{E_P[\widetilde{T}^2]E_P[\widetilde{Y}_j^2]} \leq C,$$

uniformly in j. Hence $\widetilde{U}_j = \widetilde{Y}_j - \theta_j\widetilde{T}$ is also uniformly subgaussian.

Also, because d is fixed and each D_ℓ is subgaussian, $E_P[\|D\|_2^4] < \infty$, and thus

$$\big\|\|D_i\|_2\big\|_{4,n} = \Big(E_n[\|D_i\|_2^4]\Big)^{1/4} = O_P(1)$$

by the WLLN (this will be used to control $\|e_T\|_{4,n}$ and $\|e_{Y_j}\|_{4,n}$).

Lastly, we will use that $\max_{j\leq p}\|\widetilde{Y}_j\|_{4,n} = O_P(1)$ and $\max_{j\leq p}\|\widetilde{U}_j\|_{4,n} = O_P(1)$. Concretely, $\|\widetilde{Y}_{ij}^4\|_{\psi_{1/2}} = \|\widetilde{Y}_{ij}\|_{\psi_2}^4 \leq C$ uniformly in j by (SG) and Corollary 4 of Zhang and Wei [2021], and hence $\|\widetilde{Y}_{ij}^4 - E[\widetilde{Y}_{ij}^4]\|_{\psi_{1/2}} \leq C$ by their Proposition 1. Thus Theorem 1(b) of Zhang and Wei [2021] (applied with $\theta = 1/2$ and equal weights $w_i = n^{-1}$, so that $\|b\|_2 \lesssim n^{-1/2}$ and $\|b\|_2 L_n(\theta, b) \lesssim n^{-1}$ there), evaluated at $t = s + \log p$ together with a union bound over $j \in [p]$, yields

$$\max_{j\leq p}\left|\frac{1}{n}\sum_{i=1}^n \widetilde{Y}_{ij}^4 - E_P[\widetilde{Y}_{ij}^4]\right| = O_P\left(\sqrt{\frac{\log p}{n}} + \frac{(\log p)^2}{n}\right).$$

Since $\sup_j E_P[\widetilde{Y}_j^4] < \infty$, and using the Hölder continuity bound $|a^{1/4} - b^{1/4}| \leq |a-b|^{1/4}$ for $a, b \geq 0$, and applying Assumption R, we obtain

$$\max_{j\leq p}\|\widetilde{Y}_j\|_{4,n} = O_P(1).$$

Then $\widetilde{U}_j = \widetilde{Y}_j - \theta_j \widetilde{T}$ with $\sup_j |\theta_j| < \infty$ and $\|\widetilde{T}\|_{4,n} = O_P(1)$ gives

$$\max_{j \le p} \|\widetilde{U}_j\|_{4,n} = O_P(1).$$

Decomposition. We decompose

$$\widehat{\psi}_{ij} - \psi_{ij} = \big(\widehat{\Omega}^{-1} - \Omega^{-1}\big)\widehat{\widetilde{T}}_i \widehat{\widetilde{U}}_{ij} + \Omega^{-1} e_{T,i} \widehat{\widetilde{U}}_{ij} + \Omega^{-1} \widetilde{T}_i \big(\widehat{\widetilde{U}}_{ij} - \widetilde{U}_{ij}\big),$$

where $e_{T,i} := \widehat{\widetilde{T}}_i - \widetilde{T}_i = -D_i^{\mathsf{T}}(\widehat{\gamma}_T - \gamma_T)$. By Minkowski's inequality,

$$\max_{j \le p} \|\widehat{\psi}_{\cdot j} - \psi_{\cdot j}\|_{2,n} \le (I) + (II) + (III),$$

where

$$(I) := \max_{j \le p} \big\| \big(\widehat{\Omega}^{-1} - \Omega^{-1}\big)\widehat{\widetilde{T}}_i \widehat{\widetilde{U}}_{ij} \big\|_{2,n},$$
$$(II) := \max_{j \le p} \big\| \Omega^{-1} e_{T,i} \widehat{\widetilde{U}}_{ij} \big\|_{2,n},$$
$$(III) := \max_{j \le p} \big\| \Omega^{-1} \widetilde{T}_i (\widehat{\widetilde{U}}_{ij} - \widetilde{U}_{ij}) \big\|_{2,n}.$$

(I). By Hölder,

$$(I) \le \big|\widehat{\Omega}^{-1} - \Omega^{-1}\big| \, \|\widehat{\widetilde{T}}\|_{4,n} \max_{j \le p} \|\widehat{\widetilde{U}}_j\|_{4,n}.$$

We may write

$$\widehat{\Omega} - \Omega = \big(E_n[\widetilde{T}^2] - \Omega\big) + E_n[\widehat{\widetilde{T}}^2 - \widetilde{T}^2].$$

The first term is $O_P(n^{-1/2})$ (by Bernstein/CLT since $\widetilde{T}^2$ is subexponential). For the second term, note

$$\widehat{\widetilde{T}}^2 - \widetilde{T}^2 = (\widehat{\widetilde{T}} + \widetilde{T}) e_T,$$

so by Cauchy-Schwarz and the identity $\widehat{\widetilde{T}} = \widetilde{T} + e_T$,

$$\big|E_n[(\widehat{\widetilde{T}} + \widetilde{T}) e_T]\big| \le \|\widehat{\widetilde{T}} + \widetilde{T}\|_{2,n} \|e_T\|_{2,n} \le (\|e_T\|_{2,n} + 2\|\widetilde{T}\|_{2,n}) \|e_T\|_{2,n}.$$

Recall $e_{T,i} = -D_i^{\mathsf{T}}(\widehat{\gamma}_T - \gamma_T)$, where

$$\widehat{\gamma}_T := (E_n[DD^{\mathsf{T}}])^{-1} E_n[DT], \qquad \gamma_T := \Sigma_D^{-1} E_P[DT].$$

Then

$$\widehat{\gamma}_T - \gamma_T = \big((E_n[DD^{\mathsf{T}}])^{-1} - \Sigma_D^{-1}\big) E_n[DT] + \Sigma_D^{-1}\big(E_n[DT] - E_P[DT]\big).$$

Using $A^{-1} - B^{-1} = A^{-1}(B - A)B^{-1}$ and operator-norm submultiplicativity,

$$\big\|(E_n[DD^{\mathsf{T}}])^{-1} - \Sigma_D^{-1}\big\|_{\mathrm{op}} \le \big\|(E_n[DD^{\mathsf{T}}])^{-1}\big\|_{\mathrm{op}} \big\|\Sigma_D - E_n[DD^{\mathsf{T}}]\big\|_{\mathrm{op}} \big\|\Sigma_D^{-1}\big\|_{\mathrm{op}}.$$

By (ND), $\|\Sigma_D^{-1}\|_{\mathrm{op}} < \infty$. Since d is fixed and each $D_a D_b$ is subexponential, $\|\Sigma_D - E_n[DD^{\mathsf{T}}]\|_{\mathrm{op}} = O_P(n^{-1/2})$ (e.g. via entrywise Bernstein and $\|\cdot\|_{\mathrm{op}} \le \|\cdot\|_F$, the Frobenius norm). Thus

$E_n[DD^{\mathsf{T}}] \to_P \Sigma_D$ in operator norm, hence $\|(E_n[DD^{\mathsf{T}}])^{-1}\|_{\mathrm{op}} = O_P(1)$. Finally, $\|E_n[DT]\|_2 = O_P(1)$ and $\|E_n[DT] - E_P[DT]\|_2 = O_P(n^{-1/2})$ since d is fixed and $D_\ell T$ is subexponential. Therefore,

$$\|\widehat{\gamma}_T - \gamma_T\|_2 = O_P(n^{-1/2}).$$

Then for each i, $|e_{T,i}| \le \|D_i\|_2 \|\widehat{\gamma}_T - \gamma_T\|_2$, so

$$\|e_T\|_{4,n} \le \|\widehat{\gamma}_T - \gamma_T\|_2 \big\| \|D_i\|_2 \big\|_{4,n} = O_P(n^{-1/2}),$$

and hence $\|e_T\|_{2,n} \le \|e_T\|_{4,n} = O_P(n^{-1/2})$. Using also $\|\widetilde{T}\|_{2,n} = O_P(1)$, we conclude

$$|\widehat{\Omega} - \Omega| = O_P(n^{-1/2}).$$

By the WLLN, $E_n[\widetilde{T}^2] \to \Omega$ in probability. Since $\widehat{\Omega} = E_n[\widehat{\widetilde{T}}^2] = E_n[\widetilde{T}^2] + o_P(1)$ (because $E_n[\widehat{\widetilde{T}}^2 - \widetilde{T}^2] = O_P(n^{-1/2})$), we have $\widehat{\Omega} \to \Omega$ in probability. In particular,

$$P(\widehat{\Omega} \ge C_1/2) \to 1.$$

On the event $\{\widehat{\Omega} \ge C_1/2\}$,

$$\big|\widehat{\Omega}^{-1} - \Omega^{-1}\big| = \frac{|\widehat{\Omega} - \Omega|}{\widehat{\Omega}\,\Omega} \le \frac{2}{C_1^2} |\widehat{\Omega} - \Omega| = O_P(n^{-1/2}).$$

To control $\|\widehat{\widetilde{T}}\|_{4,n}$, note $\widehat{\widetilde{T}} = \widetilde{T} + e_T$, so by Minkowski,

$$\|\widehat{\widetilde{T}}\|_{4,n} \le \|\widetilde{T}\|_{4,n} + \|e_T\|_{4,n} = O_P(1).$$

Finally, consider $\max_{j \le p} \|\widehat{\widetilde{U}}_j\|_{4,n}$:

$$\max_{j \le p} \|\widehat{\widetilde{U}}_j\|_{4,n} \le \max_{j \le p} \|\widehat{\widetilde{Y}}_j\|_{4,n} + \max_{j \le p} |\widehat{\theta}_j| \, \|\widehat{\widetilde{T}}\|_{4,n}.$$

Write $\widehat{\widetilde{Y}}_j = \widetilde{Y}_j + e_{Y_j}$ with

$$e_{Y_j,i} := \widehat{\widetilde{Y}}_{ij} - \widetilde{Y}_{ij} = -D_i^{\mathsf{T}}(\widehat{\gamma}_{Y_j} - \gamma_{Y_j}), \qquad \widehat{\gamma}_{Y_j} := (E_n[DD^{\mathsf{T}}])^{-1} E_n[DY_j].$$

Then $|e_{Y_j,i}| \le \|D_i\|_2 \|\widehat{\gamma}_{Y_j} - \gamma_{Y_j}\|_2$ implies

$$\max_{j \le p} \|e_{Y_j}\|_{4,n} \le \big\| \|D_i\|_2 \big\|_{4,n} \max_{j \le p} \|\widehat{\gamma}_{Y_j} - \gamma_{Y_j}\|_2.$$

Decompose

$$\widehat{\gamma}_{Y_j} - \gamma_{Y_j} = (E_n[DD^{\mathsf{T}}])^{-1}\big(E_n[DY_j] - E_P[DY_j]\big) + \big((E_n[DD^{\mathsf{T}}])^{-1} - \Sigma_D^{-1}\big) E_P[DY_j].$$

Since d is fixed, $(E_n[DD^{\mathsf{T}}])^{-1} = O_P(1)$ in operator norm, and $\big\|(E_n[DD^{\mathsf{T}}])^{-1} - \Sigma_D^{-1}\big\|_{\mathrm{op}} = O_P(n^{-1/2})$ as shown above. Also $\sup_j \|E_P[DY_j]\|_2 < \infty$ from the earlier uniform bound.

For the empirical term, each component of DY_j is a product of subgaussians and hence subexponential uniformly in j; thus entrywise Bernstein plus a union bound over $j \le p$ (and $\ell \le d$) yields

$$\max_{j\le p} \|E_n[DY_j] - E_P[DY_j]\|_2 = O_P\Big(\sqrt{\frac{\log p}{n}}\Big).$$

Therefore,

$$\max_{j\le p} \|\widehat{\gamma}_{Y_j} - \gamma_{Y_j}\|_2 = O_P\Big(\sqrt{\frac{\log p}{n}}\Big).$$

Consequently, since $\big\|\|D_i\|_2\big\|_{4,n} = O_P(1)$,

$$\max_{j\le p} \|e_{Y_j}\|_{4,n} = O_P\Big(\sqrt{\frac{\log p}{n}}\Big).$$

Then, using $\max_j \|\widetilde{Y}_j\|_{4,n} = O_P(1)$ from the preliminaries and Minkowski,

$$\max_{j\le p} \|\widehat{\widetilde{Y}}_j\|_{4,n} \le \max_{j\le p} \|\widetilde{Y}_j\|_{4,n} + \max_{j\le p} \|e_{Y_j}\|_{4,n} = O_P(1).$$

Lastly, consider $\widehat{\theta}_j - \theta_j$:

$$\widehat{\theta}_j - \theta_j = \widehat{\Omega}^{-1}\big(E_n[\widehat{\widetilde{T}}\widehat{\widetilde{Y}}_j] - E_P[\widetilde{T}\widetilde{Y}_j]\big) + (\widehat{\Omega}^{-1} - \Omega^{-1})E_P[\widetilde{T}\widetilde{Y}_j].$$

We already established $|\widehat{\Omega}^{-1} - \Omega^{-1}| = O_P(n^{-1/2})$ and $\sup_j |E_P[\widetilde{T}\widetilde{Y}_j]| < \infty$. For the remaining term,

$$E_n[\widehat{\widetilde{T}}\widehat{\widetilde{Y}}_j] - E_P[\widetilde{T}\widetilde{Y}_j] = \big(E_n[\widetilde{T}\widetilde{Y}_j] - E_P[\widetilde{T}\widetilde{Y}_j]\big) + E_n[e_T\widehat{\widetilde{Y}}_j] + E_n[\widetilde{T}e_{Y_j}],$$

and (as previously done) Bernstein/union bounds for $\max_j |E_n[\widetilde{T}\widetilde{Y}_j] - E_P[\widetilde{T}\widetilde{Y}_j]|$, together with Hölder and the established bounds $\|e_T\|_{4,n} = O_P(n^{-1/2})$, $\max_j \|\widehat{\widetilde{Y}}_j\|_{4,n} = O_P(1)$, and $\max_j \|e_{Y_j}\|_{4,n} = O_P(\sqrt{\log p/n})$, yield

$$\max_{j\le p} |\widehat{\theta}_j - \theta_j| = O_P\Big(\sqrt{\frac{\log p}{n}}\Big).$$

Since $\sup_j |\theta_j| < \infty$, this implies $\max_{j\le p} |\widehat{\theta}_j| = O_P(1)$. Therefore,

$$\max_{j\le p} \|\widehat{\widetilde{U}}_j\|_{4,n} = O_P(1).$$

Combining all of these results, we conclude

$$(I) = O_P(n^{-1/2}).$$

(II). By Hölder,

$$(II) \le \Omega^{-1}\|e_T\|_{4,n} \max_{j\le p} \|\widehat{\widetilde{U}}_j\|_{4,n}.$$

Recalling $\|e_T\|_{4,n} = O_P(n^{-1/2})$ and $\max_{j\le p}\|\widehat{\widetilde{U}}_j\|_{4,n} = O_P(1)$, we immediately get

$$(II) = O_P(n^{-1/2}).$$

(III). By Hölder,

$$(III) \le \Omega^{-1}\|\widetilde{T}\|_{4,n}\max_{j\le p}\|\widehat{\widetilde{U}}_j - \widetilde{U}_j\|_{4,n}.$$

We have already concluded $\|\widetilde{T}\|_{4,n} = O_P(1)$. Also,

$$\widehat{\widetilde{U}}_{ij} - \widetilde{U}_{ij} = e_{Y_j,i} - (\widehat{\theta}_j - \theta_j)\widehat{\widetilde{T}}_i - \theta_j e_{T,i}.$$

Thus by Minkowski,

$$\max_{j\le p}\|\widehat{\widetilde{U}}_j - \widetilde{U}_j\|_{4,n} \le \max_{j\le p}\|e_{Y_j}\|_{4,n} + \max_{j\le p}|\widehat{\theta}_j - \theta_j|\,\|\widehat{\widetilde{T}}\|_{4,n} + \|e_T\|_{4,n}\max_{j\le p}|\theta_j|.$$

Using the previously established bounds

$$\max_{j\le p}\|e_{Y_j}\|_{4,n} = O_P\Big(\sqrt{\frac{\log p}{n}}\Big), \quad \max_{j\le p}|\widehat{\theta}_j - \theta_j| = O_P\Big(\sqrt{\frac{\log p}{n}}\Big),$$

$$\|\widehat{\widetilde{T}}\|_{4,n} = O_P(1), \quad \|e_T\|_{4,n} = O_P(n^{-1/2}), \quad \max_{j\le p}|\theta_j| = O(1),$$

we conclude

$$(III) = O_P\Big(\sqrt{\frac{\log p}{n}}\Big).$$

Rates. The preceding analyses yield

$$\max_{j\le p}\|\widehat{\psi}_{\cdot j} - \psi_{\cdot j}\|_{2,n} = O_P\Big(\sqrt{\frac{\log p}{n}}\Big).$$

Under Assumption R, we have

$$\sqrt{\frac{\log p}{n}} = o\left(\frac{1}{\log(pn)}\right).$$

Therefore,

$$\max_{j\le p}\sqrt{E_n[(\widehat{\psi}_{ij} - \psi_{ij})^2]} = \max_{j\le p}\|\widehat{\psi}_{\cdot j} - \psi_{\cdot j}\|_{2,n} = o_P\left(\frac{1}{\log(pn)}\right).$$

□

Proposition 3 (Linearization error for many linear regressions)**.** *Assume the same setup as Proposition 2. Let*

$$\sqrt{n}(\hat{\theta}_j - \theta_j) = \frac{1}{\sqrt{n}}\sum_{i=1}^{n}\psi_{ij} + R_{n,j}$$

where

$$R_{n,j} = (\widehat{\Omega}^{-1} - \Omega^{-1})\sqrt{n}E_n[\widetilde{T}\,\widetilde{U}_j] + \widehat{\Omega}^{-1}\sqrt{n}E_n[(\widehat{\widetilde{T}} - \widetilde{T})\widetilde{U}_j].$$

Let $R_n := (R_{n,1}, \ldots, R_{n,p})^{\mathsf{T}}$. *Then, under Assumption R,*

$$\|R_n\|_\infty = o_P\Big(1/\sqrt{\log(pn)}\Big).$$

Proof. By the triangle inequality,

$$\|R_n\|_\infty \le \left|\widehat{\Omega}^{-1} - \Omega^{-1}\right| \max_{j\le p} \left|\sqrt{n} E_n[\widetilde{T}\,\widetilde{U}_j]\right| + \left|\widehat{\Omega}^{-1}\right| \max_{j\le p} \left|\sqrt{n} E_n[(\widehat{\widetilde{T}} - \widetilde{T})\widetilde{U}_j]\right|.$$

From the proof of Proposition 2, we know that

$$\left|\widehat{\Omega}^{-1} - \Omega^{-1}\right| = O_P(n^{-1/2}), \quad \left|\widehat{\Omega}^{-1}\right| = O_P(1), \quad \max_{j\le p} \left|E_n[\widetilde{T}\,\widetilde{U}_j]\right| = O_P\left(\sqrt{\frac{\log p}{n}}\right)$$

(specifically recalling that $\widetilde{T}\widetilde{U}_j$ is subexponential from the work done in Proposition 2 and that $E[\widetilde{T}\widetilde{U}_j] = 0$). Also, since

$$\widehat{\widetilde{T}}_i - \widetilde{T}_i = -D_i^{\intercal}(\widehat{\gamma}_T - \gamma_T),$$

we have for each j,

$$E_n[(\widehat{\widetilde{T}} - \widetilde{T})\widetilde{U}_j] = -(\widehat{\gamma}_T - \gamma_T)^{\intercal} E_n[D\,\widetilde{U}_j].$$

Hence using Cauchy-Schwarz,

$$\max_{j\le p} \left|E_n[(\widehat{\widetilde{T}} - \widetilde{T})\widetilde{U}_j]\right| \le \|\widehat{\gamma}_T - \gamma_T\|_2 \max_{j\le p} \|E_n[D\,\widetilde{U}_j]\|_2.$$

Again by the proof of Proposition 2,

$$\|\widehat{\gamma}_T - \gamma_T\|_2 = O_P(n^{-1/2}),$$

while entrywise Bernstein and a union bound over $j \le p$ and the fixed coordinates of D give

$$\max_{j\le p} \|E_n[D\,\widetilde{U}_j]\|_2 = O_P\left(\sqrt{\frac{\log p}{n}}\right),$$

since each coordinate of $D\widetilde{U}_j$ is subexponential uniformly in j and its expectation is zero (and then using the same logic as used in the proof of Proposition 2). Therefore,

$$\max_{j\le p} \left|E_n[(\widehat{\widetilde{T}} - \widetilde{T})\widetilde{U}_j]\right| = O_P\left(\frac{\sqrt{\log p}}{n}\right).$$

Combining the preceding results then,

$$\|R_n\|_\infty \le O_P(n^{-1/2})\sqrt{n} O_P\left(\sqrt{\frac{\log p}{n}}\right) + O_P(1)\sqrt{n} O_P\left(\frac{\sqrt{\log p}}{n}\right) = O_P\left(\sqrt{\frac{\log p}{n}}\right).$$

Under Assumption R, $\sqrt{\log p/n}\cdot\sqrt{\log(pn)} \le \log(pn)/\sqrt{n} = o(1)$, so $\|R_n\|_\infty = O_P(\sqrt{\log p/n}) = o_P\big(1/\sqrt{\log(pn)}\big)$, proving the stated claim. □