



TESTING, DETECTION AND POSSIBLE SOLUTIONS FOR THE BUFFERBLOAT PHENOMENON ON NETWORKS.

THESIS DEGREE

JUAN S. CATALAN OLMOS

Definición de Tema de Memoria
para optar al Título de:
INGENIERO CIVIL INFORMATICO

Referent Professor: Horst H. von Brand Skopnik
Coreferent Professor: Raúl Monge Anwandter

APRIL 24, 2014
VALPARAÍSO, CHILE

Contents

1	Introduction	3
2	The Transport Control Protocol	5
2.1	Fundamentals of TCP	5
2.2	TCP's Phases	7
2.3	Hidden Flaws and Bufferbloat	7
3	Active Queue Management	8
4	Interaction with Buffers	9
5	Experimental Work	10
5.1	The Test Setup	10
5.1.1	Hardware Characterization	11
5.2	Tools Definition	12
5.2.1	Speedtest	13
5.2.2	Netalyzer	13
5.2.3	Iperf	14
5.2.4	Page Benchmark	15
5.2.5	Smokeping	15
5.3	Test Description	16
5.3.1	Speed test	17
5.3.2	Signs of trouble	17
5.3.3	Collapse test	18
5.3.4	Load benchmark test	19
5.3.5	Smoke the path	20
6	Results	21
6.1	Speed test	21
6.2	Netalyzer test	21
6.3	Iperf test	21
6.4	Benchmark test	22
6.5	Smokeping Test	22
6.6	Summarising Results	22
7	Conclusions	23
8	Further Work	24

List of Figures

- | | | |
|---|--|----|
| 1 | Result Summary example from Netalyzr. Source: www.dslreports.com | 14 |
|---|--|----|

List of Tables

- | | | |
|---|--|----|
| 1 | Speed Test: Speeds and Ping measured | 21 |
| 2 | Speed Test: Variation ratio of offered vs measured speed | 22 |
| 3 | Page Benchmark Test: Total load mean times | 22 |
| 4 | Page Benchmark Test: Variation ratio over own iteration | 23 |
| 5 | Page Benchmark Test: Variation ratio over all | 23 |

1 Introduction

If a little salt makes food taste better, then a lot must make it taste great, right?. What happens if you apply the same statement to a network domain? It keeps been as good as it was? It improves the performance or makes it worse?.

Lets think of a network as a road system where everyone drives at the maximum speed. When the road gets full, there are only two choices: crash into other cars, or get off the road and wait until things get better. The former isn't as disastrous on a network as it would be in real life: losing packets in the middle of a communication session isn't a big deal. But making a packet wait for a short time is usually better than "dropping" it and having to wait for a re-transmission.[19]

At this point, the role of the router becomes important. It has to control the congestion effectively in networks. It is important to remember that the traffic in a network is inherently bursty, so the role of the buffers in the router is to smooth the flow of traffic. Without any buffering, to allocate the bandwidth evenly would be impossible. But there are some problems with current algorithms; they use tail-drop based queue management that has two big drawbacks: 1.- lockout 2.- full queue that impact with a high queue delay.

These problems are fixed with the creation of a group of FIFO based queue management mechanisms to support end-to-end congestion control in the internet. That procedure is called Active Queue Management (AQM). With AQM the loss of package and the average queue length is reduced; this impacts in a decreasing end-to-end delay by drooping packages before buffer comes full, using the exponential weighted average queue length as a congestion indicator. For the proper use of AQM, it has to be widely enabled and consistently configured the router.

Today's networks are suffering from unnecessary latency and poor system performance. The culprit is Bufferbloat, the existence of excessively large and frequently full buffers inside the network. Large buffers have been inserted all over the Internet without sufficient thought or testing. They damage or defeat the fundamental congestion-avoidance algorithms of the Internet's most common transport protocol. Long delays from bufferbloat are frequently attributed incorrectly to network congestion, and this misinterpretation of the problem leads to the wrong solutions being proposed.[2]

The existence of cheap memory and a misguided desire to avoid packet loss has led to larger and larger buffers being deployed in the hosts, routers, and switches that make up the Internet. It turns out that this is a recipe for bufferbloat. Evidence of bufferbloat has been accumulating over the past decade, but its existence has not yet become a widespread cause for concern.

2 The Transport Control Protocol

The Transport Control Protocol or TCP is main transport protocol of the internet, providing reliable host to host communication over unreliable transport media[7]. Many modifications since it was originally defines in 1981.

2.1 Fundamentals of TCP

TCP operates basically making two hosts exchange segments of data. The connection between these two hosts is identified uniquely at each end by the host's network address and a 16 bit port number. The communication between the hosts is initiated by a three way handshake between them. This time where the sequence number is synchronized between the participants. The sequence number is a 32-bit number and is the basis for a reliable data transport, working as a mechanism to assure the exchange of data through an unreliable network medium counting the bytes transmitted making possible be checked by the receiver and be acknowledged. This is, starting from the initial sequence number, each data byte sent as part of the connection has a corresponding sequence number; and only after having being acknowledged by the receiver is the data considered to be transmitted successfully.

TCP made use of the idea of pipe size and the knowledge there was reasonable but not excessive buffering along the data path to send a window of packets at a time. To control the amount of data that flows through the network path, the receiver sent the information of how much data can receive at once, so the network resource is utilized in a more efficiently way. This window of data means how many bytes the receiver can work with, given the available buffering and processing constraints. All the extra data in excess will be dropped. This window is also a constrain to the sender, because the sender is not allowed to transmits no more data than the window before waiting for the response of the host as acknowledgment of the sent data.

To manage the data sent and the acknowledgment received for those packets, TCP uses a cumulative scheme. After a packet is in flow from the server with its corresponding sequence number, sent data goes to a retransmission queue where it is held until the corresponding acknowledgment from the other end has come in or, to be resent if not acknowledgment within a timeout. When the acknowledgment of a sequence number is received, the sender discard all data with sequence numbers bellow the sequence number in the acknowledgment that has arrive. Otherwise, the data is resent. Here, *the timeout is set from the measured round trip time of the connection, taking into account the variance of the measured values*[3].

Because today's networks are dynamic and in different configurations, both topologically speaking as a bandwidth, TCP must handle these changes and still be able to maintain communication between the two hosts. The lost of communications can be an issue that TCP needs to take into account. In case of lost of one packet means subsequent packets cannot be acknowledged until the lost packet is retransmitted. This can lad to excessive retransmission and unnecessary load. TCP extension has been developed that allows the receiver to send selective acknowledgments of block of received data with sequence numbers that are not cumulative with the data acknowledged in the traditional way[6].

Since networks are shared and conditions change along the path, the algorithms continually probe the network and adapt the number of packets in flight. It is not hard also (but it is often the case) to find along the way decreases in the bandwidth. This spots are the bottlenecks and they are important because the performance or capacity of the entire connection (connection as a state between the two hosts) is limited by the resources that this trace has. With this, controlling the optimal rate of data transmission is a hard work, and the receiver window as communicated by TCP is not a necessarily a very good indicator. To fix this issue, TCP received an addition to its specifica-

tion: *congestion window*. The congestion window plays a crucial role in estimating the available bandwidth between the hosts. After this modification, the minimum between the receiver window and the congestion window is used as the transmit limit. All the TCP additions attempt to keep the network operating near the inflection point where throughput is maximized, delay is minimized, and little loss occurs.

2.2 TCP's Phases

2.3 Hidden Flaws and Bufferbloat

3 Active Queue Management

4 Interaction with Buffers

5 Experimental Work

The goal of the experiments outlined in this section is to examine different residential and public networks with the objective to proof the existence of the phenomenon under an uncontrolled scenario. This will be done by running a set of tests with different tools, first to define and characterize the network, then to measure and compare how the network behave with and without load. More specifically, the factor to be tested is the latency under load and analyzed to identify if the latency that occurs is due to an excess of buffers or due to some other problem.

This section aims to explain the setup that will be used to perform the tests, the selected tools for each of these tests and what is to be achieved and expected from each one of these tests.

5.1 The Test Setup

The tests will be ran under a pseudo controlled environment, using one physical machine and a second virtual machine hosted in first machine. These systems runs under a regular OS without any modification beside the ones that the own OS as by default. Also, for some tests two other devices will be added, one acting as an Iperf Server and a regular Android Tablet that will be used to add some extra load to the network when the Ethernet cable is used as medium.

All of these tests will be carried out in a real-world scenario, where no packet prioritization is done by the server against our flows, the routes can vary between each iteration of the same test, and many different flows will collide with other flows from different sizes and types. Nor there is more information about how the flows are treated by the queue manager algorithms or about how they are configured.

5.1.1 Hardware Characterization

Physical Machine :

The physical machine runs as host OS, Windows 7 SP1, that works with an Intel(R) Core(TM) i7-2670QM CPU 2.20GHz with 8GB of available RAM. This machine will always be connected through its wireless adapter, a *Broadcom Corp. BCM4313 802.11b/g/n Wireless LAN Controller (rev 01)*. The Ethernet controller is a *Realtek Semiconductor Co., Ltd. RTL8111/8168 PCI Express Gigabit Ethernet controller (rev 06)* adapter, and will be bridged to the virtual machine for some tests.

Virtual Machine :

The virtual machine is hosted using VMWare Player 6.0.1, with 4 processors assigned for use plus 4GB of RAM, and with the Ethernet adapter connected only for certain tests. The OS selected is a Debian based OS called Kali Linux, and using the kernel release identified as Debian 3.12.6-2kali.

The wireless adapter is a AIR-802 USB adapter with Zydaz chipset and a TP-link 8dbi antenna. This adapter is directly connected to the virtual machine and hooked to the physical machine without the USB extension, this way any extra signal loss is avoided.

Iperf Server :

This machine will be used as a server for the Iperf test. This is a VPS hosted by Digital Ocean ⁱ with 512MB Ram, 20GB SSD Disk, and located in New York data center. This machine runs Ubuntu 12.04.3 x64 under KVM software using as a processor an Intel Hex-Core 3 GHz.

ⁱ<https://digitalocean.com>

The idea of using an external device to connect the virtual machine to the network and not using a bridged configuration provided by software, is mainly because with an USB device the machine will take care of all the management and administration of the device, avoiding any possibility that the host machine modify or manages any flow. Also, by using a second machine to overload the uplink, causes to avoid overflow the queue on the machine that is performing the tests. With this, it is expected to minimize the possibility that our testing machine is causing extra latency, either by the saturation of the wireless channel, or by the queue in the traffic control subsystem into the kernel.

For the tests, the Bufferbloat community[18] has created a set of best practices[15] to follow so the results are consistent and repeatable, but in this case, computers and routers will not be modified as it will attempt to analyze what an every-day-user experience. Those practices will be taken in consideration if it is the QOS present in routers and deactivate it.

5.2 Tools Definition

The tools used for the benchmark were selected by the capability to determinate the presence of the Bufferbloat phenomenon in the network of study by the analysis of its indicator, the latency or the round trip timeⁱⁱ. So, with this as a main consideration, the tools selected for the benchmark will be chosen by the complexity and accuracy to measure and determine the RTT into an IP/TCP connection, and how hard is to consistently replicate the results under similar contexts. Other tools were selected to help determine, characterize, and proof the capability of the network to cause Bufferbloat.

ⁱⁱTo SUBTEL, organization responsible for control and supervision in the performance of telecommunications in Chile, RTT and Latency correspond to the same thing [12]

The tools selected to be used in this tests are the following:

- Speedtest test by Ookla
- Netalyzer by ICSI
- Iperf Tool with Tcptrace/Xplot.org
- Page Benchmark extension for Google Chrome
- Smokeping Latency Tool

5.2.1 Speedtest

Developed by Ooklaⁱⁱⁱ, this tool is used for most of the ISPs and many users in Chile to test their broadband's connections globally. It can be used not only in their website *www.speedtest.net* but also in Android, iOS or Windows Phone. A command line interface developed in Python can be used too for testing Internet bandwidth.

The server that will be selected to perform every test, either has or not the fastest ping, is the one hosted by the Pontificia Universidad Católica de Valparaíso (this host is the default selected most of times by the site also).

5.2.2 Netalyzer

For end-users, little is revealed about how ISPs manage their networks. That is why since 2009 ICSI has developed Netalyzer, a “two click ” tool developed to test networks that runs in web browser as a Java applet. Once downloaded, the applet contacts the back-end server using a range of protocols and mechanisms employed as part of the testing, and then conducts a series of tests. Once completed, it uploads its findings to the back-end where they are distilled into a detailed report breaking down the findings into correctly operating aspects, those that show potential signs of trouble, and those

ⁱⁱⁱ<https://www.ookla.com/about>

that are downright broken. Figure ?? is an example of the output.

The primary goal in developing Netalyzr's tests was to provide a new kind of diagnostic tool, *one that particularly illuminates under what sort of restrictions a user's Internet connection operates, like both forms of filtering (blocking) and proxying imposed by the user's ISP, and performance issues that arise from the nature of the user's Internet access setup*[5]. Among the performance considerations, Netalyzr's measures are packet loss, latency, bandwidth. Also, it compute in-path forwarding device buffer size by comparing small-packet latencies under idle and loaded states in networks (the perfect time to occur Bufferbloat). Other tests like general TCP and UDP service reachability.




Figure 1: Result Summary example from Netalyzr. Source: www.dslreports.com

5.2.3 Iperf

Iperf is a well known and commonly used network testing tool. It can create a TCP and UDP data streams and measure the bandwidth and the quality of a network link. It can perform multiple tests like Latency, Jitter or Datagram Loss.

Iperf basically tries to send as much information down a connection as quickly as possible reporting on the throughput achieved. This tool is especially useful in determining the volume of data that links between two machines can supply. This two

machines define the network, one acting like a server and the second as the client. For this scenario, the server will be the VPS that only will receive the Iperf connections (also will be running ssh but without further interaction). The VM Linux machine will work as an Iperf Client.

As mentioned in Iperf users mailing list “ *When one runs TCP tests, there are 2 things that block Iperf from having clear view of real throughput: buffering on sender’s side (TCP/IP stack) and TCP behavior itself (acking). What Iperf can measure is the pace with which it sends data to TCP/IP stack; TCP/IP stack will only accept data from application when buffers are not full. If the buffer is huge, Iperf will see high throughput initially, then it will drop. If there’s congestion or retransmission going on, Iperf will see it as lower throughput*” [4], but the data generated by Iperf won’t be further analyzed because the idea behind using this tool is a TCP’s packet generator. This means that the packets generated by Iperf will be captured and analyzed with tcpdump, tcptrace and xplot.org.

5.2.4 Page Benchmark

Page Benchmark is a Google Chrome extension that intent to test page load time performance within Chrome. Measures time-to-first-paint, overall page load time KB read/written, and several other metrics, and with its capability to clear the cache and existing connections between each page load, makes this tool one of the main sources of income to analysis.

5.2.5 Smokeping

SmokePing is a latency logging and graphing tool that consists of a running daemon which organizes the latency measurements and a CGI which presents the graphs.

SmokePing give us the ability to measure latency and packet loss in the current network, and with RRDtool, is capable to maintain a long term data store and to draw different graphs with the giving up-to-the-minute information on the state of each network connection.

Smokeping can be configured to perform a wide range of latency measurement probes each one directed to an independent target or over a set of targets selected for each proof.

5.3 Test Description

To test the existence of the Bufferbloat phenomenon, five tests are conducted as described below. Each test will be repeated under the following contexts:

1. Twice on the same day in one network to determine if does exists a considerable variance in latency for different times in a day.
2. Select different public and private networks with different “speeds”.
3. Use the Ethernet cable in order to compare the results with those previously obtained using Wireless.

Because it is intended to prove the existence of the phenomenon under circumstances experienced by everyday users, no kernel parameters will be amended nor changed, and only the ability to perform QOS on routers that have this feature is disabled. Furthermore, the overall question these tests seek to answer is the following:

Theorem. *“The networks that we use every day, have the necessary characteristics to generate the Bufferbloat phenomenon whether under low loads and if does exists, the how serious are the effects ?”*

5.3.1 Speed test

The idea under this test, is to set a baseline by comparing the speed offered by the ISP and the one at the moment of testing. To find the speed provided, the tool used is the Speedtest in the web site of Ookla.

The benefits of using this web sites is that not only it will reveal not only the available the national uplink and downlink, also it will set the baseline for the ping. The expected pings, independently of the connection bandwidth, should be around $\sim 12ms$, based on the data presented in [11] and [9] by the two most used ISP in Chile^{iv}.

As data, it is estimated that the ratio of the average speed as compared to the rated speed of the service offered for domestic bonds has a variation of 85%, while for international links decreases drastically to 35%[13]. Due this factor, none of the tests will be performed on servers located outside our country, as it is believed that the data will not very representative regarding actual service.

5.3.2 Signs of trouble

After characterize our network based on the speed, it is needed to try to define the state of the service based on the quality in which our network operates, in example: what kind of traffic is passing through our network, and give also get a little more detail on the average rates of delay and buffers with which the traffic can find along the path. To collect all this information will be used Netalyzr.

While laws present in Chile assure consumers networks free of traffic shaping barriers and filters, ISPs apply traffic management measures[10][8] to deliver an optimum experience of the service's use and thus, achieve an efficient use of the network, thus

^{iv}Telefónica has a 39.2% market share while VTR owns 38.8% respectively. [14]

further to protect the safety of users while maintaining network stability.

This is why it is expected that some ports or services are partially or completely blocked, but the most important is that this test will first light on the existence of the phenomenon under study.

5.3.3 Collapse test

Already having a clear idea of the stat of the studied network, the next will be try to check empirically that the results obtained by the previous test above described are valid. For this, Iperf will be used to generate as much traffic as possible for 5 minutes between servers (both national and international). But the main goal is not to measure the throughput of the network; instead to capture the packets that Iperf produces and study them. So before run Iperf, tcpdump will capture this information. Subsequently, the tcp's trace is taken and extracted with tcptrace tool and generate the RTT graph.

This exercise will be conducted three times as part of the test, running the first time as the sole source of network load. For the second and third time, after 50 seconds after Iperf was started, from the Windows machine will be performed an upload to a Dropbox account with a file big enough to the upload take more than the time defined to this test. This upload intends to saturate the upstream link, leading to an overload of existing buffer (indistinct whether the server is national or not, there are several levels where the route is common). The upload will be stopped 50 seconds before the time limit.

The time gap established before loading and the end of the test is to let Iperf Iperf frames reach a steady state flow and thus to generate a basis on which to analyze the time when the traffic is maximum.

The expected RTT are around $\sim 12ms$ and $\sim 100ms$ without load, for national and international servers respectively. About the expected value under load, it is hard to estimated, further that their expected behavior is to be stable round a certain value. In case of no stable behavior, the possible causes will be analyzed and tracked.

5.3.4 Load benchmark test

With the effects of excess buffers already determined, this tests seeks to show how this phenomenon affects users who surfs through a web browser. This is why the extension of Google Chrome Page Benchmark comes in and it will be used to do 5 iterations of 10 loads to a website and analyze the behavior of these.

As in the previous experiment, the first will be without any load on the network. Then, again a file will be uploaded to Dropbox from the second machine and after 30 seconds from the start of the load, and with the load active, will proceed to a second iteration. The third will begin the after a minute, canceling the file upload and after waiting 30 seconds after cancel the upload, the benchmark will be measured again. The fourth and fifth will be a minute and a half since the previous iteration have finished. The site chosen is `http://www.usm.cl`.

As like Jim Gettys showed in his video demonstration[1], the benchmark increases between 10 to 15 times with load against the original times. For this test, the expected proportions are lower, this mainly because the kernel machine that will run the tests has implemented already some improvements to mitigate this problem.

5.3.5 Smoke the path

To verify that the effect of Bufferbloat, if it is the case, does not just happen on a single server or with a single TCP flow, the Smokeping tool will be configured to perform two types of tests: Fping and echopinghttp. These tests will be directed to different types of servers (ie: physical and VPS machines) which have different connection settings and/or type of services (some servers has dedicated link), and located in both Chile and the United States.

The tool will be left couple of minutes to track and save the state of the connection under no load(except the required for testing). After that, a upload of a big file will be performed from a second machine until it finish or the behavior has become stable and then re-enter to a phase without load for couple of more minutes and repeat the upload.

With this test, in addition to verifying the validity of the previously captured data is expected to determine the presence of other factors that can contribute to the degradation of the quality of service on the network, whether factors such as quality of service provided by the host, channel/path problems, problems related to the way handling packets by the router or the machine, and/or any other that may arise.

6 Results

Here goes a description of what will be shown in this section

6.1 Speed test

Here goes the information related to test speed getting the differences and results gathered by this tests.

Will be a table with the current speed and pings. Also will be difference table with the speed that must has.

Table 1: Speeds and Pings measured.

Location	Medium	Downlink (Mbps)	Uplink (Mbps)	Ping (ms)
4low	Wireless	0,6	8,03	29
mbahamon	Wireless	0,6	10,21	24
mhbrisas	Wireless	1,19	17,96	19
mgallard	Wireless	x	x	x
garriag	Wireless	x	x	x
casa	Wireless	4,95	15,48	18
casa2	Wireless	5,09	13,46	20
polmos	Wireless	2,32	19,61	26
polmos2	Wireless	2,34	18,72	22
nalucem	Wireless	0,57	3,97	35
nalucem2	Wireless	0,56	4,06	36
mcatala	Wireless	x	x	x
mcatala2	Wireless	x	x	x

6.2 Netalyzr test

Here will be a resume of what netalyrz give us

6.3 Iperf test

Graphs and what happend with the rtts

Table 2: Variation ratio of offered vs measured speed.

Location	Uplink ratio	Downlink ratio
4low	120,00	80,30
mbahamon	120,00	102,10
mhbrisas	119,00	89,80
mgallard	0,00	0,00
garriag	0,00	0,00
casa	99,00	103,20
casa2	101,80	89,73
polmos	116,00	49,03
polmos2	117,00	46,80
nalucem	114,00	99,25
nalucem2	112,00	101,50

6.4 Benchmark test

Page benchmark results with tables with differences and mean results

Table 3: Total load mean times.

Lugar	1	2	3	4	5
4low	3415,1	20932,3	4490,5	4170,1	4087,1
casa	1654,8	3053,6	1718	1877,4	1666,8
mbahamon	2248,4	23868,5	2248	2182,6	2223,8
polmos	1623,4	3701,4	2420,6	1947	1659,3
polmos2	1912,4	4861,8	1738,5	2136,1	1827,5
nalucem	6421,4	26048,6	6280,8	6335,8	6306,4
casa2	1682,9	2354,4	1682,3	1667,5	1646,6
nalucem2	8199	32151,5	6479,1	6537,1	6349,4

6.5 Smokeping Test

Graph results

6.6 Summarising Results

all test

Table 4: Variation ratio over own iteration.

Lugar	1	2	3	4	5
4low	55,55	607,623	96,647	132,874	3202,323
casa	8,353	199,264	16,087	256,497	18,852
mbahamon	63,959	83,863	53,778	39,558	219,521
polmos	6,365	163,106	3802,472	8343,236	4050,064
polmos2	59,754	1891,192	8106,53	317,45	8126,291
nalucem	161,954	154,734	9,858	6,96	5,233
casa2	13,998	181,652	27,18	3,102	17,715
nalucem2	880,662	215,955	154,129	184,86	10,703

Table 5: Variation ratio over all iterations.

Lugar	min	max	%
4low	3415,1	20932,3	612,933
casa	1654,8	3053,6	184,529
mbahamon	2182,6	23868,5	1093,581
polmos	1623,4	3701,4	228,002
polmos2	1738,5	4861,8	279,654
nalucem	6280,8	26048,6	414,733
casa2	1646,6	2354,4	142,985
nalucem2	6349,4	32151,5	506,37

7 Conclusions

conclusions

<http://lalith.in/2012/02/15/fun-with-tcp-cubic/> Examples of iperf and wireless

8 Further Work

further

analysis in specific of how the three different flows (Elephant, mice and ant) reacts to the bufferbloat

How the linux kernel now reacts to bufferbloat.

The effects under laying the use of CTCP[?][17] in Windows and the recommendations of the Bufferbloat community[16]

References

- [1] GETTYS, J. Bufferbloat: “dark” buffers in the internet - demonstrations only. <https://www.youtube.com/watch?v=npiG7EBzH0U>, January 2012.
- [2] GETTYS, J., AND NICHOLS, K. Bufferbloat: Dark buffers in the internet. *Commun. ACM* 55, 1 (Jan. 2012), 57–65.
- [3] JACOBSON, V. Congestion avoidance and control. *SIGCOMM Comput. Commun. Rev.* 18, 4 (Aug. 1988), 314–329.
- [4] KOZELJ, M. Re: [iperf-users] how iperf works? <https://www.mail-archive.com/iperf-users@spacefactor.comlists.sourceforge.net/msg00147.html>, nov 2009.
- [5] KREIBICH, C., WEAVER, N., NECHAEV, B., AND PAXSON, V. Netalyzr: Illuminating the edge network. In *Proceedings of the 10th ACM SIGCOMM Conference on Internet Measurement* (New York, NY, USA, 2010), IMC ’10, ACM, pp. 246–259.
- [6] MATHIS, M., MAHDAVI, J., FLOYD, S., AND ROMANOW, A. TCP Selective Acknowledgment Options. RFC 2018 (Proposed Standard), Oct. 1996.
- [7] POSTEL, J. Transmission Control Protocol. RFC 793 (Standard), Sept. 1981. Updated by RFCs 1122, 3168, 6093, 6528.
- [8] S.A., T. C. Medidas o acción para la gestión del tráfico y administración de red servicio banda ancha fijo. http://www.movistar.cl/PortalMovistarWeb/ShowDoc/WLP+Repository/Portlets/P030_Generico/Recurso/ acordeones/ acordeon_banda_ancha/pdf/RED_servicio_BandaAnchaFijo.pdf, 2013.
- [9] S.A., T. C. Neutralidad en la red. <http://www.movistar.cl/PortalMovistarWeb/neutralidad-de-la-red>, 2013.

- [10] S.A., V. B. A. C. Políticas de administración de red. <http://vtr.com/neutralidad/b4.php>, 2013.
- [11] S.A., V. B. A. C. Vtr - reglamento de neutralidad de red. <http://vtr.com/neutralidad/b3.php>, 2013.
- [12] SUBTEL. Ref. fija indicadores de calidad de los enlaces de conexión para cursar el tráfico nacional de internet y sistema de publicidad de los mismos. http://www.subtel.gob.cl/images/stories/articles/subtel/asocfile/res_698_trafico_internet.PDF, June 2000.
- [13] SUBTEL. Modelo de competencia por calidad de servicio. http://www.subtel.gob.cl/images/stories/apoyo_articulos/notas_prensa/modelo_competencia_qos_subtel_23enero2012.pdf, January 2013.
- [14] SUBTEL. Información estadística, serie conexiones internet fija. http://www.subtel.gob.cl/images/stories/apoyo_articulos/informacion_estadistica/series_estadisticas/06032014/1_SERIES_CONEXIONES_INTERNET_FIJA_DIC13_050214.xlsx, March 2014.
- [15] TAHT, D., AND GETTYS, J. Best practices for benchmarking codel and fq codel. https://www.bufferbloat.net/projects/codel/wiki/Best_practices_for_benchmarking_Codel_and_FQ_Codel, March 2013. Wiki page on bufferbloat.net web site.
- [16] TAHT, D., AND *BufferBloat Community*. Bloat: Windows tips. http://www.bufferbloat.net/projects/bloat/wiki/Windows_Tips, February 2011.
- [17] TAN, K., SONG, J., ZHANG, Q., AND SRIDHARAN, M. A compound tcp approach for high-speed and long distance networks. In *INFOCOM 2006. 25th IEEE International Conference on Computer Communications. Proceedings* (April 2006), pp. 1–12.
- [18] *Bufferbloat.net*. Community web site. <http://www.bufferbloat.net/>, 2012.

- [19] VAN BEIJNUM, I. Understanding bufferbloat and the network buffer arms race. <http://arstechnica.com/tech-policy/news/2011/01/understanding-bufferbloat-and-the-network-buffer-arms-race.ars>, jan 2011. [Online, accessed 15-Dic-2011].