

# Parsing with IRONY

<http://www.codeplex.com/irony>

Roman Ivantsov, MCSD

Software Architect, Tyler Technologies, Eden Division

[www.tylertech.com](http://www.tylertech.com)

[roman.ivantsov@tylertech.com](mailto:roman.ivantsov@tylertech.com)

# Agenda

- ▣ Introduction and background
- ▣ Demo - Expression Grammar
- ▣ Inside Irony – internal architecture overview
- ▣ Future plans

# Introduction


- ▣ Name
- ▣ Motivation - upgrade compiler construction technology.
- ▣ Goal – make it easier and make it faster
- ▣ Feature set – whatever Lex/Yacc can do and more
- ▣ Method
  - All in c#: embedded Domain-Specific Language (DSL) for grammar specifications
  - No code generation: one-for-all LALR(1) Parser
  - Scanner construction from standard and custom token recognizers

# Demo

- ▣ Grammar for Arithmetic Expressions
- ▣ Grammar Explorer
- ▣ Sample Grammars

# Irony Parsing Architecture

## Parsing Pipeline




\* - optional; standard or custom filter

# Grammar

- ▣ Base class for language grammars
- ▣ c# operator overloads defined in BnfElement class; Terminal and NonTerminal are derived from BnfElement
- ▣ Helper methods for Kleene operators \* + ?; list constructor with optional delimiters

# Scanner

- ❑ OOP-style micro-framework for building custom scanners from standard and custom Terminals
- ❑ Terminal is a token recognizer
- ❑ Highly-optimized for performance
- ❑ Ignores whitespace; new-line, indent and unindent tokens are created in token filter if necessary



# Token Filters

- ▣ Sit between Scanner and Parser
- ▣ Perform language-specific tasks:
  - Code outlining - create NewLine, Indent, Unindent, EndOfStatement tokens
  - Commented-out blocks
  - Macro-expansion
  - Checking matching pairs of braces/parenthesis
  - Handling XML documentation



# Parser

- ▣ LALR(1) algorithm controlled by State Graph built at startup
- ▣ AST node type determined by NodeType property of NonTerminal in language grammar.
- ▣ Customization
  - Custom AST nodes
  - Factory methods for node creation
  - Public events and overridable methods in grammar

# Highlights

- ▣ It works!
- ▣ Easier to use, expect shorter implementation time
- ▣ High performance: 10..20 K lines/second
- ▣ High code reuse – reusable terminals, token filters, AST nodes
- ▣ No generated code => higher code quality + easier to maintain

# Future Development

- ▣ Completing features for 1.0 release (est. Feb 2008)
- ▣ Create a set of standard AST nodes
- ▣ Extending to LALR(1.5) parser – with extra token preview
- ▣ Create basic infrastructure for building interpreters
- ▣ Build Runtime
  - Extensible Object Model (Piumarta, Warth)
  - Type model (yes, wrappers!)
- ▣ Simple scripting language(s) for testing