



# ACSL Pseudo-Code

The Davidson Academy's Programming Club

Operators	! (not) , ^ or ↑(exponent), *, / (real division), % (modulus), +, -, >, <, >=, <=, !=, ==, && (and),    (or) in that order of precedence					
Functions	abs(x) - absolute value, sqrt(x) - square root, int(x) - greatest integer <= x					
Variables	Start with a letter, only letters and digits					
Sequential statements	<table><tr><td>INPUT variable</td></tr><tr><td>variable = expression (assignment)</td></tr><tr><td>OUTPUT variable</td></tr></table>	INPUT variable	variable = expression (assignment)	OUTPUT variable		
INPUT variable						
variable = expression (assignment)						
OUTPUT variable						
Decision statements	<table><tr><td>IF boolean expression THEN</td></tr><tr><td>Statement(s)</td></tr><tr><td>ELSE (optional)</td></tr><tr><td>Statement(s)</td></tr><tr><td>END IF</td></tr></table>	IF boolean expression THEN	Statement(s)	ELSE (optional)	Statement(s)	END IF
IF boolean expression THEN						
Statement(s)						
ELSE (optional)						
Statement(s)						
END IF						



Indefinite Loop statements	<table><tr><td>WHILE Boolean expression</td></tr><tr><td>Statement(s)</td></tr><tr><td>END WHILE</td></tr></table>	WHILE Boolean expression	Statement(s)	END WHILE	
WHILE Boolean expression					
Statement(s)					
END WHILE					
Definite Loop statements	<table><tr><td>FOR variable = start TO end STEP increment</td></tr><tr><td>Statement(s)</td></tr><tr><td>NEXT</td></tr></table>	FOR variable = start TO end STEP increment	Statement(s)	NEXT	If step is not provided, assume it is one.
FOR variable = start TO end STEP increment					
Statement(s)					
NEXT					
Arrays:	1 dimensional arrays use a single subscript such as A(5). 2 dimensional arrays use (row, col) order such as A(2,3). Arrays can start at location 0 for 1 dimensional arrays and location (0,0) for 2 dimensional arrays. Most ACSL past problems start with either A(1) or A(1,1). The size of the array will usually be specified in the problem statement.				
Strings:	<p>Strings can contain 0 or more characters and the indexed position starts with 0 at the first character. An empty string has a length of 0. Errors occur if accessing a character that is in a negative position or equal to the length of the string or larger. The len(A) function will find the length of the string which is the total number of characters. Strings are identified with surrounding double quotes. Use [ ] for identifying the characters in a substring of a given string as follows:</p> <p>S = "ACSL WDTPD" (S has a length of 10 and D is at location 9)</p> <p>S[:3] = "ACS" (take the first 3 characters starting on the left)</p> <p>S[4:] = "DTPD" (take the last 4 characters starting on the right)</p> <p>S[2:6] = "SL WD" (take the characters starting at location 2 and ending at location 6)</p> <p>S[0] = "A" (position 0 only).</p> <p>String concatenation is accomplished using the + symbol</p>				



# Sample Problem 1

After this program is executed, what is the value of B that is printed if the input values are 50 and 10?


```
input H, R
B = 0
if H>48 then
    B = B + (H - 48) * 2 * R
    H = 48
end if
if H>40 then
    B = B + (H - 40) * (3/2) * R
    H = 40
end if
B = B + H * R
output B
```

# Sample Problem 1 Answer

This program computes an employee's weekly salary, given the hourly rate (R) and the number of hours worked in the week (H). The employee is paid an hourly rate for the number of hours worked, up to 40, time and a half for the overtime hours, up to 48 hours, and double for all hours over 48. The table monitors variables B and H:

B	H
0	50
40	48
160	40
560	40

Therefore, the final value of B is  $2 \times 2 \times 10 + 8 \times \frac{3}{2} \times 10 + 40 \times 10 = 40 + 120 + 400 = 560$ .



## Sample Problem 2

After the following program is executed, what is the final value of NUM?

```
A = "BANANAS"  
NUM = 0: T = ""  
for J = len(A) - 1 to 0 step -1  
    T = T + A[j]  
next  
for J = 0 to len(A) - 1  
    if A[J] == T[J] then NUM = NUM + 1  
next
```



# Sample Problem 2 Answer

The program first stores the reverse of variable A into variable T and then counts the number of letters that are in the same position in both strings.

Variable NUM is incremented each time a character at position x of A is the same as the character in position x of string T.

There are 5 such positions: 1, 2, 3, 4, and 5.



## Sample Problem 3

After the following program is executed, what is the final value of C[4]?

```
A(0) = 12: A(1) = 41: A(2) = 52
A(3) = 57: A(4) = 77: A(5) = -100
B(0) = 17: B(1) = 34: B(2) = 81
J = 0: K = 0: N = 0
while A(J) > 0
    while B(K) <= A(J)
        C(N) = B(K)
        N = N + 1
        k = k + 1
    end while
    C(N) = A(J): N = N + 1: J = J + 1
end while
C(N) = B(K)
```



# Sample Problem 3 Answer

The following table traces the variables through the execution of the program.

J	K	N	A(J)	B(K)	C(N)
0	0	0	12	17	12
1	0	1	41	17	17
1	1	2	41	34	34
1	2	3	41	81	41
2	2	4	52	81	52
3	2	5	57	81	57
4	2	6	77	81	77
5	2	7	-100	81	81

Thus, the value of C(4) is 52. Note that this program merges two arrays in increasing order into one array until a negative number is input.

# Past Contests: Intermediate Problem

What is printed when this program is run?

a = 24: b = 5: c = 2: d = 4: e = 1

if a + c > c \* e then a = a / (b - 1) else a = a - 2 \* b

if a - b \* d < e + c \* d then c = c + b else b = b - 2

if (a < b + c) and (c < d + e) then d = 2 \* e else d = d + e

if b/d = int(b/d) then b = b / d else b = d

if (c ^ 2 > a / d) or (d > b - a) then a = 2 \* a else c = a \* c

if (a < b) or (c > d) and (e < a - b) then a = 10 else e = 0

print a + c / b - d \* (a / 5 + d / b) / c - c / (b + d + e)

end



# Past Contests: Intermediate Solution

Answer: 11

The table contains the values of a, b, c, d and e after each line.

Explanation:

a	b	c	d	e
24	5	2	4	1
6	5	2	4	1
6	5	7	4	1
6	5	7	5	1
6	1	7	5	1
12	1	7	5	1
10	1	7	5	1

$$\begin{aligned}\text{So } & a + c / b - d * (a / 5 + d / b) / c - c / (b + d + e) \\ & = 10 + 7 / 1 - 5 * (10 / 5 + 5 / 1) / 7 - 7 / (1 + 5 + 1) = 11\end{aligned}$$

## Past Contests: Senior Problem

After the following program is executed, what is printed?

$a = 20$ :  $b = 4$ :  $c = 2$ :  $d = 100$ :  $e = 3$

for  $i = 1$  to  $4$

    if  $a / i > d / b$  then  $a = a - 2$  else  $d = d - 20$

    if  $b + 3 * i < a * c$  then  $b = b + 1$  else  $c = c + 1$

    if  $c ^ e > e ^ c$  then  $c = c + 1$  else  $e = e + 1$

next  $i$

print  $4 * (a / e + b / c) - a / (b + 2) + d ^ 2 / a * 2$

end



# Past Contests: Senior Solution

Answer: 62

Explanation:

The table contains the values of a, b, c, d and e after each line.

a	b	c	d	e
20	5	2	80	4
20	6	2	60	5
20	7	3	40	5
20	8	4	20	5

$$\begin{aligned}\text{So } 4*(a/e+b/c)-a/(b+2)+d^2/a*2 &= 4*(20/5+8/4)-20/(8+2)+20^2/20*2 \\ &= 4*(4+2)-20/10+400/20*2 = 4*6-2+20*2 = 24-2+40 = 62\end{aligned}$$

# Credits

[https://www.categories.acsl.org/wiki/index.php?title=Main\\_Page](https://www.categories.acsl.org/wiki/index.php?title=Main_Page)

