Spark API – Getting Started

Introduction

- Click here for some of the advantages of our APIs over RETS.
- Two APIs offered through one key: the Spark API and RESO Web API. Here's a head-to-head comparison of the two.

Field Access and Interpretation

Endpoints used to query

- Spark API – Endpoint used: https://sparkapi.com/v1/
- RESO Web API – Endpoint used: https://sparkapi.com/Reso/OData/

Metadata

- Spark API
  - Standard Fields
  - Custom Fields – expansion parameter is required
- RESO Web API - http://sparkplatform.com/docs/reso/lookup
  - Retrieve all metadata
  - GET: https://sparkapi.com/Reso/OData/$metadata

Listing Date Resource

- Spark API /listings
  - https://sparkapi.com/v1/listings
- RESO Web API /Property
  - https://sparkapi.com/Reso/OData/Property

Member and Office Account Data

- Spark API
  - https://sparkapi.com/v1/accounts?_filter=UserType eq 'Member'
  - https://sparkapi.com/v1/accounts?_filter=UserType eq 'Office'
- RESO Web API
  - https://sparkapi.com/Reso/OData/Member
  - https://sparkapi.com/Reso/OData/Office

Parameters and Paging Syntax

Spark API

- http://sparkplatform.com/docs/supporting_documentation/search_and_paging_syntax
- http://sparkplatform.com/docs/supporting_documentation/selections

RESO Web API

- http://sparkplatform.com/docs/reso/request_parameters

Filter on PropertyType

Spark API

- https://sparkapi.com/v1/listings?_filter=PropertyType eq 'A'

RESO Web API

- https://sparkapi.com/Reso/OData/Property?$filter=PropertyType eq 'Residential'

Filter on timestamps

Spark API

- GREATER THAN example: https://sparkapi.com/v1/listings?_filter=ModificationTimestamp gt 2021-07-15T08:00:00Z
- LESS THAN example: https://sparkapi.com/v1/listings?_filter=ModificationTimestamp lt 2021-07-15T08:00:00Z
- BETWEEN example: https://sparkapi.com/v1/listings?_filter=ModificationTimestamp bt 2021-07-14T00:00:00Z,2021-07-15T00:00:00Z

RESO Web API

- GREATER THAN example: https://sparkapi.com/Reso/OData/Property?$filter=ModificationTimestamp gt 2021-07-15T08:00:00Z
- LESS THAN example: https://sparkapi.com/Reso/OData/Property?$filter=ModificationTimestamp lt 2021-07-15T08:00:00Z
- RESO Web API doesn't support "bt" (between) operator https://sparkapi.com/Reso/OData/Property?$filter=ModificationTimestamp gt 2021-07-14T00:00:00Z and ModificationTimestamp lt 2021-07-15T00:00:00Z

Filter by status

"MlsStatus" is the MLS-specific term; "StandardStatus" is the RESO DD term it maps to

Spark API

- request showing relations between "MlsStatus" and "StandardStatus": https://sparkapi.com/v1/standardfields/MlsStatus
- https://sparkapi.com/v1/listings?_filter=MlsStatus eq 'Active'
- https://sparkapi.com/v1/listings?_filter=StandardStatus eq 'Active'

RESO Web API

- https://sparkapi.com/Reso/OData/Property?$filter=MlsStatus eq 'Active'
- https://sparkapi.com/Reso/OData/Property?$filter=StandardStatus eq 'Active'

Specify number of records to be returned

The default for most services is 10 records returned

Spark API

- https://sparkapi.com/v1/listings?_limit=2

RESO Web API

https://sparkapi.com/Reso/OData/Property?$top=2

Specify fields to be returned examples

Spark API

- https://sparkapi.com/v1/listings?_select=ModificationTimestamp
- https://sparkapi.com/v1/listings?_select=ModificationTimestamp,ListingId

RESO Web API

- https://sparkapi.com/Reso/OData/Property?$select=ModificationTimestamp
- https://sparkapi.com/Reso/OData/Property?$select=ModificationTimestamp,ListingId

Include total number of records matching your request

Spark API

- This includes a "Pagination" hash at the end of the response, and "TotalRows" is the number of matching records
  https://sparkapi.com/v1/listings?_filter=StandardStatus eq 'Active'&_pagination=1

RESO Web API

- Includes "@odata.count" field in response
  https://sparkapi.com/Reso/OData/Property?$filter=StandardStatus eq 'Active'&_count=true

Obtain RESO field names:

- Developers can use the Spark API's /standardfields service and use an expansion to specify that when available, the equivalent RESO field names should also be included:

  https://sparkapi.com/v1/standardfields?_expand=ResoStandardNames

  The "_expand=ResoStandardNames" parameter is documented here.

- Finally, there's a field origins service. Here's an example of how to use it, for "Residential" properties:

  https://sparkapi.com/v1/flexmls/propertytypes/A/origins

  This lists out all standard and custom listing fields, along with all the fields that they contribute to, or that contribute to them.

Replication – by default, replication is not enabled

- IF Replication is enabled for your API key, then queries are written slightly differently
  - Spark API replication set up
  - RESO Web API replication set up