

ArcGIS Server feilmeldinger - et eksempel

Sverre Stikbakke
2017

Feil ved registrering av database

The screenshot shows the 'Register Database' dialog box in the ArcGIS Server interface. A red error message box is displayed at the top, stating: 'The connection property set was missing a required property or the property value was unrecognized. Bad login user'. Below the error message, the 'Name' field is filled with 'larsenar1'. The 'Publisher database connection' field contains a long string of connection properties, including 'ENCRYPTED_PASSWORD', 'SERVER', 'INSTANCE', 'DBCL', 'IENT', 'DB_CONNECTION_PROPERTIES', 'DATABASE', 'USER', and 'AUTHENTICATION_MODE'. An 'Import' button is located to the right of this field. The 'Server database connection' field is empty, and a checkbox labeled 'Same as publisher database connection' is checked at the bottom.

ArcGIS Server M Register Database

GIS Server Web Adapt

Directories
Configuration Store
Clusters
Machines
Data Stores
Extensions

Error Message:
The connection property set was missing a required property or the property value was unrecognized. Bad login user

Register a database to your ArcGIS Server site

Name:
larsenar1

Publisher database connection:
ENCRYPTED_PASSWORD=00022e684d6c4a3375736558716645644453414d7767487377467239464b4335395a4348316e4141563656442b30633d2a00;SERVER=copernicus.hig.no;INSTANCE=sde:postgresql:copernicus.hig.no;DBCLIENT=postgresql;DB_CONNECTION_PROPERTIES=copernicus.hig.no;DATABASE=larsenar1;USER=sde;AUTHENTICATION_MODE=DBMS

Import

Server database connection:
☒ Same as publisher database connection

Register: Database

The connection property set was missing
a required property

or

the property value was unrecognized.

Bad login user.

Sjekker log-filer for ArcGIS Server

```
<?xml version="1.0" encoding="utf-8" ?>
```

```
<Msg  
time='2017-01-14T00:48:59,203'  
type='SEVERE'  
code='-1'  
target='DataValidator.GPServer'  
methodName='ValidateServerDataStore.Execute'  
machine='copernicus.hig.no'  
process='6696'  
thread='3084' >
```

The connection property set was missing a required property or the property value was unrecognized. Bad login user

```
</Msg>
```

Sjekker log-filer for PostgreSQL

2017-01-14 00:48:59 CET FATAL:
no pg_hba.conf entry for host
"fe80::15db:e32a:c268:f6d%10",
user "sde",
database "sverrsti01",
SSL off

PostgreSQL konfigurasjonsfil: pg_hba.conf

```
# Put your actual configuration here
# -----
#
# If you want to allow non-local connections, you need to add more
# "host" records.  In that case you will also need to make PostgreSQL
# listen on a non-local interface via the listen_addresses
# configuration parameter, or via the -i or -h command line switches.


# TYPE      DATABASE          USER            ADDRESS                                 METHOD
#
# IPv4 local connections:
# host      all              all            127.0.0.1/32                          md5
host      all              all            0.0.0.0/0                             md5
#
# IPv6 local connections:
# host      all              all            ::1/128                              md5
host      all              all            ::0/0                                 md5
```

Applikasjonslaget

