

Design Document: Asg3

Jinghao Shen

CruzID: jshen30

1 Goals

The goal for Assignment 3 is to modify the multi-threaded RPC server to implement recursive name resolution, provide immediate persistence for key-value pairs, and improve overall performance and scalability. It will still provide all of the original functionality from earlier assignments, as well as the following additional features.

1. Ability for a variable to contain a variable name or a value. This includes setting and retrieving these names.
2. Recursive name resolution: if a variable contains a name, look up that name and use its value instead. Repeat until it hits a number, or until it exceeds a limit.
3. Variables will be persistent before the server acknowledges an operation.
4. Support for millions of variables (key-value pairs).
5. Improving performance of the server.

Original functions includes:

1. Math functions
2. Read from a file
3. Write to a file
4. Get file size
5. Create a file
6. Multi threads
7. Support for variables in math operations.
8. Sharing of the key-value store across all server threads, and synchronization between the server threads for reading and writing key-value pairs.

2 Design

Modified OLD Functions:

Making a hash table for items with a fixed-size char array as the name and a 64-bit signed integer or variable name as the value. The hash table has functions insert, replacement, delete, and lookup.

To store the key-value

```
struct HT_item{
    char* name;
    int64_t value;
    char* value2;
    uint8_t flag;
    HT_item* next;
}
```

```
struct hashTable{
    size_t size;
    HT_item** array;
```

```

        count;
    }

```

```

import DJBHash

```

Create linked hash table items. It has "Next" to reference to the item linked to the current item.

```

createItem(key, value)
    Name = key
    If (value == string)
        value2 = value
        value = NULL
        flag = 1
    if(value == number)
        value = value
        value2 = NULL
        flag = 0
    Next = null
    Return item

```

Create hash table:

```

createTable(size)
    Table = array[size]
    return hashTable

```

```

freeTable(hashTable*)
    for(0 to size)
        if(item != null)
            table[index]->null

```

Use hashFunction to get an index. Store the value to that index. If there already exists an item with the same variable name, update the value. If there already exists an item with the different variable name, link the current item to the end of the item link.

```

Insert(hashTable*, key, value){
    newItem = createItem
    Index = hashFunction(key);
    if (array[index] == NULL){
        if(count > size)
            Table full return error
        insert newItem to array[index]
        count++;
    }else{
        if(key == array[index] -> key){
            update value;
        }Else

```

```

curr = array[index]
while(curr -> next != null)
    curr = curr-> next;
curr-> next = newitem;

```

Update the value if there is an existing variable name.

```

replacement(hashTable*, key, value)
    index = hashFunction(key);
    if(no such key)
        return
    else
        if(array[index]-> next == null && key == key)
            array[index]-> value = value
        else
            while(go through linked list){
                if(key == key){
                    update value
                }
            }
    }
    return

```

Go to the index on the hash table and go through each item if there's a linked list. If the variable name is founded, remove that item from the hash table.

```

delete(hashTable*, key)
    index = hashFunction(key);
    if(no such key)
        return
    else
        if(array[index]-> next == null && key == key)
            Array[index] = null
            count--;
        else
            if(array[index]-> key == key){
                remove array[index]
                set array[index]->next to array[index]
                count--;
                return

                while(go through linked list){
                    if(key == key){
                        Remove from chain
                    }
                }
            }
    }

```

```

    }
    return null

```

Go to the index on the hash table and go through each item if there's a linked list. If the variable name is founded, return the value of that variable. If nothing is found, return a magic number 1234567890.

```

lookup(hashTable*, key)
    index = hashFunction(key);
    Item = array[index]
    while(item != Null){
        if(item->key = key)
            return item->value
        if(item->next = null){
            return 1234567890
        }
        item = item->next
    }
    return 1234567890

```

Go through all items on the index. If the index is not empty, write the variable name and value to the file. Create the file, if no destination is found.

```

dump(file)
    Open file
    for(i=0 to size){
        if(array[i] != null){
            dprintf("varname=value\n")
            if(array[i]->next != null)
                while(go through linked list)
                    dprintf("varname=value\n")
            }
        }
    }
    close(file)

```

Open and read from the file. Get the variable and the value. Insert into the table.

```

load(file)
    Open file
    while(read)
        Extract variable name
        Extract value
        insert(table, name, value)

```

To have multithread:

```

struct Thread {
    sem_t mutex;
    int cl;
};

```

```

struct thread_data {
    Thread * t;
    hashTable* ht;
}

```

Create threads[N] where N taken from argv
 Create thread_data[N] which has thread and hashtable
 Create mainMutex

```

    Initialize threads n times
    thread_data -> thread = threads[i]
    thread_data -> thread = ht (n times)
    pthread_create(...start...thread_data)

```

Start the connection

```

while(true){
    Cl = accept()
    while(available thread == 0){
        wait(mainMutex);
    }
    threads[i].cl = cl;
    signal(mainMutex);
    wait(mainMutex);
}

```

```

start(void* arg){
    td = arg
    while(true){
        wait(thread->mutex);
        process(cl, ht);
        cl = 0;
        signal(mainMutex);
    }
}

```

```

process(cl, hashtable)
    read
    process recvBuffer
    write

```

New Features:

setv function. Get the name of variable and variable name to set to. Insert that to the hashtable.

```
function(buffer[], operator, ifError){
    varLenX;
    varNameX;
    varLenY;
    varNameY;
    insert(varNameX, varNameY);
    return;
}
```

getv function. Get the name of variable. Search in the hashtable. Return 2 if no such variable name, 14 if the value is not a variable name, variable name if found.

```
function(buffer[], operator, ifError){
    varLen;
    varName;
    varValue = lookUp(varNameX);
    if(varValue == int64_t)
        Return error(14);
    Else if(==1234567890)
        Return error(2);
    Else
        Return varValue;
    return;
}
```

For Math functions, the input is separated into seven cases. Then, retrieve the value from the hashtable based on the variable name. If a 0x80 flag is encountered and the value of that variable name is another variable name, set the variable name to the value variable name and do a loopUp again until the value is a number. Calculate the result based on the input operator and return the result to the main function:

```
function(buffer[], operator, ifError){
    if(del){
        Read 1 operand
    }
    Switch
        Case 0x10
            A as operand
        Case 0x20
            B as operand
        Case 0x30
            A as operand
            B as operand
```

```
Case 0x40
    res as operand
Case 0x50
    A as operand
    res as operand
Case 0x60
    B as operand
    res as operand
Case 0x70
    A as operand
    B as operand
    res as operand
Case 0x90
    A as operand
    while(A!=number)
        A=A.value
        loopUp(A)
Case 0xa0
    B as operand
    while(B!=number)
        B=B.value
        loopUp(B)
Case 0xb0
    A as operand
    B as operand
    while(A!=number)
        A=A.value
        loopUp(A)
    while(B!=number)
        B=B.value
        loopUp(B)
Case 0xc0
    res as operand
Case 0xd0
    A as operand
    res as operand
    while(A!=number)
        A=A.value
        loopUp(A)
Case 0xe0
    B as operand
    res as operand
    while(B!=number)
        B=B.value
```

```
                                loopUp(B)
    Case 0xf0
        A as operand
        B as operand
        res as operand
        while(A!=number)
            A=A.value
            loopUp(A)
        while(B!=number)
            B=B.value
            loopUp(B)
    Default
        a = read 8 bytes from the buffer
        b = read another 8 bytes from the buffer
}

if(overflow)
    ifError = 22;
else
    ifError = 0;
if(there is a res as operand){
    insert(ht, key, value);
}
return a+b or a-b or a*b or a/b or a%b
```