### mycscons on Mio

January 6, 2020

### Submitting to the cluster

- When logging into Mio you are on the head node
- The head node is not meant for computations
  - Especially when many users are on (like today!)

# Submitting to the cluster

- When logging into Mio you are on the head node
- The head node is not meant for computations
  - Especially when many users are on (like today!)

- We can use **srun** to submit to the cluster
  - This allows us to batch submit scripts
  - However, we have another option for m8r

# Submitting to the cluster

- When logging into Mio you are on the head node
- The head node is not meant for computations
  - Especially when many users are on (like today!)
- We can use **./mycscons** to submit an SConstruct to the cluster
  - Requires from rsf.mycluster import \*
  - Requires Cluster() command in Sconstruct

#### Some helpful tools

- Submit a job
  - ./mycscons submits the SConstruct in that location
  - Option: -f filename if you have other naming conventions

### Some helpful tools

- Submit a job
  - ./mycscons submits the SConstruct in that location
  - Option: -f filename if you have other naming conventions
- Submitting in this way automatically lists where log and error files go
  - They live in your scratch directory

- Using squeue shows all running jobs on the cluster
  - Adding -u username filters on that username
  - Probably a good idea to alias in your ~/.bashrc
    - alias sq="squeue -u username"

- Using squeue shows all running jobs on the cluster
  - Adding -u username filters on that username
  - Probably a good idea to alias in your ~/.bashrc
    - alias sq="squeue -u username"
- Also shows the task number
  - If you have a job that hangs or is incorrect, rather than waiting you should cancel it:
    - scancel #### (←the task number!)

- It is not possible to simply log into a compute node and run a task!!!
  - Slurm allocates resources for us
  - This is to avoid conflicts with other users

- It is not possible to simply log into a compute node and run a task!!!
  - Slurm allocates resources for us
  - This is to avoid conflicts with other users

- However, once resources are allocated to your job, you can log into that node to QC
  - Usually not necessary

# Running an interactive job

- If you have a larger compute job not appropriate for the head node, you can request a resource for command line operations
  - srun -n12 --pty bash -i

# Running an interactive job

- If you have a larger compute job not appropriate for the head node, you can request a resource for command line operations
  - srun -n12 --pty bash -i
    - Requests a 12 cpu node with taskname "bash" for an interactive job
- This is not a standard request
  - Remember to exit the interactive job when finished or you will hold the node!

Once a job is submitted, the following text is output.

This is good to note! It tells about the job submission...

```
[agirard@mio001 05 Seismic Modelling]$ vim mycscons
[agirard@mio001 05 Seismic Modelling]$ ./mycscons -f SConstruct complete
'USER IS:', 'agirard')
STARTING SUBMISSION SCRIPT
IN ELSE
SConstruct complete
Removing extra jobs...
Found: 1 jobs
Creating job directory...
.....pbs directory already exists
.....Fig directory already exists
Preparing jobs...
Job 1/1 - Serial:60 1 12 - TESTm8r-s-00
Making job files...
MAKING FILE
'gpfs/lb/sets/geop/scratch/agirard/
 'SCONSJ: ', 1)
 'PPN: ', 12)
 'NSOCKET', 2)
 'NODES', 1)
nodes: 1
Submitting jobs...
Executing... sbatch /gpfs/lb/sets/geop/scratch/agirard/SLURM//TESTm8r-s-00
Job submitted to: Submitted batch job 8266842
EXECUTED COMMAND
[agirard@mio001 05 Seismic Modelling]$
```

Once a job is submitted, the following text is output.

This is good to note! It tells about the job submission...

The most important part is the log and error file locations (in red)

```
[agirard@mio001 05 Seismic Modelling]$ vim mycscons
[agirard@mio001 05 Seismic Modelling]$ ./mycscons -f SConstruct complete
'USER IS:', 'agirard')
STARTING SUBMISSION SCRIPT
IN ELSE
SConstruct complete
Removing extra jobs...
Found: 1 jobs
Creating job directory...
.....pbs directory already exists
.....Fig directory already exists
Preparing jobs...
Job 1/1 - Serial:60 1 12 - TESTm8r-s-00
Making job files...
MAKING FILE
'qpfs/lb/sets/geop/scratch/agirard/
 'SCONSJ: ', 1)
 'PPN: ', 12)
 'NSOCKET', 2)
 'NODES'. 1)
nodes: 1
Submitting jobs...
Executing... sbatch /gpfs/lb/sets/geop/scratch/agirard/SLURM//TESTm8r-s-00
Job submitted to: Submitted batch job 8266842
EXECUTED COMMAND
[agirard@mio001 05 Seismic Modelling]$ [
```

```
EXECUTED COMMAND

[agirard@mio001 05_Seismic_Modelling]$ ls -ltr /gpfs/lb/sets/geop/scratch/agirard/SLURM//TESTm8r-s-00*
-rw-r----- 1 agirard agirard 1439 Jan 6 15:23 /gpfs/lb/sets/geop/scratch/agirard/SLURM//TESTm8r-s-00.out
-rw-r----- 1 agirard agirard 65536 Jan 6 15:23 /gpfs/lb/sets/geop/scratch/agirard/SLURM//TESTm8r-s-00.out
-rw-r----- 1 agirard agirard 65536 Jan 6 15:23 /gpfs/lb/sets/geop/scratch/agirard/SLURM//TESTm8r-s-00.sconsign.dbhash
-rw-r----- 1 agirard agirard 2290 Jan 6 15:23 /gpfs/lb/sets/geop/scratch/agirard/SLURM//TESTm8r-s-00.err
[agirard@mio001 05_Seismic_Modelling]$ 

[agirard@mio001 05_Seismic_Modelling]$ 
[agirard@mio001 05_Seismic_Modelling]$ 
[agirard@mio001 05_Seismic_Modelling]$ 
[agirard@mio001 05_Seismic_Modelling]$ 
[agirard@mio001 05_Seismic_Modelling]$ 
[agirard@mio001 05_Seismic_Modelling]$ 
[agirard@mio001 05_Seismic_Modelling]$ 
[agirard@mio001 05_Seismic_Modelling]$ 
[agirard@mio001 05_Seismic_Modelling]$ 
[agirard@mio001 05_Seismic_Modelling]$ 
[agirard@mio001 05_Seismic_Modelling]$ 
[agirard@mio001 05_Seismic_Modelling]$ 
[agirard@mio001 05_Seismic_Modelling]$ 
[agirard@mio001 05_Seismic_Modelling]$ 
[agirard@mio001 05_Seismic_Modelling]$ 
[agirard@mio001 05_Seismic_Modelling]$ 
[agirard@mio001 05_Seismic_Modelling]$ 
[agirard@mio001 05_Seismic_Modelling]$ 
[agirard@mio001 05_Seismic_Modelling]$ 
[agirard@mio001 05_Seismic_Modelling]$ 
[agirard@mio001 05_Seismic_Modelling]$ 
[agirard@mio001 05_Seismic_Modelling]$ 
[agirard@mio001 05_Seismic_Modelling]$ 
[agirard@mio001 05_Seismic_Modelling]$ 
[agirard@mio001 05_Seismic_Modelling]$ 
[agirard@mio001 05_Seismic_Modelling]$ 
[agirard@mio001 05_Seismic_Modelling]$ 
[agirard@mio001 05_Seismic_Modelling]$ 
[a
```

#### The LOG file

(has the same information that would be output to terminal if you ran scons)

Can view with vim or by following it during execution: tail -f /gpfs/lb/sets/geop/scratch/agirard/SLURM/TESTm8r-s-00.out

```
Executing... sbatch /gpfs/lb/sets/geop/scratch/agirard/SLURM//TESTm8r-s-00
Job submitted to: Submitted batch job 8266842

EXECUTED COMMAND
[agirard@mio001 05_Seismic_Modelling]$ ls -ltr /gpfs/lb/sets/geop/scratch/agirard/SLURM//TESTm8r-s-00*
-rw-r----- 1 agirard agirard 744 Jan 6 15:23 /gpfs/lb/sets/geop/scratch/agirard/SLURM//TESTm8r-s-00
-rw-r----- 1 agirard agirard 1439 Jan 6 15:23 /gpfs/lb/sets/geop/scratch/agirard/SLURM//TESTm8r-s-00.out
-rw-r----- 1 agirard agirard 65536 Jan 6 15:23 /gpfs/lb/sets/geop/scratch/agirard/SLURM//TESTm8r-s-00.sconsign.dbhash
-rw-r----- 1 agirard agirard 2290 Jan 6 15:23 /gpfs/lb/sets/geop/scratch/agirard/SLURM//TESTm8r-s-00.err
[agirard@mio001 05_Seismic_Modelling]$ [
```

#### The ERROR file

(all warning log information)

Not important unless you find an error, but will allow for debugging!!!!