


Applicative Functors in Isabelle/HOL

Joshua Schneider
joshuas@student.ethz.ch

December 8, 2015

Introduction: Tree Labels


`data Tree a = Leaf a | Node (Tree a) (Tree a)`



Inspired by G. Hutton and D. Fulger, "Reasoning About Effects: Seeing the Wood Through the Trees." in *Proceedings of the Symposium on Trends in Functional Programming*, (Nijmegen, The Netherlands, 2008).

Introduction: Tree Labels


`data Tree a = Leaf a | Node (Tree a) (Tree a)`



Inspired by G. Hutton and D. Fulger, "Reasoning About Effects: Seeing the Wood Through the Trees." in *Proceedings of the Symposium on Trends in Functional Programming*, (Nijmegen, The Netherlands, 2008).

Introduction: Tree Labels

`data Tree a = Leaf a | Node (Tree a) (Tree a)`



Inspired by G. Hutton and D. Fulger, “Reasoning About Effects: Seeing the Wood Through the Trees.” in *Proceedings of the Symposium on Trends in Functional Programming*, (Nijmegen, The Netherlands, 2008).

Composing Stateful Computations

Standard solution:
state monad

```
fresh = do
  x <- get
  put (x + 1)
  return x
```

Composing Stateful Computations

Standard solution:
state monad

```
fresh = do
  x <- get
  put (x + 1)
  return x

numberTree (Leaf _) = do
  x <- fresh
  return (Leaf x)
numberTree (Node l r) = do
  l' <- numberTree l
  r' <- numberTree r
  return (Node l' r')
```

Composing Stateful Computations

Standard solution:
state monad

```
fresh = do
  x <- get
  put (x + 1)
  return x
```

```
numberTree (Leaf _) = do
  x <- fresh
  return (Leaf x)
numberTree (Node l r) = do
  l' <- numberTree l
  r' <- numberTree r
  return (Node l' r')
```

Applicative style

```
class Applicative m => Monad m where
  ...
class Functor f => Applicative f where
  pure  :: a -> f a
  (<*>) :: f (a -> b) -> f a -> f b
```

Composing Stateful Computations

Standard solution:
state monad

```
fresh = do
  x <- get
  put (x + 1)
  return x
```

```
numberTree (Leaf _) = do
  x <- fresh
  return (Leaf x)
numberTree (Node l r) = do
  l' <- numberTree l
  r' <- numberTree r
  return (Node l' r')
```

Applicative style

```
class Applicative m => Monad m where
  ...
class Functor f => Applicative f where
  pure  :: a -> f a
  (<*>) :: f (a -> b) -> f a -> f b
```

```
numberTree (Leaf _) =
  pure Leaf <*> fresh
numberTree (Node l r) =
  pure Node <*>
    numberTree l <*> numberTree r
```


Renaming Trees and Lists

```
labels (Leaf x)    = [x]
```

```
labels (Node l r) = labels l ++ labels r
```

Renaming Trees and Lists

```
labels (Leaf x)    = [x]
```

```
labels (Node l r) = labels l ++ labels r
```

```
numberList []      = pure []
```

```
numberList (x:xs) = pure (:) <*> fresh <*> numberList xs
```

```
numberTree (Leaf _)    = pure Leaf <*> fresh
```

```
numberTree (Node l r) = pure Node <*> numberTree l <*> numberTree r
```

Renaming Trees and Lists

```
labels (Leaf x) = [x]
```

```
labels (Node l r) = labels l ++ labels r
```

```
numberList [] = pure []
```

```
numberList (x:xs) = pure (:) <*> fresh <*> numberList xs
```

```
numberTree (Leaf _) = pure Leaf <*> fresh
```

```
numberTree (Node l r) = pure Node <*> numberTree l <*> numberTree r
```

Proposition

```
pure labels <*> numberTree t = numberList (labels t)
```

Proof by induction on t . Leaf case:

```
pure labels <*> (pure Leaf <*> fresh) = pure (:) <*> fresh <*> pure []
```

Compare with

```
labels (Leaf x) = (:) x []
```

A Proof Method for Isabelle

Project Goal

Implement a proof method for Isabelle/HOL which lifts equations to applicative functors.

base equation \implies lifted equation

A Proof Method for Isabelle

Project Goal

Implement a proof method for Isabelle/HOL which lifts equations to applicative functors.

base equation \implies lifted equation

- ▶ Proof method: User interface for goal state transformation
- ▶ Applicative functor or *idiom* given by
 - ▶ type constructor
 - ▶ constants pure, \diamond ($<*>$ in Haskell)
 - ▶ proofs of applicative functor laws

A Proof Method for Isabelle

Project Goal

Implement a proof method for Isabelle/HOL which lifts equations to applicative functors.

base equation \implies lifted equation

- ▶ Proof method: User interface for goal state transformation
- ▶ Applicative functor or *idiom* given by
 - ▶ type constructor
 - ▶ constants `pure`, \diamond (`<*>` in Haskell)
 - ▶ proofs of applicative functor laws
- ▶ Lifting an equation (x is a variable): `[] @ x = x`

base equation: `append [] x = x`
 \implies `pure append \diamond pure [] \diamond x = x`

Overview of Operation

Input: Lifted equation

$$e_1 = e_2$$

Transform into *canonical forms*

$$\Longleftarrow \text{pure } f \diamond x_1 \diamond \dots \diamond x_n = \text{pure } g \diamond x_1 \diamond \dots \diamond x_n$$

Overview of Operation

Input: Lifted equation

$$e_1 = e_2$$

Transform into *canonical forms*

$$\Longleftarrow \text{pure } f \diamond x_1 \diamond \dots \diamond x_n = \text{pure } g \diamond x_1 \diamond \dots \diamond x_n$$

Reduce by congruence

$$\Longleftarrow f = g$$

Extensionality

$$\Longleftarrow \forall y_1 \dots y_n. \quad fy_1 \dots y_n = gy_1 \dots y_n$$

Hinze's Lemmas

Lemma (Normal Form)

Let e be an idiomatic term with variables x_1, \dots, x_n , from left to right. There exists f such that

$$e = \text{pure } f \diamond x_1 \diamond \dots \diamond x_n.$$

Can lift equations

1. where both sides have the same list of variables, and
2. no variable is repeated.

Hinze's Lemmas

Lemma (Normal Form)

Let e be an idiomatic term with variables x_1, \dots, x_n , from left to right. There exists f such that

$$e = \text{pure } f \diamond x_1 \diamond \dots \diamond x_n.$$

Can lift equations

1. where both sides have the same list of variables, and
2. no variable is repeated.

Lemma (Lifting Lemma, modified)

Let e' be the lifted term of e , with variables x_1, \dots, x_n . If the idiom satisfies additional properties, then

$$e' = \text{pure } e \diamond x_1 \diamond \dots \diamond x_n.$$

Lifts any equation, but not to all applicative functors.

Combinatory Logic

- ▶ Eliminate variables from terms, introduce combinator constants
- ▶ BCKW system is equivalent to lambda calculus

$$\mathbf{B}gfx = g(fx)$$

$$\mathbf{C}fxy = fyx$$

$$\mathbf{K}xy = x$$

$$\mathbf{W}fx = fxx$$

Combinatory Logic

- ▶ Eliminate variables from terms, introduce combinator constants
- ▶ BCKW system is equivalent to lambda calculus

$$\mathbf{B}gfx = g(fx)$$

$$\mathbf{C}fxy = fyx$$

$$\mathbf{K}xy = x$$

$$\mathbf{W}fx = fxx$$

- ▶ If not all combinators are available, not all terms can be represented
- ▶ Conversion by *bracket abstraction* algorithms

Fancier Idioms

- ▶ Some idioms satisfy additional laws, one or more of

$$(c) \qquad \text{pure } \mathbf{C} \diamond f \diamond x \diamond y = f \diamond y \diamond x$$

$$(k) \qquad \text{pure } \mathbf{K} \diamond x \diamond y = x$$

$$(w) \qquad \text{pure } \mathbf{W} \diamond f \diamond x = f \diamond x \diamond x$$

- ▶ Hinze's Lifting Lemma requires all three

- ▶ Examples

- ▶ state monad: none
- ▶ set (application via Cartesian product): (c)
- ▶ sum type, e.g. `Either`: (w)
- ▶ option/`Maybe`: (c), (w)
- ▶ environment functor, streams: (c), (k), (w)

Lifting Bracket Abstraction

- ▶ Assume an applicative functors satisfies (c)

$$\begin{array}{ll} \lambda xy. x(fy) & x \diamond (\text{pure } f \diamond y) \\ = \mathbf{CB}f & = \text{pure } \mathbf{C} \diamond \text{pure } \mathbf{B} \diamond \text{pure } f \diamond x \diamond y \\ & = \text{pure } (\mathbf{CB}f) \diamond y \diamond x \\ & = \text{pure } (\lambda xy. x(fy)) \diamond y \diamond x \end{array}$$

- ▶ We obtain a canonical form if the base term is representable

Lifting Bracket Abstraction

- ▶ Assume an applicative functors satisfies (c)

$$\begin{aligned} & \lambda xy. x(fy) & x \diamond (\text{pure } f \diamond y) \\ = \quad \mathbf{CB}f & = \text{pure } \mathbf{C} \diamond \text{pure } \mathbf{B} \diamond \text{pure } f \diamond x \diamond y \\ & = \text{pure } (\mathbf{CB}f) \diamond y \diamond x \\ & = \text{pure } (\lambda xy. x(fy)) \diamond y \diamond x \end{aligned}$$

- ▶ We obtain a canonical form if the base term is representable
- ▶ Variable order for idiomatic terms? Remember

$$\text{pure } f \diamond x_1 \diamond \dots \diamond x_n = \text{pure } g \diamond x_1 \diamond \dots \diamond x_n$$

Usage (1)

applicative state

for

pure: Pair

ap: "ap_state :: ('s \Rightarrow ('a \Rightarrow 'b) \times 's) \Rightarrow ('s \Rightarrow 'a \times 's) \Rightarrow 's \Rightarrow 'b \times 's"

unfolding ap_state_def

by (auto **split**: split_split)

Usage (2)

```
lemma "Pair labels  $\diamond$  number_tree t = number_list (labels t)"
proof (induction t)
  case (Leaf x)
  have "Pair labels  $\diamond$  (Pair Leaf  $\diamond$  fresh) = Pair op #  $\diamond$  fresh  $\diamond$  Pair []"
    by applicative_lifting simp
  thus ?case by simp
next
  case (Node l r)
  let ?ll = "Pair labels  $\diamond$  number_tree l"
  let ?lr = "Pair labels  $\diamond$  number_tree r"
  have "Pair labels  $\diamond$  (Pair Node  $\diamond$  number_tree l  $\diamond$  number_tree r) = Pair op @  $\diamond$  ?ll  $\diamond$  ?lr"
    by applicative_lifting simp
  thus ?case using Node.IH by (simp add: label_append)
qed
```

Conclusion

- ▶ Implemented applicative lifting in Isabelle/HOL
- ▶ Extended Hinze's results with bracket abstraction
- ▶ Use case: Algebra lifted to streams and infinite trees

Questions?

Applicative Functor Laws

(identity)

$$\text{pure } \mathbf{I} \diamond u = u$$

(composition)

$$\text{pure } \mathbf{B} \diamond u \diamond v \diamond w = u \diamond (v \diamond w)$$

(homomorphism)

$$\text{pure } f \diamond \text{pure } x = \text{pure } (fx)$$

(interchange)

$$u \diamond \text{pure } x = \text{pure } (\lambda f. fx) \diamond u$$

What are the Variables?

- ▶ Remember that both canonical forms need the same variable lists:

$$\text{pure } f \diamond x_1 \diamond \dots \diamond x_n = \text{pure } g \diamond x_1 \diamond \dots \diamond x_n$$

- ▶ Must be able to represent terms with available combinators
- ▶ Instantiation:

$$\begin{aligned} & \forall xy. \text{pure } f \diamond x \diamond y = \dots \\ \implies & \forall z. \text{pure } f \diamond z \diamond z = \dots \end{aligned}$$

What if we want to prove the latter, but can only represent the former?

- ▶ Algorithm depends on available combinators, partially a heuristic