

Neural Structural Consolidation: Learning from Transient Relational Structure at Inference Time

Position Paper, Evidence Update, and Research Plan

Jorge Simão

EInnovator R&D — Center for the Sciences of Computation, Cognition, and Complexity

September 2026

Abstract

Transformer inference repeatedly constructs rich relational objects—attention matrices, residual trajectories, token graphs, routing decisions, and task-conditioned substructures—but normally discards most of their episode-specific structure after the current computation. Training exploits these quantities indirectly through end-to-end gradients, yet deployed models generally lack a mechanism for explicitly accumulating recurrent relational regularities observed during use. We call the broader opportunity *Neural Structural Consolidation* (NSC): extracting validated structure from transient neural computation and progressively consolidating it into routing, sparse attention, prototype memories, adapters, fast weights, residual controllers, or, at the slowest timescale, backbone parameters. The program is deliberately staged. Completed controlled studies now draw a consistent boundary. Visible n-gram and hierarchy structure need not predict causal utility; cue-free semantic composition remains at chance; learned propositional inference can pass while functor binding fails one seed; structured in-context rule acquisition fails its selectivity gate; and added autoregressive supervision, partial starts, or diversity do not move the learned recurrence frontier beyond the training boundary. Paper 0.9 Stage A now adds a controller result: neither one-call tool use nor an iterative harness exceeds its learned depth-three boundary after exact continuation to 2,000 and 4,000 updates. A frozen-Qwen candidate intervention likewise yields favorable bridge means but unresolved intervals. Persistent continual learning therefore remains blocked pending the preregistered larger natural replication; later Paper 0.9 allocation, diversity, and training-depth stages remain unfinished.

1 Scope and Contributions

NSC is a research program rather than a claim that attention graphs are symbols or that inference-time learning is universally beneficial. Its proposed contributions are: (i) an operational unit of recurrent structure; (ii) a common metric and artifact contract across sequential, semantic, retrieval, and residual experiments; (iii) causal tests separating visible structure from useful computation; (iv) a hierarchy of persistence mechanisms with matched-capacity controls; and (v) explicit decision gates that allow the program to stop after a negative result.

The immediate scope is frozen or locally trained small Transformers with inspectable blocks. Production continual learning, unrestricted self-modification, and claims of brain–Transformer equivalence are outside the initial program. A successful measurement paper need not produce an online learner, and a successful learner need not establish symbolic computation.

2 Position

For layer l , a Transformer creates

$$A_l(x) = \text{softmax}(Q_l K_l^\top / \sqrt{d}),$$

a dense context-specific relational structure. Training gradients pass through A_l , so training does not ignore attention structure. The asymmetry is subtler: sample-level relational structures are usually not retained as explicit reusable learned objects. At inference time, a model may repeatedly rediscover stable edges, communities, bridge relations, layer-persistent motifs, residual refinements, and task-conditioned subgraphs without accumulating those observations into persistent structural knowledge.

NSC hypothesis: relations produced during inference are themselves potential training data. Recurrent, useful relational structure should be measured, validated, and selectively consolidated.

The unit of analysis is an episode-level structural observation

$$o_t = (c_t, S_t, u_t, m_t), \tag{1}$$

where c_t records context and controls, S_t is a compact structural summary, u_t is a task-conditioned causal utility estimate, and m_t is complete provenance. Consolidation is warranted only for equivalence classes of observations that recur across held-out lexical items, templates, tasks, or episodes. Recurrence without transfer is memorization; stability without causal utility is description; utility without a matched baseline is not evidence for structural learning.

3 Three Clocks and Four Evidential Levels

Depth ℓ , interaction episode t , and slower learning or development τ are distinct clocks. A pattern that persists across layers is not thereby learned across episodes, and an association that emerges over training checkpoints is not an online memory. Every claim should identify its clock.

We distinguish four evidential levels:

1. **Observation:** a reproducible statistic exists, such as an aligned attention motif, residual trajectory, hierarchy geometry, or routing graph.
2. **Prediction:** the statistic predicts held-out target progress or causal utility beyond lexical, frequency, score, and generic-layer controls.
3. **Intervention:** ablation, patching, replacement, or matched-budget selection changes behavior as predicted.
4. **Consolidation:** persistent state learned from the statistic improves future episodes while retaining override behavior and avoiding matched unrelated harm.

Claims must not silently move upward in this hierarchy.

4 Relation to Existing Approaches

Titans introduces neural long-term memory learned during test-time processing and combines it with attention [1]. TTT layers make recurrent hidden state a model updated by self-supervised learning [2]. Linear attention has been related formally to fast-weight programming [3]. Infini-attention combines local attention with bounded compressive memory [4]. These demonstrate that inference need not be read-only. NSC generalizes the question from “what content should persist?” to “what recurrent computational structure should persist, where, and on what timescale?”

Family	Persistent state	Main distinction from NSC
KV/context memory	token representations	stores content rather than recurrent relational statistics
Compressive memory	bounded summary	compresses history into fixed state
Fast weights / linear attention	associative mapping	online binding is itself the state update
TTT	trainable hidden model	self-supervised gradient updates at test time
Titans	neural long-term memory	surprise-driven associative memory update
Continual/LoRA adaptation	adapter/backbone parameters	typically optimized from task/self-supervised loss
NSC	structural summaries and parameters	explicitly learns from relational/dynamical statistics

Table 1: Conceptual positioning.

5 Structural Signals

Candidate signals include attention entropy and concentration, edge persistence across layers or repeated episodes, cross-head agreement, graph communities, bridge centrality, motifs, token-role correlations, residual-update geometry, causal skip utility, task/goal state Z , and validation outcomes:

$$S_t = \Phi(A_{1:L}, R_{1:L}, Z, \text{routing}, \text{outcome}).$$

A central methodological rule is to distinguish correlation from utility. A consistently large edge is not necessarily causally useful, while a weak edge may be an essential bridge for multi-hop inference.

6 Common Measurement Contract

For a pre-normalized block, record tensor locations explicitly:

$$r_\ell \rightarrow r'_\ell = r_\ell + \Delta_\ell^{\text{SA}}, \quad (2)$$

$$r'_\ell \rightarrow r_{\ell+1} = r'_\ell + \Delta_\ell^{\text{FF}}. \quad (3)$$

Descriptive target progress, such as the signed logit change produced by an update, is not a causal effect. Primary mechanistic claims require interventions and generic-layer controls. Residual geometry includes update norm, update-to-state norm ratio, state-update cosine, update-update cosine, effective rank, and representational similarity. Positive, orthogonal, or negative alignment are labeled *refinement candidates*, *complementarity candidates*, or *interference candidates*; strong interference additionally requires negative task-conditioned utility and later repair.

Every artifact records run and schema identifiers, git commit, command, resolved configuration, model and tokenizer revision, dataset and split, seed, device/dtype, package versions, timestamp, and the exact atlas or hierarchy hash. Raw rows are aggregated at the scientific unit—n-gram, semantic item/branch, candidate memory, or episode—rather than treating correlated token occurrences as independent evidence. Paper values and figures must regenerate from committed machine-readable artifacts.

7 Two Measurement Gates Before Continual Learning

Paper 0.5: recurrent token prediction. For token prefix g and continuation y , the corpus supplies frequency, continuation entropy, and association strength. Layerwise SA/FFN updates, causal interventions, attention-motif controls, contextual override, and checkpoint trajectories test whether the relation is compiled, retrieved, distributed, or repaired. Corpus counts for opaque pretrained models are explicitly reference-corpus proxies, not training frequency.

Paper 0.6: semantic abstraction. Natural and synthetic hierarchies supply known instance–category–superclass distances and transformation families. Within/between dispersion, hierarchy–activation correspondence, invariant onset/persistence/re-entry, SA/FFN interventions, and cross-template transfer test whether approximate abstraction invariants emerge. Lexical and Paper 0.5 n-gram statistics are mandatory controls. Probe accuracy and geometric resemblance alone are insufficient.

These gates determine the candidate structural state S_t and the outcome signal u_t for later consolidation. If stable signatures vanish under matched controls, or causal measurements disagree with descriptive ones, later learners must not be engineered around the preferred story.

8 Empirical Status Through Paper 0.9 Stage A

The completed experiments replace the original forward-looking narrative with an evidence ledger:

Stage	Main result	Consequence
Paper 0.5	Relation-specific attention motifs are visible (specificity 0.228) but do not predict SA causal contribution ($\rho = -0.009$); frequency/context regression explains only $R^2 = 0.073$.	Recurrent appearance is not a sufficient consolidation signal; component responsibility must be measured under the requested transformation and intervention.
Paper 0.6	Earlier hierarchy-neighbor recovery exceeds permutation (0.477 versus 0.254), but the completed cue-free v7 study is at chance: mean test accuracy is 0.496/0.502/0.498 for L2/L4/L8, and every three-seed frontier is zero, including depth one.	Geometry and the earlier direct endpoint-membership result are diagnostics, not evidence of acquired compositional abstraction; $L_{\min}(d)$ is ineligible.
Paper 0.7	The three-seed P2 propositional gate passes (test accuracy 0.993–1.000), whereas F2 functor binding fails because seed 23 reaches only 0.917 overall and 0.901 on its worst template.	Local formal competence is task-specific. Deeper P3–P6/F3–F9 mechanism claims remain stopped at the failed prerequisite.
Paper 0.8	D5 evaluates 12 learned architecture/variant cells and 51,456 rows on seen parameters, held-out parameters, and a held-out function family. No seed passes; selectivity is nonpositive in nearly every aggregate cell.	Information-valid demonstrations and a Bayes ceiling of one do not ensure acquisition or nuisance-selective rule use.
Paper 0.85	Across baseline, partial starts, high diversity, and their combination, all three-seed autoregressive frontiers remain $K_{AR} = 3$ and $P(\text{acquire } K = 4) = 0$.	More supervised starting states and examples do not by themselves induce length-general recurrence; the result is an acquisition null, not an impossibility theorem.
Paper 0.9 Stage A	At both 2,000 and 4,000 updates, M3 and M4 have final-answer frontier three; under its machine-specific one-call coverage gate M3 has frontier one. Neither has all-seed $K = 4$ competence, and M4 is exactly zero at every tested $K \geq 4$.	A local tool and explicit loop change the machine interface but do not ensure acquisition of a train-short/test-long controller. Later architecture, diversity, and training-depth stages remain pending.
Paper 1	At four chunks, bridge preservation raises controlled quality from 0.297 to 0.627. In the initial natural frozen-Qwen intervention, bridge-minus-base answer log probability is positive in all six HotpotQA/QASPER budget cells, but all 95% intervals cross zero and S5 mostly degrades.	Natural bridge utility is a replication target, not a gate pass; the larger three-seed replication is pending and online consolidation remains blocked.

Table 2: Series-level result ledger. Positive controlled results and negative generalization evidence are retained together.

The common storyline is consequently not “motifs become symbols.” It is: (i) recurrent computation exposes candidate structure; (ii) representability, information sufficiency, acquisition, and length generalization are distinct; (iii) descriptive structure and causal utility can disagree; (iv) useful structure is conditional on task and requested resolution; and (v) persistence is justified only by held-out outcome utility. This shifts the candidate learning target from recurring attention patterns to compact, outcome-grounded structural summaries with explicit negative and rollback

signals.

9 Mechanism Spectrum

9.1 Training-free contrast adaptation

A minimal intervention is

$$a'_i = \frac{a_i^\gamma}{\sum_j a_j^\gamma}, \quad \gamma > 1,$$

equivalent to lowering softmax temperature. A stronger version predicts γ from entropy, layer, head, goal, or graph structure. Global sharpening is only a baseline because it can erase bridge edges and minority hypotheses. Graph-aware redistribution should preserve edges with persistence, bridge value, goal relevance, or measured causal utility.

9.2 Prototype consolidation

Structural observations can update local prototypes without backpropagation:

$$p_k \leftarrow (1 - \eta)p_k + \eta S_t,$$

with competitive, normalized, Hebbian, Oja-like, or hierarchical variants. Prototypes may represent edge types, motifs, subgraphs, task structures, or residual-update regimes.

9.3 Structural adapters and fast weights

An adapter can condition on structural summaries,

$$\Delta h_l = g_\phi(h_l, S_t),$$

or a hypernetwork can map structural state to low-rank updates. Online variants update ϕ with structural objectives. This is a controlled middle ground between transient activation changes and backbone fine-tuning.

9.4 Slow backbone consolidation

For local deployments, validated episodes can populate a build dataset for periodic LoRA, FFN, or restricted backbone updates. This should be the slowest timescale because model drift, forgetting, and attribution become progressively harder to control.

9.5 Consolidation objective and controls

Let P_t denote persistent structural state and V a validation signal. A generic update is

$$P_{t+1} = \mathcal{U}(P_t, S_t; V_t), \tag{4}$$

but the scientific comparison is not update versus no update alone. It includes token/label-only memory, hidden-state-conditioned memory, random or shuffled structural features, matched-capacity ordinary adapters, replay where applicable, and an oracle diagnostic. Outcomes include future-task loss, transfer, retention, contextual override, contamination sensitivity, update cost, and reversibility. Online updates require bounded scope, versioned state, rollback, and an audit trail linking each persistent change to its source episodes.

10 Integration with the Research Program

PRA. PRA is the first experimental vehicle because better structural discrimination can directly reduce retrieved chunks that must be materialized. The principal Pareto curve is task quality versus materialized KV tokens, supplemented by latency and GPU memory.

Gated residuals. Residual work asks whether updates refine, complement, or interfere. NSC adds historical structural evidence:

$$g_l = f(Z, r_l, \Delta_l, G_l, P),$$

where P is consolidated prototype state. This separates instantaneous intrinsic gating from experience-consolidated control.

Modal LLMs. A non-causal encoding mode can construct a complete prompt graph before generation. Generation consumes it causally; review re-encodes the solution; validation compares prompt, generation, review, and goal state. The modes create a natural loop: encode $\rightarrow$ act $\rightarrow$ inspect $\rightarrow$ validate $\rightarrow$ consolidate.

Emergent quasi-symbolic inference. Hierarchical prototypes provide a testable bridge:

neural dynamics $\rightarrow$ graph invariants $\rightarrow$ stable prototypes $\rightarrow$ relations $\rightarrow$ composable operators.

The scientific question is whether recurrent motifs become invariant, discrete, compositional, and causally reusable enough to function as latent relations without manually installing symbols.

11 Research Program and Paper Sequence

1. **Paper 0.5 – Common n-grams as causal probes (completed).** Distributed, transformation-dependent SA–FFN mechanisms are supported; motif recurrence fails as a causal-utility signal.
2. **Paper 0.6 – Hierarchical semantic abstraction (v7 complete).** Earlier weak geometry remains descriptive; the cue-free compositional frontier is zero for L2/L4/L8, so compositional acquisition is not supported.
3. **Paper 0.7 – Formal operators (P2/F2 complete).** Propositional competence passes; the functor-binding all-seed gate fails, so deeper formal phases remain stopped.
4. **Paper 0.8 – In-context task specification (D5 complete).** The dataset is informative, but no tested learned cell acquires selective rule use.
5. **Paper 0.85 – Learned recurrence frontier (v2 complete).** Partial starts and higher diversity do not move the three-seed frontier beyond $K = 3$.
6. **Paper 0.9 – Tool/controller ladder (Stage A complete).** Exact 2,000/4,000-update continuation leaves both final-answer frontiers at three, while M3’s stricter one-call coverage frontier is one; neither machine has all-seed $K = 4$ competence. Stages B–E remain pending and supply no evidence here.

7. **Paper 1 – Structural statistics as sparse-control signals (initial intervention complete).** Bridge-aware selection shifts a synthetic frontier; initial natural bridge means are favorable but uncertain, while S5 and removal prediction fail.
8. **Natural replication gate (pending).** Repeat the unchanged HotpotQA/QASPER native-K/V protocol at 24 validation and 24 test identities per dataset over three sampling seeds, without test-set tuning.
9. **Paper 2 – Local prototype consolidation (blocked).** Learn recurrent structural summaries only if the natural candidate-level gate passes.
10. **Paper 3 – Structural adapters.** Compare graph-conditioned LoRA/adapters with ordinary task/domain adapters under matched budgets.
11. **Paper 4 – Online validated consolidation.** Update persistent state from successful/reviewed episodes; characterize stability, forgetting, contamination, reversibility, and provenance.
12. **Paper 5 – Structural residual control.** Predict refinement, complementarity, interference, and selective layer execution.
13. **Paper 6 – Modal consolidation.** Exploit encoding/generation/review/validation as distinct observation and learning phases.
14. **Paper 7 – Emergent relational operators.** Test invariance, discreteness, systematic composition, transfer, counterfactual behavior, and causal reuse.

12 Decision Ledger

Each paper freezes hypotheses, controls, primary endpoints, and stop/go criteria before the next mechanism is introduced. Paper 0.5 passed as a measurement framework but failed motif recurrence as a learning signal. Paper 0.6’s cue-free v7 frontier is zero, overriding any compositional reading of its earlier cue-bearing success. Paper 0.7 permits the propositional branch but stops the functor branch; Paper 0.8 D5 and Paper 0.85 v2 are acquisition nulls under their tested regimes. Paper 0.9 Stage A is complete: increasing the baseline optimization budget does not move either M3 or M4 beyond the previously measured boundary. Its later allocation, diversity, and training-depth stages are pending, as is Paper 1’s larger natural replication. Learned prototypes and adapters therefore remain blocked. An inconclusive or negative gate is not permission for unbounded tuning.

13 Cross-Cutting Evaluation Principles

Use matched-compute baselines; frozen-backbone baselines before trainable mechanisms; task quality plus systems cost; causal interventions; multiple seeds; layer/head breakdowns; explicit negative results; contamination controls for online learning; and separation of structural prediction from structural utility. Report the largest contiguous all-seed frontier rather than isolated passing depths, and distinguish an informative dataset from successful acquisition. Ablations should distinguish semantic retrieval score, lexical score, attention magnitude, persistence, community structure, bridge score, residual geometry, goal conditioning, and outcome feedback.

14 Falsification Criteria

The program weakens if n-gram mechanisms do not replicate across seeds or model settings; semantic hierarchy effects vanish after lexical and continuation-statistical controls; descriptive motifs do not predict causal component utility; structural statistics fail to predict causal utility beyond ordinary activations/scores; graph-aware selection cannot improve quality per materialized token over tuned top- k /temperature baselines; prototypes fail to transfer and merely memorize lexical identity; structural adapters offer no advantage over matched ordinary adapters; contextual override degrades after consolidation; or apparent quasi-symbolic prototypes fail invariance and compositionality tests. Several warnings have now materialized: motif stability did not predict causal utility; cue-free semantic composition stayed at chance; formal and contextual-rule acquisition failed outside narrower successful strata; added recurrence supervision and diversity did not extend the $K = 3$ frontier; Paper 0.9 Stage A found no M3/M4 budget rescue at $K = 4$; retained pretrained graph summaries did not predict held-out recovery; and the first natural candidate intervention produced favorable bridge means without statistical resolution or learned-selector transfer. The program now depends on the fixed natural replication and the remaining preregistered controller allocation/data comparisons, not on descriptive structure alone.

15 From Consolidated Relations to Emergent Symbols

A persistent neural object is not symbolic merely because it is sparse, clustered, or human-interpretable. The strongest endpoint requires a ladder of tests: invariance to nuisance substitutions; discreteness relative to continuous controls; systematic recombination; transfer across lexical and task domains; counterfactual sensitivity to relation changes; causal reuse in a new computation; and stable reference across episodes. The term *quasi-symbolic* is reserved for partial success on this ladder, with failed rungs reported. This criterion prevents the program from equating a probe direction, attention motif, or prototype centroid with a symbol.

16 Strategic Value

NSC supplies a common experimental language for memory, sparse inference, residual control, modal processing, and local learning. It also provides a disciplined path from systems work to architecture and cognitive-theory questions: first show that transient structure predicts useful sparse decisions; then show that recurrent structure can be consolidated; only then ask whether resulting objects support stable relational computation.

17 Current Conclusion

The series supports a modest claim and rejects a stronger one. Transformers expose recurrent, partially structured computation whose causal realization changes with context, intervention, and requested abstraction. The completed acquisition studies show that informative inputs, visible geometry, local competence, autoregressive output space, more training diversity, and—in Paper 0.9 Stage A—a local tool or explicit loop with fourfold optimization budget do not automatically produce the intended compositional procedure. Aggregate bridge structure improves sparse selection when the mechanism is known and moves initial natural frozen-Qwen means in a favorable direction, but current uncertainty and transfer failures prevent a causal-learning claim. Paper 0.9

Stages B–E and the larger Paper 1 replication remain pending; until a preregistered gate passes, NSC is a falsifiable research program rather than an established structural-consolidation capability.

References

- [1] A. Behrouz, P. Zhong, V. Mirrokni. *Titans: Learning to Memorize at Test Time*. arXiv:2501.00663.
- [2] Y. Sun et al. *Learning to (Learn at Test Time): RNNs with Expressive Hidden States*. arXiv:2407.04620.
- [3] I. Schlag, K. Irie, J. Schmidhuber. *Linear Transformers Are Secretly Fast Weight Programmers*. arXiv:2102.11174.
- [4] T. Munkhdalai, M. Faruqui, S. Gopal. *Leave No Context Behind: Efficient Infinite Context Transformers with Infini-attention*. arXiv:2404.07143.