# Autoreason: Autoresearch for Subjective Domains

shl0ms

https://github.com/NousResearch/autoreason

**Abstract**

We introduce autoreason, a method for iterative LLM refinement in subjective domains where no objective metric exists. The method constructs a subjective fitness function through independent blind evaluation, extending the autoresearch paradigm. Autoreason uses fresh isolated agents per role, blind judge panels with Borda count aggregation, and conservative tiebreaking. Across 5 task types, autoreason ranked first or second in every 7-judge blind comparison, winning 3 of 5 tasks outright. Monte Carlo analysis (5 independent runs) shows 80% convergence rate with consistent output quality despite variable convergence speed. We additionally ran autoreason on the writing of this paper, discovering that ground-truth context for the critic eliminates hallucination. We find that the method's advantage is task-dependent: autoreason excels on tasks with genuine tradeoffs and stakeholder tensions, while direct critique-and-revise can outperform on tasks with more objectively verifiable requirements.

## 1 Introduction

LLMs exhibit systematic failures when iterating on subjective work: sycophancy, overcriticism, overcompromise, authorship bias, scope drift, and context collapse. These failures persist across prompting strategies—even in code generation, iterative refinement leads to progressive degradation [2].

We present autoreason, extending Karpathy's autoresearch [1] to subjective domains. Each iteration produces three competing versions—the incumbent (A), an adversarial revision (B), and a synthesis (AB)—evaluated by a blind judge panel. The method constructs a fitness function through the evaluation process itself.

We distinguish two modes. **v1 (quick pass)**: a single cycle through critic → B → AB → judge. Five LLM calls. **v2 (convergence loop)**: repeats with a full judge panel until the incumbent survives consecutive challenges. All experiments use v2.

## 2 Method

**Critic**: A fresh agent identifies problems in the current incumbent A. Finds problems only—no fixes. Optionally receives ground-truth data for fact-checking.

**Author B**: A fresh agent revises A based on the critique. Sees the task, A, and the critique. No drafting history.

**Synthesizer**: A fresh agent receives A and B with randomized labels. Produces AB by taking the strongest elements of each.

**Judge Panel**: 3 fresh agents rank A, B, AB via Borda count (3/2/1 points). Randomized labels and order. Conservative tiebreak: incumbent wins ties. Convergence at 2 consecutive A wins.

Every role is a fresh, isolated agent. The original task prompt anchors all evaluation.

## 3 Experiments

Five tasks: (1) go-to-market strategy, (2) notification system design, (3) remote work policy, (4) competitive positioning document, (5) incident response process. All experiments used claude-sonnet-4-20250514 (temp=0.8 authors, 0.3 judges). Each task ran autoreason to convergence plus four baselines (conservative, improve_this, harsh_critic, critique_and_revise) at 15 passes each from the same initial output, evaluated by a 7-judge blind panel.

## 4 Results

### 4.1 Multi-Task Comparison

| Method | T1 | T2 | T3 | T4 | T5 |
|---|---|---|---|---|---|
| **Autoreason** | **35** | 19 | **29** | 25 | **31** |
| Critique & rev. | 13 | **22** | 26 | **32** | 19 |
| Harsh critic | 18 | 19 | 27 | 20 | 26 |
| Conservative | 21 | 19 | 15 | 18 | 15 |
| Improve this | 18 | 11 | 8 | 10 | 14 |

Table 1: Borda scores (max 35) across 5 tasks. Bold = winner. Autoreason won tasks 1, 3, 5. Critique-and-revise won tasks 2, 4.




Figure 1: **5-way blind panel across all tasks.** Autoreason wins 3/5, never below 2nd place. Critique-and-revise wins 2/5. Improve_this is consistently worst.

Autoreason won 3 of 5 tasks (1, 3, 5) and placed second on the other two. Critique-and-revise won tasks 2 and 4. The pattern: autoreason excels on tasks with genuine tradeoffs (strategy, policy, cross-timezone incident response) where the A/B/AB structure surfaces different valid perspectives. Critique-and-revise wins on tasks with more concrete technical requirements (system design, competitive positioning) where a direct find-and-fix loop is more efficient.

Improve_this ranked last or near-last on every task. Conservative performed inconsistently—second on task 1, but 4th–5th elsewhere.




Figure 2: **Aggregate performance.** Autoreason averages 27.8 Borda (rank 1.4) across 5 tasks, never dropping below 2nd. Critique-and-revise averages 22.4 (rank 2.0). Improve_this averages 12.2 (rank 4.4).

### 4.2 Convergence Behavior




Figure 3: **Convergence speed varies by task.** All 5 tasks converged at threshold 2. Task 5 (incident response) required 28 passes.

All tasks converged at threshold 2 (consecutive A wins), requiring 9–28 passes. Task complexity correlates with convergence time: simple policy tasks converge faster than multi-stakeholder operational processes.

### 4.3 Trajectory Analysis

Figure 4 shows the full trajectory for Task 1 as a tree, where vertical position represents cumulative drift from the initial version. A wins produce horizontal movement (no drift). B wins drift upward by 1 unit, AB by 0.5. Unchosen alternatives are shown as faded branches.




Figure 4: **Trajectory tree for Task 1 (26 passes).** The path shows where each pass's winner came from. Flat segments = A surviving. Upward jumps = displacement. Stars mark 2-consecutive A-win points.

The trajectory reveals a key tension. At pass 15, A had won twice consecutively (convergence). But 11 more passes followed with B winning 5 of them. Were those later B wins genuine improvements or noise?

We tested directly: a 7-judge panel comparing pass 15 vs pass 25 output chose pass 15 by 6–1. The later passes were churn, not improvement. This validates the convergence threshold but raises an important question about judge accuracy within the loop.

### 4.4 Judge Accuracy

The judges are accurate *on average across a panel* but noisy *per individual pass*. At pass 16, the same architecture that correctly identified the pass 15 output as strong nonetheless picked AB over A by one Borda point. This is not a failure of the method—it's inherent stochasticity in LLM evaluation. The convergence threshold filters this noise: requiring consecutive wins means a single noisy pass can't cause premature convergence, while sustained noise (as in passes 17–21) represents genuine ambiguity about which framing is better rather than clear improvement.

### 4.5 Monte Carlo Analysis

Five independent runs of Task 1 tested convergence reliability (Figure 5).




Figure 5: **Monte Carlo: 5 runs, same task.** 4/5 converged (80%). Convergence speed varies widely (6–17 passes). Final word counts cluster around 1450–1660.

4 of 5 runs converged (80%). Convergence pass varied: 6, 8, 14, 17. One run hit the 30-pass cap without converging. Despite this variance in path length, final word counts clustered tightly (1451–1660), suggesting the loop reaches a similar quality ceiling regardless of the path taken. The convergence threshold is a practical stopping rule, not a guarantee of optimality.

### 4.6 Constrained Tasks

We ran Task 1 with a constrained prompt (1000-word limit, 6 required sections with specific deliverables). The constraint eliminated word count oscillation entirely (all outputs 600–800 words vs 847–2500 unconstrained). However, it made convergence harder—B won 18 of 25 passes (72%) because specific constraints give the critic a verifiable checklist. The loop never converged in 25 passes.

This reveals that scope constraints and convergence are orthogonal problems. Constraints stabilize output length but enable more targeted critique.

## 5 Writing This Paper

We ran autoreason on this paper (Claude Opus 4, 3 Opus judges, ground-truth context for all roles). Converged in 9 passes.

**Ground-truth critic.** Without ground-truth access, the initial generation hallucinated a fabricated ablation study, fake confidence intervals, wrong model names, and incorrect role descriptions. With ground-truth access (actual experiment data), the critic caught all four on pass 1. This suggests a general pattern: the author writes from understanding, the critic verifies against evidence—mirroring peer review.

**Judge panel integrity.** An earlier run with a broken Gemini parser reduced the effective panel to 2 judges, preventing convergence for 11 passes. Once fixed to 3 working judges, the same incumbent converged in 2 passes. Panel integrity is a prerequisite for convergence.

## 6 Related Work

**Autoresearch** [1] uses val_bpb as an objective fitness function. Autoreason extends this to subjective domains. **SlopCodeBench** [2] shows iterative code degradation that prompting can't fix. **ACE** [3] documents context collapse in iterative rewriting. **LLM Council** [4] uses multi-model panels for single-turn evaluation; autoreason adds iteration with role separation.

## 7 Discussion

**Task-dependent advantage.** Autoreason is not universally superior. It excels where genuine tradeoffs exist between competing valid perspectives—strategy, policy, process design. For tasks with concrete, verifiable requirements, simpler methods can suffice. The recommendation: use autoreason when you don't know which framing will produce the best result; use critique-and-revise when the improvement direction is clear.

**Convergence as practical stopping rule.** The threshold does not guarantee optimality. It filters noise—a single stochastic judge panel can't cause premature stopping, and post-convergence passes on Task 1 produced no improvement (pass 15 beat pass 25, 6–1). But the Monte Carlo results show 20% non-convergence at 30 passes, meaning some runs need a cap.

**Bloat/prune oscillation** signals underdetermined scope. Constraining scope eliminates this but makes convergence harder by giving the critic concrete criteria to enforce.

**Ground-truth context** eliminates hallucination when reference material exists. The pattern generalizes beyond paper writing to any domain with source documents.

**Limitations.** All results from one model family (Anthropic). No human evaluation. No ablation studies isolating individual components. Judge accuracy within the loop is noisy per-pass.

## 8 Conclusion

Autoreason demonstrates that systematic isolation and blind evaluation can construct useful fitness functions for subjective domains. Across 5 tasks, it ranked first or second in every comparison. The method's advantage is clearest on tasks with genuine ambiguity—where the A/B/AB structure surfaces perspectives that a single revision loop cannot explore. The primary insight: the obstacle to LLM self-improvement in subjective domains is not capability but evaluation methodology.

## References


[1] A. Karpathy. Autoresearch, 2024.

[2] G. Orlanski et al. SlopCodeBench: Benchmarking how coding agents degrade over iterative tasks. *arXiv:2603.24755*, 2026.

[3] J. Zhang et al. ACE: Agentic context engineering. *ICLR*, 2026.

[4] A. Karpathy. LLM Council, 2025.

## A Trajectory Trees

Figure 6 shows trajectory trees for all experiments: 5 task types and 5 Monte Carlo runs. Vertical position represents cumulative drift from the initial version (B wins shift up 1 unit, AB shifts up 0.5, A stays flat). Unchosen alternatives shown as faded branches.




Figure 6: **All trajectories.** Tasks 2–3 converge quickly (10–12 passes). Task 5 requires 28 passes. Monte Carlo runs show variable convergence speed (6–30 passes) on the same task, with 1 of 5 failing to converge at the 30-pass cap.