Data Science Gallery 2

Justin Skycak

July 11, 2016

Previous Blueprint for Integrating my Prototype with Notebooks

ds-gallery/	
dslib/	network_plot.py save_to_gallery.py
assets/ images/	au-network.png
_includes/	image_list.html
_posts/	2016-06-27-au-network.markdown
scripts/	2016-06-27-au-dep-network.ipynb

> import library >

> import library >

> import library >

< save image <

< save image <

< save image <

au-network.png



< append to object list <

< append to object list <

{date: "2016-06-27",
name: "au-network",
image_ext: ".png",
tags: ["au", "network"]}

save file

2016-06-27-au-network.markdown

---
layout: post
image_ext: .png
code_ext: .ipynb

This is a network visualization of Aunsight dependencies

> manipulate args >

> import library >

> save script >

< manipulate args <

notebook

```
import dslib
load data

my_img = dslib.network_plot(data)

dslib.save_to_gallery(image = my_img,
                      image_ext = ".png",
                      name = "au-dep-network",
                      tags = ["au","network"],
                      description = "This is a network
                                     visualization of
                                     Aunsight
dependencies",
                      date = "2016-06-27" (implicit)
                      code_ext = ".ipynb" (implicit)   )
```

< import library <

< import library <

2016-06-27-au-dep-network.ipynb

```
import dslib
load data
my_img = dslib.network_plot(data)
dslib.save_to_gallery(image = my_img, image_ext = ".png",
name = "au-dep-network", tags = ["au","network"],
description = "This is a network visualization of Aunsight
dependencies")
```

< snapshot <

< snapshot <

GraphDash can do more, better, than my prototype.

GraphDash in Action

Setting Up GraphDash

```
$ git clone https://github.com/AmadeusITGroup/graphdash.git
$ cd graphdash
$ pip install --user
```

Add `export PATH = "~/.local/bin:$PATH"` to `~/.bash_profile`

```
$ GraphDash -c docs/graphdash.yaml
```

(make sure you're in `graphdash` directory)

Graphs and their metadata are stored in `default_graph_dir`

default_graph_dir/ ⟶ http://0.0.0.0:5555/

graph.svg



graph.png



data.csv

```
15/01/2014,0.2257,0.1149,0.6594
16/01/2014,0.2164,0.1272,0.6565
17/01/2014,0.2196,0.1232,0.6572
18/01/2014,0.2222,0.122,0.6558
```

graph.yaml

```
name: graph.svg
family: [category 1, subcategory]
title: '*Real serious* graph'
export: graph.png
file: data.csv
labels: new
index: keyword
text: |
        Title
        -----
        This is the *overall* data.

        ```bash
        $ some code
        ```

        ```python
        i = 0
        def f():
           return 2
        ```
```



default_graph_dir/ ⟶ http://0.0.0.0:5555/

graph.svg



graph.png



data.csv

```
15/01/2014,0.2257,0.1149,0.6594
16/01/2014,0.2164,0.1272,0.6565
17/01/2014,0.2196,0.1232,0.6572
18/01/2014,0.2222,0.122,0.6558
```

graph.yaml

```
name: graph.svg
family: [category 1, subcategory]
title: '*Real serious* graph'
export: graph.png
file: data.csv
labels: new
index: keyword
text: |
        Title
        -----
        This is the *overall* data.

        ```bash
        $ some code
        ```

        ```python
        i = 0
        def f():
           return 2
        ```
```



default_graph_dir/ ⟶ http://0.0.0.0:5555/

graph.svg



graph.png



data.csv

```
15/01/2014,0.2257,0.1149,0.6594
16/01/2014,0.2164,0.1272,0.6565
17/01/2014,0.2196,0.1232,0.6572
18/01/2014,0.2222,0.122,0.6558
```

graph.yaml

```
name: graph.svg
family: [category 1, subcategory]
title: '*Real serious* graph'
export: graph.png
file: data.csv
labels: new
index: keyword
text: |
        Title
        -----
        This is the *overall* data.

        ```bash
        $ some code
        ```

        ```python
        i = 0
        def f():
           return 2
        ```
```



default_graph_dir/ ⟶ http://0.0.0.0:5555/

graph.svg



graph.png



data.csv

```
15/01/2014,0.2257,0.1149,0.6594
16/01/2014,0.2164,0.1272,0.6565
17/01/2014,0.2196,0.1232,0.6572
18/01/2014,0.2222,0.122,0.6558
```

graph.yaml

```
name: graph.svg
family: [category 1, subcategory]
title: '*Real serious* graph'
export: graph.png
file: data.csv
labels: new
index: keyword
text: |
        Title
        -----
        This is the *overall* data.

        ```bash
        $ some code
        ```

        ```python
        i = 0
        def f():
           return 2
        ```
```





default_graph_dir/ ⟶ http://0.0.0.0:5555/

graph.svg



graph.png



data.csv

```
15/01/2014,0.2257,0.1149,0.6594
16/01/2014,0.2164,0.1272,0.6565
17/01/2014,0.2196,0.1232,0.6572
18/01/2014,0.2222,0.122,0.6558
```

graph.yaml

```
name: graph.svg
family: [category 1, subcategory]
title: '*Real serious* graph'
export: graph.png
file: data.csv
labels: new
index: keyword
text: |
        Title
        -----
        This is the *overall* data.

        ```bash
        $ some code
        ```

        ```python
        i = 0
        def f():
           return 2
        ```
```



default_graph_dir/ ⟶ http://0.0.0.0:5555/

graph.svg



graph.png



data.csv

```
15/01/2014,0.2257,0.1149,0.6594
16/01/2014,0.2164,0.1272,0.6565
17/01/2014,0.2196,0.1232,0.6572
18/01/2014,0.2222,0.122,0.6558
```

graph.yaml

```
name: graph.svg
family: [category 1, subcategory]
title: '*Real serious* graph'
export: graph.png
file: data.csv
labels: new
index: keyword
text: |
        Title
        -----
        This is the *overall* data.

        ```bash
        $ some code
        ```

        ```python
        i = 0
        def f():
           return 2
        ```
```



default_graph_dir/ ⟶ http://0.0.0.0:5555/

graph.svg



graph.png



data.csv

```
15/01/2014,0.2257,0.1149,0.6594
16/01/2014,0.2164,0.1272,0.6565
17/01/2014,0.2196,0.1232,0.6572
18/01/2014,0.2222,0.122,0.6558
```

graph.yaml

```
name: graph.svg
family: [category 1, subcategory]
title: '*Real serious* graph'
export: graph.png
file: data.csv
labels: new
index: keyword
text: |
        Title
        -----
        This is the *overall* data.

        ```bash
        $ some code
        ```

        ```python
        i = 0
        def f():
           return 2
        ```
```



default_graph_dir/ ⟶ http://0.0.0.0:5555/

graph.svg



graph.png



data.csv

```
15/01/2014,0.2257,0.1149,0.6594
16/01/2014,0.2164,0.1272,0.6565
17/01/2014,0.2196,0.1232,0.6572
18/01/2014,0.2222,0.122,0.6558
```

graph.yaml

```
name: graph.svg
family: [category 1, subcategory]
title: '*Real serious* graph'
export: graph.png
file: data.csv
labels: new
index: keyword
text: |
        Title
        -----
        This is the *overall* data.

        ```bash
        $ some code
        ```

        ```python
        i = 0
        def f():
           return 2
        ```
```



default_graph_dir/ ⟶ http://0.0.0.0:5555/

graph.svg



graph.png



data.csv

```
15/01/2014,0.2257,0.1149,0.6594
16/01/2014,0.2164,0.1272,0.6565
17/01/2014,0.2196,0.1232,0.6572
18/01/2014,0.2222,0.122,0.6558
```

graph.yaml

```
name: graph.svg
family: [category 1, subcategory]
title: '*Real serious* graph'
export: graph.png
file: data.csv
labels: new
index: keyword
text: |
        Title
        -----
        This is the *overall* data

        ```bash
        $ some code
        ```

        ```python
        i = 0
        def f():
           return 2
        ```
```



Site layout/structure can be modified

Webapp Configuration

docs/graphdash.yaml

```
root: ../default_graph_dir
title: "Example of title ;)"
subtitle: "Example of subtitle"
placeholder: "Free text and #keywords"
logfile: application.log
showfamilynumbers : true
showgraphnumbers: true
theme: light
keep: 0.20
raw: false
verbose: false
debug: false
port: 5555
footer : |
    ---------------------------------
    The footer
    ----------

    . . .
```







Next step: create function to upload graphs/metadata/code to GraphDash from notebook