(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property Organization International Bureau



(43) International Publication Date 5 February 2004 (05.02.2004)

PCT

(10) International Publication Number WO 2004/011050 A1

(51) International Patent Classification⁷: 27/42, C01B 25/32

A61L 27/12,

(21) International Application Number:

PCT/SG2003/000179

(22) International Filing Date:

30 July 2003 (30.07.2003)

(25) Filing Language:

English

(26) Publication Language:

English

(30) Priority Data: 60/399,938

30 July 2002 (30.07.2002) U


- (71) Applicant (for all designated States except US): NANYANG TECHNOLOGICAL UNIVERSITY [SG/SG]; c/o Innovation and Technology Transfer Office, Nanyang Ave., Singapore 639798 (SG).
- (72) Inventors: and
- (75) Inventors/Applicants (for US only): CHEANG HONG NING, Philip [SG/SG]; c/o Nanyang Technological University, Innovation and Technology Transfer Office, Nanyang Ave., Singapore 639798 (SG). RAJENDRA KUMAR S/O N KASINATH [SG/SG]; c/o Nanyang

Technological University, Innovation and Technology Transfer Office, Nanyang Ave., Singapore 639798 (SG). KHOR KHIAM, Alk [SG/SG]; c/o Nanyang Technology University, Innovation and Technology Transfer Office, Nanyang Ave., Singapore 639798 (SG).

- (74) Agent: ELLA CHEONG MIRANDAH & SPRUSONS LTD; Robinson Road Post Office, P.O.Box 1531, Singapore 903031 (SG).
- (81) Designated States (national): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.
- (84) Designated States (regional): ARIPO patent (GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PT, RO,

[Continued on next page]

(54) Title: SPHERICAL NANO-COMPOSITE POWDER AND A METHOD OF PREPARING THE SAME



(57) Abstract: The present invention provides a composition and method of producing nano-composite powder consisting essentially of hydroxyapatite(HA) and zirconium oxide (Zr02). The method comprises the steps of reacting orthophosphoric acid with calcium hydroxide to form a HA suspension, adding Zr02 suspension to the HA suspension to form a composite feedstock, and subjecting the composite feedstock to Radio Frequency (RF) Plasma Spraying to form the nano-composite powder. Quantity of the zirconium oxide suspension added is in the range of 10 to 40 weight % of the composite feedstock. The nano-composite powder comprises 60-90wt% calcium hydroxyapatite, 10-40wt% zirconium oxide and traces of calcium phosphate.

004/011050 A1 ||||||||||||

WO 2004/011050 A1

Published:

with international search report

SE, SI, SK, TR), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

1

SPHERICAL NANO-COMPOSITE POWDER AND A METHOD OF PREPARING THE SAME

FIELD OF INVENTION

The invention generally relates to a composition and method of producing nano-composite powders, in particular nano-composite calcium hydroxyapatite strengthened with zirconium oxide.

BACKGROUND

The study of biomaterials has seen immense growth over the last two decades. A new generation of bio-active materials has emerged promising better properties over existing biomaterials because of their ability to promote intimate bone growth and rapid fixation. In this respect hydroxyapatite (HA) has been recognised as a bioactive material having the potential for development as a bone substitute.

Biological compatibility of HA is strongly dependent on its crystallinity and phase content. Preventing decomposition of HA into more resorbable phases such as tricalcium phosphate (TCP), tetracalcium phosphate (TTCP) is therefore crucial in controlling the physiological stability of HA. A need thus exists to control the physiological stability of HA for this purpose.

HA is a very brittle ceramic with fracture toughness that is lower than 1MPam^{1/2} which prevents its use in loaded situations. As such its present application is limited to non-load bearing maxillo-facial implants and dental fillers. Therefore, a need exists to improve the mechanical properties (mainly fracture toughness) of HA.

SUMMARY

An aspect of the present invention is to provide a method of producing nano-composite powder consisting essentially of hydroxyapatite(HA) and zirconium oxide (ZrO₂) comprising the steps of reacting orthophosphoric acid with calcium hydroxide to form a HA suspension, adding ZrO₂ suspension to the HA suspension to form a composite feedstock, and subjecting the composite feedstock to Radio Frequency (RF) Plasma Spraying to form the nano-composite powder. Quantity of the zirconium oxide suspension added is in the range of 10 to 40 weight % of the composite feedstock.

Another aspect of the present invention is to provide a nano-composite powder comprising 60-90wt% calcium hydroxyapatite, 10-40wt% zirconium oxide and traces of calcium phosphate.

BRIEF DESCRIPTION OF DRAWINGS

These and other features, objects and advantages of embodiments of the invention will be better understood and readily apparent to one of ordinary skill in the art from the following written description, in conjunction with drawings, in which:

Figure 1 shows the variation of particle size of nano-composite powders as a function of quantity of zirconium oxide added.

Figure 2a shows a SEM micrograph of the general morphology of nano HA powder without ZrO₂ particles.

Figure 2b shows a SEM micrograph of the morphology of nano-composite ZrO₂/HA powder (40% ZrO₂/HA) with embedded spherical ZrO₂ particles. **Figure 2c** shows a SEM micrograph of the morphology of nano-composite ZrO₂/HA powder (40% ZrO₂/HA) with embedded irregular shaped ZrO₂ particles.

3

Figure 2d shows a SEM micrograph of the morphology of nano-composite ZrO₂/HA powder (40% ZrO₂/HA) with surface attached spherical ZrO₂ particles.

Figure 2e shows a SEM micrograph of the morphology of nano-composite ZrO₂/HA powder (40% ZrO₂/HA) with embedded cubic ZrO₂ particles. **Figure 2f** shows a SEM micrograph of the morphology of HA powder with cubic pores.

Figure 3 shows a TEM micrograph of ZrO₂/HA nano-composite powders-(40% ZrO₂/HA) before and after Radio Frequency Plasma Spraying.

Figure 4 shows X-ray diffraction pattern of the as-sprayed ZrO₂/HA nano-composite powders.

DETAILED DESCRIPTION

An embodiment of the invention is to provide a composition and method of manufacturing nano-composite hydroxyapatite (HA) powders which exhibits enhanced physiological stability and improved mechanical properties. In order to achieve this, zirconium oxide (ZrO₂) is added to the hydroxyapatite to form nano-composite ZrO₂/HA powders.

Calcium Hydroxyapatite, commonly known as Hydroxyapatite (HA), is produced in-house using wet chemical approach by reacting orthophosphoric acid (H₃PO₄) with calcium hydroxide (Ca(OH)₂). This results in a formation of calcium hydroxyapatite suspended in water. The HA suspension is stirred for two hours and left to settle overnight. Thickening of gelatinous HA precipitate in water is achieved by centrifugation. Monoclinic ZrO₂ suspension (of particle size < 100 nm) is then added to the HA suspension to produce a composite feedstock. Samples of composite feedstock with varying quantities of ZrO₂ suspension and HA suspension in the following quantities, 10/90, 20/80, 30/70 and 40/60 wt% ZrO₂/HA are produced.

The suspension is then fed axially into an induction plasma by a special atomisation probe. Atomisation parameters (suspension flow rate, gas flow rate and angle of atomisation) were adjusted for optimum flow as shown in Table 1.

Table 1: Parameters used for atomising the suspension feedstock.

| Atomisation parameters | Settings |
|----------------------------------|----------|
| Atomising gas (slpm) | 4-5 |
| Angle of atomisation | 90-100° |
| HA suspension flow rate (g/min) | 6 |
| Solid content of suspension(wt%) | 13 |

The same parameters were maintained throughout the investigation. Plasma spraying was carried out on a 35-kW, Tekna Plasma System Inc., with RF plasma torch (PL-35) operating at 3 MHz. Argon is used for both the plasma forming gas and atomisation gas. Spraying parameters are summarised in Table 2.

Table 2 Parameters used for RF plasma spraying

| RF plasma parameters | Settings |
|---------------------------------|----------|
| Plate power (kW) | 12.5 |
| Chamber pressure (kPa) | 53.2 |
| Probe position (cm) | 3.5 |
| Ar central gas flow rate (slpm) | 20 |
| Ar sheath gas flow rate (slpm) | 50 |

The average particle size variation of the as-sprayed nano-composite ZrO₂/HA powders with increasing ZrO₂ in the feedstock is shown in Figure 1.

The morphology of the as-sprayed nano-composite ZrO₂/HA powders is shown in Figure 2 (SEM and FEM) and that of medium and large particle sized powders in Figure 3 (SEM).

Nano-composite HA/ZrO₂ powders of the present invention consists essentially of a mixture of HA/calcium phosphate(CaPO₄) particles and HA/CaPO₄/ZrO₂ composite particles. The powders comprises two kinds of particle size distributions: particle sizes in the range 1-3μm, and particle sizes smaller than 200nm for the nano-composite powders. Four different morphologies for the HA/CaPO₄/ZrO₂ composite particles were present:

- 1. Embedded islands of secondary particles (Figures 2c and 2e),
- 2. Embedded nano-sized secondary particles (Figure 2b),
- 3. Surface attached secondary particles (Figure 2d) and
- 4. HA particles with nano-pores (Figure 2f), the pores originating from ejected secondary particles once part of the original HA sphere (Figure 2e).

The morphology seen in Figure 2b is predominant in the composite powders of the present invention (~70%) as compared to that in Figure 2c. The morphology of the medium sized composite powders is similar to that of the nano-composite powders except for the size difference. The large particle sized powders showed similar amount of secondary nano 'alloyed' particles. One clear feature of the composite powders, regardless of size is the high level of dispersion of the secondary particles, seemingly well spaced out. This indicates that a similar sort of dispersion could have been present in the feedstock due to the surface chemistry of the ZrO₂ and HA particles in suspension.

The final morphology of the powders is also due to the thermal history of the particles in the plasma. In the plasma, the liquid in the atomised droplets containing HA and ZrO₂ would have first undergone flash evaporation. Following this the somewhat consolidated particle would have melted and spherodised to

varying degrees trapping whatever secondary particles present in them. As the particles leave the plasma they would have rapidly cooled producing HA with varying amounts of embedded secondary particles.

The as-sprayed nano-composite powders is then sintered by Spark Plasma Sintering (SPS). After polishing, the hardness and fracture toughness were calculated from micro-indentation techniques. The values were then compared to that of HA powders (\sim 10 μ m) sintered conventionally and ultra-fine HA powders sintered by SPS. The Young's Modulus, fracture toughness and micro-hardness values of the various compacts are shown comparatively in Table 3.

Table 3 Mechanical properties of the as-sintered compacts.

| Powder type | Young's Modulus (GPa) | Fracture Toughness (MPam ^{1/2}) | Hardness |
|--|--------------------------|---|--------------|
| Conventionally sintered powders (at 1100°C) * | 87±4 [8] | 0.77±0.12 [8] | 508±40HV [9] |
| RFSPS ultra-fine Powders (HA+CaPO ₄) | 103 ±9 | 1.17±0.11 | 5.7±0.3GPa |
| RFSPS ultra-fine powders (HA+CaPO ₄ +ZrO ₂) | 130±6 | 1.60±0.21 | 5.5±0.5GPa |
| Medium (HA+CAP+ZrO₂) | 106±4 | 1.41±0.11 | 5.2±0.2GPa |

^{*} Values are for conventionally sintered powders by other researchers.

WO 2004/011050 PCT/SG2003/000179

7

The results indicate that the compacts with ZrO₂ had higher Young's Modulus, fracture toughness and hardness than the one without. Fracture toughness of the compacts sintered from the ultra-fine powders is about 1.60MPam^{1/2} and for the medium sized powders is about 1.41MPam^{1/2}. The sintered composite compacts were also annealed to see the effect of heat treatment on the mechanical property changes. These changes to the mechanical properties are rather substantial considering the minimal loading of ZrO₂ (~1vol%).

It has been shown that ultra-fine/nano-composite powders of ZrO₂/HA can be produced using the Radio Frequency Suspension Plasma Spraying Technique (RFSPS). The various morphologies of the powders indicated that nano-sized ZrO₂ particles existed both within and as surface-attachments on HA particles. QPA indicated that HA and ZrO₂ reacted in the plasma, giving rise to partially stabilised zirconia (PSZ) and CaZrO₃ (CAZ). Also, ZrO₂ content did not change appreciably after 20wt% ZrO₂ in the feedstock. DSC also showed a small amount of amorphous calcium phosphate in the as-sprayed powders. The experiment confirmed that nano-composite powders of HA/ZrO₂ with controlled composition can be produced using the RF suspension plasma spraying technique. The nano-ZrO₂ present in the powders was partially stabilised in-situ, in the presence of CaO from HA, during the plasma spraying process.

The mechanical properties of the compacts sintered from the HA/ZrO₂ nano-composite powders were substantially higher those without considering the low volume loading of ZrO₂ in the powders. As such it is possible that even further additions of ZrO₂ in the powders during suspension plasma spraying will give rise to higher volume loading with subsequent increases in the mechanical properties of sintered compacts.

WO 2004/011050 PCT/SG2003/000179

8

CLAIMS

- A method of producing nano-composite powder consisting essentially of hydroxyapatite(HA) and zirconium oxide (ZrO₂) comprising the steps of: reacting orthophosphoric acid with calcium hydroxide to form a HA suspension; adding zirconium suspension to the HA suspension to form a composite feedstock; subjecting the composite feedstock to Radio Frequency (RF) Plasma Spraying to form the nano-composite powder.
- 2. The method according to claim 1, wherein the quantity of zirconium oxide suspension added is in the range of 10 to 40 weight %.
- 3. A nano-composite powder comprising:
 60-90wt% calcium hydroxyapatite;
 10-40wt% zirconium oxide; and
 traces of calcium phosphate.




Figure 1




Figure 2a




Figure 2b



Figure 2c




Figure 2d




Figure 2e




Figure 2f

PCT/SG2003/000179





Figure 3



Substitute Sheet

INTERNATIONAL SEARCH REPORT

International application No.

PCT/SG03/00179

| Y JP 07-008550 A (KONDO M), 13 J X, Y Whole document (automatic transla Paragraphs [0007], [0015], [0019], WO 90/11979 A (STIFTELSEN CE | lowed by 35/00 - 3 n to the ex h (name of | classification symbols) 35/49, A61K 6/00 - 7/34 In that such documents are included in the fields search of data base and, where practicable, search terms used) | hed | |
|--|--|---|--------------------------------|--|
| According to International Patent Classification (IPC) of B. FIELDS SEARCHED Minimum documentation searched (classification system foll A61L 27/00 - 27/42, C01B 25/00 - 25/32, C04B 3 Documentation searched other than minimum documentation Electronic data base consulted during the international search WPAT, JAPIO, CAPLUS, IPC (above) and/or Ke C. DOCUMENTS CONSIDERED TO BE RE Category* Citation of document, with indication, vice and property of the patent Abstracts of Japan, JP 05-032526 A (SEKISUI PLAST) Y Y IP 07-008550 A (KONDO M), 13 J WO 90/11979 A (STIFTELSEN CEBIOMATERIAL I HUDDINGE), 18 | lowed by 35/00 - 3 n to the ex h (name of | classification symbols) 35/49, A61K 6/00 - 7/34 In that such documents are included in the fields search of data base and, where practicable, search terms used) | hed | |
| Minimum documentation searched (classification system foll A61L 27/00 - 27/42, C01B 25/00 - 25/32, C04B 3 Documentation searched other than minimum documentation electronic data base consulted during the international search WPAT, JAPIO, CAPLUS, IPC (above) and/or Ke C. DOCUMENTS CONSIDERED TO BE RE Category* Citation of document, with indication, was a consulted during the international search wpat, JAPIO, CAPLUS, IPC (above) and/or Ke C. DOCUMENTS CONSIDERED TO BE RE X, Y Patent Abstracts of Japan, JP 05-032526 A (SEKISUI PLAST) Y JP 07-008550 A (KONDO M), 13 J Whole document (automatic translated paragraphs [0007], [0015], [0019], WO 90/11979 A (STIFTELSEN CEBIOMATERIAL I HUDDINGE), 18 | lowed by 35/00 - 3 n to the ex h (name of cywords | classification symbols) 35/49, A61K 6/00 - 7/34 In that such documents are included in the fields search of data base and, where practicable, search terms used) | hed | |
| Minimum documentation searched (classification system folional A61L 27/00 - 27/42, C01B 25/00 - 25/32, C04B 3 Documentation searched other than minimum documentation searched other than minimum documentation searched during the international search WPAT, JAPIO, CAPLUS, IPC (above) and/or Kerner Company and/or Kerner Category* Citation of document, with indication, with indication indication, with indication indication, with i | 35/00 - 3 n to the ex h (name of eywords | 35/49, A61K 6/00 - 7/34 Extent that such documents are included in the fields search of data base and, where practicable, search terms used) | hed | |
| A61L 27/00 - 27/42, C01B 25/00 - 25/32, C04B 3 Documentation searched other than minimum documentation Electronic data base consulted during the international search WPAT, JAPIO, CAPLUS, IPC (above) and/or Ke C. DOCUMENTS CONSIDERED TO BE RE Category* Citation of document, with indication, v Patent Abstracts of Japan, JP 05-032526 A (SEKISUI PLAST) Y JP 07-008550 A (KONDO M), 13 J Whole document (automatic transla Paragraphs [0007], [0015], [0019], WO 90/11979 A (STIFTELSEN CE BIOMATERIAL I HUDDINGE), 13 | 35/00 - 3 n to the ex h (name of eywords | 35/49, A61K 6/00 - 7/34 Extent that such documents are included in the fields search of data base and, where practicable, search terms used) | hed | |
| Electronic data base consulted during the international search WPAT, JAPIO, CAPLUS, IPC (above) and/or Ket. C. DOCUMENTS CONSIDERED TO BE RECEATED TO BE RE | h (name o cywords ELEVAN | of data base and, where practicable, search terms used) | hed | |
| WPAT, JAPIO, CAPLUS, IPC (above) and/or Ke C. DOCUMENTS CONSIDERED TO BE RE Category* Citation of document, with indication, v Patent Abstracts of Japan, JP 05-032526 A (SEKISUI PLAST) Y JP 07-008550 A (KONDO M), 13 J Whole document (automatic transla Paragraphs [0007], [0015], [0019], WO 90/11979 A (STIFTELSEN CE BIOMATERIAL I HUDDINGE), 13 | eywords ELEVAN | 3 | | |
| Category* Citation of document, with indication, with in | | T | | |
| Patent Abstracts of Japan, JP 05-032526 A (SEKISUI PLAST) Y JP 07-008550 A (KONDO M), 13 J X, Y Whole document (automatic transla Paragraphs [0007], [0015], [0019], WO 90/11979 A (STIFTELSEN CE BIOMATERIAL I HUDDINGE), 13 | where ap | , - | | |
| X, Y Y JP 05-032526 A (SEKISUI PLAST) JP 07-008550 A (KONDO M), 13 J Whole document (automatic transla Paragraphs [0007], [0015], [0019], WO 90/11979 A (STIFTELSEN CE BIOMATERIAL I HUDDINGE), 13 | | opropriate, of the relevant passages | Relevant to claim No. | |
| X, Y Whole document (automatic transla Paragraphs [0007], [0015], [0019], WO 90/11979 A (STIFTELSEN CE BIOMATERIAL I HUDDINGE), 13 | JP 05-032526 A (SEKISUI PLASTICS Co. Ltd.), 9 February 1993 | | | |
| BIOMATERIAL I HUDDINGE), 18 | JP 07-008550 A (KONDO M), 13 January 1995 Whole document (automatic translated version) Paragraphs [0007], [0015], [0019], [0029], [0043] 1-2 | | | |
| - 1-26 c (200) Page 10 (220) | WO 90/11979 A (STIFTELSEN CENTRUM FOR DENTALTEKNIK OCH BIOMATERIAL I HUDDINGE), 18 October 1990 Page 6 (L35) - page 10 (L25) | | | |
| X Further documents are listed in the con | | | | |
| * Special categories of cited documents: "A" document defining the general state of the art which is not considered to be of particular relevance "B" earlier application or patent but published on or after the international filing date "T" later document published after the international filing date or priorit and not in conflict with the application but cited to understand the p or theory underlying the invention "X" document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive st | | | rstand the principle cannot be | |
| when the document is taken alone "L" document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified) when the document is taken alone document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combi with one or more other such documents, such combination being ob | | | cannot be ent is combined | |
| "O" document referring to an oral disclosure, use, "&" document member of the same patent family exhibition or other means "P" document published prior to the international filing date but later than the priority date claimed | | | | |
| Date of the actual completion of the international search 28 August 2003 Date of mailing of the international search report - 2 SEP 2003 | | | | |
| Name and mailing address of the ISA/AU | | Authorized officer | | |
| AUSTRALIAN PATENT OFFICB PO BOX 200, WODEN ACT 2606, AUSTRALIA E-mail address: pct@ipaustralia.gov.au Facsimile No. (02) 6285 3929 JAMES DZIEDZIC Telephone No : (02) 6283 2495 | | | | |

INTERNATIONAL SEARCH REPORT

International application No.
PCT/SG03/00179

| C (Continua | | <u> </u> |
|-------------|--|-----------------------|
| Category* | Citation of document, with indication, where appropriate, of the relevant passages | Relevant to claim No. |
| х . | GB 2354519 A (DYTECH CORPORATION LTD), 28 March 2001 Page 4, page 9 (paragraph 2) | 3 |
| X | Patent Abstracts of Japan, JP 03-037071 A (JGC CORPORATION), 18 February 1991 | 3 |
| . X | US 2002/0041854 A (HADASCH et al), 11 April 2002 Page 2 ([0027]-[0028] and [0030]-[0031]) | 3 |
| | , | - |
| | | |
| | | |
| | | |
| | | |
| | | |
| | | |
| | | |
| | | |
| | | |
| <u> </u> | | |

INTERNATIONAL SEARCH REPORT

Information on patent family members

International application No. PCT/SG03/00179

This Annex lists the known "A" publication level patent family members relating to the patent documents cited in the above-mentioned international search report. The Australian Patent Office is in no way liable for these particulars which are merely given for the purpose of information.

| | nt Document Cited in Search Report | Patent Family Member | | | | | |
|----|---------------------------------------|----------------------|------------|----|---------|-------------|--|
| US | 2002041854 | CN | 1331967 | FR | 2808999 | ĴР | 2002020236 |
| | | | | EP | 1155676 | | |
| JР | 5032526 | JР | 2839758 B2 | | • | | • |
| JР | 7008550 | NONE | | | | | |
| JP | 3037071 | NONE | | | | | ······································ |
| wo | 9011979 | AU | 55287/90 | EP | 467948 | HK | 1280/96 |
| | | SE | 8901294 | US | 5306673 | _ | • |
| GB | 2354519 | · AU | 45639/97 | EP | 958261 | GB | 2317887 |
| | | wo | 9815505 | GB | 2354518 | | |
| | | | 6 | | | | |
| | | | | | | | END OF ANNEX |

This Page is Inserted by IFW Indexing and Scanning Operations and is not part of the Official Record

BEST AVAILABLE IMAGES

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images include but are not limited to the items checked:

| BLACK BORDERS |
|---|
| ☐ IMAGE CUT OFF AT TOP, BOTTOM OR SIDES |
| ☐ FADED TEXT OR DRAWING |
| ☐ BLURRED OR ILLEGIBLE TEXT OR DRAWING |
| ☐ SKEWED/SLANTED IMAGES |
| ☐ COLOR OR BLACK AND WHITE PHOTOGRAPHS |
| ☐ GRAY SCALE DOCUMENTS |
| ☐ LINES OR MARKS ON ORIGINAL DOCUMENT |
| REFERENCE(S) OR EXHIBIT(S) SUBMITTED ARE POOR QUALITY |
| OTHER: |

IMAGES ARE BEST AVAILABLE COPY.

As rescanning these documents will not correct the image problems checked, please do not report these problems to the IFW Image Problem Mailbox.