CS₂₁₇ (2010-2011)

COMPUTER GRAPHICS 1: IMAGE PROCESSING AND SYNTHESIS

(Attempt 2 questions out of 3)

Question 1

(a) Error Diffusion Dithering

This is a grey-level image containing pixel values between 0 and 255.

120	200	200	180	150
160	180	190	170	160

- (i) What would be the results after *thresholding* to display on a bi-level device? [2 marks]
- (ii) Calculate the total and average error between the image and the thresholded image. [2 marks]
- (iii) Demonstrate standard error-diffusion on the image. [3 marks]
- (iv) Calculate the total and average error between the image and the error-diffusion image. [2 marks]
- (v) How does standard error-diffusion process retain error in the local area? [1 marks]
- (vi) Why is error-diffusion used, and in general what do the images that have this technique applied, look like? [2 marks]
- (vii) What is the Floyd-Steinberg method?

[2 marks]

[Practical application of theory]

(i) Thresholding becomes:

0	1	1	1	1
1	1	1	1	1

[2 marks]

(ii) Original total = 1710. Bi-level image = $9 \times 255 = 2295$. Error=585 too bright. Average=58.5 too bright.

[2 marks]

(iii) Error

120	65	10	-65	85
-75	20	95	-95	-10

Pixels+error

Results

[3 marks]

120	320	265	190	85
180	275	95	160	245

0	255	255	255	0
255	255	0	255	255

(iv) New dither = $7 \times 255 = 1785$. Error=75 too bright. Average=7.5 too bright.

[2 marks]

(v) It passes the error to the next undrawn pixel and down to the pixel directly below when at the end of the row.

[1 marks]

(vi) Its used to persuade the viewer that there is higher dynamic range by introducing noise. Close up we see dots of a different colour in what would otherwise have been single colour regions

[2 marks]

Floyd Steinberg passes error to 4 undrawn pixels. Error is retained in local area by passing error to neighbourhood, and pixel below at image edges.

[2 marks]

Part a subtotal=[14 marks]

(b) Maximum Intensity Projection

- (i) Describe the data for which the Maximum Intensity Projection (MIP) algorithm is useful. [2 marks]
- (ii) Describe the MIP algorithm (you can also give pseudo-code).

[3 marks]

(iii) Why is the MIP algorithm so useful?

[2 marks]

[Understanding of (very) advanced topics]

- (i) Volume data 3D array of data resulting from MR/CT scanners. [2 marks]
- (ii) For each pixel, trace a ray through the volume data set taking samples. Find the max sample along the ray, and use its value to colour the pixel according to a map function. [3 marks]
- (iii) Gives a 3D X-ray like view of the data. Useful for doctors as they already know how to interpret X-rays. [2 marks]

Part **b** subtotal=[7 marks]

(c) Images in Java

How are images stored internally? Give some example code that loops through every pixel of an image. How much memory does an image occupy?

[4 marks]

Images in Java

A 3D array (or a 2D array of RGB triples). Each of RGB is a single byte - giving values between 0–255. The memory is width \times height \times 3.

e.g. gamma correction code (but only the 3 loops+the array assignment is needed).

```
for (j=0; j<height; j++)
for (i=0; i<width; i++)</pre>
```

[4 marks]

Question 1 total=[25 marks]

Threshold: (a) 8 marks (should get i, iii, vii largely right and some answer for the rest), (b) 4 marks, (c) 2 marks: Total=14 marks

Question 2

(a) Cross Correlation

(i) Given a 3x3 sub-image of pixels:

$$I_{ij} = \left[\begin{array}{c} p_{11} \ p_{12} \ p_{13} \\ p_{21} \ p_{22} \ p_{23} \\ p_{31} \ p_{32} \ p_{33} \end{array} \right]$$

and a 3×3 filter kernel:

$$M_{ij} = \left[\begin{array}{c} m_{11} \ m_{12} \ m_{13} \\ m_{21} \ m_{22} \ m_{23} \\ m_{31} \ m_{32} \ m_{33} \end{array} \right]$$

what is the equation for calculating the new intermediate value at pixel p_{22} ? [2 marks]

(ii) Given the following 5×5 image (grey-level 0-255 image):

and 3x3 filter kernel:

1	3	1
3	9	3
1	3	1

give the intermediate values for all possible pixels when applying the filter kernel to the image using the process of cross correlation. [3 marks]

- (iii) What choices could be made at the pixels the filter cannot be operated on. [2 marks]
- (iv) What are the maximum and minimum intermediate values. [1 marks]
- (v) Give the normalisation equation. [1 marks]
- (vi) Use the normalisation equation to create the final pixel values. [2 marks]
- (vii) What differences occur when a 4×4 filter is used, and when a 5×5 filter is used? [2 marks]
- (viii) What difference is made when a colour image needs to be cross correlated? [1 marks]
- (ix) Name some applications of cross correlation. What is a hi-pass filter and what is a low-pass filter and when should they be used? Identify the filter given in the question. [3 marks]

 $[Bookwork,\,understanding,\,practical\,\,application\,\,of\,\,topic]$

(i)

$$p_{22} = \sum_{i=1}^{3} \sum_{i=1}^{3} p_{ij} m_{ij}$$

[2 marks]

	*	*	*	*	*
	*	2770	3120	3470	*
(ii)	*	3230	3630	3830	*
	*	3710	4110	4260	*
	*	*	*	*	*

[3 marks]

- (iii) *=could not be applied. Could reduce size of image, make black, keep old colour, use nearest known neighbour's colour, use smaller filters at the image edges. [2 marks]
- (iv) max=4260, min=2770. [1 marks]
- (v) Normalisation equation $P = (I min) \times \frac{255}{(max min)}$ [1 marks]
- (vi) In this case:

$$P = (I - 2270) \times \frac{255}{(4260 - 2770)}$$
 Gives

*	*	*	*	*
*	0	59.9	119.8	*
*	78.7	147.2	181.4	*
*	160.9	229.3	255.	*
*	*	*	*	*

[2 marks]

- (vii) $A\ 4 \times 4$ will have an extra row and column unknown on the top and one side (or bottom and one side). $A\ 5 \times 5$ will have 2 rows unknown all the way round.
 - Also, increasing the size of the filter will result in the need for more calculation. [2 marks]
- (viii) A colour image will require the above operation to be carried out for each colour channel. The min and max are for all colour channels, and not each individually. [I marks]
- (ix) Applications medical imaging and astronomy (low-pass to remove noise). Object recognition, facial recognition (hi-pass to enhance edges).

This filter is an edge detector. [3 marks]

Part a subtotal=[21 marks]

(b) Histogram

- (i) How is a histogram computed for an image and what does it represent? [2 marks]
- (ii) What effect does uniformly brightening or darkening an image have on the histogram? [2 marks]
- (iii) What is the cumulative distribution function?

[2 marks]

(iv) Describe the procedure for *histogram equalisation* and indicate the situation when it should be used and the effect it produces. [2 marks]

[Understanding first part, application second part]

- (i) Created by counting the number of pixels at each intensity level, and represents the distribution of intensity throughout the image. Could also give some lines of code, but not required. [2 marks]
- (ii) Brighter, histogram gathers to right. Dimmer, histogram gathers to left. [2 marks]
- (iii) t(f) = The total amount of pixels that have a value up to and including f. [2 marks]
- (iv) Histogram equalisation is used to increase contrast by distributing the available intensity levels better throughout the image. The CDF is used to create a mapping from original values to new values.

[2 marks]

Part **b** subtotal=[8 marks]

Question 2 total=[25 marks]

Threshold: (a) 8 marks (should get i, ii, iii, ix largely right), (b) 5 (should get i, ii correct, and describe the effect in iv) = 13 total

Question 3

(a) Object Representation

Define each of the following terms, also giving their advantages/disadvantages:

(i) Triangle list [2 marks]

(ii) Triangle strip [2 marks]

(iii) Pointers to vertex list [2 marks]

(iv) Implicit representation [2 marks]

- (i) For each triangle store 3 x 3D points representing the spatial location of each vertex. [2 marks]
- (ii) For n triangles, store n+2 points so that the points k, k+1, k+2 give the kth triangle. k takes all values between 1 and n. [2 marks]
- (iii) Store a list of 3D points. For each triangle, store the 3 pointers to the vertices that make it. [2 marks]
- (iv) An object is described using an equation. [2 marks]

Part a subtotal=[8 marks]

(b) Bounding Volumes for Ray Tracing

- (i) Explain, with an example scene, why ray tracing can be computationally expensive. (You should include some example calculations). [2 marks]
- (ii) How can bounding volumes lead to better computational times? (Again use your example to demonstrate by showing some calculations). [2 marks]
- (iii) Discuss a hierarchy of bounding volumes constructed manually. [2 marks]
- (iv) How does an automatic hierarchical acceleration structure such as a kd-tree or an octree operate? How does it accelerate ray-tracing? [4 marks]

Ray Tracing

- (i) View plane rays passing through centre of projection (perspective model) or in parallel (orthographic)
- (ii) Primary rays hitting a surface, then reflecting as secondary rays.
- (iii) Primary rays hitting a surface, then refracting through a transparent object.
- (iv) Primary rays hitting a surface, then secondary rays being used to determine light visibility (shadow)
- (v) Recursive ray tracing: secondary rays can interact just like primary (i.e. further reflection and refraction)
- (vi) Derive ray/sphere intersection equation by substituting the equation of a ray in the equation of sphere.

[10 marks]

Part **b** subtotal=[10 marks]

(c) **Descriptions**

Write descriptions (about $\frac{1}{2}$ page) about **two** of the following six topics:

Illumination (ambient, diffuse/Lambertian, specular);

Gamma correction;

Adaptive supersampling;

Linear and bilinear interpolation.

Jittered sampling, random/stochastic sampling and Poisson disk sampling.

Nyquist rate, quantization and sampling for discrete images.

[7 marks]

Descriptions

Illumination (ambient, diffuse/Lambertian, specular): Give the simple rendering equation. Talk about light colour and object colour. Talk about the angle, surface normal and angle of incidence. Gamma correction: Raise pixel to the power of gamma. Allows non-linear variation of image brightness. Adapts to log sensitivity of eye.

Adaptive supersampling: Sample once per pixel corner. Where these differ by more than predefined threshold, take more samples at sub-pixels, and continue as a recursive algorithm.

Linear and bilinear interpolation: Define equation for linear interpolation. Demonstrate this applied to 2D using bilinear interpolation. Maybe mention use for image resizing.

Jittered sampling, random/stochastic sampling and Poisson disk sampling: Jittered - one sample per sub-pixel, but randomly offset from centre (but still in sub-pixel, fast to compute). Random - random samples over pixel (could lead to undersampled areas, fast to compute). Poisson-disk - best kind of sampling, but O(logn) to generate each sample (other methods O(1).

Nyquist rate, quantization and sampling for discrete images: Sampling frequency (2f) needed to reconstruct a signal of frequency f. Sample at a finite number of positions along signal (e.g. regular sampling for digitising images). Quantization of signal to available bit resolution.

[7 marks]

Part c subtotal=[7 marks]

Question 3 total=[25 marks]

Threshold: (a) 5 should get something on the first 3, (b) 4 should get the concepts of bounding volumes and expense of intersections across, (c) 4 should be able to chose something they are good at = 13 total