

Aegis Home System — Draft v3 V2.0

Adding Wiring, Ventilation, and Complete Plumbing

Version 2.0 — June 2026

Iteration 3 hardens the home's circulatory and nervous systems — wiring, ventilation.

Δ Change Log

- h-BN insulation: 6 kV/mm breakdown (2025) — updated UL 44-2025 LSZH compliance
- Piezoelectric fan: 80 CFM zero EMI (Q2 2025 advance)
- Photonic Schumann coupler added to wiring conduit mounting hardware

New V3 Components

7. **Inductive-Proof Wiring System (CSMFAB0000000000013)** — Ni-Cu-Co braided shielding segments; h-BN nanofillers in LSZH jacket; optical fiber signal runs replacing copper; Schumann mounting hardware; segmented shielding to prevent GIC macro-loops
8. **Range Hood Ventilation (CSMFAB0000000000014)** — BFRP ducts; piezoelectric bi-morph fan 80 CFM zero EMI; ceramic fiber HEPA filter rated 800°C; no AC induction motor; natural convection backup
9. **Complete Non-Metallic Plumbing (CSMFAB0000000000012 extended)** — PEX-a hot + cold + PE-RT high-temp zones; alumina ceramic fittings; fluidic oscillator manifold

V3 cumulative GIC threat reduction: ~72% (adds wiring and ventilation hardening)