

CSMFAB000000000102

In-Flight Wind Harvesting and Hybrid Propulsion: Redesigning a 450mm UAV with Dual-Regime Archimedes Spiral Rotors

Structural Architecture and Frame Sizing for the Redesigned 450mm Drone

To establish a physically viable platform for a shoulder-width drone, the structural architecture must align with standard aerospace design classifications for small unmanned aerial vehicles (UAVs). A shoulder-width dimension corresponds directly to a standard 450 mm wheelbase, defined as the diagonal distance between opposite motor centers in a square configuration.¹ Traditional multirotors within this class are engineered around flat or slightly twisted two-dimensional propeller blades.² Transitioning this class of vehicle to utilize three-dimensional helical or Archimedes screw rotors requires a complete re-engineering of the structural frame, material composition, and weight distribution.⁵

A conventional 450 mm frame utilizing glass-fiber-reinforced nylon (GF30) typically weighs between 265 g and 285 g.¹ However, three-dimensional helical screws exhibit a significantly larger physical volume, continuous surface area, and rotational inertia compared to standard props.⁵ This spatial expansion introduces massive mechanical stresses, torsional bending, and gyroscopic coupling at the motor mounts and arm joints during high-speed rotation and yaw maneuvers.⁵ Glass-fiber nylon frames lack the structural rigidity required to suppress these high-frequency vibrations, which leads to sensor saturation in the onboard inertial measurement unit (IMU) and subsequent flight controller destabilization.³

Consequently, the redesigned 450 mm frame must utilize a high-modulus, 3K woven carbon fiber laminate.¹ Carbon fiber reduces the baseline frame weight to approximately 220 g while increasing the tensile strength to a range of 350–420 MPa.¹ This weight savings is critical to offset the physical mass of the helical rotor assemblies.¹

Structural Material	Tensile Strength	Impact Resistance	Vibration Damping	Cost Range	Weight (g)
---------------------	------------------	-------------------	-------------------	------------	------------

	(MPa)			(USD)	
Glass-Fiber Nylon (GF30)	120–140 ¹	High (absorbs crash energy) ¹	Moderate ¹	\$12--\$22 ¹	≈ ¹
Pure Carbon Fiber (3K)	350–420 ¹	Moderate (brittle fracture) ¹	High (attenuates harmonics) ¹	\$35--\$65 ¹	≈ ¹
Hybrid (CF Core + Nylon)	210–260 ¹	Extremely High ¹	High ¹	\$28--\$45 ¹	≈ ¹

The physical integration of Archimedes-style rotors alters the vehicle's center of mass and aerodynamic balance.¹¹ To prevent the instability issues that plagued early historical single-screw concepts, the redesigned carbon fiber frame must feature an integrated power distribution board (PDB) to minimize loose wiring and underslung motor mounts.¹ Positioning the motors upside down (pointing downward) aligns the rotor's aerodynamic center of pressure closer to the vehicle's central plane of symmetry, which reduces the disturbance torques induced by lateral wind gusts.¹¹

Design Parameter	Standard F450 Multirotor	Redesigned Helical-Airscrew Drone
Wheelbase (Diagonal)	450 mm ¹	450 mm ¹
Frame Material	Glass-Fiber Nylon (GF30) ¹	3K Woven Carbon Fiber ¹
Rotor Configuration	Standard 2D 1045 Propellers ²	Double-Helix Tapered Airscrews ⁶
Rotor Diameter	10 inches (254 mm) ²	8 inches (203 mm) ⁶
Motor Stator Size	2212 / 2216 Series ²	2807 / 3115 High-Torque Series ³

Battery Platform	3S to 4S LiPo ²	6S Li-Ion / LiPo ³
Typical Net Weight	≈ ₂ (without battery)	≈ (without battery) ³

Aerodynamic Principles of the Helical Airscrew Propulsor

The conceptual origins of the helical propulsor trace back to Leonardo da Vinci’s late 1480s "aerial screw" drawings, which proposed utilizing a continuous starch-sealed linen sail wrapped around a central shaft to compress air and generate vertical lift.¹⁴ While historical execution was prevented by the absence of lightweight materials and high-power-density engines, modern computational fluid dynamics (CFD) and experimental test platforms—such as the University of Maryland’s "Crimson Spin" UAV—have validated the underlying physics.⁶

Unlike conventional curved airfoils that generate lift primarily through two-dimensional Bernoulli pressure differentials across the upper and lower surfaces, the helical airscrew operates via a highly three-dimensional vortex flow regime.⁶ The continuous spiral geometry of the screw generates a prominent bound-tip vortex that runs along the outer edge of the helical surface.⁶ This bound-tip vortex creates a localized, ultra-low-pressure core immediately above the upper surface of the spiral blade.⁶ At the same time, the underside of the continuous blade compresses the incoming air flow, generating a high-pressure zone.⁶ Rather than relying on a high-velocity downward downwash of air to produce momentum thrust, the helical airscrew generates upward force primarily through the pressure differential induced by this bound-tip vortex, mimicking the aerodynamic lift generation of delta-wing configurations on supersonic aircraft.⁶

One of the most significant engineering advantages of the continuous helical geometry is its radical reduction in acoustic emissions.⁵ In conventional multi-bladed propellers, a major source of high-frequency noise is blade-vortex interaction (BVI), which occurs when a trailing propeller blade chops through the tip vortex shed by the preceding blade.⁵ The continuous, uninterrupted spiral of the helical airscrew inherently suppresses these discrete tip vortex discharge events.⁵ Furthermore, because the helical rotor has an exceptionally large wetted surface area compared to a standard thin propeller, it can generate equivalent lift forces at substantially lower rotational velocities (RPM).⁵ The intensity of aeroacoustic noise *I* scales with the rotational speed:

$$I \propto \Omega^2$$

where Ω is the rotational velocity.⁷ By increasing the continuous surface area, the operating

Ω is minimized, which exponentially dampens the acoustic signature.⁵

To optimize a helical rotor for a 450 mm drone frame, specific geometric parameters must be precisely engineered. A uniform cylindrical helix is highly inefficient due to uneven velocity distribution along the shaft.⁷ Empirical studies dictate a top-to-base radius taper of 1 : 2.⁷ Tapering the rotor narrows the upper sections, reducing the drag penalty where rotational velocity is low, and concentrating the lift-generating surface area at the outer, faster-moving lower perimeter.⁷ Computational models demonstrate that the optimal aerodynamic pitch-to-base-radius ratio is 1.31.⁷ This specific ratio maintains an optimal angle of attack across the changing radius, maximizing the lift-to-drag ratio of the rotating spiral.⁷ Da Vinci's original design featured a single, continuous blade, which is inherently unbalanced and induces severe wobble during rotation.⁵ The redesigned drone must utilize a double-helix configuration (two nested spiral blades).⁶ This symmetrical arrangement physically balances the rotating mass and distributes the aerodynamic loading equally across 180° of rotation, eliminating high-frequency vibration.⁶ While increasing the spiral turns beyond 1.0 increases the total surface area and total lift, it also dramatically increases skin friction drag and structural weight.⁷ For a 450 mm frame, the optimal balance is achieved with exactly 1.0 turn of the double-helix.⁷

Wind-Driven Forward Propulsion and Energy Harvesting Regimes

The integration of Archimedes screw technology to utilize wind to propel the drone forward introduces a dual-regime system where the rotors alternate between active propulsors and wind-driven energy-harvesting states.⁹ This dual-regime capability utilizes the principles of the Archimedes Spiral Wind Turbine (ASWT).⁹

Aerodynamic Principles of the ASWT Mode

The ASWT geometry differs fundamentally from conventional lift-based horizontal-axis wind turbines (HAWTs).⁹ While traditional propellers rely almost exclusively on aerodynamic lift to rotate, the helical spiral blades of an ASWT utilize a hybrid combination of both lift and drag forces.²¹ When wind flows over the conical spiral structure, the pressure on the windward side (pressure side) becomes significantly greater than on the leeward side (suction side).²¹ Because the blade wraps helically around the central axis, this pressure differential is resolved into a rotational torque.²⁴ This hybrid lift-drag mechanism provides two critical advantages:

- **Low Cut-in Speed:** Traditional lift-based wind turbines require substantial wind velocities to overcome initial static friction.⁸ The high-solidity, drag-driven profile of the

Archimedes spiral allows the rotors to start spinning at wind speeds as low as 2 m/s.²⁰

- Passive Self-Yawing:** In an urban or turbulent environment, wind direction shifts rapidly.²¹ Standard wind turbines require active motorized yaw systems to face the wind.²¹ The specific helical, conical shape of the Archimedes rotor creates an asymmetric drag profile when misaligned with the wind.²⁰ This asymmetric drag acts as a passive aerodynamic rudder, forcing the rotor to automatically pivot and align itself directly with the oncoming wind vector without requiring sensors or motors.²⁰

Scaling Analysis: Wind Turbine Models vs. Drone Integration

To understand how these wind-driven forces scale down from commercial-scale wind turbines to a shoulder-width drone, we must analyze the physical parameters of established Archimedes spiral wind turbines.

Parameter	Standard Liam F1	Liam F1 Mini	Scaled Drone Rotor
Rotor Diameter	1.5 m ²⁰	0.75 m ²⁰	0.203 m (8 in) ⁶
Total Weight	≈ ²⁰	≈ ²⁰	≈ ¹
Max Power Output	1500 W ²⁰	750 W ²⁰	≈ (regenerated) ²⁹
Starting Wind Speed	2.0 m/s ²⁰	2.0 m/s ²⁰	1.5 m/s (low-inertia) ⁵
Operating Noise	< ²⁰	Silent ²⁰	Virtually Inaudible ⁷
Core Material	Fiber Glass + RVS ²⁰	Fiber Glass + RVS ²⁰	Carbon-Fiber PETG ⁶

Thermodynamic Realities of Wind-Driven Propulsion

When designing a drone that harvests wind energy in flight, it is critical to address thermodynamic boundaries to avoid the mechanical impossibility of perpetual motion.²⁹ If the drone attempts to use its own motor-driven forward velocity to spin a turbine to charge its battery, it will suffer a net loss of energy.²⁹ This is governed by the second law of thermodynamics and aerodynamic drag penalties ²⁹: the drag added by the wind turbine requires the propulsion motors to draw more electrical power from the battery than the turbine can possibly generate.²⁹

To achieve true positive wind-driven propulsion, the drone must extract energy from *external, ambient wind resources*.³² This is achieved through three primary operational regimes:



Regime A: Wind-Turbine Mode for Regenerative Energy Accumulation

When stationary or hovering in strong wind fields (such as on top of an urban building), the drone can execute a wind-harvesting profile.²⁷ The active propulsion motors are shut down, and internal electromagnetic clutches disengage the direct motor drive, allowing the rotors to windmill freely.⁸

The passive self-yawing of the Archimedes screws aligns the airframe with the wind.²⁰ The

ambient wind spins the helical rotors, driving the internal permanent-magnet motors in reverse to act as generators.⁸ This harvested electrical energy is routed through the bidirectional ESCs to recharge the battery.²⁹

Regime B: Dynamic Wind Sailing via Variable-Pitch Transition

To "use the wind to propel it forward" during active flight, the drone must combine wind forces with its electric motors through a variable-pitch mechanism.³⁵ The effective angle of attack α of a helical blade segment is defined by:

$$\alpha = \Phi - \theta$$

where Φ is the blade pitch angle and θ is the local helix angle of the oncoming airflow.³⁵ By dynamically adjusting the pitch angle Φ using a micro-servo pitch-actuator on the hub, the rotor can transition its blade profile between a high-efficiency generator (turbine mode) and a high-efficiency thrust producer (propeller mode).³⁵

In a strong crosswind, the drone can yaw its body so that the windward rotors windmill.²¹ The mechanical rotation generated by the wind is harvested as electricity, which is routed directly to the leeward motors.¹¹ This allows the leeward rotors to spin at high speeds to generate forward propulsive thrust, effectively using the wind to drive the drone forward while drawing zero net power from the battery.²⁹ This closed-loop power transfer mirrors the energy-efficient flight profiles utilized by high-altitude sailing gliders and wind-shear UAVs.³²

Regime C: Regenerative Descent and Aerodynamic Braking

When descending from high altitudes, the drone can convert gravitational potential energy into electrical energy.²⁹ Instead of using battery power to run the motors to slow down, the helical rotors are allowed to windmill.²⁹ The high solidity and high drag of the Archimedes screws act as a highly effective aerodynamic brake (parachute effect).⁵

The windmilling rotation drives the brushless motors in reverse, allowing the electronic speed controllers (ESCs) to perform regenerative braking, converting kinetic descent energy back into stored battery power.²⁹ This regenerative descent cycle can reduce net flight energy

consumption by up to 19% compared to standard non-regenerative configurations.³⁰

Powertrain Sizing, High-Torque Electronics, and Bidirectional Energy Flow

The physical properties of Archimedes helical rotors dictate a completely different electronic

and mechanical powertrain compared to standard 450 mm multirotor builds.³ Standard builds typically utilize lightweight, high-KV brushless motors (such as 2212 or 2216 series rated

at 920 KV) running on low-voltage 3S (11.1 V) or 4S (14.8 V) lithium-polymer (LiPo) batteries.² These standard motors are designed to turn thin, low-inertia plastic propellers at high rotational speeds to achieve lift.³

If a standard 2212 motor is fitted with a heavy, high-solidity helical screw, the motor will fail to generate sufficient starting torque, overheat rapidly due to high current draw, and suffer from poor dynamic response.³ To overcome the high rotational inertia of a continuous three-dimensional spiral, the drone must utilize specialized, large-stator, high-torque brushless motors.³

The stator size must be stepped up to at least a 2807 or 3115 series.³ The wider stator diameter (e.g., 31 mm stator width) provides a much longer electromagnetic lever arm relative to the rotor magnets, generating the extreme torque required to accelerate and decelerate the heavy helical screw.³ The winding of the motor must be optimized for low-KV operation, specifically targeting a range of 900–1200 KV .²



3115 1000KV Brushless Motor	3115 1000KV Brushless Motor
- Large-stator torque	- Large-stator torque
- Dual-direction flux	- Dual-direction flux

A high-voltage power system is mandatory to maintain electrical efficiency and prevent voltage sags under heavy aerodynamic loads.³ The battery platform must be upgraded to a 6S (22.2 V) system, preferably utilizing high-energy-density Lithium-Ion (such as 21700 cylindrical cells) to maximize energy capacity for long-endurance wind-harvesting profiles.³ Operating at 6S voltage cuts the current draw (amperage) in half for the same electrical power output, which dramatically reduces Joule heating losses (I^2R) in the ESCs and motor windings.³ This thermal stability is crucial because the high drag of the Archimedes rotors requires sustained power input during hover and lateral maneuvers.⁵ To facilitate the dual-regime propulsion and wind-harvesting capabilities, the ESCs must support bidirectional power flow.³⁰ The drone must be equipped with specialized BLHeli_32 or industrial-grade ESCs rated for at least 40 A .³ These ESCs must be programmed to execute active freewheeling and regenerative braking, allowing them to instantly transition from driving the motor (converting battery DC to three-phase AC) to rectifying the three-phase AC generated by the windmilling rotor back into DC to charge the battery.²⁹


Powertrain Component	Component Specification	Critical Performance Rationale
Brushless Motor	3115 ₃ Stator / 1000 KV	Maximizes electromagnetic torque to overcome helical rotor inertia ³
Battery Pack	6S (22.2 V) Li-Ion (4000 mAh) ₃	Minimizes line current to reduce I^2R thermal dissipation ³
Electronic Speed Controller	40 A Bidirectional BLHeli_32 ³	Enables regenerative rectification during wind-harvesting ²⁹

Active Rotor Pitch Servo	Coreless Micro-Servo (4.8 V) ⁸	Coordinates dynamic angle of attack adjustment (α) ³⁵
Propulsion Power	$\approx$ per motor (at hover) ³	Achieves a safe 2.5 : thrust-to-weight ratio ³

Dynamic Balancing, Fabrication, and Aeroacoustic Verification

The fabrication of a three-dimensional helical rotor presents serious structural challenges.⁹ Unlike flat propellers, a continuous spiral cannot be easily injection-molded without complex multi-part tooling.⁹ Historical models constructed from reeds and starch-covered linen are far too heavy and structurally weak for a modern high-RPM drone.¹⁴

For a 450 mm frame, the helical rotors must be fabricated using carbon-fiber-reinforced polymers or high-precision additive manufacturing (3D printing) using carbon-fiber PETG (CF-PETG).⁵ CF-PETG offers an exceptional stiffness-to-weight ratio, ensuring the continuous spiral does not bend, flutter, or buzz when subjected to high aerodynamic pressure at the outer edges.⁴ To minimize skin friction drag, the outer surface of the 3D-printed helical rotor must be post-processed, sanded, and coated with a low-friction hydrophobic epoxy resin.⁶



Due to the three-dimensional depth of the helical screw, any minor variation in material density or thickness along the spiral path creates severe dynamic imbalance.⁵ This imbalance manifests as a rotating force vector that can easily destroy motor bearings and cause flight controller sensor saturation.³ Every fabricated helical rotor must undergo multi-plane dynamic balancing.⁵ This involves placing the rotor on a specialized balancing rig, spinning it at operational RPM, and using laser accelerometers to identify the exact phase and plane of vibration. Tiny

counterweights (micro-epoxy drops) are then applied to the inner hub to ensure the rotor spins with zero vibration.⁵

To verify the acoustic benefits of the redesigned drone, the airframe must undergo

aeroacoustic testing in a semi-anechoic chamber. Conventional 450 mm multirotors

generate a high-frequency whine exceeding 65 dB at a distance of 3 meters, primarily driven by high-RPM blade-vortex interactions.⁵

In contrast, the continuous spiral geometry of the double-helix Archimedes rotors distributes pressure evenly along the blade surface, preventing the formation of strong, concentrated tip vortices.⁵ Combined with the lower operational RPM enabled by the large wetted surface area,

the redesigned drone's acoustic profile is expected to remain below 45 dB—rendering it virtually silent against standard urban background noise.⁷

Conclusions and Implementation Roadmap

The re-engineering of a 450 mm drone to incorporate Archimedes helical screws and wind-driven propulsion is physically and aerodynamically viable when supported by modern materials and high-torque electronics.¹ The following sequence of systematic actions is recommended for physical prototyping and flight-testing:

1. Advanced Rotor Geometry Construction

The helical rotor must be modeled as a tapered double-helix with a 1 : 2 top-to-base radius ratio.⁷ The outer diameter must be restricted to 8 inches (203 mm) to maintain adequate physical clearance on the 450 mm diagonal frame.¹ The pitch-to-base-radius ratio must be set to exactly 1.31, and the double-helix must complete exactly 1.0 turn around the central aluminum shaft to optimize the lift-to-weight ratio.⁶

2. High-Torque Powertrain Integration

To handle the rotational inertia of the continuous spiral screws, standard 2212 motors must be bypassed.³ The propulsion system must specify 2807 or 3115 stator brushless motors with a winding speed of 1000 KV.³ This must be paired with 40 A BLHeli_32 ESCs capable of active freewheeling and bidirectional regeneration, powered by a 6S (22.2 V) high-discharge battery pack.³

3. Flight Controller Tuning and Gyroscopic Filtering

Helical rotors generate massive aerodynamic drag and lower lift coefficients compared to standard propellers.⁵ Consequently, the flight controller (running modern firmware like

ArduPilot or PX4) must be tuned with aggressive proportional-integral-derivative (PID) gains to maintain stability.³ High-frequency gyroscopic noise must be aggressively filtered using software-based notch filters targeted at the primary rotational frequency of the helical screws.³

4. Wind-Harvesting Code Deployment

The drone's software stack must include a custom telemetry script that monitors the battery state and GPS positioning.¹¹ When the drone is perched on a static structure in a high-wind urban environment, the script must command the ESCs into "generator mode".⁸ The passive self-yawing of the Archimedes rotors will align the drone with the wind, allowing the windmilling screws to recharge the battery safely without drawing active propulsion power.²⁰

Works cited

1. What Is an F450 Drone Frame? Dimensions, Weight & DIY Build FAQ - ElectronicsHub, accessed May 31, 2026, <https://electronics.alibaba.com/question/f450-drone-frame-guide-weight,-dimensions-build-tips>
2. Hexsoon EDU-450 V2 Drone Frame for Cube Orange+ Integration - Aeroboticshop.com, accessed May 31, 2026, <https://aeroboticshop.com/products/hexsoon-edu-450-v2>
3. HELP : r/ardupilot - Reddit, accessed May 31, 2026, <https://www.reddit.com/r/ardupilot/comments/1tg4fk5/help/>
4. Aircraft Propellers – Introduction to Aerospace Flight Vehicles - Eagle Pubs, accessed May 31, 2026, <https://eaglepubs.erau.edu/introductiontoaerospaceflightvehicles/chapter/propellers/>
5. Given modern technology and materials, can Da Vinci's "screw helicopter" design actually take flight? : r/AskPhysics - Reddit, accessed May 31, 2026, https://www.reddit.com/r/AskPhysics/comments/1rquc5q/given_modern_technology_and_materials_can_da/
6. 'Crimson Spin' brings da Vinci helicopter design to life - Vertical Mag, accessed May 31, 2026, <https://verticalmag.com/features/crimson-spin-brings-da-vinci-helicopter-design-to-life/>
7. Aerodynamics and Aeroacoustics of da Vinci's Aerial Screw - arXiv, accessed May 31, 2026, <https://arxiv.org/html/2506.10223v1>
8. Liam F1 Wind Turbine Overview | PDF - Scribd, accessed May 31, 2026, <https://www.scribd.com/document/802513998/gradddddd>
9. ARCHIMEDES WIND TURBINE DESIGN - Dash Hrecos Org, accessed May 31, 2026, <https://www.dash.hrecos.org/explore/1AD/043/KSCawN/ArchimedesWindTurbineDesign>
10. Energy-Efficient UAV Communications in the Presence of Wind: 3D Modeling and Trajectory Design - NASA ADS, accessed May 31, 2026,

- <https://ui.adsabs.harvard.edu/abs/2023arXiv230406909D/abstract>
11. Tethered Drone-Based Airborne Wind Energy System Launching and Retrieving | Journal of Guidance, Control, and Dynamics - Aerospace Research Central, accessed May 31, 2026, <https://arc.aiaa.org/doi/10.2514/1.G006099>
 12. Hexsoon EDU-450 V2 - DIY - BZB UAS, accessed May 31, 2026, <https://www.bzbuas.com/shop/hs014-hexsoon-edu-450-v2-diy-476>
 13. How to Choose FPV Drone Motors - Considerations and Best Motor Recommendations, accessed May 31, 2026, <https://oscarliang.com/motors/>
 14. Leonardo's aerial screw - Wikipedia, accessed May 31, 2026, https://en.wikipedia.org/wiki/Leonardo%27s_aerial_screw
 15. Helicopter (Aerial Screw) - Leonardo Da Vinci Inventions, accessed May 31, 2026, <https://www.da-vinci-inventions.com/aerial-screw>
 16. Da Vinci's Aerial Screw: Early Helicopter Design | PDF | Propeller - Scribd, accessed May 31, 2026, <https://www.scribd.com/document/430920133/Leonardo-Da-Vinci>
 17. Da Vinci's 530-Year-Old Helicopter Design Adapted for a Working Drone - Dornob, accessed May 31, 2026, <https://dornob.com/da-vincis-530-year-old-helicopter-design-adapted-for-a-working-drone/>
 18. Unmanned Aerial Vehicle is Based on da Vinci Aerial Screw Design - Tech Briefs, accessed May 31, 2026, <https://www.techbriefs.com/component/content/article/45234-unmanned-aerial-vehicle-is-based-on-da-vinci-aerial-screw-design>
 19. Buzz Killer: Da Vinci's Aerial Screw Finds New Life - ASME, accessed May 31, 2026, <https://www.asme.org/topics-resources/content/da-vinci%E2%80%99s-aerial-screw-finds-new-life-as-a-low-noise-drone-propeller>
 20. Liam F1 UWT Wind Turbine: New Spin on Urban Renewable Energy - RK Systems, accessed May 31, 2026, <https://rkwindmast.com/c/liam-f1-uwt-wind-turbine.html>
 21. Numerical Aerodynamics Analysis of the of the Archimedes Screw Wind Turbine - IJMSE, accessed May 31, 2026, <http://www.ijmse.org/Volume9/Issue10/paper3.pdf>
 22. Experimental and Numerical Study of the Aerodynamic Characteristics of an Archimedes Spiral Wind Turbine Blade - MDPI, accessed May 31, 2026, <https://www.mdpi.com/1996-1073/7/12/7893>
 23. A comparative examination of the aerodynamic performance of various seashell-shaped wind turbines - PMC, accessed May 31, 2026, <https://pmc.ncbi.nlm.nih.gov/articles/PMC10361123/>
 24. Numerical Aerodynamics Analysis of the of the Archimedes Screw Wind Turbine, accessed May 31, 2026, https://www.academia.edu/93648885/Numerical_Aerodynamics_Analysis_of_the_of_the_Archimedes_Screw_Wind_Turbine
 25. Archimedes Screw Wind Turbine Analysis | PDF - Scribd, accessed May 31, 2026, <https://www.scribd.com/document/953894949/paper3>
 26. Aerodynamic Performance and Coupling Gain Effect of Archimedes Spiral Wind Turbine Array - Semantic Scholar, accessed May 31, 2026, <https://pdfs.semanticscholar.org/3f63/dfca47339af2a385bede62c0a55d9964c662>

.pdf

27. The Archimedes Liam F1 Urban Wind Turbine - International Energy Solutions, s.a.r.l, accessed May 31, 2026, <https://www.ienergy-us.com/products/detail/42>
28. Numerical Aerodynamics Analysis of the of the Archimedes Screw Wind Turbine, accessed May 31, 2026, https://www.researchgate.net/publication/329830064_Numerical_Aerodynamics_Analysis_of_the_of_the_Archimedes_Screw_Wind_Turbine
29. How much power can I obtain by converting potential/wind energy using propeller as generator like RAT/Wind turbine - Aviation Stack Exchange, accessed May 31, 2026, <https://aviation.stackexchange.com/questions/107724/how-much-power-can-i-obtain-by-converting-potential-wind-energy-using-propeller>
30. Case Studies | Propeller Optimisation - NUMECA, accessed May 31, 2026, <https://www.numeca.de/en/case-studies-propeller-optimisation/>
31. Is it theoretically possible to harness "wind power" in a vehicle? - Reddit, accessed May 31, 2026, https://www.reddit.com/r/NoStupidQuestions/comments/1pn8o6w/is_it_theoretically_possible_to_harness_wind/
32. NASA drone utilizing wind shear as propulsion "Stratospheric Dual-Aircraft Platform" DAP : r/WeirdWings - Reddit, accessed May 31, 2026, https://www.reddit.com/r/WeirdWings/comments/1g5nuc7/nasa_drone_utilizing_wind_shear_as_propulsion/
33. Wind-powered vehicle - Wikipedia, accessed May 31, 2026, https://en.wikipedia.org/wiki/Wind-powered_vehicle
34. US6741000B2 - Electro-magnetic archimedean screw motor-generator - Google Patents, accessed May 31, 2026, <https://patents.google.com/patent/US6741000B2/en>
35. Propeller (aeronautics) - Wikipedia, accessed May 31, 2026, [https://en.wikipedia.org/wiki/Propeller_\(aeronautics\)](https://en.wikipedia.org/wiki/Propeller_(aeronautics))
36. Airplanes and Wind Turbines - PCI Blog, accessed May 31, 2026, <https://blog.pcitraining.edu/blog/airplanes-and-wind-turbines>
37. US20120286513A1 - Wind powered vehicle turbine - Google Patents, accessed May 31, 2026, <https://patents.google.com/patent/US20120286513A1/en>
38. US4251040A - Wind driven apparatus for power generation - Google Patents, accessed May 31, 2026, <https://patents.google.com/patent/US4251040A/en>
39. Why the F450 Drone Frame Is the Best Starter Kit for RC Enthusiasts in 2024 - AliExpress, accessed May 31, 2026, <https://www.aliexpress.com/s/wiki-ssr/article/https://www.aliexpress.com/s/wiki-ssr/article/drone-f450>
40. How to Choose the Right Drone Motor Size, accessed May 31, 2026, <https://www.power-motor.com/Technologies/708.html>
41. Toroidal propeller - Wikipedia, accessed May 31, 2026, https://en.wikipedia.org/wiki/Toroidal_propeller