

CSMFAB000000000104

The Dielectric Citadel Perimeter Protocol: Advanced Aegis-Class Fencing and Barrier Infrastructure for Carrington-Event Resilience

1. Heliophysical Threat Vector Analysis on Perimeter Infrastructure

The contemporary perimeter security paradigm operates under a fundamentally flawed axiom: thermodynamic and electromagnetic environmental stability. Standard industrial fencing and crash-rated barrier systems are constructed predominantly from ferromagnetic steel and conductive aluminum alloys.¹ In the context of a Carrington-class Coronal Mass Ejection (CME) and subsequent geomagnetic induction events, this extensive metallic infrastructure transforms from a passive physical deterrent into a highly energized, lethal conductive lattice.⁴ The reliance on these materials guarantees catastrophic failure during extreme heliophysical events.

1.1 Magnetohydrodynamic Coupling and Loop Antenna Physics

A Carrington-style event compresses the magnetosphere, generating surface geoelectric fields (E_{geo}) that drive massive Geomagnetically Induced Currents (GICs) through continuous conductive paths.⁴ Long linear runs of industrial security fencing—particularly those installed parallel to high-voltage transmission lines, subterranean pipelines, or geological fault lines—function as macro-scale loop antennas.⁶ Faraday's Law of Induction dictates the electromotive force ($\mathcal{E}$) induced within these continuous metallic structures:

$$\mathcal{E} = -\frac{d\Phi_B}{dt} = -\frac{d}{dt} \int \mathbf{B} \cdot d\mathbf{A}$$

Where Φ_B is the magnetic flux and $\mathbf{A}$ is the loop area formed by the fence line and the conductive earth return path. Given that these installations frequently span multiple kilometers around critical infrastructure, the integrated loop area is massive, resulting in induced potentials that current hardware cannot withstand.⁶ The resulting quasi-Direct Current (DC) can reach hundreds of amperes, saturating the ferromagnetic mass of the fence.⁴

1.2 Joule Heating and Plasma Arcing

When these massive DC currents encounter high-resistance discontinuities within the perimeter architecture—such as standard mechanical fasteners, powder-coated panel brackets, hinges, or expansion joints—Joule heating ($P = I^2 R$) creates localized energy densities.⁴ This energy is sufficient to initiate sustained plasma arcing.⁴ This arcing vaporizes standard protective finishes (like polyester powder coats or zinc galvanization) and resistance-welds the structural components.³ The resulting thermal expansion, denied relief by fused joints, induces buckling and catastrophic shear failure across the barrier line.⁴

1.3 High-Power Microwave (HPM) and Skin Effect Degradation

Simultaneously, the threat of Directed Energy Weapons (DEW) or High-Power Microwave (HPM) attacks necessitates the evaluation of perimeter barriers under high-frequency electromagnetic loading. At gigahertz frequencies, the Skin Effect forces induced currents to the extreme outer surface of the metal pickets and rails.⁷ The skin depth (δ) is defined mathematically as:

$$\delta = \sqrt{\frac{2\rho}{\omega\mu}}$$

For highly permeable ferromagnetic steel ($\mu_r \gg 1$), the skin depth is measured in mere microns.⁸ This confinement results in intense, localized heating and rapid thermal structural degradation, entirely bypassing the core of the metal and initiating surface ablation.⁸ Standard perimeter systems lack the dielectric properties necessary to survive this bimodal threat profile.

Threat Vector	Physical Mechanism	Primary Target Structure	Deterministic Outcome
GIC (Low Freq)	Quasi-DC Telluric Currents ($P = I^2 R$)	Continuous Rails, Anchor Bolts, Brackets	Plasma Arcing, Resistance Welding, LME
HPM (High Freq)	Skin Effect Attenuation & Eddy Currents	Picket Surfaces, Mesh Panels	Rapid Thermal Ablation, Spalling

EMP (E1 Pulse)	High Voltage Transients	Gate Automation, Induction Loops	Dielectric Breakdown, Logic Gate Fusion
-----------------------	-------------------------	----------------------------------	---

2. Forensic Vulnerability Analysis of Existing Perimeter Architectures

The prevailing industry standard for high-security and industrial fencing relies on hot-dip galvanized steel or heavy-gauge aluminum.¹ An exhaustive analysis of prominent commercial systems reveals severe vulnerabilities to electromagnetic excitation.

2.1 Ameristar Aegis II and Aegis Plus Vulnerabilities

The Ameristar Aegis II and Aegis Plus systems represent the industry standard for ornamental steel fencing, utilizing a proprietary ForeRunner rail design.¹⁰ The Aegis II specifies a 1.75-inch square 14-gauge high-strength architectural shape, while the Aegis Plus utilizes a 1.5-inch 14-gauge profile.¹⁰ Both systems contain an internally secured retaining rod that allows for variable pitch connection and eliminates external fasteners.¹¹

While architecturally sound against kinetic threats, this configuration creates a continuous, shielded internal conductive channel.¹¹ During a GIC event, the internal retaining rod acts as a high-resistance choke point. As telluric currents attempt to flow through the panels, the rod-to-picket interface experiences extreme thermal loading. The internal zinc galvanization

(melting point $\approx 419^{\circ}C$) rapidly liquefies within the rail cavity.⁴

The presence of molten zinc in contact with stressed high-strength steel triggers Liquid Metal Embrittlement (LME).⁴ The liquid zinc penetrates the grain boundaries of the 14-gauge steel pickets and ForeRunner rails, causing immediate, brittle fracture of the security perimeter.⁴ Furthermore, the highly touted PermaCoat multi-layer finish—consisting of an epoxy powder coat and a polyester powder coat designed to withstand 3,500 hours of salt spray¹³—provides zero dielectric shielding against bulk magnetic induction. Instead, it acts as a flammable hydrocarbon fuel source upon the initiation of plasma arcing at the bracket connections.

2.2 Crash-Rated Barrier Systems (Tymetal and Gibraltar)

High-security facilities utilize crash-rated steel cable fences, such as the Tymetal TCF-M50-P1 or Gibraltar Cable Barrier systems, designed to arrest 15,000-pound vehicles traveling at 50 mph (ASTM F2656 M50-P1).¹⁵ These systems string massive galvanized steel cables between heavy steel I-beam posts.¹⁵

During a Carrington-class event, these miles of grounded, continuous steel cable act as optimal conduits for megawatt-scale telluric currents. The immense DC load saturates the steel, generating heat that exceeds the annealing temperature of the tensioned cables. This induces "hidden tendon relaxation," identical to the failure modes observed in post-tensioned bridge

structures.⁴ As the cables relax, the system loses the structural tension required for kinetic arrest, risking catastrophic plasma vaporization of the cable anchors and rendering the M50 rating entirely void.⁴

2.3 Substation Perimeter Earthing and Touch Voltage Hazards

At high-voltage outdoor substations, legacy metallic fencing introduces fatal step-and-touch voltage hazards. Regulatory frameworks, specifically the Canadian Electrical Code (CEC) Section 36-312 and IEEE-80 standards, mandate rigorous grounding of metallic fence enclosures.¹⁹ Fences must be located at least 1 meter inside the ground electrode area and bonded with No. 2/0 AWG copper conductors at all corner posts, gate posts, and intermediate posts (at intervals not exceeding 12 meters).¹⁹

Grounding systems optimized for 60 Hz AC faults are wholly inadequate for managing sustained, high-amperage quasi-DC GIC flows.⁴ In a Carrington event, the massive DC influx saturates the substation ground grid, elevates the local earth potential, and drives lethal currents outward through the mandated 4/0 and 2/0 copper ground taps directly into the perimeter fence.²¹ The fence transforms into a high-voltage radiating element, establishing a lethal Ground Potential Rise (GPR). This neutralizes its function as a security barrier and renders the perimeter impassable to maintenance personnel due to extreme touch voltages.⁷

2.4 Gate Automation and Inductive Loop Susceptibility

Vehicle access points in industrial perimeters rely on induction loop detectors embedded in the roadway.²³ These systems operate via an LC oscillator circuit. When a metallic vehicle alters the local magnetic field, the inductance of the loop changes, shifting the oscillator frequency to trigger the gate mechanism.²³

Under GMD or EMP conditions, the massive external $\frac{dB}{dt}$ flux completely overwhelms the micro-inductance variations measured by the LC circuit. The induced currents instantly exceed the dielectric breakdown voltage of the capacitor banks, destroying the logic gates within the loop detector housing.⁸ Consequently, automated security gates are rendered inoperable, failing either in an exposed open configuration or a permanently fused locked state.

3. Material Replacement Fundamentals: The Stellar-Aegis Protocol

The rectification of these fatal vulnerabilities requires the total elimination of the conductive pathway. The structural paradigm must transition from the "Iron Age" of ferromagnetic dependency to the "Dielectric Citadel" architecture.⁴ The Stellar-Aegis Protocol dictates the immediate substitution of legacy metals with Advanced Dielectrics, Ultra-High Temperature Ceramics (UHTCs), and Spectrally Selective Composites.⁴

3.1 Basalt Fiber Reinforced Polymer (BFRP) Matrix

For standard picket, rail, and post substitution, Basalt Fiber Reinforced Polymer (BFRP) serves

as the foundational structural skeleton.

- **Origin and Extrusion Thermodynamics:** BFRP is synthesized by melting crushed volcanic basalt rock at temperatures exceeding 1400°C and extruding the melt into continuous micro-filaments.⁴
- **Electrodynamic Inertness:** BFRP is inherently non-conductive, non-magnetic ($\mu_r \approx 1$), and completely transparent to RF energy and magnetic flux.⁴ A perimeter fence constructed of pultruded BFRP cannot act as a loop antenna; no eddy currents can be induced, and Joule heating is a physical impossibility.
- **Mechanical Supremacy:** BFRP exhibits a tensile strength of 1100–1300 MPa and a stiffness modulus of 50–60 GPa, significantly outperforming the 414 MPa yield strength of standard Grade 60 carbon steel, at a fraction of the mass (2.1 g/cm^3 vs 7.85 g/cm^3).
- **Thermal Tolerance:** The basalt fibers retain total structural integrity up to $700 - 800^{\circ}\text{C}$, ensuring survival during adjacent urban firestorms or localized intense thermal anomalies where standard aluminum components (660°C melting point) undergo selective metallurgical liquefaction.⁴

3.2 Zirconium Diboride (ZrB_2) and Silicon Nitride (Si_3N_4) Core Matrices

For high-security applications requiring impact resistance equivalent to heavy-gauge steel (e.g., M50-rated bollards and anti-ram rails), purely polymeric matrices are insufficient. Aegis-class components must utilize Ultra-High Temperature Ceramics (UHTCs).

- **Composition and Sintering:** The structural core consists of Zirconium Diboride (ZrB_2) sintered within a Silicon Nitride (Si_3N_4) matrix.⁷ Synthesis is achieved via Spark Plasma Sintering (SPS), utilizing Boron Carbide (B_4C) as a reactive agent. During heating, B_4C reacts with surface oxides on the ZrB_2 particles ($2\text{ZrO}_2 + \text{B}_4\text{C} + 3\text{C} \rightarrow 2\text{ZrB}_2 + 4\text{CO}_{(gas)}$), removing oxygen as Carbon Monoxide gas and purifying the grain boundaries for maximum densification.⁷
- **Thermodynamic Refractivity:** ZrB_2 possesses a melting point of 3245°C and acts as a massive thermal battery, absorbing and rapidly distributing intense localized heat loads ($k \approx 60 \text{ W/m} \cdot \text{K}$) to prevent localized ablation under directed energy flux.⁸
- **Dielectric Status:** While pure ZrB_2 exhibits moderate conductivity, its encapsulation

within the dense Si_3N_4 matrix guarantees macroscopic bulk electrical insulation ($> 10^{10} \Omega \cdot m$).⁴ This composite yields the fracture toughness necessary to arrest vehicular kinetic energy while remaining entirely immune to GIC and eddy current formation.⁸

3.3 Spectral Shielding and Thermal Management

Perimeter fences are subjected to intense solar loading and potential directed energy flux. Thermal regulation and spectral reflection are critical to maintaining the mechanical properties of the underlying polymer matrices and negating the thermal gradients that precede structural failure.

3.3.1 YInMn Blue ($YIn_{1-x}Mn_xO_3$)

This inorganic complex oxide serves as the primary "Event Horizon" exterior glaze.

- **Crystallography:** The Manganese ion (Mn^{3+}) occupies a trigonal bipyramidal coordination site within the Yttrium-Indium oxide lattice. This geometry establishes an electronic bandgap that absorbs visible red and green photons (appearing vibrant blue).⁴
- **NIR Reflectance:** Crucially, the structure is highly transparent/reflective to Near-Infrared (NIR) photons. It reflects $> 85\%$ of NIR radiation (700 nm – 2500 nm).⁵
- **Application:** Applying YInMn Blue as the exterior coating on all perimeter components acts as an absolute "Cool Roof" mechanism, repelling radiative heat loads from solar flares or DEWs, and preventing the thermal degradation of the internal BFRP matrix.⁴

3.3.2 Cobalt Aluminate ($CoAl_2O_4$)

To address high-frequency microwave threats, Cobalt Aluminate is integrated into the polymer matrix.

- **Synthesis and Spinel Structure:** Synthesized at temperatures exceeding $1200^\circ C$, this normal spinel structure (AB_2O_4) is chemically inert and thermodynamically stable beyond $1900^\circ C$.⁵
- **Dielectric Scattering:** At microwave frequencies (e.g., 11 GHz), the real permittivity (ϵ') of the aluminate matrix exceeds 15.⁵ When doped into the resin matrices of the fencing components, the particles act as scattering centers. They disrupt the coherence of incoming high-frequency wave fronts (from HPM attacks), dissipating the energy as negligible structural heat rather than allowing it to couple destructively with the barrier's core.⁵

Material	Primary Function	Key Physics / Metric	Threat Mitigation
BFRP (Basalt)	Structural Skeleton	1100 MPa Tensile, $\sigma = 0$	GIC Immunity, $700^{\circ}C$ Thermal Limit
ZrB_2 , Si_3N_4	Kinetic Arrest Core	$3245^{\circ}C$ MP, $> 10^{10} \Omega \cdot m$	Anti-Ram Capability, Plasma Arc Resistance
YInMn Blue	Exterior Glaze	$> 85\%$ NIR Reflectance	Radiative Heat Deflection (DEW/Solar)
Cobalt Aluminate	Matrix Doping	$\epsilon' > 15$ at 11 GHz	Microwave Scattering, High-Frequency Immunity

4. Immediate Retrofit Procedures: Legacy Infrastructure Hardening

Immediate, wholesale replacement of thousands of kilometers of existing steel industrial fencing¹ is logistically improbable prior to the next solar maximum. Therefore, rigorous, immediate-action retrofits must be deployed to decouple and harden existing ferromagnetic assets utilizing Aegis protocols.

4.1 Ground Loop Decoupling and Capacitive Isolation

The primary vulnerability of continuous steel fencing is its uninterrupted conductivity. To neutralize the loop antenna effect and halt the progression of telluric currents, the perimeter must be systematically segmented.

- **Rail Severance Procedure:** At intervals not exceeding 30 meters, the continuous metallic rails (e.g., the 1.75-inch ForeRunner rails¹⁰) must be physically severed.
- **Dielectric Bridging:** The severed junctions must be reconnected using high-toughness structural insulators. Ytria-Stabilized Zirconia (YSZ) dowel pins ($6mm \times 20mm$)⁷ or Basalt-epoxy bridging sleeves must be inserted into the hollow rail channels. These

inserts are bonded using high-temperature, silicate-based adhesives (e.g., Cotronics Resbond 907GF).⁷ This effectively breaks the conductive loop without compromising the mechanical rigidity of the fence line.

- **Anchor Decoupling:** Base plates bolted to concrete footings must be electrically isolated from the earth. Existing steel nuts are removed, and Capacitive Isolation Washers—machined from Basalt Fiber Reinforced Polymer (BFRP)—are installed under the anchor nuts.⁴ This physically decouples the A354BD anchor rods from the fence potential, halting the flow of GICs and neutralizing the electrolytic cell that causes hydrogen embrittlement at the foundation.⁴

4.2 Spectrally Selective In-Situ Coatings

To mitigate high-frequency skin-effect heating and NIR radiative loading on legacy steel, the existing aesthetic finishes (which provide mere corrosion resistance¹³) must be upgraded to functional defensive shields.

- **Surface Preparation:** Abrasive blasting of the external faces is required to achieve a requisite surface profile, stripping the vulnerable polyester powder coats.
- **Aegis Glaze Application:** Application of a polysiloxane or potassium silicate binder heavily doped with YInMn Blue pigment and Tantalum Pentoxide (Ta_2O_5).⁴
- **Mechanism of Action:** The Tantalum doping drastically increases the dielectric breakdown voltage of the surface, repelling localized electrical leaders and preventing plasma arc attachment during ambient electrostatic discharge. Concurrently, the YInMn pigment rejects the thermal load, keeping the underlying steel below its critical annealing temperature during external thermal events.⁴

4.4 Remediation of Gate Automation and Induction Loops

Automated entry points utilizing LC oscillator induction loops²³ must be decoupled from the system to prevent EMP burnout and subsequent gate seizure.

- **Bypass Procedure:** The capacitive wiring connecting the induction loop to the gate controller is severed.
- **Optical Replacement Architecture:** Install passive, non-magnetic optical arrays (LIDAR or IR break-beams) housed in ZrB_2 composite enclosures.
- **Sub-Surface Piezoelectric Alternative:** For applications requiring physical sub-surface detection, install piezoelectric pressure transducers embedded in BFRP/epoxy matrices. These sensors generate a voltage strictly via mechanical stress (vehicle weight) without relying on magnetic inductance, rendering them completely immune to electromagnetic flux disruption.⁷

5. Intermediate Replacement Fundamentals: Component Substitution

Where immediate retrofits are insufficient, but full system replacement is unfeasible,

intermediate component substitution targets the most critical failure points of existing commercial barriers.

5.1 Remediation of the Ameristar Aegis Architecture

The Ameristar Aegis II and Aegis Plus systems rely on an internally secured retaining rod within the ForeRunner rail.¹⁰ This rod is the primary conductor and failure point for Liquid Metal Embrittlement.

- **Extraction and Substitution:** The steel retaining rods must be extracted from the rail cavities. They are replaced by precision-pultruded Carbon Fiber rods encased in a thick PTFE (Polytetrafluoroethylene) or Yttria-Stabilized Zirconia (YSZ) sleeve.
- **Biomechanical/Structural Equivalency:** The carbon core provides extreme flexural rigidity, maintaining the structural integrity and high-angle biasability of the fence. The YSZ/PTFE sleeve guarantees absolute electrical isolation between the internal rod and the steel pickets⁵, entirely eliminating the LME threat.

5.2 Decoupling Crash-Rated Cable Systems (Tymetal / Gibraltar)

The continuous high-tension steel cables used in M50/K12 anti-ram systems¹⁵ must be neutralized.

- **Dielectric Cable Substitution:** The heavy steel cables are unspooled and replaced with Bio-based Dyneema SK99 (Ultra-High-Molecular-Weight Polyethylene - UHMWPE) or Vectran synthetic ropes.⁵
- **Mechanical and Electrical Properties:** A 1-inch Dyneema SK99 rope exhibits a minimum breaking load (118 kN) that exceeds equivalent steel wire rope, while possessing a volume resistivity $> 10^{14} \Omega \cdot \text{cm}$.⁵ It is entirely invisible to electromagnetic flux.
- **Aegis-Wall Thermal Encapsulation:** Because UHMWPE is susceptible to thermal degradation (melting point $\approx 150^\circ \text{C}$), the load-bearing synthetic core is encapsulated within a flexible Aegis-Wall Blanket.⁴ This woven sheath consists of continuous basalt fibers impregnated with a Silicon Carbide (SiC) and YInMn Blue slurry.⁴ This sheath provides an ablative, high-temperature thermal barrier ($> 1000^\circ \text{C}$) against flash fires and DEW lasers, protecting the kinetic arresting power of the synthetic core without reintroducing metallic elements.⁴

5.3 Neutralization of Substation Grounding Loops

The mandatory 2/0 AWG copper bonding mandated by CEC 36-312¹⁹ must be physically decoupled to prevent the fence from becoming a radiating element during GPR events.

- **Isolation Protocol:** The copper taps connecting the fence posts to the ground grid are severed.
- **Dielectric Anchoring:** The existing steel posts are unbolted and remounted on "Densolith" standoffs. Densolith is a polymer concrete utilizing Barite and Zirconia

aggregates to achieve extreme mass and compressive strength, anchoring the posts while breaking the electrical connection to the earth.⁵ The perimeter is no longer part of the station's fault-dissipation network, neutralizing the step-and-touch hazard.

6. Full System Overhaul: The Aegis-Class Dielectric Barrier System

For new installations, high-threat environments, or total perimeter replacements, the architecture must transition fully to Aegis-Class specifications. This involves the mass fabrication of industrial deterrent fencing entirely devoid of conductive elements.

6.1 Pultrusion and Thermoforming of BFRP Structures

The complete BFRP perimeter system is fabricated using an advanced continuous pultrusion process.

- **The "Magma" Bath and Die:** Continuous basalt fiber rovings are drawn from a 200-spool creel library and passed through an impregnation bath containing Elium thermoplastic resin. The resin is maintained at a precise viscosity of 150 cPs at $25^{\circ}C$ to ensure complete fiber wet-out at the molecular level.
- **Polymerization:** The impregnated fibers pass through a heated 3-zone "Forge" die ($60^{\circ}C/140^{\circ}C/80^{\circ}C$) to polymerize the matrix and form the final geometric cross-sections—such as the 1" square pickets and 1.75" rails mandated by industrial specifications.
- **On-Site Thermoforming:** Unlike traditional thermoset composites (e.g., epoxy or vinyl ester), the thermoplastic nature of the Elium matrix resolves the "Composite Logistics Problem". Contractors can utilize portable induction or hot air sleeves to heat the bending zones of the rails to $150 - 180^{\circ}C$ (above the glass transition temperature, T_g). Within 30-60 seconds, the rails can be reshaped to conform to modest changes in grade or prominent hills, mirroring the rackability of standard steel systems.

6.2 Fastening and Assembly Protocols

The intersection of pickets and rails must not introduce micro-antennas.

- **Polymer Fastening:** Panel brackets are injection-molded from Polyether Ether Ketone (PEEK) reinforced with 30% short basalt fibers. Fastening is executed exclusively using RAPTOR® polymer composite nails or High-Toughness Zirconia (ZrO_2) structural screws.
- **Ultrasonic Welding:** Alternatively, because the Elium matrix is thermoplastic, the structural joints can be fused using ultrasonic welding.⁸ High-frequency acoustic friction melts the matrix locally, fusing the components into a seamless, monolithic, hardware-free dielectric grid.⁸

6.3 Circular Economy: Solvolysis and Resource Reclamation

The Aegis-Class perimeter system operates under the "Phoenix Protocol," ensuring absolute circularity of materials at the end of their operational lifecycle.

- **Depolymerization via Solvolysis:** The BFRP components are not destined for landfills. They are immersed in a solvent (e.g., sub-critical water or acetic acid) and heated to $200 - 350^{\circ}C$. This process breaks the ester/amide bonds, depolymerizing the Elium matrix back into its monomer state.
- **Fiber Recovery:** The continuous basalt fibers are released completely intact, retaining 90% of their original tensile strength. The recovered monomer is re-polymerized, and the undamaged basalt fibers are re-carded and spun into new rovings.
- **Indium Harvesting:** The YInMn Blue exterior glazes are subjected to acid leaching (H_2SO_4). The Indium is captured via Solvent Extraction (SX) using Di-(2-ethylhexyl) phosphoric acid (D2EHPA), precipitated as Indium Hydroxide, and calcined to regenerate pure Indium Oxide for future shielding applications.⁸

7. Conclusion

The continued reliance on ferromagnetic and conductive materials for perimeter security constitutes an unacceptable operational risk. Steel and aluminum fences, crash cables, and loop detectors are mathematically deterministic failure points under the magnetohydrodynamic forces of a Carrington-class CME or the spectral loading of Directed Energy. The physics of Joule heating, Skin Effect concentration, and plasma arcing cannot be mitigated through thicker steel or heavier grounding cables; the conductive pathway itself must be entirely eradicated. The implementation of the Stellar-Aegis Protocol—utilizing Basalt Fiber Reinforced Polymers, Zirconium Diboride ceramics, and YInMn Blue spectral shielding—provides a comprehensive, scientifically rigorous replacement architecture. By systematically deploying the immediate decoupling retrofits, transitioning intermediate components, and ultimately building the Dielectric Citadel from continuous pultruded basalt, perimeter infrastructure achieves total immunity to induction, thermal overload, and electromagnetic disruption. The transition from the conductive vulnerabilities of the Iron Age to the engineered isolation of the Dielectric Age is a non-negotiable mandate for the survival of critical infrastructure.

Works cited

1. Industrial Fences - Ultra Aluminum, accessed June 4, 2026, <https://www.ultrafence.com/industrialfences.html>
2. What is Industrial Security Fence? - FENCE DEPOT, accessed June 4, 2026, <https://www.fencedepots.com/what-is-industrial-security-fence.html>
3. AMERISTAR® PERIMETER SECURITY USA INC. AEGIS II® - Heavy Industrial Steel Ornamental Fence System, accessed June 4, 2026, https://resources.finalsite.net/images/v1697846900/lawndalek12caus/yzbf3hiewi3u7ojpdhrk/TwainSMF_Specification-AegisII_V034.pdf

4. 09CSMProBridge2025.pdf
5. 03CSMVessel0000000001to7.pdf
6. 3.5 Electromagnetic Fields and Electromagnetic Interference - Federal Railroad Administration, accessed June 4, 2026,
https://railroads.dot.gov/sites/fra.dot.gov/files/fra_net/2494/03_5.pdf
7. 07CSMFabAegisHome2025.pdf
8. 08CSMPRO00000001 Robot Resilience Proposal_ Aegis Integration.pdf
9. 02CSMVessel0000000008 Rebuilding Ships for Carrington Events.pdf
10. Aegis II | Ameristar, accessed June 4, 2026,
<https://www.ameristarperimeter.com/us/en/products/ornamental-fence-gates/aegis/aegis-ii>
11. Aegis Plus | Ameristar, accessed June 4, 2026,
<https://www.ameristarperimeter.com/us/en/products/ornamental-fence-gates/aegis/aegis-plus>
12. ARCHITECTURAL FENCE GUIDE, accessed June 4, 2026,
https://dm-fencing.com/wp-content/uploads/2025/03/brochure-ameristar-architectural-fence-guide-opt-optimized-pdfresizer.com_.pdf
13. industrial ornamental steel fence - Ameristar, accessed June 4, 2026,
<https://www.ameristarperimeter.com/us/en/content-fragments/products/ornamental-fence-gates/aegis/aegis-ii/assets/product-information/Brochure-Aegis.pdf>
14. ARCHITECTURAL FENCE GUIDE, accessed June 4, 2026,
<https://files.aptvitvcdn.com/GRQO7mo8da-1811/docs/Architectural-Fence-Guide.pdf>
15. TCF-M50-P1 (K12) - TYMETAL, accessed June 4, 2026,
<https://www.tymetal.com/commercial-crash-rated-barriers/crash-fence/tcf-m50-p1-k12/>
16. Atlas S | Crash Rated Cable Barrier - Ameristar, accessed June 4, 2026,
<https://www.ameristarperimeter.com/us/en/products/high-security-fence/atlas/atlas-cable-fence-m50>
17. Gibraltar Cable Barrier System, accessed June 4, 2026,
<https://www.gibraltarglobal.com/>
18. Crash Rated Fencing and Perimeter Barriers | G-FORCE Series | Gibraltar, accessed June 4, 2026,
<https://www.gibraltarperimetersecurity.com/crash-rated-perimeter-fencing/>
19. Substation Fence Earthing: Touch Voltage Analysis and CEC 36-312 Requirements, accessed June 4, 2026,
<https://industrialmonitordirect.com/blogs/knowledgebase/substation-fence-earthing-touch-voltage-analysis-and-cec-36-312-requirements>
20. Substation grounding - Sac State Scholars, accessed June 4, 2026,
https://scholars.csus.edu/view/pdfCoverPage?instCode=01CALS_USL&filePid=13246954440001671&download=true
21. 6B.6—Substation Grounding - PacifiCorp, accessed June 4, 2026,
https://www.pacificorp.com/content/dam/pcorp/documents/en/pacificorp/suppliers/rfps/2017r-rfp-docs-and-appendices/A-7.11_Part_6B_6_Substation_Grounding.pdf
22. Substation Ground Grid Design Guide Standard No.: SF0201 Rev.06 Effect -

Entergy Arkansas, accessed June 4, 2026,

<http://www.entergyarkansas.com/wp-content/uploads/2025/06/Appendix-B-2-Solar-BOT-Scope-Book-Appendix-12-Substation-Grounding.pdf>

23. Induction loop for gates, doors and barriers - at doorautomation24, accessed June 4, 2026, <https://www.doorautomation24.com/Loop-Detector/>
24. Induction loop | YourStudent Gemini Wiki - Fandom, accessed June 4, 2026, https://yourstudent-gemini.fandom.com/wiki/Induction_loop
25. 04CSMManVibration2025.pdf
26. 05CSMFabAegisMetal1Chrome2025 (1).pdf
27. Ametco Manufacturing | Steel and Aluminum Fence and Gates, accessed June 4, 2026, <https://www.ametco.com/>