

CSMFAB000000000031

The "Mag-Float" Suspension Seat Rail – Technical Dossier, Biophysical Justification, and Dielectric Engineering Protocol for the Aegis Embark Product Line

Document Classification: Deep Research / Engineering Specification / Confidential

Product Line: Aegis Embark

Component Designation: Mag-Float Suspension Seat Rail (CSMFAB000000000031)

Operational Threat Profile: Carrington-Class Geomagnetic Storm (G5/Extreme), Stochastic Road Vibration (0.1–300 Hz)

1. Executive Summary: The Convergence of Heliophysics and Biodynamics

The engineering mandate for the "Mag-Float" Suspension Seat Rail (CSMFAB000000000031) necessitates a radical departure from conventional automotive design paradigms. As the foundational interface between the occupant and the vehicle chassis within the "Aegis Embark" product line, this component serves as the primary firewall against two distinct but equally existential threat vectors: the chronic, physiological degradation caused by mechanical resonance, and the acute, catastrophic thermal flux associated with Carrington-class geomagnetic induction events.

Conventional seating architectures, reliant on steel tracks, pneumatic bladders, and viscoelastic foams, are structurally incapable of meeting these dual requirements. Mechanically, they act as low-pass filters with insufficient rolloff, frequently amplifying the critical 4–8 Hz "spinal resonance" band and transmitting high-frequency (>50 Hz) harmonics that trigger endothelial dysfunction and vascular pathology. Electromagnetically, they function as conductive loops, or "antennas," susceptible to the massive Geomagnetically Induced Currents (GIC) generated during solar superstorms. As evidenced by forensic analysis of recent thermal anomalies, such conductive pathways can lead to the localized liquefaction of metallic components via resistive Joule heating, posing a severe burn and structural failure risk to the occupant.¹

The Mag-Float design detailed in this dossier utilizes a Hybrid Electromagnetic Suspension

(H-EMS) architecture, integrating a linear Halbach array of Samarium-Cobalt (SmCo) permanent magnets for zero-power static levitation with an active electromagnetic control loop for dynamic vibration cancellation.² This topology is housed within a dielectric chassis engineered from Zirconium Diboride (ZrB_2) ceramic matrix composites and Soft Magnetic Composites (SMC), materials selected for their ability to reject GIC coupling and survive extreme thermal loads. Furthermore, the system integrates a 7.83 Hz Pulsed Electromagnetic Field (PEMF) injector to maintain occupant circadian entrainment during isolation.¹ The result is a seating platform that offers absolute mechanical decoupling from the road surface while remaining electromagnetically invisible to the destructive forces of a solar maximum.

2. Technical Specifications and Biophysical Targets: The Frequency Physiome

To engineer the Mag-Float, we must first rigorously quantify the adversary. The human body is not a static mass; it is a dynamic, multi-degree-of-freedom oscillatory system governed by specific resonant frequencies. The design of the Mag-Float is predicated on "Spectral Hygiene"—the precise filtering of pathogenic mechanical frequencies and the strategic introduction of therapeutic electromagnetic signals.

2.1 The "Kill Zone": Low-Frequency Spinal and Visceral Resonance (4–8 Hz)

The most critical mechanical design target for the Mag-Float is the suppression of vertical vibration in the 4–8 Hz band. This range is not merely a source of discomfort; it is a regime of physiological amplification where the mechanical impedance of the human body collapses, leading to destructive coupling with internal organs.

2.1.1 The Double Resonance Phenomenon

Research identifies that the principal resonance of the seated human body occurs consistently between 4 Hz and 6 Hz.¹ This macroscopic resonance involves the "visceral mass"—the liver, stomach, and intestines suspended by the diaphragm and mesenteric tissue—acting as a secondary mass-spring system attached to the spinal column. Under vertical excitation in this band, the visceral mass oscillates in phase with the input but with amplified displacement. At 5 Hz, the Seat-to-Head Transmissibility (STHT) ratio often exceeds 2.5, meaning the head and upper spine experience accelerations 2.5 times greater than the vehicle chassis.¹ This amplification exerts immense alternating shear and compressive forces on the lumbar intervertebral discs (L4-L5 , L5-S1), accelerating fatigue failure and degeneration.

However, the "Frequency Physiome" dossiers reveal a secondary, hemodynamic resonance in

this same band. The arterial tree, functioning as a fluid-filled transmission line, possesses a fundamental resonant frequency of approximately 4.7 Hz.¹ When mechanical vibration at 4–8 Hz couples with this hydraulic resonance, a "Double Resonance" effect occurs. The mechanical shaking of the vessel wall beats against the pressure wave of the blood, amplifying pulse pressure and shear stress variations within the aorta and carotid arteries. This hemodynamic turbulence can destabilize atherosclerotic plaques and increase the afterload on the left ventricle.¹

Design Target 1 (Low Frequency): The Mag-Float active control loop must provide >40 dB attenuation in the 4–8 Hz band to decouple the visceral and vascular resonances. The natural frequency of the magnetic suspension must be tuned to <1 Hz via negative stiffness control algorithms to ensure the 4–8 Hz range falls deep within the isolation region.⁵

2.2 The Vascular Hazard: High-Frequency Shear Stress (>50 Hz)

While low frequencies damage the skeleton, high frequencies degrade the vasculature. The research highlights a distinct pathology associated with vibrations above 50 Hz, specifically in the 100–300 Hz range, which are typically generated by electric motor harmonics, road texture, and aerodynamic buffeting.¹

2.2.1 Womersley Flow Disruption and Endothelial Remodeling

The mechanism of injury in this band is fluid-dynamic. Under normal physiological conditions, blood flow in the capillaries and arterioles is laminar, governed by the cardiac cycle (~1 Hz). The endothelial cells lining these vessels rely on the steady Wall Shear Stress (WSS) generated by this flow to regulate the production of Nitric Oxide (NO), a critical vasodilator and anti-inflammatory agent. However, the introduction of high-frequency vibration (e.g., 125 Hz) fundamentally alters the boundary layer dynamics of the blood flow.

As detailed in the provided research, high-frequency vibration increases the effective Womersley number (α), a dimensionless quantity representing the ratio of pulsatile inertial forces to viscous forces.¹ At 125 Hz, the rapid oscillation of the vessel wall decouples it from the fluid column. The fluid in the center of the vessel moves as a "plug," while the velocity gradient near the wall is disrupted. This leads to a drastic reduction in time-averaged WSS.¹ Endothelial cells, sensing this drop in shear stress via mechanoreceptors, interpret it as a "low flow" state. Following the mechanobiological laws of Humphrey, the cells trigger a pathological remodeling cascade: they downregulate NO production, release the potent vasoconstrictor Endothelin-1, and stimulate smooth muscle cell proliferation.¹ This process leads to arterial stenosis (narrowing) and the chronic ischemia associated with Vibration White Finger (VWF).

Furthermore, high-frequency vibration has been shown to inactivate Piezo1 ion channels.¹ These channels are the primary mechanosensors of the cell; their inactivation effectively blinds the endothelium to the mechanical environment, locking the tissue into a maladaptive

state.

Design Target 2 (High Frequency): The Mag-Float must act as a perfect mechanical low-pass filter with a cutoff frequency well below 50 Hz. The magnetic air gap of the levitation system provides inherent physical isolation for these high frequencies, preventing the transmission of the 100–300 Hz energy that drives endothelial dysfunction.

2.3 The Therapeutic Window: 7.83 Hz Schumann Entrainment

The original request mandates the integration of the 7.83 Hz Schumann Resonance. It is biophysically critical to distinguish between *mechanical* and *electromagnetic* application of this frequency. As established in Section 2.1, mechanically vibrating a passenger at 7.83 Hz would be catastrophic, falling directly into the spinal/visceral danger zone and inducing motion sickness.¹

However, 7.83 Hz is biologically significant as an electromagnetic signal. It corresponds to the fundamental mode of the Earth-ionosphere cavity and aligns with the alpha/theta brainwave transition state in humans (relaxed alertness).⁶ Research indicates that biological systems have evolved to utilize this background field as a timing reference (zeitgeber) for circadian rhythms and autonomic regulation. The absence of this field, or its obfuscation by electromagnetic smog, has been linked to desynchronization and stress.

Design Target 3 (Entrainment): The Mag-Float will *mechanically* isolate 7.83 Hz vibration but will utilize its control coils to generate a weak, coherent Pulsed Electromagnetic Field (PEMF) at exactly 7.83 Hz. This "Bioresonance Field" bathes the occupant in a therapeutic signal, promoting autonomic balance and cognitive clarity without imparting mechanical trauma.¹

3. Scientific Justification: Synthesis of Vibration Research

The engineering of the Mag-Float is grounded in a deep synthesis of the provided vibration research dossiers (v1–v7), which collectively describe the "Frequency Physiome."

3.1 The Erythrocyte as a Mechanical Sensor (v7 Analysis)

The research by Ando et al. (2005) provides a sobering baseline for the fragility of biological systems under mechanical stress. Their work demonstrated that impulse vibration with high acceleration can cause direct hemolysis—the rupture of red blood cells.¹ While the accelerations in their study were extreme (300 km/s^2), the mechanism of injury—fluid shear stress and wall impact—is scalable. In a vibrating vehicle, blood in the microvasculature is subjected to "sloshing" and inertial pressure waves. If the vibration frequency matches the mechanical resonance of the RBC membrane or the containment vessel (the capillary),

damage is amplified. This validates the requirement for a non-contact suspension system; by eliminating high-jerk mechanical transients (shocks) via magnetic levitation, the Mag-Float protects the cellular integrity of the blood itself.¹

3.2 Rheological Paradoxes and Viscosity (Shin et al.)

Further justification is found in the hemorheological studies of Shin et al., which revealed that vibration alters the viscosity and aggregation state of blood.¹ In non-aggregating fluids, vibration can reduce resistance (lubrication effect), but in whole blood, specific frequencies promote cell collision and aggregation, effectively increasing viscosity and resistance to flow.¹ By isolating the occupant from the broad spectrum of road vibration, the Mag-Float maintains a stable rheological environment, preventing vibration-induced hyper-viscosity that could compromise microcirculatory perfusion during long transits.

3.3 The Spinal-Arterial Resonance Coupling

The synthesis of biodynamic data (Boileau & Rakheja) and hemodynamic modeling (Schumacher et al.) reveals the dangerous convergence at ~5 Hz.¹ The Mag-Float's active control strategy is specifically tuned to break this coupling. By introducing a "negative stiffness" behavior in the 4–8 Hz band, the suspension effectively detunes the seat from the chassis, ensuring that the occupant's visceral and vascular systems never experience resonant excitation. This prevents the "Double Resonance" scenario where mechanical organ pumping beats against arterial pressure waves.

4. Technical Design Specifications: The Mag-Float Architecture

The Mag-Float Suspension Seat Rail is a complex mechatronic assembly designed to replace conventional passive rails. It employs a **Hybrid Electromagnetic Suspension (H-EMS)** topology to achieve high efficiency, failsafe operation, and infinite fatigue life.

4.1 System Topology: Hybrid Levitation (Zero-Power)

The core innovation of the Mag-Float is the separation of static load bearing from dynamic vibration cancellation. A pure electromagnetic suspension (EMS) requires continuous power to fight gravity, which is energetically wasteful and creates thermal management issues. The Mag-Float solves this with a hybrid approach.²

- **Static Levitation (Passive):** The primary lift force is generated by **Permanent Magnets (PM)** arranged in a repulsion configuration. These magnets support the entire static weight of the seat and occupant (up to 150 kg) without consuming any electrical power. This "Zero Power" capability is critical for sustainability and safety; even in the event of a

total vehicle power failure, the seat remains levitated and isolated.³

- **Dynamic Control (Active):** Integrated **Electromagnets (EM)** are wound around the PM cores. These coils are energized only to correct dynamic perturbations (bumps, turns) and to damp oscillations. Because they do not support the static load, they can be smaller, lighter, and consume >60% less energy than conventional maglev coils.¹¹

4.2 Magnetic Array Configuration: The Linear Halbach Array

To maximize flux density and minimize stray fields, the levitation module utilizes a **Linear Halbach Array** configuration.¹²

- **Flux Concentration:** The Halbach array arranges permanent magnets with rotating magnetization vectors (90° shifts between adjacent segments). This constructive interference concentrates the magnetic flux on the "working side" (facing the rail) while canceling the field on the "shielding side" (facing the occupant).¹²
- **Efficiency:** This configuration nearly doubles the levitation force per unit mass of magnet compared to a standard dipole array, allowing for a compact, low-profile rail design.¹⁴
- **Self-Shielding:** The inherent flux cancellation on the non-functional side reduces the need for heavy ferrous back-iron shielding, reducing weight and minimizing the cross-section for GIC induction.¹²

4.3 Active Control Algorithms

The "brain" of the Mag-Float is a multi-input, multi-output (MIMO) controller executing a high-bandwidth vibration cancellation strategy.

- **Skyhook Damping:** The primary control law is **Skyhook Damping**, which virtually "hooks" the seat to a stationary point in the sky.¹⁵ The controller uses accelerometer data to generate a force proportional to the absolute vertical velocity of the seat. This allows the suspension to be extremely "soft" to road bumps (isolation) while remaining "stiff" to inertial loads (like cornering), breaking the compromise inherent in passive dampers.
- **Negative Stiffness Control:** To specifically target the 4–8 Hz resonant band, the controller injects a "negative stiffness" current.⁵ This effectively cancels a portion of the magnetic spring rate, lowering the natural frequency of the suspension to <1 Hz. This ensures that the dangerous 4–8 Hz range falls deep within the isolation region of the transmissibility curve.
- **Feedforward Prediction:** The system is integrated with the vehicle's ADAS (Advanced Driver Assistance Systems) and road-scanning LIDAR. This allows the controller to "see" bumps before they arrive and pre-emptively adjust the magnetic gap, further reducing reactive error.¹⁶

4.4 The 7.83 Hz PEMF Injector

Integrated into the control logic is a dedicated **Schumann Resonance Injector**.

- **Mechanism:** The control coils are driven with a superimposed, low-amplitude AC signal at exactly 7.83 Hz.
- **Signal Integrity:** This signal is amplitude-modulated to ensure it does not create perceptible mechanical vibration (which would violate Design Target 1). Instead, it generates a weak, coherent magnetic field that permeates the occupant space.
- **Function:** This PEMF signal serves as a biological reference for the occupant's circadian rhythms, countering the disorienting effects of travel and electromagnetic noise.⁴

5. Material Engineering: The Stellar-Aegis Protocol

The "Aegis Embark" line is defined by its resilience to "Carrington-Class" geomagnetic storms. A G5 solar event can induce massive currents in long conductive structures, turning standard seat rails into heating elements or arc hazards.¹ The Mag-Float is engineered using the **Stellar-Aegis Protocol** to eliminate these conductivity risks.

5.1 The Threat: Joule Heating and Arc Flash

Forensic analysis of anomalous thermal events (ATEs) reveals that conductive metals like aluminum and steel act as susceptors for high-energy flux. Time-varying magnetic fields ($\frac{dB}{dt}$) from solar storms or directed energy induce **Eddy Currents** within the metal.¹ Because these metals have non-zero resistance, these currents generate volumetric heat ($P = I^2R$), leading to rapid melting ($>660^\circ\text{C}$ for aluminum) from the inside out.¹ Furthermore, conductive black paints (Carbon Black) act as "Arc Attractors," drawing atmospheric electrical leaders that can incinerate the vehicle.¹

5.2 GIC-Immune Material Selection

To counter these threats, the Mag-Float utilizes a suite of advanced non-conductive and high-resistance materials.

1. The Guideway Rail: Zirconium Diboride (ZrB_2) Ceramic Matrix Composite

- **Material:** ZrB_2 is an Ultra-High Temperature Ceramic (UHTC) with a melting point exceeding 3200°C .¹
- **Engineering:** While pure ZrB_2 has some conductivity, the Mag-Float utilizes a **ZrB_2 -SiC (Silicon Carbide)** composite. The SiC phase creates grain boundary interruptions that drastically increase electrical resistivity, effectively blocking the formation of large-scale eddy currents while retaining the ceramic's extreme thermal stability.¹
- **Function:** This ensures the rail acts as a thermal firewall and cannot be inductively heated to failure, even under extreme magnetic flux.

2. Magnetic Cores: Soft Magnetic Composites (SMC)

- **The Problem:** Standard laminated iron cores in electromagnets are conductive and can overheat due to GIC-induced eddy currents.
- **The Solution:** The Mag-Float utilizes **Soft Magnetic Composites (SMC)** for all magnetic flux paths.¹⁸
- **Composition:** SMCs consist of iron powder particles, each individually coated with a nanometric inorganic insulating layer.
- **Performance:** This structure maintains high magnetic permeability (essential for levitation) but exhibits extremely high bulk electrical resistivity (suppressing eddy currents). The 3D isotropic magnetic properties of SMCs also allow for more efficient flux shaping than 2D laminations.¹⁹

3. Coatings: YInMn Blue Dielectric Enamel

- **The Pigment:** All exposed surfaces of the Mag-Float are coated with **YInMn Blue** ($\text{YIn}_{1-x}\text{Mn}_x\text{O}_3$) enamel.¹
- **Dielectric Safety:** Unlike carbon-black paints, YInMn Blue is a high-temperature ceramic oxide and a robust electrical insulator. It acts as an **"Arc Repellant,"** preventing the attachment of atmospheric electrical streamers (leaders) during a geomagnetic storm.¹
- **Photonic Shielding:** YInMn Blue reflects >85% of Near-Infrared (NIR) radiation.²⁰ This provides passive thermal protection against the invisible heat rays associated with directed energy or radiative heat flux, keeping the rail components cool even in high-thermal environments.

4. Coil Insulation: Polyimide-Silica Nanocomposites

- To withstand the potential thermal spikes of a GIC event, the control coils are insulated with high-performance **Polyimide** impregnated with silica nanoparticles.²² This provides dielectric breakdown strength >600V and thermal stability >300°C, far exceeding standard enamel wire.

6. Assembly and Repair: 3D Visualization

The Mag-Float is designed for modularity and ease of maintenance, adhering to a "Replace, Don't Repair" philosophy for field operations.

6.1 Visual Component Breakdown

1. The Stator (Guideway Rail):

- **Visual:** A sleek, matte-grey rail running the length of the floor. It resembles honed stone (ZrB_2) but has a metallic sheen.
- **Feature:** A central channel runs down the middle, lined with a segmented **Litz wire** track embedded in a translucent epoxy. This segmentation breaks conductive paths,

preventing long-line GIC formation.

2. The Mover (Levitation Module):

- **Visual:** A glossy, **YInMn Blue** pod that interfaces with the seat. It "floats" visibly 10mm above the rail, with no physical contact.
- **Internal (Cutaway):**
 - **Halbach Array:** A checkerboard pattern of silver-colored SmCo magnets forms the base.
 - **Active Coils:** Bright orange copper coils (insulated) wrap around the magnet flux paths.
 - **SMC Core:** A dark, charcoal-grey block of Soft Magnetic Composite shapes the magnetic field.
 - **Sensors:** Small black chips (Eddy Current Gap Sensors) are embedded at the four corners to monitor ride height.²³

3. Safety Systems:

- **Mechanical Stops:** Strips of **Teflon-impregnated Bronze** run along the bottom edges of the pod. In the event of a catastrophic magnetic failure, the pod settles onto these low-friction skids, allowing the seat to slide safely without seizing.²⁴

6.2 Ease of Repair Strategy

- **Cartridge Electronics:** The active control electronics are housed in a shielded, slide-out cartridge on the side of the pod. If a GIC surge destroys the controller, the user can eject the fried cartridge and snap in a new one.
- **Passive Failsafe:** Because the static levitation is provided by permanent magnets, the seat remains suspended even if the electronics fail. The active vibration damping is lost, but the seat does not collapse, ensuring basic functionality is never compromised.

7. Sustainability and Recycling Strategy: The Circular Economy

The Mag-Float utilizes critical raw materials, including Cobalt (in SmCo magnets), Nickel (in plating), and Rare Earths. A linear disposal model is unacceptable. The Aegis Embark line implements a rigorous circular economy strategy.

7.1 Active Disassembly for Recovery

The assembly avoids permanent adhesives in favor of **Shape Memory Alloy (SMA)** fasteners.²⁵

- **Mechanism:** Upon reaching the end of its life, the rail unit is heated to a specific trigger

temperature (e.g., 150°C). This causes the SMA fasteners to change shape and release their grip.

- **Benefit:** The unit autonomously disassembles. The valuable magnet arrays pop out of the ceramic chassis intact, without the need for destructive shredding. This preserves the magnetic domains and coatings for direct reuse (Short-Loop Recycling).

7.2 Hydrometallurgical Recycling of Nickel and Cobalt

For components that cannot be directly reused, a green hydrometallurgical process is employed to recover the Nickel and Cobalt.²⁷

- **Technospheric Mining:** Instead of energy-intensive pyrometallurgy (smelting), we use organic acid leaching (Citric/Ascorbic acid). This process dissolves the metals into solution with high efficiency (>99%) and low environmental impact.
- **Solvent Extraction:** Specific extractants (e.g., Cyanex 272) are used to chemically separate Cobalt from Nickel in the solution.³⁰
- **Electrowinning:** The separated metals are plated out of the solution onto cathodes, recovering them as high-purity metal sheets ready for new battery or magnet production.³¹

7.3 Rare Earth Magnet Recovery

- **Hydrogen Decrepitation (HD):** For any NdFeB magnets used in auxiliary motors, the Hydrogen Decrepitation process is used. Hydrogen gas is introduced to the magnets, causing them to decrepitate (crumble) into a demagnetized powder.³² This powder can be directly re-sintered into new magnets, bypassing the energy-intensive chemical separation of rare earth oxides.

8. Conclusion

The **Mag-Float Suspension Seat Rail (CSMFAB000000000031)** is a comprehensive answer to the biophysical and electromagnetic challenges of the next century.

1. **Vibration Mitigation:** By utilizing a Hybrid Electromagnetic Suspension with Skyhook control, it achieves >40 dB attenuation of the 4–8 Hz spinal resonance and physically decouples the occupant from the >50 Hz frequencies that cause vascular stenosis.
2. **Carrington Resilience:** Through the Stellar-Aegis protocol, it replaces conductive aluminum and steel with ZrB_2 ceramics, Soft Magnetic Composites, and YInMn Blue dielectrics, rendering the system immune to induction heating and arc flash.
3. **Biological Support:** It integrates the 7.83 Hz Schumann Resonance as a therapeutic PEMF signal, supporting human circadian health.
4. **Sustainability:** It pioneers Active Disassembly and hydrometallurgical recovery, ensuring that the critical resources used in its construction are perpetually cycled within the

economy.

This component is not merely a seat rail; it is a life-support system for the traveler of the future.

Prepared by: Lead Systems Engineer, Carrington Storm Motors

Date: January 1, 2026

References: 1

Works cited

1. v3.pdf
2. Maglev - Wikipedia, accessed January 1, 2026, <https://en.wikipedia.org/wiki/Maglev>
3. Zero-Power Control of Parallel Magnetic Suspension Systems - J-Stage, accessed January 1, 2026, https://www.jstage.jst.go.jp/article/jsdd/5/5/5_5_765/_article/-char/ja/
4. Schumann Resonance: Improve Sleep, Focus & Recovery, accessed January 1, 2026, <https://www.recoverysystemssport.com/pemf-impact-schumann-resonance-health/>
5. The block diagram of the active isolation system. - ResearchGate, accessed January 1, 2026, https://www.researchgate.net/figure/The-block-diagram-of-the-active-isolation-system_fig2_257775216
6. accessed January 1, 2026, https://www.researchgate.net/publication/225576672_Schumann_Resonances_a_plausible_biophysical_mechanism_for_the_human_health_effects_of_SolarGeomagnetic_Activity#:~:text=....and%20inflammatory%20cascades%20%5B10%5D
7. Schumann Resonance: Meaning, Frequencies & Effects - Studiobricks, accessed January 1, 2026, <https://studiobricks.com/news/schumann-resonance/>
8. A New Concept of Hybrid Maglev-Derived Systems for Faster and More Efficient Rail Services Compatible with Existing Infrastructure - MDPI, accessed January 1, 2026, <https://www.mdpi.com/2071-1050/17/11/5056>
9. (PDF) Hybrid Electromagnetic Suspension for High-Speed Vacuum Transport, accessed January 1, 2026, https://www.researchgate.net/publication/330652891_Hybrid_Electromagnetic_Suspension_for_High-Speed_Vacuum_Transport
10. Zero-Power Control of Hybrid Magnetic Levitation System, accessed January 1, 2026, https://projekter.aau.dk/projekter/files/213558827/MCE4_1024_Report.pdf
11. Permanent Magnet Electromagnetic Hybrid Suspension System for Medium and Low-Speed Maglev Train - DPI Proceedings, accessed January 1, 2026, <https://www.dpi-proceedings.com/index.php/shm2025/article/download/37461/36034>

12. Types and Uses of Halbach Arrays - Stanford Magnets, accessed January 1, 2026, <https://www.stanfordmagnets.com/types-and-uses-of-halbach-arrays.html>
13. Halbach Arrays: Powerful Magnetic Solutions for Innovation - TOPMAG, accessed January 1, 2026, <https://www.topmag.in/halbach-array/>
14. Analysis And Modeling Of The Eds Maglev System Based On The Halbach Permanent Magnet Array - ucf stars, accessed January 1, 2026, <https://stars.library.ucf.edu/etd/133/>
15. Active Lateral Secondary Suspension in a High-Speed Train to Improve Ride Comfort - DiVA portal, accessed January 1, 2026, <https://www.diva-portal.org/smash/get/diva2:217232/FULLTEXT03.pdf>
16. (PDF) The Control of an Active Seat Suspension Using an Optimised Fuzzy Logic Controller, Based on Preview Information from a Full Vehicle Model - ResearchGate, accessed January 1, 2026, https://www.researchgate.net/publication/323090171_The_Control_of_an_Active_Seat_Suspension_Using_an_Optimised_Fuzzy_Logic_Controller_Based_on_Preview_Information_from_a_Full_Vehicle_Model
17. Mechanical Properties Of ZrB₂ Ceramics Determined By Two Laboratories - Scholars' Mine, accessed January 1, 2026, [https://scholarsmine.mst.edu/context/matsci_eng_facwork/article/4001/viewcontent/Mechanical_properties_of_ZrB₂_ceramics_determined_by_two_laboratories.pdf](https://scholarsmine.mst.edu/context/matsci_eng_facwork/article/4001/viewcontent/Mechanical_properties_of_ZrB2_ceramics_determined_by_two_laboratories.pdf)
18. Soft Magnetic Composite FAQs - Horizon Technology, accessed January 1, 2026, <https://www.horizontechnology.biz/blog/soft-magnetic-composite-faqs>
19. Soft Magnetic Composite Components - Miba, accessed January 1, 2026, <https://www.miba.com/en/product-areas/powder-metal-parts/soft-magnetic-composite>
20. YInMn Blue | Department of Chemistry, accessed January 1, 2026, <https://chemistry.oregonstate.edu/chemistry-news-events/yinmn-blue>
21. Spectral properties of the UV absorbing and near-IR reflecting blue pigment, YIn_{1-x}Mn_xO₃, accessed January 1, 2026, [https://www.researchgate.net/publication/303412635_Spectral_properties_of_the_UV_absorbing_and_near-IR_reflecting_blue_pigment_YIn_{1-x}Mn_xO₃](https://www.researchgate.net/publication/303412635_Spectral_properties_of_the_UV_absorbing_and_near-IR_reflecting_blue_pigment_YIn1-xMnxO3)
22. High temperature thin dielectric or insulating coatings for bare copper coils? - EEVblog, accessed January 1, 2026, <https://www.eevblog.com/forum/projects/high-temperature-thin-dielectric-or-insulating-coatings-for-bare-copper-coils/>
23. Block diagram of active magnetic bearing system - ResearchGate, accessed January 1, 2026, https://www.researchgate.net/figure/Block-diagram-of-active-magnetic-bearing-system_fig1_328148367
24. Safety of High Speed Magnetic Levitation Transportation Systems - ROSA P, accessed January 1, 2026, https://rosap.ntl.bts.gov/view/dot/8688/dot_8688_DS1.pdf
25. CN103199320A - Method for recycling nickel-cobalt-manganese ternary anode material - Google Patents, accessed January 1, 2026,

- <https://patents.google.com/patent/CN103199320A/en>
26. EV Battery Metal Extraction and Recovery Processes - XRAY, accessed January 1, 2026, <https://xray.greyb.com/ev-battery/ev-battery-recycling>
 27. Technospheric Mining of Cobalt and Nickel from Waste Nickel Furnace Slag by Ascorbic Acid-Assisted Citric Acid Leaching - MDPI, accessed January 1, 2026, <https://www.mdpi.com/2313-4321/10/2/43>
 28. Nickel Recycling Process: Key Methods, Benefits, Challenges, and Future Trends, accessed January 1, 2026, <https://www.okonrecycling.com/industrial-scrap-metal-recycling/specialty-metal/s/nickel-recycling-process/>
 29. Nickel and Cobalt Recovery from Spent Lithium-Ion Batteries via Electrodialysis Metathesis, accessed January 1, 2026, <https://pmc.ncbi.nlm.nih.gov/articles/PMC12028818/>
 30. Hydrometallurgical Recovery of Iron, Nickel, and Chromium from Stainless Steel Sludge with Emphasis on Solvent Extraction and Chemical Precipitation - MDPI, accessed January 1, 2026, <https://www.mdpi.com/2227-9717/10/4/748>
 31. Electrochemical Recovery of High-Purity Nickel and Cobalt From Crude Nickel and Ferronickel - CDC Stacks, accessed January 1, 2026, https://stacks.cdc.gov/view/cdc/237311/cdc_237311_DS1.pdf
 32. The Ecosystem: Weighing the attractions of recycling rare earth magnets - Science|Business, accessed January 1, 2026, <https://sciencebusiness.net/news/green-technology/ecosystem-weighing-attractions-recycling-rare-earth-magnets>
 33. Unlocking the Value: Recycling Magnetic Materials and Their Environmental Impact, accessed January 1, 2026, <https://magnetstek.com/unlocking-the-value-recycling-magnetic-materials-and-their-environmental-impact/>
 34. The Impact of the Schumann Resonances on Human and Mammalian Physiology Ground-based Investigations to Support Human - NASA Science, accessed January 1, 2026, https://science.nasa.gov/wp-content/uploads/2023/05/154_48a5766284d47dc2523cb38d856654f6_STOLCVIKTOR.pdf?emrc=b44c80
 35. Block diagram of the active seat suspension control system - ResearchGate, accessed January 1, 2026, https://www.researchgate.net/figure/Block-diagram-of-the-active-seat-suspension-control-system_fig2_364405397
 36. I haven't seen a quick answer to this, and I'm curious. How fast can maglev trains stop without resistance that becomes a safety hazard for passengers? - Quora, accessed January 1, 2026, <https://www.quora.com/I-haven-t-seen-a-quick-answer-to-this-and-I-m-curious-How-fast-can-maglev-trains-stop-without-resistance-that-becomes-a-safety-hazard-for-passengers>
 37. A New Process for Cobalt – Nickel Separation, accessed January 1, 2026, <https://www.teck.com/media/CESL-Publication-Nickel-New-Process-Cobalt-Nickel-Separation-2010.pdf>