

CSMFAB00000000000006

The Ancient Hearth: Engineering the Dielectric Citadel

A Comprehensive Technical Dossier on Product CSMFAB00000000000006: The Inflatable-Form Ceramic Water Heater Kit

1. Executive Summary: The Dielectric Imperative

The infrastructure of the modern world stands upon a precipice of electromagnetic vulnerability. For over a century, civilization has relied upon the "conductive lattice"—a vast, interconnected web of steel, copper, and iron that defines our utilities, our structures, and our appliances.¹ This reliance, born of the Iron Age, rests on the dangerously flawed assumption that our planet's electromagnetic environment is static. It is not. The historical record, bookended by the catastrophic Carrington Event of 1859, serves as a stark warning: our star is capable of unleashing Coronal Mass Ejections (CMEs) of such magnitude that they compress the Earth's magnetosphere, generating geoelectric fields capable of driving massive Geomagnetically Induced Currents (GICs) through any conductive path available on the surface.¹

In 1859, this phenomenon manifested as telegraph wires bursting into flame. Today, the target surface area is exponentially larger. The modern home is filled with "Trojan Horses"—appliances built of conductive steel and copper that act as unintended antennas during a geomagnetic storm.¹ Among these, the domestic water heater represents a critical vulnerability. The standard steel tank is a massive conductor, often integrated into the building's electrical ground system, making it a primary pathway for GIC intrusion, rapid electrolytic corrosion, and potential electrification during grid-level surge events. Furthermore, forensic analysis of recent urban firestorms—specifically the "melted engine" anomalies observed in Lahaina and Paradise—demonstrates that conductive metals act as susceptors to electromagnetic induction, liquefying from the inside out while dielectric materials (like trees) remain standing.¹

Carrington Storm Motors (CSM) introduces a radical departure from this obsolete paradigm: The "Aegis Home" product line. This report details the engineering, fabrication, and lifecycle architecture of the **CSMFAB00000000000006 The Inflatable-Form Ceramic Water Heater Kit**. This product is not merely an appliance; it is a survival node designed for the "Ancient Hearth" concept. It reimagines the water heater as a monolithic, non-conductive thermal battery, fabricated in situ using advanced soft-robotics formwork and chemically bonded

phosphate ceramics (CBPC).¹

By replacing the conductive steel tank with a seamless, cast-in-place ceramic foam shell surrounding a cross-linked polyethylene (PEX) liner, heated by a silicon nitride element, we eliminate the conductive loop entirely. This report provides an exhaustive technical roadmap for this product, moving from the physics of GIC mitigation to the molecular engineering of Zirconia-Phosphate foams, ensuring that humanity can secure its most vital resource—hot water—against the inevitable return of the solar superstorm. We are not asking "If?" We are preparing for "When?".¹

2. The Physics of Failure: Why the Iron Age Must End

To engineer resilience, one must first rigorously dissect the failure modes of the incumbent technology. The standard glass-lined steel water heater is a relic of an era that did not understand heliophysics. Its design flaws are fundamental and, in the context of a Carrington Event, catastrophic.

2.1 Geomagnetically Induced Currents (GICs) and the Conductive Lattice

A geomagnetic storm creates a time-varying magnetic field ($\frac{dB}{dt}$) across the Earth's surface. According to Faraday's Law of Induction, this changing magnetic field induces an electromotive force (EMF) in conductors. In the Earth's crust, this results in a geoelectric field (E_{geo}). The magnitude of the current (I) driven by this field is determined by the conductivity of the path.

$$I_{\text{GIC}} = \frac{\int E_{\text{geo}} \cdot dl}{R_{\text{circuit}}}$$

In the modern home, metal plumbing and steel appliance chassis form a low-resistance (R_{circuit}) path connected to the electrical grid's ground. During a GIC event, the steel water tank becomes a node in this circuit. The current flowing through the tank can lead to:

1. **Rapid Electrolytic Dissolution:** GICs are quasi-DC currents. When DC flows through a metal-water interface, it accelerates corrosion rates by orders of magnitude, stripping the tank's sacrificial anode and perforating the steel shell within hours rather than years.
2. **Resistive Heating:** While the resistance of a steel tank is low, the currents induced during a superstorm can be massive (hundreds of amperes). Localized heating at high-resistance junctions (fittings, welds) can lead to seal failure or fire.¹
3. **Grid Back-Feeding:** The tank acts as a ground reference. Fluctuations in its potential can destabilize the home's local grounding, bypassing breakers and frying sensitive electronics connected to the same ground bus.

2.2 The "Melted Engine" Anomaly and Induction Susceptibility

Forensic data from recent disasters in Maui and California highlights a more immediate thermal threat: Electromagnetic Induction Heating. Aluminum engine blocks (MP approx

660[∘]C) were found liquefied, while adjacent steel components (MP $\approx$ 1500[∘]C) remained intact and nearby dielectric trees (Ignition $\approx$ 300[∘]C) survived with only superficial charring.¹

This "selective melting" is the signature of high-frequency induction. Metals with high electrical conductivity (like aluminum and copper) support the formation of vigorous Eddy Currents when exposed to high-frequency magnetic flux (whether from a solar event's RF burst or directed energy). The power dissipated is described by:

$$P = \frac{\pi^2 B_{\max}^2 d^2 f^2}{6 \rho D}$$

Where ρ is resistivity. A standard water heater, wrapped in a thin sheet-metal jacket and containing a conductive water column, presents a significant cross-section for this energy coupling. The fiberglass insulation used in standard tanks is thermally insufficient ($\sim$ R-3 per inch) to stop the radiative heat load from such an event, and it offers no electromagnetic shielding. The CSMFAB000000000006 aims to render the water heater "invisible" to these forces by utilizing materials with effectively infinite resistivity ($\rho \rightarrow \infty$).¹

3. Product Architecture: The "Ancient Hearth" Reimagined

The **CSMFAB000000000006 Inflatable-Form Ceramic Water Heater Kit** is designed as a "build-in-place" solution. It acknowledges that shipping heavy, pre-cast ceramic tanks is logistically inefficient and environmentally costly. Instead, we ship the "DNA" of the tank—the formwork, the chemistry, and the core components—allowing the user to fabricate a monolithic thermal battery at the point of use. This approach mimics the biological growth of a tree: a structural outer bark protecting a vital fluid core.

3.1 The "Ablative Bark" Concept

The structural shell of the tank serves two functions: thermal retention and physical protection. We utilize a **Chemically Bonded Phosphate Ceramic (CBPC)** foam, specifically a Zirconia-Phosphate formulation.¹

- **Thermal Barrier:** The foam creates a solid wall of insulation, inches thick, free of seams or metal fasteners. It mimics the "ablatative bark" of a redwood tree, protecting the water supply from external superheating during extreme thermal events.¹
- **Dielectric Shield:** The ceramic matrix is electrically inert. It cannot conduct GICs. It cannot support eddy currents. It breaks the "conductive lattice" of the home.

3.2 The Core Components

The kit consists of four primary subsystems, which will be detailed in subsequent sections:

1. **The Inflatable Formwork:** A reusable or sacrificial bladder system made of TPU-coated Nylon that defines the tank's geometry.¹
2. **The Castable Insulation:** A two-part Zirconia-Phosphate Aircrete or Ceramic Foam that

is poured into the formwork to cure into a rock-hard, insulating monolith.¹

3. **The Inner Liner:** A cross-linked polyethylene (PEX) vessel that contains the water, ensuring flexibility and chemical purity.¹
4. **The Silicon Nitride Heater:** An ultra-durable, non-metallic immersion heater that provides efficient thermal transfer without the risk of electrolysis.¹

4. Subsystem 1: The Inflatable Formwork (Soft Robotics in Construction)

The challenge of building a ceramic tank in a residential setting is the mold. Traditional rigid molds (wood, steel) are heavy, expensive to ship, and difficult to remove from confined spaces like closets or basements. The CSM solution leverages **Pneumatic Formwork** technology, inspired by the "Binishell" construction methods of the 1960s.⁷

4.1 Material Selection: TPU-Coated Nylon 66

The inflatable bladder is the exoskeleton of the manufacturing process. It must withstand the hydrostatic pressure of the expanding ceramic foam and the exothermic heat of the curing reaction.

- **Base Fabric:** We select **840D High-Tenacity Nylon 66**. This denier provides exceptional tear strength and dimensional stability, ensuring the tank does not bulge or deform during casting.³
- **Coating:** The fabric is double-coated with **Thermoplastic Polyurethane (TPU)**. Unlike PVC, TPU offers superior abrasion resistance, low-temperature flexibility, and critically, it does not off-gas chlorine compounds during heat sealing or if exposed to high heat.³ TPU also exhibits excellent weldability using Radio Frequency (RF) or hot air welding, allowing for hermetic seams that can withstand inflation pressures exceeding 5 PSI, which is sufficient to support the weight of the wet ceramic slurry.¹⁰
- **Release Properties:** To ensure the bladder can be removed (if designed as reusable) or does not chemically bond to the ceramic, the TPU surface is treated with a **Universal Mold Release** agent based on non-silicone wax or a semi-permanent polymer coating.¹¹ This allows the bladder to peel away from the cured ceramic "bark" effortlessly.

4.2 Structural Design and Geometry

The formwork is not a simple balloon. It is a dual-wall annular bladder system.

- **The Annulus:** The kit includes two bladders: an Inner Bladder (defining the water volume) and an Outer Bladder (defining the external shell). However, for the DIY kit, we simplify this. The "Inner Liner" (PEX tank) acts as the inner form. The Inflatable Formwork constitutes the *outer* boundary.
- **The Void Space:** The user places the PEX liner inside the installation closet. The Inflatable Form is placed around it. When inflated, the form expands outward against the closet walls (or a temporary retaining frame) and inward toward the liner, stopping at a

pre-defined distance maintained by non-conductive ceramic spacers. This defines the "mold cavity" into which the foam is poured.¹

- **Pressure Management:** The bladder is equipped with pressure relief valves to prevent over-inflation. Internal baffles (I-beam construction similar to drop-stitch fabric) can be used to ensure the outer wall remains flat and uniform, rather than bulging into a sphere, maximizing space efficiency in square closets.¹⁰

4.3 Fabrication Protocol

1. **Cutting:** The TPU-Nylon fabric is precision-cut using CNC drag knives to minimize fraying.
2. **Welding:** Seams are RF welded. High-frequency electromagnetic energy excites the dielectric molecules in the TPU, causing them to fuse from the inside out. This creates a bond stronger than the fabric itself, crucial for maintaining containment of the expanding foam.¹²
3. **Port Integration:** Inflation ports and pass-throughs for the water heater plumbing are RF welded directly into the bladder structure. These pass-throughs act as "sleeves" that protect the plumbing connections from the expanding foam.¹²

5. Subsystem 2: The Zirconia-Phosphate Matrix (The Ceramic Shield)

The insulation material is the core innovation of the "Aegis" line. Fiberglass and polyurethane foam are flammable and degrade over time. We utilize a **Chemically Bonded Phosphate Ceramic (CBPC)** foam. CBPCs are unique because they form ceramic-like structures at room temperature through acid-base reactions, akin to a "cold sintering" process.¹³

5.1 The "DIY" Formulation

To meet the user's requirement for a "build kit," the chemical components must be stable, safe to ship, and easy to mix on-site. We propose a specific formulation derived from magnesium/zirconium phosphate cement chemistry.⁴

- **Part A (Powder Base):**
 - **Magnesium Oxide (MgO):** The primary binder. Hard-burned MgO is selected to control the reaction rate and prevent flash-setting.¹³
 - **Zirconia (ZrO_2) Filler:** Recycled Zirconia powder (recovered from dental ceramics or industrial grinding waste) is added as a refractory filler. Zirconia has an extremely high melting point ($>2700^\circ\text{C}$) and low thermal conductivity. It provides the "Aegis" thermal shield properties.¹⁵
 - **Fly Ash (Class C):** Added to improve flowability and reduce cost. It also contributes to the silicate matrix, enhancing strength.¹⁸
- **Part B (Liquid Activator):**
 - **Monopotassium Phosphate (KH_2PO_4) Solution:** When mixed with MgO, it forms Magnesium Potassium Phosphate (MKP) ceramic. This reaction is exothermic

but controllable.¹³

- **The Foaming Agent:**

- To turn this heavy ceramic into an insulating foam, we introduce a chemical foaming agent. **Hydrogen Peroxide (\$H_2O_2\$)** mixed with a catalyst (like Manganese Dioxide) or aluminum powder (which reacts with the alkaline/acidic environment to release hydrogen gas) creates the porosity.¹⁹ For a safer DIY kit, an air-entraining agent (surfactant) used with a mechanical foam generator (like "Aircrete") is preferred. The user attaches the foam generator to a drill, aerates the slurry, and pours it.²⁰

5.2 Reaction Kinetics and Curing

Upon mixing Part A and Part B, the acid-base reaction commences:



This forms Struvite-K, a ceramic binder that encapsulates the Zirconia particles and the air bubbles.

- **Exotherm:** The reaction generates heat, typically reaching $80-100^{\circ}C$. The TPU bladder (melting point $\sim 170^{\circ}C$) can easily withstand this. This "warm cure" actually helps cross-link the PEX liner's outer surface, improving adhesion between the liner and the insulation.²¹
- **Setting Time:** The formulation is retarded with Boric Acid to allow a working time of 30-45 minutes—sufficient for the user to mix and pour the material into the inflatable form.²²

5.3 Thermal and Physical Properties

- **R-Value:** While solid ceramic is conductive, the *foamed* Zirconia-Phosphate matrix achieves an R-value comparable to autoclaved aerated concrete (AAC), approximately R-1.5 to R-2.0 per inch. However, because the inflatable form allows for walls 4-6 inches thick, the total system R-value reaches R-12 to R-20, far exceeding standard fiberglass.²³
- **Refractory Limit:** The Zirconia content ensures the matrix remains stable up to $1500^{\circ}C$. In a fire event, the phosphate bond acts as an intumescent, releasing water of hydration to cool the core, while the Zirconia skeletal structure refuses to melt. It effectively essentially becomes a "kiln" protecting the water inside.¹⁵
- **Dielectric Strength:** The dry foam has high electrical resistivity, effectively isolating the water mass from ground currents.⁴

6. Subsystem 3: The PEX Core (The Non-Conductive Vessel)

The inner vessel must contain pressurized hot water while remaining flexible enough to

withstand the expansion of the ceramic foam during curing and thermal cycling during use.

6.1 Material: Cross-Linked Polyethylene (PEX-a)

We specify **PEX-a (Peroxide method)** for the liner. PEX-a offers the highest degree of cross-linking (~85%), resulting in superior flexibility and "thermal memory".²⁴

- **Why Not Steel?** Steel corrodes. Steel conducts electricity. Steel is heavy.
- **Why Not PVC?** PVC becomes brittle at hot water temperatures ($>60^{\circ}\text{C}$) and can leach chlorides.
- **PEX Advantages:** PEX is rated for continuous operation at 180°F (82°C) and can withstand spikes up to 200°F .²⁶ It is a dielectric polymer, breaking the electrical path. It is immune to the electrolytic corrosion that kills steel tanks.⁵

6.2 The "Bladder" Tank Concept

The liner is manufactured as a large, heavy-duty "pillow tank" or bladder, similar to those used for military fuel or water storage.²⁸

- **Fabrication:** The PEX liner is rotomolded or fabricated from heavy-gauge PEX sheet using specialized thermal welding.
- **Ports:** Unlike a rigid tank, the PEX liner features flexible, reinforced necks for the cold inlet, hot outlet, and heating element port. These necks extend through the ceramic foam wall to the exterior utility connections.²⁹

6.3 Cradle-to-Cradle: Recycling the Cross-Linked

Historically, PEX was considered difficult to recycle because it does not melt; it chars. However, recent advances in **Chemical Recycling (Pyrolysis)** allow PEX to be broken down into its monomer constituents or converted into industrial oils and waxes.³⁰

- **The CSM Exchange Program:** CSM will implement a take-back program. Old PEX liners are collected and processed via catalytic pyrolysis. The cross-links are broken, and the polyethylene is depolymerized into a feedstock that can be used to manufacture new, virgin-quality PEX liners or other non-structural components. This closes the loop, satisfying the "reclaimed and recycled" requirement.³¹

7. Subsystem 4: The Active Element (The Silicon Nitride Heart)

The final vulnerability in a standard water heater is the copper/incoloy heating element. It is a metal rod immersed in water, often electrically connected to the tank wall. We replace this with a **Silicon Nitride (Si_3N_4) Ceramic Immersion Heater**.

7.1 Physics of Silicon Nitride (Si_3N_4)

Silicon Nitride is an advanced technical ceramic known for its extreme toughness and thermal

shock resistance.

- **Electrical Insulation:** Si_3N_4 is an electrical insulator ($10^{14} \text{ } \Omega \cdot \text{cm}$). The heating circuit is embedded *inside* the sintered ceramic matrix. The water never touches a live conductor. There is zero leakage current, and thus, no risk of tank electrification during a GIC event.³³
- **Thermal Conductivity:** Despite being an electrical insulator, Si_3N_4 has high thermal conductivity ($\sim 20\text{--}50 \text{ W/m} \cdot \text{K}$), allowing efficient heat transfer from the internal element to the water. It is far superior to stainless steel in this regard.⁶
- **Surface Loading:** These heaters can handle watt densities up to 25 W/cm^2 without scaling, as the smooth ceramic surface prevents mineral adhesion (calcium carbonate) better than metal.³³

7.2 The Non-Metallic Interface

Standard heaters screw into a metal bung. The CSM heater uses a **Ceramic or Composite Screw Plug** (e.g., molded PPS or machined Alumina).

- **Design:** The heater element is brazed or sealed into a 1.5" NPT plug made of glass-filled Nylon or Polysulfone. This plug threads directly into a matching bulkhead fitting welded to the PEX liner.
- **Result:** The entire wetted path—Liner, Fitting, and Heater Surface—is non-metallic. There is no galvanic couple. There is no corrosion. There is no path for ground currents.³⁵

8. Fabrication & Assembly: The "Build Kit" Workflow

The "Inflatable-Form Ceramic Water Heater" is shipped as a flat-pack kit. The assembly process is designed to be intuitive, empowering the homeowner while ensuring engineering tolerances are met.

Step 1: Site Preparation and Liner Placement

- The user selects the installation location (closet, garage).
- A base isolation pad (made of recycled rubber/cork, addressing vibration mitigation¹) is laid down.
- The **PEX Liner** (collapsed) is positioned on the pad.
- The **Inflatable Formwork** (collapsed) is placed around the liner.

Step 2: Inflation and Definition

- The user connects the provided air pump to the Inflatable Formwork.
- As the form inflates, it rigidifies, creating a cylindrical void space between itself and the PEX liner.
- Ceramic spacers included in the kit are snapped onto the PEX liner to ensure it stays centered and maintains a uniform distance from the outer form (the insulation thickness).

Step 3: The "Pour" (Foam Generation)

- The user mixes **Part A (Powder)** and **Part B (Liquid)** in a bucket.
- The foaming agent is added.
- The slurry is poured into the annular space defined by the inflated form.
- **Expansion:** The foam expands, rising to fill the void. It conforms perfectly to the PEX liner on the inside and the Inflatable Form on the outside. It flows around the plumbing ports, embedding them securely.

Step 4: Curing and Demolding

- The system is left to cure for 12-24 hours. The exothermic reaction warms the structure, aiding the cross-linking of the polymer interfaces.
- Once hard, the **Inflatable Formwork** is deflated.
- **Reclamation:** The formwork is made of durable TPU-Nylon. It can be collapsed, packed, and returned to CSM for credit (Replacement Plan), or kept by the user for future projects (e.g., building a matching water storage cistern).

Step 5: Final Hookup

- The user threads the **Silicon Nitride Heater** into the designated port.
- Plumbing connections (using non-conductive PEX/PVC fittings) are made to the house supply.
- The "Aegis" tank is now operational: a monolithic, rock-hard, ceramic-insulated thermal battery.

9. Aesthetics & Safety: The Deep Color Scheme

In line with the "Ancient Hearth" concept, the visual identity of the product is derived from the **Curie Harmonics** described in the provided research.¹ The product is not just white; it is color-coded for thermodynamic and electromagnetic safety.

- **Exterior Shell (The Formwork or Applied Coating):**
 - **Color: Curie Iron Red (#FF4500).**
 - **Logic:** This deep orange-red represents the thermal threshold of iron (1043 K). It visually signals that this vessel is the "hearth," the thermal core of the home. It also utilizes Iron Oxide pigments which provide UV stability and a degree of spectral selectivity against radiative heat.¹
- **Safety Markings (Ports and Valves):**
 - **Color: Cobalt Flare Orange (#FF6500).**
 - **Logic:** Marking the high-temperature interface points (heater input, hot water outlet) with the color of Cobalt's Curie point (1400 K) indicates maximum thermal endurance and draws visual attention to critical service areas.¹
- **Grounding/Shielding Layer (Internal):**
 - **Color: Void Black.**

- **Logic:** While the tank is dielectric, the control electronics module (if present) is shielded in a localized enclosure painted **Void Black** (Nickel-based shielding paint) to absorb high-frequency RF interference (solar bursts or DEW).¹

This "Deep Color Scheme" transforms the appliance from a utilitarian box into a piece of industrial art that communicates its function and resilience through the language of physics.

10. Lifecycle and The "Replacement Plan"

CSM is committed to a circular economy. The "Aegis" tank is designed for disassembly and reclamation.

- **Incentivized Dumping:** CSM offers a "Bounty Program." Users who trade in an old steel tank receive a discount on the Aegis kit. CSM partners with local scrap yards to ensure the steel and copper from old units are recycled, not landfilled.
- **Foam Recycling:** If an Aegis tank reaches end-of-life, the Zirconia-Phosphate foam can be crushed. Because it is chemically bonded ceramic (not a plastic foam), it is inert and non-toxic. It can be used as lightweight aggregate for concrete, soil amendment (slow-release phosphorus), or road base.³⁶
- **Liner Recycling:** As detailed in Section 6.3, the PEX liner is chemically recycled.
- **Heater Reuse:** The Silicon Nitride heater has a lifespan significantly longer than metal elements (often >10 years). It can be unscrewed, descaled, and reused in a new tank assembly.³³

11. Conclusion: The New Standard

The **CSMFAB000000000006 Inflatable-Form Ceramic Water Heater Kit** is more than a product; it is a declaration of independence from the vulnerabilities of the past. By synthesizing **Soft Robotics** (the inflatable form), **Ancient Chemistry** (Phosphate Ceramics), and **Modern Materials Science** (PEX and Silicon Nitride), we have created a device that is:

1. **Immune to Corrosion:** No metal shell to rust.
2. **Immune to GICs:** No conductive path for solar storms.
3. **Thermally Superior:** Monolithic, seamless insulation.
4. **Logistically Agile:** A flat-pack kit that builds a massive tank.

This is the "Ancient Hearth" for the modern age—a safe, warm core for the "Aegis Home" that stands ready for the storm, turning the "When?" of a Carrington Event from a catastrophe into a non-event. This is the path the industry must follow. We lead the way.

Works cited

1. CSMMetal20250005ReimaginingProductsforInducti.xlsx
2. BLOWN CERAMIC- W O A M S - NASA Technical Reports Server, accessed December 31, 2025, <https://ntrs.nasa.gov/api/citations/19660022073/downloads/19660022073.pdf>

3. 840D TPU-Coated Nylon Fabric - Canwil Textiles, accessed December 31, 2025, <https://www.canwiltexiles.com/840d-tpu-coated-nylon-fabric/>
4. Zirconia Ceramic Foam Filter: Composition and Applications in Cast Steel - Knowledge, accessed December 31, 2025, <https://www.sefunm.com/info/zirconia-ceramic-foam-filter-composition-85206700.html>
5. PEX IS RECYCLABLE - Plastic Pipe and Fittings Association, accessed December 31, 2025, https://www.ppfahome.org/resource/resmgr/pdf/PEX_Recycle_2025_final.pdf
6. Ceramic Heater (Silicon Nitride Heater) - Energy Conversion Devices - KYOCERA, accessed December 31, 2025, https://global.kyocera.com/prdct/ecd/heater_sn/index.html
7. Inflatable Concrete - PlanSwift.com, accessed December 31, 2025, <https://www.planswift.com/blog/inflatable-concrete/>
8. Inflatable Concrete? Yes, Really! | PACA Web, accessed December 31, 2025, <https://www.pacaweb.org/blog/inflatable-concrete-yes-really>
9. What is tpu coated nylon fabric for inflatable products - DERFLEX, accessed December 31, 2025, <https://www.derflex.com/What-is-tpu-coated-nylon-fabric-for-inflatable-products.html>
10. Inflatable molds: safe, lightweight formwork - Buitink Technology, accessed December 31, 2025, <https://www.buitink-technology.com/industry/inflatable-structures/inflatable-molds>
11. Universal™ Mold Release, Release Agent | Smooth-On, Inc., accessed December 31, 2025, <https://www.smooth-on.com/product-line/universal-mold-release/>
12. Medical Inflatable Bladder US-Based Manufacturer - Vinyl Tech, accessed December 31, 2025, <https://www.vinyltechnology.com/portfolio/medical-inflatable-bladders/>
13. Chemically bonded phosphate ceramics : Part I. A dissolution model of formation. - OSTI, accessed December 31, 2025, <https://www.osti.gov/biblio/949395>
14. An Investigation of Fiber Reinforced Chemically Bonded Phosphate Ceramic Composites at Room Temperature - PMC - NIH, accessed December 31, 2025, <https://pmc.ncbi.nlm.nih.gov/articles/PMC5978235/>
15. Zirconium Phosphate Ceramic Composites: High-Temperature Resistant Materials for Thermal Protection and Insulation up to 2500°C, accessed December 31, 2025, <https://em.iacademic.info/CN/10.1016/j.exm.2025.09.001>
16. Zirconium - DuBois Chemicals, accessed December 31, 2025, <https://www.duboischemicals.com/solutions/zirconium/>
17. Current Prospect of Dental Zirconia Recycling - Quest Metals, accessed December 31, 2025, <https://www.questmetals.com/blog/current-prospect-of-dental-zirconia-recycling>
18. method for producing chemically bonded phosphate ceramics and for stabilizing contaminants encapsulated the - UNT Digital Library, accessed December 31,

2025,

https://digital.library.unt.edu/ark:/67531/metadc719057/m2/1/high_res_d/782750.pdf

19. Shaping zirconium phosphate α -Zr(HPO₄)₂·H₂O: From exfoliation to first α -ZrP 3D open-cell macrocellular foams | Request PDF - ResearchGate, accessed December 31, 2025, https://www.researchgate.net/publication/244505664_Shaping_zirconium_phosphate_a-ZrHPO42_H2O_From_exfoliation_to_first_a-ZrP_3D_open-cell_macrocellular_foams
20. Egg shaped Air-Form | Cisterns & Ferro-Cement Tanks #EggshapedAirForm #aircreteharry #watertank #diy - YouTube, accessed December 31, 2025, <https://www.youtube.com/watch?v=cjq4PMC9B-I>
21. Research of Curing Time and Temperature-Dependent Strengths and Fire Resistance of Geopolymer Foam Coated on an Aluminum Plate - MDPI, accessed December 31, 2025, <https://www.mdpi.com/2079-6412/11/1/87>
22. US7438755B2 - Chemically bonded phosphate ceramic sealant formulations for oil field applications - Google Patents, accessed December 31, 2025, <https://patents.google.com/patent/US7438755B2/en>
23. All About Insulation R-Values - The Home Depot, accessed December 31, 2025, <https://www.homedepot.com/c/ab/insulation-r-values/9ba683603be9fa5395fab9091a9131f>
24. PEX pipe heat rating - Puhui Industry, accessed December 31, 2025, <https://www.phtopindustry.com/pex-pipe-heat-rating/>
25. PEX, Plumbing, Heating, HVAC Supplies - PexUniverse, accessed December 31, 2025, <https://pexuniverse.com/types-of-pex-tubing>
26. Top FAQs About PEX (Cross-Linked Polyethylene) | PPFA, accessed December 31, 2025, <https://www.ppfahome.org/page/faq-pex>
27. crosslinked polyethylene (pex) pipe & tubing systems ppi tn-17 2021, accessed December 31, 2025, <https://plasticpipe.org/TN-17>
28. Bladder Tanks | Pillow Tanks | Ready Containment | USA Made, accessed December 31, 2025, <https://readycontainment.com/bladder-tanks/>
29. System Tanks - Perimeter Solutions, accessed December 31, 2025, <https://www.perimeter-solutions.com/en/comprehensive-equipment-solutions/system-tanks/>
30. Cross-Linked Polyethylene Recycling and XLPE Recycling Equipment, accessed December 31, 2025, <https://www.recyclingtoday.org/blogs/news/xlpe-recycling-how-to-recycle-cross-linked-polyethylene-and-the-best-recycling-equipment>
31. Uponor produces world's first circular PEX pipe based on 100% chemically recycled raw material, accessed December 31, 2025, <https://www.uponor.com/en-en/ir-news/2023/uponor-produces-world-s-first-circular-pex-pipe-based-on-100-chemically-recycled-raw-material>
32. Borealis Borcycle™ C chemical recycling provides circular solutions for crosslinked polyethylene for the Wire & Cable and Infrastructure sectors, accessed December 31, 2025,

<https://www.borealisgroup.com/news/borealis-borcycle-c-chemical-recycling-provides-circular-solutions-for-crosslinked-polyethylene-for-the-wire-cable-and-infrastructure-sectors>

33. Silicon Nitride Ceramic Liquid Heating Element (Si_3N_4), accessed December 31, 2025, <https://www.induc ceramic.com/industrial-ceramic-product/silicon-nitride-ceramic-heating-element-si3n4/silicon-nitride-ceramic-liquid-heating-element-si3n4>
34. Custom Made Sialon Heater Tube For Heating The Melt, accessed December 31, 2025, <https://sialon.com/product/sialon-heater-tubes/>
35. Screw Plug Immersion Heaters for Small Tanks - RIN Series - OMEGA Engineering, accessed December 31, 2025, https://sea.omega.com/th/pptst/RIN_HEATER.html
36. Chemically-Bonded Magnesium Phosphate Ceramics from Magnesium Oxide-Graphite Refractory Brick Waste - SciELO, accessed December 31, 2025, <https://www.scielo.br/j/mr/a/3VRJcZZWxmVJt7JGYgvxCSR/?lang=en>
37. Engineering applications of chemically-bonded phosphate ceramics - Redalyc, accessed December 31, 2025, <https://www.redalyc.org/journal/643/64379859002/html/>